



Report Reference ID:	278619-2TRFWL
----------------------	---------------

Test specification:	Title 47 – Telecommunication Chapter I – Federal Communications Commission Subchapter D – Safety and special radio services Part 90 – Private land mobile services Subpart I – General technical standards
---------------------	---

Applicant:	TEKO Telecom Srl Via Meucci, 24/a I-40024 Castel S. Pietro Terme (BO) (Italy)
Apparatus:	Very High Power Amplifier
Model:	MVHPA0001S9
FCC ID:	XM2- VHPA

Testing laboratory:	Nemko Italy Spa Via del Carroccio, 4 20853 Biassono (MB) – Italy Telephone: +39 039 2201201 Facsimile: +39 039 2201221
---------------------	---

	Name and title	Date
Tested by:	 G. Curioni, Wireless/EMC Specialist	2015-03-13
Reviewed by:	 P. Barbieri, Wireless/EMC Specialist	2015-03-13

Nemko Spa, 20853 Biassono (MB) - Italy. All rights reserved.

This publication may be reproduced in whole for non-commercial purposes as long as Nemko Spa is acknowledged as copyright owner and source of the material. Nemko Spa takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This test report may not be partially reproduced, except with the prior written permission of Nemko Spa. The test report merely corresponds to the test sample. The phase of sampling / collection of equipment under test is carried out by the customer.

This Test Report, when bearing the Nemko name and logo is only valid when issued by a Nemko laboratory, or by a laboratory having special agreement with Nemko.

Table of contents

Section 1: Report summary	3
Section 2: Equipment under test	4
2.1 Identification of equipment under test (EUT)	4
2.2 Accessories and support equipment	5
2.3 EUT description	6
2.4 Technical specifications of the EUT	6
2.5 EUT setup diagram	7
2.6 Operation of the EUT during testing	8
2.7 Modifications incorporated in the EUT	8
Section 3: Test conditions	9
3.1 Deviations from laboratory tests procedures	9
3.2 Test conditions, power source and ambient temperatures	9
3.3 Measurement uncertainty	10
3.4 Test equipment	10
Section 4: Result summary	11
4.1 FCC Part 90: test results	11
Appendix A: Test results	12
Clause 90.205, 90.219(e)(1) Output power	12
Clause 90.209, 90.219(e)(4) Occupied bandwidth	14
Clause 90.209, 90.210(i), 90.210(j), 90.219(e)(3) Spurious emissions at the antenna terminal	15
Clause 90.209, 90.219(e)(3) Field strength of spurious radiation	17
Clause 90.219(e)(2) Noise Figure	19
Clause 935210 D02v02r01 Appendix D.3 (i) Intermodulation	20
Clause 935210 D02v02r01 (D.3)(l) Out of band rejection	21
Appendix B: Block diagrams of test set-ups	22
Appendix C: EUT Photos	23

Section 1: Report summary

This report contains an assessment of apparatus against specifications based upon tests carried out on samples submitted at Nemko Spa.

Test specification:

FCC Part 90 Private land mobile services

Subpart I – General technical standards

Compliance status:	Complies
--------------------	----------

Exclusions:	None
-------------	------

Non-compliances:	None
------------------	------

Report release history:	Original release
-------------------------	------------------

Test location:	Nemko Spa Via Del Carroccio, 4 – 20853 Biassono (MB) - Italy
----------------	---

Registration number:	481407 (10 m Semi anechoic chamber)
----------------------	-------------------------------------

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025.

Nemko Spa authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

Section 2: Equipment under test

2.1 Identification of equipment under test (EUT)

The following information identifies the EUT under test:

Type of equipment:	Very High Power Amplifier
Product marketing name:	Teko Telecom Srl
Model number:	MVHPA0001S9
Serial number:	na
Nemko sample number:	--
FCC ID:	XM2-VHPA
Date of receipt:	2015-03-09

2.2 Accessories and support equipment

The following information identifies accessories used to exercise the EUT during testing:

No other FCC-ID equipment are used to exercise the EUT during testing

Item # 1

Type of equipment:	Power supply
Brand name:	Teko Telecom
Model name or number:	MPSURU28AC1K0001
Serial number:	na
Nemko sample number:	na
Connection port:	To supply amplifier
Cable length and type:	

Item # 2

Type of equipment:	Power Supply
Brand name:	DF
Model name or number:	DF1731SB
Serial number:	na
Nemko sample number:	na
Connection port:	To supply cooling fan of heatsink
Cable length and type:	

Item # 3

Type of equipment:	
Brand name:	
Model name or number:	
Serial number:	
Nemko sample number:	
Connection port:	
Cable length and type:	

Item # 4

Type of equipment:	
Brand name:	
Model name or number:	
Serial number:	
Nemko sample number:	
Connection port:	
Cable length and type:	

Section 2: Equipment under test, continued

2.3 EUT description

See confidential block diagram and operational description

2.4 Technical specifications of the EUT

Operating band:	Down Link: 935–940 MHz, Up Link: 896-901 MHz	
Operating frequencies:	Wideband	
Modulation type:	iDEN	
Occupied bandwidth:	Standard	
Channel spacing:	Standard	
Emission designator:	iDEN: D7W	
RF Output	Down Link: 43dBm (20W) Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)	
Gain	Down Link: 48dB Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)	
Antenna data:	No antenna provided	
Antenna type:	No antenna provided	
	External Antenna (Equipment that has an external 50 Ω RF connector)	
Power source	28-30 Vdc	

Section 2: Equipment under test, continued

2.5 EUT setup diagram

In this system, Very High Power Amplifier is the EUT and it is intended for mounting in Remote Unit and Digital Service Front-End (optical system with Master Unit that includes only management module and optical module, to convert RF signal in optical signal in down link direction and viceversa optical signal in RF signal in up link direction). As described in "Operational description", master unit is connected directly to base station, so the system doesn't use another equipment (under another FCC ID) to exercise the EUT. Signal generator is linked directly to the RF input connector.


Test setup for output power, occupied bandwidth, spurious emissions:



Procedure

Connect the signal modulated generator to the input of the EUT, so that the EUT works at the max gain. Raise the input level to the EUT until reach the maximum output power. Connect the spectrum analyzer to the RF output connector of the EUT.


Test setup for intermodulation:



Procedure

Connect two signal modulated generators to the input of the EUT, so that the two input signals are same level. The EUT works at the max gain. Raise the input level to the EUT until reach the maximum output power. Connect the spectrum analyzer to the RF output connector of the EUT. At maximum drive level, for each modulation applies two tones for fulfill two tests (high-band edge and low-band-edge)

Test setup for Noise figure:



Procedure

Connect the EUT with the spectrum analyzer as described in the picture below. Connect the "Output Noise Source" spectrum analyzer with the RF input connector of the Remote Unit. Connect the output RF connector with the spectrum analyzer. Between spectrum analyzer and Remote Unit use a "Noise Source" (Test probe), so the noise of reference is generated. Set the EUT at max gain.

2.6 Operation of the EUT during testing

In down-link direction, normal working at max gain with max RF power output

2.7 Modifications incorporated in the EUT

None

There were no modifications performed to the EUT during this assessment

Section 3: Test conditions

3.1 Deviations from laboratory tests procedures

No deviations were made from laboratory test procedures.

3.2 Test conditions, power source and ambient temperatures

Normal temperature, humidity and air pressure test conditions	<p>Temperature: 15–30 °C Relative humidity: 20–75 % Air pressure: 86–106 kPa</p> <p>When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.</p>
Power supply range:	<p>The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages ± 5 %, for which the equipment was designed.</p>

Section 3: Test conditions, continued

3.3 Measurement uncertainty

Nemko S.p.A. measurement uncertainty has been calculated using the standard CISPR 16-4-2 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modeling – Uncertainty in EMC measurements". All calculations can be found in Nemko S.p.A. document WML1002.

3.4 Test equipment

Equipment	Manufacturer	Model No.	Asset/Serial No.	Next cal.
Vector Signal Generator	Agilent	N5172B EXG	MY53050534	Feb 2017
Vector Signal Generator	Agilent	E4438C ESG	MY45094485	Ago 2016
Spectrum Analyzer	Agilent	N9030A PXA	MY53120882	Apr 2015
Network Analyzer	Agilent	E5071B ENA	MY46418709	Jan 2016
--	--	--	--	--
EMI Receiver	R & S	ESCI	100888	08/2015
V-network	R & S	ESH2-Z5	872 460/041	09/2015
Trilog Broad Band Antenna 25-2000 MHz	Schwarzbeck	VULB 9168	VULB 9168-242	02/2015
Trilog Broad Band Antenna 25-8000 MHz	Schwarzbeck	VULB 9162	VULB 9162-25	05/2015
Antenna 1-18 GHz	Schwarzbeck	STLP 9148	STPL 9148-123	02/2015
Double ridge waveguide horn	RFspin	DRH40	061106A40	08/2016
Preamplifier 18-40 GHz	Miteq	JS44	1648665	11/2015
Broadband preamplifier 1-18 GHz	Schwarzbeck	BBV 9718	9718-137	10/2015
EMI receiver 20 Hz ÷ 8 GHz	R&S	ESU8	100202	02/2015
EMI receiver 20 Hz ÷ 3 GHz	R&S	ESCI	100888	08/2015
Hydraulic revolving platform	Nemko	RTPL 01	4.233	NCR
Turning-table	R&S	HCT	835 803/03	NCR
Antenna mast	R&S	HCM	836 529/05	NCR
Controller	R&S	HCC	836 620/7	NCR
Spectrum Analyzer 9kHz ÷ 40GHz	R&S	FSEK	848255/005	08/2015
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	530	09/2016
Shielded room	Siemens	10m control room	1947	NCR
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	70	NCR
Shielded Room	Siemens	3m semi-anechoic chamber	3	NCR
Motor controller	Emco	1051-25	9012-1559	NCR
Motor controller	Emco	1061-1.521	9012-1508	NCR
Antenna Tower	Emco	2071-2	9601-1940	NCR
Controller pole/table	Emco	2090	9511-1099	NCR
V-Network	R & S	ESH2-Z5	872 460/041	09/2015

Note: N/A = Not Applicable, NCR = No Cal Required, COU = CAL On Use
 (*) Equipment supplied by manufacturer's

Section 4: Result summary

4.1 FCC Part 90: test results

The column headed 'Required' indicates whether the associated clauses were invoked for the apparatus under test. The following abbreviations are used:

N	No : not applicable / not relevant.
Y	Yes : Mandatory i.e. the apparatus shall conform to these tests.
N/T	Not Tested, mandatory but not assessed. (See report summary)

Part	Test method	Test description	Required	Result
§90.205 §90.219(e)(1)	§2.1047	Output power	Y	Pass
§90.209 §90.219(e)(4)	§2.1049	Occupied bandwidth	Y	Pass
§90.209, §90.210(i), §90.210(j), §90.219(e)(3)	§2.1051	Spurious Emissions at the antenna terminal	Y	Pass
§90.209 §90.219(e)(3)	§2.1053	Field strength of spurious radiation	Y	Pass
§90.213	§2.1055	Frequency stability	N	N/A a)
§90.219(e)(2)	--	Noise Figure	Y	Pass
935210 D02v02r01 (D.3)(i)	--	Intermodulation	Y	Pass
935210 D02v02r01 (D.3)(l)	--	Out of Band Rejection (Filter Frequency Response)	Y	Pass

Notes:

- a) NOT APPLICABLE: Modulation/frequency conversion circuitry not in use. No frequency change in EUT (input and output have same frequency)

Appendix A: Test results

Clause 90.205, 90.219(e)(1) Output power

§ 90.205

Applicants for licenses must request and use no more power than the actual power necessary for satisfactory operation. Except where otherwise specifically provided for, the maximum power that will be authorized to applicants whose license applications for new stations are filed after August 18, 1995 is as follows in FCC Part 90.205 (a) through (r).

§ 90.219(e)(1)

The output power capability of a signal booster must be designed for deployments providing a radiated power not exceeding 5 Watts ERP for each retransmitted channel.

Test date: [2015-03-11](#)

Test results: [Pass](#)

Special notes


Conducted measurement were performed:

- The power was measured using spectrum analyzer with RMS detector / average power meter.

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB.

Only conducted measurement at antenna connector was possible, no antenna provided by manufacturer.

Test data					
Direction	Modulation	Frequency (MHz)	RF output channel Power (dBm)	RF output channel Power (W)	PAR (dB)
Down-link	iDEN (25 kHz)	937.5	43.11	20.46	3.23



Test result

In a DAS system, we suppose a loss due to cable insertion, splitter, etc, about of 12dB.

$$G_{\text{max antenna gain (dBi)}} = \text{EIRP} - \text{Pout} + \text{insertion loss} = 39 - 43.15 + 12.15 = 8 \text{ dBi}$$

$$\text{EIRP} = \text{Pout} - \text{insertion loss} + G_{\text{max antenna gain (dBi)}} = 43.15 - 12.15 + 8 = 39 \text{ dBm}$$

$$\text{ERP} = 39 - 2.14 = 36.86 \text{ dBm} = 4.85 \text{ W} < 5 \text{ W ERP}$$

Clause 90.209, 90.219(e)(4) Occupied bandwidth

§ 90.219(e)(4)

A signal booster must be designed such that all signals that it retransmits meet the following requirements:

- (i) The signals are retransmitted on the same channels as received. Minor departures from the exact provider or reference frequencies of the input signals are allowed, *provided that* the retransmitted signals meet the requirements of § 90.213.
- (ii) There is no change in the occupied bandwidth of the retransmitted signals.
- (iii) The retransmitted signals continue to meet the unwanted emissions limits of § 90.210 applicable to the corresponding received signals (assuming that these received signals meet the applicable unwanted emissions limits by a reasonable margin).


Test date: 2015-03-11

Test results: Pass


Test data

Resolution bandwidth was set wider or equal than occupied bandwidth.

Mod. iDEN (QAM)



Output



Input

Clause 90.209, 90.210(i), 90.210(j), 90.219(e)(3) Spurious emissions at the antenna terminal

§ 90.210(i)

Emission Mask I. For transmitters that are equipped with an audio low pass filter, the power of any emission must be attenuated below the unmodulated carrier power of the transmitter (P) as follows:

(3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency of more than 15 kHz: At least $43 + 10 \log (P)$ dB, or 70 dB, whichever is the lesser attenuation

§ 90.210(j)

Emission Mask J. For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power of the transmitter (P) as follows:

(3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 9.5 kHz: At least $157 \log (fd/5.3)$ dB, or $50 + 10 \log (P)$ dB or 70 dB, whichever is the lesser attenuation.

§ 90.219(e)(3)

Spurious emissions from a signal booster must not exceed -13 dBm within any 100 kHz measurement bandwidth.

§ 2.1051 Measurements required: Spurious emissions at antenna terminals.

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in §2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.


Test date: 2015-03-11

Test results: Pass


Special notes

Spurious emissions at antenna terminal:


Mod. iDEN (QAM) (Down-link)




9kHz-150kHz



150kHz-30MHz



30MHz-1GHz



1GHz-10GHz

Clause 90.209, 90.219(e)(3) Field strength of spurious radiation

§ 90.219(e)(3)

Spurious emissions from a signal booster must not exceed –13 dBm within any 100 kHz measurement bandwidth.

§ 2.1053 Measurements required: Field strength of spurious radiation.

(a) Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of §2.1049, as appropriate. For equipment operating on frequencies below 890 MHz, an open field test is normally required, with the measuring instrument antenna located in the far-field at all test frequencies. In the event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurements will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from halfwave dipole antennas.

(b) The measurements specified in paragraph (a) of this section shall be made for the following equipment:

- (1) Those in which the spurious emissions are required to be 60 dB or more below the mean power of the transmitter.
- (2) All equipment operating on frequencies higher than 25 MHz.
- (3) All equipment where the antenna is an integral part of, and attached directly to the transmitter.
- (4) Other types of equipment as required, when deemed necessary by the Commission.

Test date: 15-03-11

Test results: Pass

Special notes

- The spectrum was searched from 30 MHz to the 10th harmonic.
- The EUT was measured on three orthogonal axis.
- All measurements were performed at a distance of 3 m.
- Only the worst data presented in the test report.

Clause 90.210 Field Strength of spurious radiation, continued**Test data**

The D.U.T. was positioned according to the radiated emissions set-up

The D.U.T. antenna connector was terminated by a 50 Ω shielded dummy load.

The spectrum was searched from 30 MHz to 1 GHz (RBW 100 kHz) & 1 GHz (RBW 1 MHz) to the tenth harmonic of the carrier.

There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.

Clause 90.219(e)(2) Noise Figure

§ 90.219(e)(2)


The noise figure of a signal booster must not exceed 9 dB in either direction.

Test date: 2015-03-11

Test results: Pass

Special notes

In the Remote Unit, only up-link measurement can be performed (test probe is connect to antenna port)



Clause 935210 D02v02r01 Appendix D.3 (i) Intermodulation

Intermodulation – Test all modulation types [TDMA, CDMA, and FM (covers GSM and F1D)]


- (1) For part 90 boosters, apply the requirements of § 90.219(d) and (e).
- (2) For other boosters: (i) CW signal rather than typical signal is acceptable (for FM).
 - (ii) At maximum drive level, for each modulation: one test with three tones, or two tests (high-band edge, low- band edge) with two tones
 - (iii) Limit usually is -13 dBm conducted.
 - (iv) Not needed for Single Channel systems.
 - (v) Combination of modulation types not needed.

Test date: 2015-03-11

Test results: Pass

Special notes

Mod. iDEN (QAM) (Down-link)




The in-band signal between the two tones is internally generated by the “multicarrier” feature of the signal generator.

Clause 935210 D02v02r01 (D.3)(I) Out of band rejection

Out of Band Rejection – Test for rejection of out of band signals.
Filter frequency response plots are acceptable.


Test date: 2015-03-11

Test results: Pass




Appendix B: Block diagrams of test set-ups

Radiated emissions set-up




Substitution method set-up



Appendix C: EUT Photos

Photo Set up







Photo EUT



Label EUT

TEKO TELECOM
MODEL: MVHPA0001S9
FCC ID: XM2-VHPA

WARNING. This is NOT a CONSUMER device. This is a 90.219 Class B signal booster. It is designed for installation by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC LICENSE or express consent of an FCC Licensee to operate this device. You MUST register Class B signal boosters (as defined in 47 CFR 90.219) online at www.fcc.gov/signal-boosters/registration. Unauthorized use may result in significant forfeiture penalties, including penalties in excess of \$100,000 for each continuing violation.