



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2519-1,XT2519-2,XT2519V
FCC ID : IHDT56AU6
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure
TEST DATE(S) : Jan. 13, 2025 ~ Feb. 19, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	9
1.6 Specification of Accessory	10
1.7 Testing Location	10
1.8 Test Software.....	10
1.9 Applicable Standards.....	11
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	12
2.1 Carrier Frequency and Channel	12
2.2 Test Mode.....	14
2.3 Connection Diagram of Test System.....	16
2.4 Support Unit used in test configuration and system	17
2.5 EUT Operation Test Setup	17
2.6 Measurement Results Explanation Example.....	17
3 TEST RESULT	18
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	18
3.2 Maximum Conducted Output Power Measurement	20
3.3 Power Spectral Density Measurement	22
3.4 Unwanted Emissions Measurement	25
3.5 AC Conducted Emission Measurement.....	30
3.6 Antenna Requirements	32
4 LIST OF MEASURING EQUIPMENT	34
5 MEASUREMENT UNCERTAINTY	35
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR510740E	Rev. 01	Initial issue of report	Mar. 07, 2025



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	6dB Bandwidth > 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm/MHz	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 3.16 dB at 5459.280 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 5.37 dB at 0.204 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	15.203 & 15.407(a)	15.203 & 15.407(a)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2519-1,XT2519-2,XT2519V
FCC ID	IHDT56AU6
IMEI / SN Code	Conducted:355782390034910/355782390034928 Conduction: 355782390040016/355782390040024 Radiation SN : 33810EB16A40
HW Version	DVT2
SW Version	V2VD35.27
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. The different model name is different for market purpose.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	MIMO <Ant. 6+7> <5180 MHz ~ 5240 MHz> 802.11a : 20.92 dBm / 0.1236 W 802.11n HT20 : 20.75 dBm / 0.1189 W 802.11n HT40 : 22.37 dBm / 0.1726 W 802.11ac VHT20: 20.67 dBm / 0.1167 W 802.11ac VHT40: 22.28 dBm / 0.1690 W 802.11ac VHT80: 12.80 dBm / 0.0191 W 802.11ax HE20: 21.47 dBm / 0.1403 W 802.11ax HE40: 22.58 dBm / 0.1811 W 802.11ax HE80: 12.83 dBm / 0.0192 W <5260 MHz ~ 5320 MHz> 802.11a : 21.06 dBm / 0.1276 W 802.11n HT20 : 20.95 dBm / 0.1245 W 802.11n HT40 : 22.56 dBm / 0.1803 W 802.11ac VHT20: 20.86 dBm / 0.1219 W 802.11ac VHT40: 22.47 dBm / 0.1766 W 802.11ac VHT80: 17.11 dBm / 0.0514 W 802.11ax HE20: 21.60 dBm / 0.1276 W 802.11ax HE40: 22.75 dBm / 0.1884 W 802.11ax HE80: 17.26 dBm / 0.0532 W <5500 MHz ~ 5720 MHz > 802.11a : 21.10 dBm / 0.1288 W 802.11n HT20 : 21.13 dBm / 0.1297 W 802.11n HT40 : 22.08 dBm / 0.1614 W 802.11ac VHT20: 21.04 dBm / 0.1271 W 802.11ac VHT40: 21.99 dBm / 0.1581 W 802.11ac VHT80: 21.69 dBm / 0.1476 W 802.11ax HE20: 21.40 dBm / 0.1380 W 802.11ax HE40: 22.42 dBm / 0.1746 W 802.11ax HE80: 21.77 dBm / 0.1503 W <5745 MHz ~ 5825 MHz> 802.11a : 21.89 dBm / 0.1545 W 802.11n HT20 : 21.75 dBm / 0.1496 W 802.11n HT40 : 22.05 dBm / 0.1603 W 802.11ac VHT20: 21.63 dBm / 0.1455 W 802.11ac VHT40: 21.96 dBm / 0.1570 W 802.11ac VHT80: 22.22 dBm / 0.1667 W 802.11ax HE20: 21.94 dBm / 0.1563 W 802.11ax HE40: 22.35 dBm / 0.1718 W 802.11ax HE80: 22.34 dBm / 0.1714 W MIMO <Ant. 6+10> <5180 MHz ~ 5240 MHz> 802.11a : 21.13 dBm / 0.1297 W 802.11n HT20 : 21.11 dBm / 0.1291 W 802.11n HT40 : 22.65 dBm / 0.1841 W 802.11ac VHT20: 21.02 dBm / 0.1265 W



	802.11ac VHT40: 22.57 dBm / 0.1807 W 802.11ac VHT80: 17.85 dBm / 0.0610 W 802.11ax HE20: 21.66 dBm / 0.1466 W 802.11ax HE40: 22.82 dBm / 0.1914 W 802.11ax HE80: 17.89 dBm / 0.0615 W <5260 MHz ~ 5320 MHz> 802.11a : 21.21 dBm / 0.1321 W 802.11n HT20 : 21.42 dBm / 0.1387 W 802.11n HT40 : 22.82 dBm / 0.1914 W 802.11ac VHT20: 21.33 dBm / 0.1358 W 802.11ac VHT40: 22.74 dBm / 0.1879 W 802.11ac VHT80: 19.06 dBm / 0.0805 W 802.11ax HE20: 21.56 dBm / 0.1432 W 802.11ax HE40: 22.97 dBm / 0.1982 W 802.11ax HE80: 19.15 dBm / 0.0822 W <5500 MHz ~ 5720 MHz > 802.11a : 21.32 dBm / 0.1355 W 802.11n HT20 : 21.42 dBm / 0.1387 W 802.11n HT40 : 22.15 dBm / 0.1641 W 802.11ac VHT20: 21.32 dBm / 0.1355 W 802.11ac VHT40: 22.07 dBm / 0.1611 W 802.11ac VHT80: 22.02 dBm / 0.1592 W 802.11ax HE20: 21.63 dBm / 0.1455 W 802.11ax HE40: 22.49 dBm / 0.1774 W 802.11ax HE80: 22.12 dBm / 0.1629 W <5745 MHz ~ 5825 MHz> 802.11a : 22.14 dBm / 0.1637 W 802.11n HT20 : 22.03 dBm / 0.1596 W 802.11n HT40 : 22.33 dBm / 0.1710 W 802.11ac VHT20: 21.92 dBm / 0.1556 W 802.11ac VHT40: 22.25 dBm / 0.1679 W 802.11ac VHT80: 22.63 dBm / 0.1832 W 802.11ax HE20: 22.09 dBm / 0.1618 W 802.11ax HE40: 22.59 dBm / 0.1816 W 802.11ax HE80: 22.68 dBm / 0.1854 W
99% Occupied Bandwidth	<Ant. 6+7> <5180 MHz ~ 5240 MHz> 802.11a : 17.478 MHz 802.11n HT20 : 18.362 MHz 802.11n HT40 : 37.444 MHz 802.11ac VHT80 : 76.936 MHz 802.11ax HE20: 19.210 MHz 802.11ax HE40: 38.076 MHz 802.11ax HE80: 78.104 MHz <5260 MHz ~ 5320 MHz> 802.11a : 17.818 MHz 802.11n HT20 : 18.970 MHz 802.11n HT40 : 37.428 MHz 802.11ac VHT80 : 76.952 MHz 802.11ax HE20: 19.318 MHz 802.11ax HE40: 38.092 MHz 802.11ax HE80: 78.392 MHz <5500 MHz ~ 5720 MHz> 802.11a : 17.546 MHz 802.11n HT20 : 18.630 MHz



	802.11n HT40 : 38.028 MHz 802.11ac VHT80 : 76.904 MHz 802.11ax HE20: 19.294 MHz 802.11ax HE40: 38.244 MHz 802.11ax HE80: 78.552 MHz <5745 MHz ~ 5825 MHz> 802.11a : 17.914 MHz 802.11n HT20 : 19.994 MHz 802.11n HT40 : 37.172 MHz 802.11ac VHT80 : 77.240 MHz 802.11ax HE20: 19.262 MHz 802.11ax HE40: 38.148 MHz 802.11ax HE80: 78.328 MHz <Ant. 6+10> <5180 MHz ~ 5240 MHz> 802.11a : 17.450 MHz 802.11n HT20 : 18.634 MHz 802.11n HT40 : 37.236 MHz 802.11ac VHT80 : 76.776 MHz 802.11ax HE20: 19.274 MHz 802.11ax HE40: 38.132 MHz 802.11ax HE80: 78.632 MHz <5260 MHz ~ 5320 MHz> 802.11a : 17.922 MHz 802.11n HT20 : 18.998 MHz 802.11n HT40 : 37.140. MHz 802.11ac VHT80 : 77.208 MHz 802.11ax HE20: 19.310 MHz 802.11ax HE40: 38.220 MHz 802.11ax HE80: 78.568 MHz <5500 MHz ~ 5720 MHz> 802.11a : 17.794 MHz 802.11n HT20 : 18.842 MHz 802.11n HT40 : 37.540 MHz 802.11ac VHT80 : 77.224 MHz 802.11ax HE20: 19.230 MHz 802.11ax HE40: 38.444 MHz 802.11ax HE80: 78.616 MHz <5745 MHz ~ 5825 MHz> 802.11a : 18.642 MHz 802.11n HT20 : 20.314 MHz 802.11n HT40 : 37.292 MHz 802.11ac VHT80 : 77.304 MHz 802.11ax HE20: 19.546 MHz 802.11ax HE40: 38.140 MHz 802.11ax HE80: 78.296 MHz
--	--

Antenna Type / Gain	<Ant. 6+7> <5180 MHz ~ 5240 MHz> <Ant. 6> : Loop Antenna with gain -7.50 dBi <Ant. 7> : Loop Antenna with gain -8.00 dBi <5260 MHz ~ 5320 MHz> <Ant. 6> : Loop Antenna with gain -7.00 dBi <Ant. 7> : Loop Antenna with gain -8.00 dBi <5500 MHz ~ 5720 MHz> <Ant. 6> : Loop Antenna with gain -6.50 dBi <Ant. 7> : Loop Antenna with gain -8.10 dBi <5745 MHz ~ 5825 MHz> <Ant. 6> : Loop Antenna with gain -8.00 dBi <Ant. 7> : Loop Antenna with gain -8.10 dBi <Ant. 6+10> <5180 MHz ~ 5240 MHz> <Ant. 6> : Loop Antenna with gain -7.50 dBi <Ant. 10> : IFA Antenna with gain -8.10 dBi <5260 MHz ~ 5320 MHz> <Ant. 6> : Loop Antenna with gain -7.00 dBi <Ant. 10> : IFA Antenna with gain -8.50 dBi <5500 MHz ~ 5720 MHz> <Ant. 6> : Loop Antenna with gain -6.50 dBi <Ant. 10> : IFA Antenna with gain -8.90 dBi <5745 MHz ~ 5825 MHz> <Ant. 6> : Loop Antenna with gain -8.00 dBi <Ant. 10> : IFA Antenna with gain -8.40 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)

Note:

1. 802.11ax support full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) are tested for conducted power/PSD/RSE, the full RU power > partial RU, therefore the full RU perform full test and Partial RU verified power/PSD/RSE.
2. WLAN MIMO support CDD mode.
3. For WLAN SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to the higher normal output power.
4. For 802.11n HT20/HT40 & ac VHT20/VHT40 mode, the whole testing have assessed only 802.11n HT20/HT40 by referring to the higher output power.
5. The device supports Ant 6+7 and Ant 6+10 MIMO mode.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Specification of Accessory				
Battery	Brand Name	Motorola(ATL)	Model Name	RM52
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18D86731
USB Cable 2	Brand Name	Motorola(Luxshare)	Model Name	SC18E08103

1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH05-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH05-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z for Adapter mode, WPT charger mode and Earphone mode. The worst cases (X/Z-plane-Adapter mode) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210	-	-
Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290	-	-
Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5500-5720MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700
Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825



Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 [#]	5610	128	5640
	-	-	-	-

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138 [#]	5690	144	5720
	142*	5710	-	-

Note:

1. The above Frequency and Channel in "*" are 40MHz bandwidth.
2. The above Frequency and Channel in "[#]" are 80MHz bandwidth.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

MIMO <Ant 6+7>Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

MIMO <Ant 6+10>Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link(5G) + USB Cable (1)(Charging From Adaptor)
Remark: For Radiated Test Cases, The tests were performance with Adapter and USB Cable 1	




Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		20M BW	20M BW	20M BW	20M BW
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		40M BW	40M BW	40M BW	40M BW
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159
Straddle		-	-	142	-


Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		80M BW	80M BW	80M BW	80M BW
L	Low	-	-	106	-
M	Middle	42	58	-	155
H	High	-	-	122	-
Straddle		-	-	138	-

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A
6.	Adapter	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.50 dB and 20dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.50 + 20 = 24.50(\text{dB})
 \end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

☒	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW) and 99% OBW
	- Set RBW = approximately 1% of the emission bandwidth. - Set the VBW > RBW. - Detector = Peak. - Trace mode = max hold - Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. - For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set to 1%~5% of the OBW and set the Video bandwidth (VBW) $\geq 3 \times$ RBW. - Measure and record the results in the test report.
☒	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	- Set RBW = 100kHz. - Set the VBW $\geq 3 \times$ RBW. - Detector = Peak. - Trace mode = max hold - Measure the maximum width of the emission that is 6 dB down from the peak of the emission. - Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log_{10} B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For the 5.47–5.6 GHz and 5.65–5.725 GHz band, the maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever power is less. The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures


The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.
4. For MIMO mode, the measure-and-sum technique should be used for measuring the in-band transmit power of a device.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.

Section F) Maximum power spectral density.

For devices operating in the bands UNII-1/2A/2C

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW $\geq$ 3 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

For devices operating in the band UNII-3

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500KHz (or 300 kHz if the SA can't set RBW=500KHz).
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- If the SA can't set RBW=500KHz, then add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.


Method (a): Measure and sum the spectra across the outputs for bands UNII-1/2A/2C.

The total final Power Spectral Density is the bin-by-bin summation to obtain the combined spectrum. For the device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

Method (b): Measure and sum spectral maxima across the outputs for band UNII-3.

The measurement on each individual output were performed with the same span and number on each individual output. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz .

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz . Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz .

- (2) For transmitters operating in the 5.725-5.85 GHz band:
- 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

(4) EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

(4) ANSI C63.10-2013 clause 12.7.3 note 97

As specified by regulatory requirements, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit. However, an out-of-band emission that complies with both the average and peak general regulatory limits is not required to satisfy the peak emission limit.

3.4.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



**3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2), if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = GANT + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(\text{NANT}/\text{NSS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $\text{NANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with

GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain GANT is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 6	Ant. 7	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
UNII-1	-7.50	-8.00	-7.50	-4.74	0.00	0.00
UNII-2A	-7.00	-8.00	-7.00	-4.48	0.00	0.00
UNII-2C	-6.50	-8.10	-6.50	-4.25	0.00	0.00
UNII-3	-8.00	-8.10	-8.00	-5.04	0.00	0.00

<CDD Modes>						
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 6	Ant. 10	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
UNII-1	-7.50	-8.10	-7.50	-4.78	0.00	0.00
UNII-2A	-7.00	-8.50	-7.00	-4.71	0.00	0.00
UNII-2C	-6.50	-8.90	-6.50	-4.61	0.00	0.00
UNII-3	-8.00	-8.40	-8.00	-5.19	0.00	0.00

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Jan. 13, 2025 ~Feb. 19, 2025	Oct. 09, 2025	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2025	Jan. 13, 2025 ~Feb. 19, 2025	Jan. 01, 2026	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2025	Jan. 13, 2025 ~Feb. 19, 2025	Jan. 01, 2026	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY57290151	3Hz~8.5GHz;Max x 30dBm	Jul. 04, 2024	Jan. 13, 2025 ~Feb. 17, 2025	Jul. 03, 2025	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz~44G,MAX 30dB	Oct. 10, 2024	Jan. 13, 2025 ~Feb. 17, 2025	Oct. 09, 2025	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Jan. 13, 2025 ~Feb. 17, 2025	Sep. 07, 2025	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz~1GHz	Apr. 18, 2024	Jan. 13, 2025 ~Feb. 17, 2025	Apr. 17, 2025	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 11, 2024	Jan. 13, 2025 ~Feb. 17, 2025	Apr. 10, 2025	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101116	18GHz~40GHz	Oct. 22, 2024	Jan. 13, 2025 ~Feb. 17, 2025	Oct. 21, 2025	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 03, 2024	Jan. 13, 2025 ~Feb. 17, 2025	Jul. 02, 2025	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Jan. 02, 2025	Jan. 13, 2025 ~Feb. 17, 2025	Jan. 01, 2026	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060843	1Ghz~18Ghz	Jan. 02, 2025	Jan. 13, 2025 ~Feb. 17, 2025	Jan. 01, 2026	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz~18Ghz	Jan. 02, 2025	Jan. 13, 2025 ~Feb. 17, 2025	Jan. 01, 2026	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 13, 2025 ~Feb. 17, 2025	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 13, 2025 ~Feb. 17, 2025	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 13, 2025 ~Feb. 17, 2025	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 18, 2024	Feb. 08, 2025	Apr. 17, 2025	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Aug. 20, 2024	Feb. 08, 2025	Aug. 19, 2025	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Apr. 18, 2024	Feb. 08, 2025	Apr. 17, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 09, 2024	Feb. 08, 2025	Oct. 08, 2025	Conduction (CO01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Conducted Power Spectral Density	±0.88 dB
Frequency	±0.4 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84dB
---	--------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.02dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.22dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.34dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results

Appendix A. Test Result of Conducted Test Items

Test Engineer:	He QingSheng	Temperature:	21~25	°C
Test Date:	2025/1/13~2025/2/19	Relative Humidity:	51~54	%

TEST RESULTS DATA
Average Power Table

FCC Band I															
Mod.	Data Rate	N _{TX}	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
11a	6Mbps	2	36	Full	5180	0.15	0.12	17.21	16.94	20.09	24.00	-7.50		Pass	
11a	6Mbps	2	44	Full	5220	0.15	0.12	18.02	17.60	20.83	24.00	-7.50		Pass	
11a	6Mbps	2	48	Full	5240	0.15	0.12	18.17	17.63	20.92	24.00	-7.50		Pass	
HT20	MCS0	2	36	Full	5180	0.16	0.16	17.49	17.42	20.47	24.00	-7.50		Pass	
HT20	MCS0	2	44	Full	5220	0.16	0.16	17.95	17.52	20.75	24.00	-7.50		Pass	
HT20	MCS0	2	48	Full	5240	0.16	0.16	18.06	17.39	20.75	24.00	-7.50		Pass	
HT40	MCS0	2	38	Full	5190	0.26	0.26	13.27	13.18	16.24	24.00	-7.50		Pass	
HT40	MCS0	2	46	Full	5230	0.26	0.26	19.60	19.11	22.37	24.00	-7.50		Pass	
VHT20	MCS0	2	36	Full	5180	0.13	0.13	17.41	17.33	20.38	24.00	-7.50		Pass	
VHT20	MCS0	2	44	Full	5220	0.13	0.13	17.87	17.43	20.67	24.00	-7.50		Pass	
VHT20	MCS0	2	48	Full	5240	0.13	0.13	17.98	17.30	20.66	24.00	-7.50		Pass	
VHT40	MCS0	2	38	Full	5190	0.26	0.26	13.18	13.09	16.15	24.00	-7.50		Pass	
VHT40	MCS0	2	46	Full	5230	0.26	0.26	19.51	19.02	22.28	24.00	-7.50		Pass	
VHT80	MCS0	2	42	Full	5210	0.63	0.63	10.01	9.55	12.80	24.00	-7.50		Pass	
HE20	MCS0	2	36	Full	5180	0.17	0.17	17.58	17.49	20.54	24.00	-7.50		Pass	
			44	Full	5220	0.17	0.17	18.69	18.23	21.47	24.00	-7.50		Pass	
			48	Full	5240	0.17	0.17	18.60	18.08	21.36	24.00	-7.50		Pass	
HE40	MCS0	2	38	Full	5190	0.32	0.32	13.36	13.27	16.32	24.00	-7.50		Pass	
			46	Full	5230	0.32	0.32	19.77	19.37	22.58	24.00	-7.50		Pass	
HE80	MCS0	2	42	Full	5210	0.56	0.56	10.00	9.62	12.83	24.00	-7.50		Pass	

TEST RESULTS DATA
Average Power Table

FCC Band II																
Mod.	Data Rate	NTx	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7		
11a	6Mbps	2	52	Full	5260	0.15	0.12	18.02	17.68	20.87	23.98		-7.00		26.99	Pass
11a	6Mbps	2	60	Full	5300	0.15	0.12	18.14	17.91	21.04	23.98		-7.00		26.99	Pass
11a	6Mbps	2	64	Full	5320	0.15	0.12	18.09	18.01	21.06	23.98		-7.00		26.99	Pass
HT20	MCS0	2	52	Full	5260	0.16	0.16	18.00	17.50	20.77	23.98		-7.00		26.99	Pass
HT20	MCS0	2	60	Full	5300	0.16	0.16	18.11	17.75	20.95	23.98		-7.00		26.99	Pass
HT20	MCS0	2	64	Full	5320	0.16	0.16	17.95	17.78	20.88	23.98		-7.00		26.99	Pass
HT40	MCS0	2	54	Full	5270	0.26	0.26	19.64	19.46	22.56	23.98		-7.00		26.99	Pass
HT40	MCS0	2	62	Full	5310	0.26	0.26	17.03	16.91	19.98	23.98		-7.00		26.99	Pass
VHT20	MCS0	2	52	Full	5260	0.13	0.13	17.92	17.41	20.68	23.98		-7.00		26.99	Pass
VHT20	MCS0	2	60	Full	5300	0.13	0.13	18.03	17.66	20.86	23.98		-7.00		26.99	Pass
VHT20	MCS0	2	64	Full	5320	0.13	0.13	17.87	17.69	20.79	23.98		-7.00		26.99	Pass
VHT40	MCS0	2	54	Full	5270	0.26	0.26	19.55	19.37	22.47	23.98		-7.00		26.99	Pass
VHT40	MCS0	2	62	Full	5310	0.26	0.26	16.94	16.82	19.89	23.98		-7.00		26.99	Pass
VHT80	MCS0	2	58	Full	5290	0.63	0.63	14.32	13.87	17.11	23.98		-7.00		26.99	Pass
HE20	MCS0	2	52	Full	5260	0.17	0.17	18.57	18.29	21.44	23.98		-7.00		26.99	Pass
			60	Full	5300	0.17	0.17	18.68	18.51	21.60	23.98		-7.00		26.99	Pass
			64	Full	5320	0.17	0.17	18.64	18.50	21.58	23.98		-7.00		26.99	Pass
HE40	MCS0	2	54	Full	5270	0.32	0.32	19.72	19.77	22.75	23.98		-7.00		26.99	Pass
			62	Full	5310	0.32	0.32	17.11	17.03	20.08	23.98		-7.00		26.99	Pass
HE80	MCS0	2	58	Full	5290	0.56	0.56	14.37	14.13	17.26	23.98		-7.00		26.99	Pass

TEST RESULTS DATA
Average Power Table

FCC Band III																
Mod.	Data Rate	NTx	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7		
11a	6Mbps	2	100	Full	5500	0.15	0.12	17.56	17.43	20.51	23.98		-6.50		26.99	Pass
11a	6Mbps	2	116	Full	5580	0.15	0.12	18.04	18.14	21.10	23.98		-6.50		26.99	Pass
11a	6Mbps	2	140	Full	5700	0.15	0.12	18.05	17.70	20.89	23.98		-6.50		26.99	Pass
11a	6Mbps	2	144	Full	5720	0.15	0.12	17.96	17.68	20.84	23.98		-6.50		26.99	Pass
HT20	MCS0	2	100	Full	5500	0.16	0.16	18.05	18.02	21.05	23.98		-6.50		26.99	Pass
HT20	MCS0	2	116	Full	5580	0.16	0.16	18.05	18.18	21.13	23.98		-6.50		26.99	Pass
HT20	MCS0	2	140	Full	5700	0.16	0.16	18.06	17.74	20.92	23.98		-6.50		26.99	Pass
HT20	MCS0	2	144	Full	5720	0.16	0.16	17.97	17.72	20.86	23.98		-6.50		26.99	Pass
HT40	MCS0	2	102	Full	5510	0.26	0.26	19.01	19.12	22.08	23.98		-6.50		26.99	Pass
HT40	MCS0	2	110	Full	5550	0.26	0.26	18.82	18.97	21.91	23.98		-6.50		26.99	Pass
HT40	MCS0	2	134	Full	5670	0.26	0.26	18.24	18.62	21.44	23.98		-6.50		26.99	Pass
HT40	MCS0	2	142	Full	5710	0.26	0.26	18.61	18.50	21.57	23.98		-6.50		26.99	Pass
VHT20	MCS0	2	100	Full	5500	0.13	0.13	17.97	17.93	20.96	23.98		-6.50		26.99	Pass
VHT20	MCS0	2	116	Full	5580	0.13	0.13	17.97	18.09	21.04	23.98		-6.50		26.99	Pass
VHT20	MCS0	2	140	Full	5700	0.13	0.13	17.98	17.65	20.83	23.98		-6.50		26.99	Pass
VHT20	MCS0	2	144	Full	5720	0.13	0.13	17.89	17.63	20.77	23.98		-6.50		26.99	Pass
VHT40	MCS0	2	102	Full	5510	0.26	0.26	18.92	19.03	21.99	23.98		-6.50		26.99	Pass
VHT40	MCS0	2	110	Full	5550	0.26	0.26	18.73	18.88	21.82	23.98		-6.50		26.99	Pass
VHT40	MCS0	2	134	Full	5670	0.26	0.26	18.15	18.53	21.35	23.98		-6.50		26.99	Pass
VHT40	MCS0	2	142	Full	5710	0.26	0.26	18.52	18.41	21.48	23.98		-6.50		26.99	Pass
VHT80	MCS0	2	106	Full	5530	0.63	0.63	13.01	13.25	16.14	23.98		-6.50		26.99	Pass
VHT80	MCS0	2	122	Full	5610	0.63	0.63	18.29	18.72	21.52	23.98		-6.50		26.99	Pass
VHT80	MCS0	2	138	Full	5690	0.63	0.63	18.59	18.77	21.69	23.98		-6.50		26.99	Pass
HE20	MCS0	2	100	Full	5500	0.17	0.17	18.09	18.33	21.22	23.98		-6.50		26.99	Pass
			116	Full	5580	0.17	0.17	18.13	18.64	21.40	23.98		-6.50		26.99	Pass
			140	Full	5700	0.17	0.17	18.12	17.96	21.05	23.98		-6.50		26.99	Pass
			144	Full	5720	0.17	0.17	18.09	18.07	21.09	23.98		-6.50		26.99	Pass
HE40	MCS0	2	102	Full	5510	0.32	0.32	19.34	19.49	22.42	23.98		-6.50		26.99	Pass
			110	Full	5550	0.32	0.32	19.03	19.33	22.19	23.98		-6.50		26.99	Pass
			134	Full	5670	0.32	0.32	18.58	18.89	21.74	23.98		-6.50		26.99	Pass
			142	Full	5710	0.32	0.32	18.91	18.82	21.87	23.98		-6.50		26.99	Pass
HE80	MCS0	2	106	Full	5530	0.56	0.56	13.15	13.32	16.25	23.98		-6.50		26.99	Pass
			122	Full	5610	0.56	0.56	18.38	18.86	21.64	23.98		-6.50		26.99	Pass
			138	Full	5690	0.56	0.56	18.62	18.90	21.77	23.98		-6.50		26.99	Pass

TEST RESULTS DATA
Average Power Table

Band IV																
Mod.	Data Rate	NTx	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)			Pass/Fail
						Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7		
11a	6Mbps	2	149	Full	5745	0.15	0.12	19.31	18.40	21.89	30.00	-8.00			Pass	
11a	6Mbps	2	157	Full	5785	0.15	0.12	18.97	17.99	21.52	30.00	-8.00			Pass	
11a	6Mbps	2	165	Full	5825	0.15	0.12	19.16	18.54	21.88	30.00	-8.00			Pass	
HT20	MCS0	2	149	Full	5745	0.16	0.16	19.01	18.28	21.67	30.00	-8.00			Pass	
HT20	MCS0	2	157	Full	5785	0.16	0.16	19.02	18.23	21.66	30.00	-8.00			Pass	
HT20	MCS0	2	165	Full	5825	0.16	0.16	18.98	18.47	21.75	30.00	-8.00			Pass	
HT40	MCS0	2	151	Full	5755	0.26	0.26	19.40	18.65	22.05	30.00	-8.00			Pass	
HT40	MCS0	2	159	Full	5795	0.26	0.26	19.36	18.70	22.05	30.00	-8.00			Pass	
VHT20	MCS0	2	149	Full	5745	0.13	0.13	18.90	18.17	21.56	30.00	-8.00			Pass	
VHT20	MCS0	2	157	Full	5785	0.13	0.13	18.91	18.12	21.54	30.00	-8.00			Pass	
VHT20	MCS0	2	165	Full	5825	0.13	0.13	18.87	18.36	21.63	30.00	-8.00			Pass	
VHT40	MCS0	2	151	Full	5755	0.26	0.26	19.31	18.56	21.96	30.00	-8.00			Pass	
VHT40	MCS0	2	159	Full	5795	0.26	0.26	19.27	18.61	21.96	30.00	-8.00			Pass	
VHT80	MCS0	2	155	Full	5775	0.63	0.63	19.48	18.93	22.22	30.00	-8.00			Pass	
HE20	MCS0	2	149	Full	5745	0.17	0.17	19.18	18.42	21.82	30.00	-8.00			Pass	
HE20	MCS0	2	157	Full	5785	0.17	0.17	19.20	18.42	21.84	30.00	-8.00			Pass	
HE20	MCS0	2	165	Full	5825	0.17	0.17	19.18	18.67	21.94	30.00	-8.00			Pass	
HE40	MCS0	2	151	Full	5755	0.32	0.32	19.66	18.99	22.34	30.00	-8.00			Pass	
HE40	MCS0	2	159	Full	5795	0.32	0.32	19.65	19.02	22.35	30.00	-8.00			Pass	
HE80	MCS0	2	155	Full	5775	0.56	0.56	19.59	19.04	22.34	30.00	-8.00			Pass	

TEST RESULTS DATA
Average Power Table

FCC Band I																
Mod.	Data Rate	N _{TX}	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)			Pass/Fail
						Ant 6	Ant 10	Ant 6	Ant 10	SUM	Ant 6	Ant 10	Ant 6	Ant 10		
11a	6Mbps	2	36	Full	5180	0.12	0.12	18.14	18.10	21.13	24.00		-7.50			Pass
11a	6Mbps	2	44	Full	5220	0.12	0.12	18.01	17.62	20.83	24.00		-7.50			Pass
11a	6Mbps	2	48	Full	5240	0.12	0.12	17.54	17.18	20.38	24.00		-7.50			Pass
HT20	MCS0	2	36	Full	5180	0.16	0.16	18.03	18.17	21.11	24.00		-7.50			Pass
HT20	MCS0	2	44	Full	5220	0.16	0.16	17.98	17.68	20.85	24.00		-7.50			Pass
HT20	MCS0	2	48	Full	5240	0.16	0.16	17.94	17.58	20.78	24.00		-7.50			Pass
HT40	MCS0	2	38	Full	5190	0.26	0.26	17.67	17.65	20.67	24.00		-7.50			Pass
HT40	MCS0	2	46	Full	5230	0.26	0.26	19.75	19.53	22.65	24.00		-7.50			Pass
VHT20	MCS0	2	36	Full	5180	0.13	0.13	17.95	18.07	21.02	24.00		-7.50			Pass
VHT20	MCS0	2	44	Full	5220	0.13	0.13	17.90	17.58	20.75	24.00		-7.50			Pass
VHT20	MCS0	2	48	Full	5240	0.13	0.13	17.86	17.48	20.68	24.00		-7.50			Pass
VHT40	MCS0	2	38	Full	5190	0.26	0.26	17.59	17.57	20.59	24.00		-7.50			Pass
VHT40	MCS0	2	46	Full	5230	0.26	0.26	19.67	19.45	22.57	24.00		-7.50			Pass
VHT80	MCS0	2	42	Full	5210	0.63	0.63	14.99	14.69	17.85	24.00		-7.50			Pass
HE20	MCS0	2	36	Full	5180	0.17	0.17	18.62	18.69	21.66	24.00		-7.50			Pass
			44	Full	5220	0.17	0.17	18.60	18.38	21.50	24.00		-7.50			Pass
			48	Full	5240	0.17	0.17	18.52	18.26	21.40	24.00		-7.50			Pass
HE40	MCS0	2	38	Full	5190	0.39	0.39	17.78	17.69	20.75	24.00		-7.50			Pass
			46	Full	5230	0.39	0.39	19.91	19.70	22.82	24.00		-7.50			Pass
HE80	MCS0	2	42	Full	5210	0.56	0.56	15.01	14.75	17.89	24.00		-7.50			Pass

TEST RESULTS DATA
Average Power Table

FCC Band II																
Mod.	Data Rate	NTx	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 6	Ant 10	Ant 6	Ant 10	SUM	Ant 6	Ant 10	Ant 6	Ant 10		
11a	6Mbps	2	52	Full	5260	0.12	0.12	18.07	17.88	20.99	23.98		-7.00		26.99	Pass
11a	6Mbps	2	60	Full	5300	0.12	0.12	18.28	18.11	21.21	23.98		-7.00		26.99	Pass
11a	6Mbps	2	64	Full	5320	0.12	0.12	18.09	18.15	21.13	23.98		-7.00		26.99	Pass
HT20	MCS0	2	52	Full	5260	0.16	0.16	17.97	17.74	20.87	23.98		-7.00		26.99	Pass
HT20	MCS0	2	60	Full	5300	0.16	0.16	18.03	17.92	20.99	23.98		-7.00		26.99	Pass
HT20	MCS0	2	64	Full	5320	0.16	0.16	18.45	18.36	21.42	23.98		-7.00		26.99	Pass
HT40	MCS0	2	54	Full	5270	0.26	0.26	19.76	19.86	22.82	23.98		-7.00		26.99	Pass
HT40	MCS0	2	62	Full	5310	0.26	0.26	19.23	19.27	22.26	23.98		-7.00		26.99	Pass
VHT20	MCS0	2	52	Full	5260	0.13	0.13	17.89	17.64	20.78	23.98		-7.00		26.99	Pass
VHT20	MCS0	2	60	Full	5300	0.13	0.13	17.95	17.82	20.90	23.98		-7.00		26.99	Pass
VHT20	MCS0	2	64	Full	5320	0.13	0.13	18.37	18.26	21.33	23.98		-7.00		26.99	Pass
VHT40	MCS0	2	54	Full	5270	0.26	0.26	19.68	19.78	22.74	23.98		-7.00		26.99	Pass
VHT40	MCS0	2	62	Full	5310	0.26	0.26	19.15	19.19	22.18	23.98		-7.00		26.99	Pass
VHT80	MCS0	2	58	Full	5290	0.63	0.63	16.10	16.00	19.06	23.98		-7.00		26.99	Pass
HE20	MCS0	2	52	Full	5260	0.17	0.17	18.49	18.32	21.41	23.98		-7.00		26.99	Pass
			60	Full	5300	0.17	0.17	18.58	18.49	21.54	23.98		-7.00		26.99	Pass
			64	Full	5320	0.17	0.17	18.56	18.54	21.56	23.98		-7.00		26.99	Pass
HE40	MCS0	2	54	Full	5270	0.39	0.39	19.94	19.98	22.97	23.98		-7.00		26.99	Pass
			62	Full	5310	0.39	0.39	19.39	19.35	22.38	23.98		-7.00		26.99	Pass
HE80	MCS0	2	58	Full	5290	0.56	0.56	16.14	16.13	19.15	23.98		-7.00		26.99	Pass

TEST RESULTS DATA
Average Power Table

FCC Band III																
Mod.	Data Rate	NTx	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 6	Ant 10	Ant 6	Ant 10	SUM	Ant 6	Ant 10	Ant 6	Ant 10		
11a	6Mbps	2	100	Full	5500	0.12	0.12	17.58	17.69	20.65	23.98		-6.50		26.99	Pass
11a	6Mbps	2	116	Full	5580	0.12	0.12	18.17	18.45	21.32	23.98		-6.50		26.99	Pass
11a	6Mbps	2	140	Full	5700	0.12	0.12	18.24	18.01	21.14	23.98		-6.50		26.99	Pass
11a	6Mbps	2	144	Full	5720	0.12	0.12	18.16	18.06	21.12	23.98		-6.50		26.99	Pass
HT20	MCS0	2	100	Full	5500	0.16	0.16	18.09	18.10	21.11	23.98		-6.50		26.99	Pass
HT20	MCS0	2	116	Full	5580	0.16	0.16	18.30	18.50	21.42	23.98		-6.50		26.99	Pass
HT20	MCS0	2	140	Full	5700	0.16	0.16	17.69	17.50	20.61	23.98		-6.50		26.99	Pass
HT20	MCS0	2	144	Full	5720	0.16	0.16	18.31	18.24	21.29	23.98		-6.50		26.99	Pass
HT40	MCS0	2	102	Full	5510	0.26	0.26	18.73	18.94	21.85	23.98		-6.50		26.99	Pass
HT40	MCS0	2	110	Full	5550	0.26	0.26	18.98	19.30	22.15	23.98		-6.50		26.99	Pass
HT40	MCS0	2	134	Full	5670	0.26	0.26	18.62	18.81	21.73	23.98		-6.50		26.99	Pass
HT40	MCS0	2	142	Full	5710	0.26	0.26	18.84	18.72	21.79	23.98		-6.50		26.99	Pass
VHT20	MCS0	2	100	Full	5500	0.13	0.13	18.01	18.00	21.02	23.98		-6.50		26.99	Pass
VHT20	MCS0	2	116	Full	5580	0.13	0.13	18.22	18.40	21.32	23.98		-6.50		26.99	Pass
VHT20	MCS0	2	140	Full	5700	0.13	0.13	17.61	17.40	20.52	23.98		-6.50		26.99	Pass
VHT20	MCS0	2	144	Full	5720	0.13	0.13	18.23	18.14	21.20	23.98		-6.50		26.99	Pass
VHT40	MCS0	2	102	Full	5510	0.26	0.26	18.65	18.86	21.76	23.98		-6.50		26.99	Pass
VHT40	MCS0	2	110	Full	5550	0.26	0.26	18.90	19.22	22.07	23.98		-6.50		26.99	Pass
VHT40	MCS0	2	134	Full	5670	0.26	0.26	18.54	18.73	21.64	23.98		-6.50		26.99	Pass
VHT40	MCS0	2	142	Full	5710	0.26	0.26	18.76	18.64	21.71	23.98		-6.50		26.99	Pass
VHT80	MCS0	2	106	Full	5530	0.63	0.63	15.46	15.65	18.57	23.98		-6.50		26.99	Pass
VHT80	MCS0	2	122	Full	5610	0.63	0.63	18.71	18.95	21.84	23.98		-6.50		26.99	Pass
VHT80	MCS0	2	138	Full	5690	0.63	0.63	19.00	19.02	22.02	23.98		-6.50		26.99	Pass
HE20	MCS0	2	100	Full	5500	0.17	0.17	18.36	18.45	21.41	23.98		-6.50		26.99	Pass
			116	Full	5580	0.17	0.17	18.45	18.79	21.63	23.98		-6.50		26.99	Pass
			140	Full	5700	0.17	0.17	17.95	17.68	20.83	23.98		-6.50		26.99	Pass
			144	Full	5720	0.17	0.17	18.41	18.36	21.39	23.98		-6.50		26.99	Pass
HE40	MCS0	2	102	Full	5510	0.39	0.39	19.01	19.27	22.15	23.98		-6.50		26.99	Pass
			110	Full	5550	0.39	0.39	19.36	19.59	22.49	23.98		-6.50		26.99	Pass
			134	Full	5670	0.39	0.39	18.93	19.05	22.00	23.98		-6.50		26.99	Pass
			142	Full	5710	0.39	0.39	19.19	19.10	22.16	23.98		-6.50		26.99	Pass
HE80	MCS0	2	106	Full	5530	0.56	0.56	15.51	15.70	18.62	23.98		-6.50		26.99	Pass
			122	Full	5610	0.56	0.56	18.77	19.05	21.92	23.98		-6.50		26.99	Pass
			138	Full	5690	0.56	0.56	19.09	19.12	22.12	23.98		-6.50		26.99	Pass

TEST RESULTS DATA
Average Power Table

Band IV																
Mod.	Data Rate	N _{Tx}	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)			Pass/Fail
						Ant 6	Ant 10	Ant 6	Ant 10	SUM	Ant 6	Ant 10	Ant 6	Ant 10		
11a	6Mbps	2	149	Full	5745	0.12	0.12	19.44	18.80	22.14	30.00	-8.00			Pass	
11a	6Mbps	2	157	Full	5785	0.12	0.12	19.11	18.43	21.80	30.00	-8.00			Pass	
11a	6Mbps	2	165	Full	5825	0.12	0.12	19.28	18.90	22.11	30.00	-8.00			Pass	
HT20	MCS0	2	149	Full	5745	0.16	0.16	19.32	18.58	21.98	30.00	-8.00			Pass	
HT20	MCS0	2	157	Full	5785	0.16	0.16	19.15	18.40	21.81	30.00	-8.00			Pass	
HT20	MCS0	2	165	Full	5825	0.16	0.16	19.25	18.77	22.03	30.00	-8.00			Pass	
HT40	MCS0	2	151	Full	5755	0.26	0.26	19.65	18.96	22.33	30.00	-8.00			Pass	
HT40	MCS0	2	159	Full	5795	0.26	0.26	19.54	19.01	22.29	30.00	-8.00			Pass	
VHT20	MCS0	2	149	Full	5745	0.13	0.13	19.21	18.47	21.87	30.00	-8.00			Pass	
VHT20	MCS0	2	157	Full	5785	0.13	0.13	19.04	18.29	21.69	30.00	-8.00			Pass	
VHT20	MCS0	2	165	Full	5825	0.13	0.13	19.14	18.66	21.92	30.00	-8.00			Pass	
VHT40	MCS0	2	151	Full	5755	0.26	0.26	19.58	18.89	22.25	30.00	-8.00			Pass	
VHT40	MCS0	2	159	Full	5795	0.26	0.26	19.47	18.94	22.22	30.00	-8.00			Pass	
VHT80	MCS0	2	155	Full	5775	0.63	0.63	19.82	19.40	22.63	30.00	-8.00			Pass	
HE20	MCS0	2	149	Full	5745	0.17	0.17	19.42	18.71	22.09	30.00	-8.00			Pass	
HE20	MCS0	2	157	Full	5785	0.17	0.17	19.36	18.71	22.06	30.00	-8.00			Pass	
HE20	MCS0	2	165	Full	5825	0.17	0.17	19.30	18.86	22.09	30.00	-8.00			Pass	
HE40	MCS0	2	151	Full	5755	0.39	0.39	19.92	19.21	22.59	30.00	-8.00			Pass	
HE40	MCS0	2	159	Full	5795	0.39	0.39	19.78	19.23	22.53	30.00	-8.00			Pass	
HE80	MCS0	2	155	Full	5775	0.56	0.56	19.87	19.45	22.68	30.00	-8.00			Pass	



<Ant. 6+7>

Emission Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	26dB EBW [MHz]	FL[MHz]	FH[MHz]
11A-CDD	Ant6	5180	24.20	5167.10	5191.30
	Ant7	5180	22.30	5169.50	5191.80
	Ant6	5220	20.10	5209.90	5230.00
	Ant7	5220	19.80	5209.90	5229.70
	Ant6	5240	20.10	5229.90	5250.00
	Ant7	5240	20.10	5229.80	5249.90
	Ant6	5260	20.30	5249.80	5270.10
	Ant7	5260	20.50	5249.90	5270.40
	Ant6	5300	26.80	5286.20	5313.00
	Ant7	5300	27.70	5285.60	5313.30
	Ant6	5320	25.00	5307.00	5332.00
	Ant7	5320	24.80	5306.60	5331.40
	Ant6	5500	26.10	5487.70	5513.80
	Ant7	5500	24.70	5488.00	5512.70
	Ant6	5580	20.70	5569.70	5590.40
	Ant7	5580	20.90	5569.80	5590.70
	Ant6	5700	22.80	5687.70	5710.50
	Ant7	5700	23.80	5686.70	5710.50
	Ant6	5720	20.90	5709.60	5730.50
	Ant7	5720	21.10	5708.80	5729.90
	Ant6	5745	22.70	5734.80	5757.50
	Ant7	5745	25.00	5732.00	5757.00
	Ant6	5785	23.60	5774.00	5797.60
	Ant7	5785	23.40	5773.80	5797.20
	Ant6	5825	29.70	5808.60	5838.30
	Ant7	5825	24.40	5810.90	5835.30
11N20MIMO	Ant6	5180	24.20	5169.00	5193.20
	Ant7	5180	23.40	5168.60	5192.00
	Ant6	5220	21.80	5209.10	5230.90
	Ant7	5220	21.20	5209.20	5230.40
	Ant6	5240	21.60	5229.20	5250.80
	Ant7	5240	21.90	5229.20	5251.10
	Ant6	5260	21.50	5249.10	5270.60
	Ant7	5260	21.30	5249.20	5270.50
	Ant6	5300	27.20	5285.80	5313.00



	Ant7	5300	27.80	5286.20	5314.00
	Ant6	5320	23.60	5307.80	5331.40
	Ant7	5320	26.60	5304.80	5331.40
	Ant6	5500	28.70	5485.90	5514.60
	Ant7	5500	25.00	5488.60	5513.60
	Ant6	5580	23.20	5568.00	5591.20
	Ant7	5580	23.00	5567.80	5590.80
	Ant6	5700	22.60	5688.00	5710.60
	Ant7	5700	24.70	5686.10	5710.80
	Ant6	5720	21.30	5709.10	5730.40
	Ant7	5720	21.90	5708.60	5730.50
	Ant6	5745	23.80	5734.20	5758.00
	Ant7	5745	24.70	5733.00	5757.70
	Ant6	5785	25.60	5772.00	5797.60
	Ant7	5785	24.30	5773.00	5797.30
	Ant6	5825	28.70	5808.70	5837.40
	Ant7	5825	25.40	5810.90	5836.30
11N40MIMO	Ant6	5190	52.60	5165.80	5218.40
	Ant7	5190	49.80	5165.20	5215.00
	Ant6	5230	59.20	5197.20	5256.40
	Ant7	5230	59.20	5197.20	5256.40
	Ant6	5270	62.40	5240.80	5303.20
	Ant7	5270	60.20	5243.00	5303.20
	Ant6	5310	57.80	5277.20	5335.00
	Ant7	5310	46.20	5284.20	5330.40
	Ant6	5510	51.40	5485.20	5536.60
	Ant7	5510	42.60	5489.40	5532.00
	Ant6	5550	59.20	5517.20	5576.40
	Ant7	5550	45.40	5529.60	5575.00
	Ant6	5670	62.60	5637.20	5699.80
	Ant7	5670	58.20	5640.60	5698.80
	Ant6	5710	55.00	5677.20	5732.20
	Ant7	5710	52.80	5677.40	5730.20
	Ant6	5755	54.40	5734.20	5788.60
	Ant7	5755	47.00	5734.40	5781.40
	Ant6	5795	67.60	5760.60	5828.20
	Ant7	5795	55.60	5765.60	5821.20
11AC80MIMO	Ant6	5210	112.80	5163.20	5276.00
	Ant7	5210	100.00	5162.80	5262.80
	Ant6	5290	105.60	5231.20	5336.80
	Ant7	5290	95.20	5240.40	5335.60
	Ant6	5530	116.00	5483.60	5599.60



	Ant7	5530	98.80	5487.60	5586.40
	Ant6	5610	91.60	5562.40	5654.00
	Ant7	5610	80.80	5569.60	5650.40
	Ant6	5690	82.40	5649.20	5731.60
	Ant7	5690	80.40	5649.60	5730.00
	Ant6	5775	161.20	5691.40	5852.60
	Ant7	5775	94.00	5735.00	5829.00
11AX20MIMO	Ant6	5180	23.50	5169.00	5192.50
	Ant7	5180	23.50	5167.90	5191.40
	Ant6	5220	22.30	5209.00	5231.30
	Ant7	5220	22.30	5208.60	5230.90
	Ant6	5240	21.80	5229.20	5251.00
	Ant7	5240	21.40	5229.30	5250.70
	Ant6	5260	21.30	5249.30	5270.60
	Ant7	5260	21.30	5249.30	5270.60
	Ant6	5300	24.60	5287.60	5312.20
	Ant7	5300	31.10	5284.40	5315.50
	Ant6	5320	27.50	5305.30	5332.80
	Ant7	5320	25.00	5306.00	5331.00
	Ant6	5500	30.40	5485.70	5516.10
	Ant7	5500	28.40	5485.90	5514.30
	Ant6	5580	22.20	5569.10	5591.30
	Ant7	5580	21.20	5569.30	5590.50
	Ant6	5700	23.90	5687.10	5711.00
	Ant7	5700	27.40	5684.40	5711.80
	Ant6	5720	23.40	5707.50	5730.90
	Ant7	5720	22.80	5707.80	5730.60
	Ant6	5745	24.80	5733.90	5758.70
	Ant7	5745	23.80	5734.20	5758.00
	Ant6	5785	21.70	5774.20	5795.90
	Ant7	5785	21.80	5774.40	5796.20
	Ant6	5825	27.10	5808.90	5836.00
	Ant7	5825	24.50	5811.30	5835.80
11AX40MIMO	Ant6	5190	46.00	5170.00	5216.00
	Ant7	5190	42.40	5167.60	5210.00
	Ant6	5230	40.00	5210.00	5250.00
	Ant7	5230	42.80	5209.80	5252.60
	Ant6	5270	40.00	5250.00	5290.00
	Ant7	5270	39.80	5250.20	5290.00
	Ant6	5310	40.80	5289.20	5330.00
	Ant7	5310	45.40	5284.80	5330.20
	Ant6	5510	49.20	5489.40	5538.60



	Ant7	5510	48.40	5490.00	5538.40
	Ant6	5550	40.00	5530.00	5570.00
	Ant7	5550	40.00	5530.00	5570.00
	Ant6	5670	54.00	5641.80	5695.80
	Ant7	5670	53.40	5645.20	5698.60
	Ant6	5710	45.00	5690.00	5735.00
	Ant7	5710	39.80	5690.00	5729.80
	Ant6	5755	51.00	5735.00	5786.00
	Ant7	5755	44.60	5735.00	5779.60
	Ant6	5795	54.40	5769.00	5823.40
	Ant7	5795	40.00	5775.00	5815.00
11AX80MIMO	Ant6	5210	81.60	5169.20	5250.80
	Ant7	5210	82.00	5168.80	5250.80
	Ant6	5290	85.20	5245.60	5330.80
	Ant7	5290	81.60	5249.20	5330.80
	Ant6	5530	90.40	5489.20	5579.60
	Ant7	5530	93.60	5489.60	5583.20
	Ant6	5610	81.60	5569.20	5650.80
	Ant7	5610	81.60	5569.20	5650.80
	Ant6	5690	81.20	5649.20	5730.40
	Ant7	5690	81.20	5649.20	5730.40
	Ant6	5775	117.20	5718.20	5835.40
	Ant7	5775	81.20	5734.60	5815.80



Test Graphs

