

# SAR TEST REPORT

## No. I19Z60737-SEM02

## For

Samsung Electronics Co Ltd

Tablet

Model name: SM-T290

## With

Hardware Version: Rev0.4

Software Version: T290XXU1ASF1

FCC ID: ZCASMT290

Issued Date: 2019-6-25

TESTING NVLAP LAB CODE 600118-0

#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

#### Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191. Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504 Email: <u>cttl\_terminals@caict.ac.cn</u>, website: <u>www.caict.ac.cn</u>



## **REPORT HISTORY**

Report Number	Revision	Issue Date	Description
I19Z60737-SEM02	Rev.0	2019-6-24	Initial creation of test report
I19Z60737-SEM02	Rev.1	2019-6-25	Update conducted output power 5G WiFi 802.11n(20) on page 21. Remove this description: "the BT and Wi-Fi can transmit simultaneous with other transmitters." Update the probe ConvF for WiFi 802.11a on 5600MHz. Update the conducted power reduced information on page 24 and 88



## TABLE OF CONTENT

1 TEST LABORATORY	5
1.1 INTRODUCTION & ACCREDITATION	5
1.2 TESTING LOCATION	5
1.3 TESTING ENVIRONMENT	5
1.4 Project Data	5
1.5 Signature	5
2 STATEMENT OF COMPLIANCE	6
3 CLIENT INFORMATION	7
3.1 APPLICANT INFORMATION	7
3.2 MANUFACTURER INFORMATION	7
4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	8
4.1 About EUT	
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	8
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	8
5 TEST METHODOLOGY	9
5.1 APPLICABLE LIMIT REGULATIONS	9
5.2 Applicable Measurement Standards	9
6 SPECIFIC ABSORPTION RATE (SAR)	10
6.1 INTRODUCTION	
6.2 SAR DEFINITION	10
7 TISSUE SIMULATING LIQUIDS	11
7.1 TARGETS FOR TISSUE SIMULATING LIQUID	
7.2 DIELECTRIC PERFORMANCE	11
8 SYSTEM VERIFICATION	13
8.1 System Setup	
8.2 System Verification	14
9 MEASUREMENT PROCEDURES	15
9.1 Tests to be performed	
9.2 GENERAL MEASUREMENT PROCEDURE	17
9.3 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR	
9.4 Power Drift	
10 AREA SCAN BASED 1-G SAR	19
10.1 REQUIREMENT OF KDB	19
10.2 FAST SAR ALGORITHMS	19
11 WI-FI AND BT MEASUREMENT RESULT	20



## No.I19Z60737-SEM02 Page 4 of 91

12 SIMUL	TANEOUS TX SAR CONSIDERATIONS	24
12.1 Intro	DUCTION	24
12.2 TRAN	SMIT ANTENNA SEPARATION DISTANCES	24
12.3 SAR	MEASUREMENT POSITIONS	25
12.4 STAN	DALONE SAR TEST EXCLUSION CONSIDERATIONS	25
13 SAR TE	EST RESULT	26
13.1 WLA	N EVALUATION FOR 2.4G	26
13.2 WLA	N EVALUATION FOR 5G	28
14 SAR M	EASUREMENT VARIABILITY	32
15 MEASU	JREMENT UNCERTAINTY	33
16.1 MEAS	SUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (300MHz~3GHz)	33
16.2 MEAS	SUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (3~6GHz)	34
16.3 MEAS	SUREMENT UNCERTAINTY FOR FAST SAR TESTS (300MHz~3GHz)	35
16.4 MEAS	SUREMENT UNCERTAINTY FOR FAST SAR TESTS (3~6GHz)	36
16 MAIN T	EST INSTRUMENTS	37
ANNEX A	GRAPH RESULT	38
ANNEX B	SYSTEM VERIFICATION RESULTS	42
ANNEX C	SAR MEASUREMENT SETUP	46
ANNEX D	POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM	52
ANNEX E	EQUIVALENT MEDIA RECIPES	54
ANNEX F	SYSTEM VALIDATION	55
ANNEX G	PROBE CALIBRATION CERTIFICATE	56
ANNEX H	DIPOLE CALIBRATION CERTIFICATE	67
ANNEX I	SENSOR TRIGGERING DATA SUMMARY	88
ANNEX J	ACCREDITATION CERTIFICATE	91

## **1 Test Laboratory**

#### 1.1 Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

#### **1.2 Testing Location**

Company Name:	CTTL(Shouxiang)
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District,
	Beijing, P. R. China100191

#### **1.3 Testing Environment**

Temperature:	Relative humidity:	Ground system resistance:	Ambient noise & Reflection:
18°C~25°C	30%~ 70%	< 0.5 Ω	< 0.012 W/kg

#### 1.4 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	June 19, 2019
Testing End Date:	June 20, 2019

#### 1.5 Signature

Lin Xiaojun (Prepared this test report)



Qi Dianyuan (Reviewed this test report)

Lu Bingsong Deputy Director of the laboratory (Approved this test report)



## **2 Statement of Compliance**

The maximum results of SAR found during testing for Samsung Electronics Co Ltd. Tablet SM-T290 are as follows:

<b>J</b>					
Exposure Configuration	Technology Band	Highest Reported SAR 1g(W/kg)	Equipment Class		
Hotspot	WLAN 2.4 GHz	0.66	DTS		
(Separation Distance 0mm)	WLAN 5 GHz	0.80	UNII		

Table 2.	1: Highest	Reported	SAR	(1g)
----------	------------	----------	-----	------

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1992.

For body operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 0/4/9mm between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report. The highest reported SAR value is obtained at the case of **(Table 2.1)**, and the values are: **0.80 W/kg(1g)**.



## **3 Client Information**

## **3.1 Applicant Information**

Company Name:	Samsung Electronics Co Ltd
Address/Post:	19 Chapin Rd.,Building D Pine Brook, NJ 07058
Contact Person:	Jenni Chun
E-mail:	1
Telephone:	1
Fax:	/

## 3.2 Manufacturer Information

Company Name:	Jiaxing Yongrui Electron Technology Co., Ltd.			
Address /Dest	NO.777 Yazhong Road, Daqiao Town, Nanhu District, Jiaxing			
Address/Post.	City ,Zhejiang			
Contact Person:	1			
E-mail:	1			
Telephone:	1			
Fax:	1			



## 4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 4.1 About EUT

Description:	Tablet
Model name:	SM-T290
Operating mode(s):	BT, Wi-Fi
Tostad Tx Fraguenov	2412 – 2462 MHz (Wi-Fi 2.4G)
Tested 1x Frequency.	5150-5825 MHz (Wi-Fi 5G)
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna

#### 4.2 Internal Identification of EUT used during the test

EUT ID*	SN	HW	SW Version
EUT1	R0WM5002CWJ	Rev0.4	T290XXU1ASF1
EUT2	15ec7d3d7d06	Rev0.4	T290XXU1ASF1

\*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test SAR with the EUT1&2 and conducted power with the EUT1.

#### 4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	SWD-WT-N8	/	Sunwoda Electronic Co., Ltd .
AE2	Battery	SCUD-WT-N8	/	SCUD(Fujian) Electronic Co., Ltd.
AE3	Headset	GH59-15054A	/	WATA

\*AE ID: is used to identify the test sample in the lab internally.



## **5 TEST METHODOLOGY**

#### 5.1 Applicable Limit Regulations

**ANSI C95.1–1992:**IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

#### 5.2 Applicable Measurement Standards

**IEEE 1528–2013:** Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

**KDB447498 D01: General RF Exposure Guidance v06:** Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

**KDB941225 D06 Hotspot Mode SAR v02r01:** SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227 D01 802.11 Wi-Fi SAR v02r02: SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

**KDB865664 D01SAR measurement 100 MHz to 6 GHz v01r04:** SAR Measurement Requirements for 100 MHz to 6 GHz.

**KDB865664 D02RF Exposure Reporting v01r02:** RF Exposure Compliance Reporting and Documentation Considerations



## 6 Specific Absorption Rate (SAR)

#### 6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

#### 6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density  $(\rho)$ . The equation description is as below:

$$SAR = \frac{d}{dt}(\frac{dW}{dm}) = \frac{d}{dt}(\frac{dW}{\rho dv})$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c(\frac{\delta T}{\delta t})$$

Where: C is the specific head capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.



## 7 Tissue Simulating Liquids

#### 7.1 Targets for tissue simulating liquid

#### Table 7.1: Targets for tissue simulating liquid

Frequency(MHz)	Liquid Type	Conductivity(o)	± 5% Range	Permittivity(ε)	± 5% Range
2450	Body	1.95	1.85~2.05	52.7	50.1~55.3
5250	Body	5.36	5.09~5.63	48.9	46.5~51.3
5600	Body	5.77	5.48~6.06	48.5	46.1~50.9
5750	Body	5.94	5.64~6.24	48.3	45.9~50.7

## 7.2 Dielectric Performance

#### Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Туре	Frequency	Permittivity ε	Drift (%)	Conductivity σ (S/m)	Drift (%)
2019.6.19	Body	2450 MHz	52.16	-1.02	1.96	0.51
	Body	5250 MHz	47.09	-3.70	5.274	-1.60
2019.6.20	Body	5600 MHz	47.14	-2.80	5.719	-0.88
	Body	5750 MHz	46.25	-4.24	5.856	-1.41

Note: The liquid temperature is 22.0°C



Picture 7-1 Liquid depth in the Flat Phantom (2450MHz)





Picture 7-2 Liquid depth in the Flat Phantom (5GHz)



## 8 System verification

#### 8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup



#### 8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Measurement		Target val	ue (W/kg)	Measured	/alue (W/kg)	Deviation					
Date	Frequency	10 g 1 g		10 g	1 g	10 g	1 g				
(yyyy-mm-dd)		Average	Average	Average	Average	Average	Average				
2019.6.19	2450 MHz	24.1	51.3	24.16	51.40	0.25%	0.19%				
	5250 MHz	21.2	75.7	20.76	74.10	-2.08%	-2.11%				
2019.6.20	5600 MHz	22.1	78.6	22.50	79.50	1.81%	1.15%				
	5750 MHz	21.4	76.9	20.76	75.50	-2.99%	-1.82%				

#### Table 8.2: System Verification of Body



## **9 Measurement Procedures**

#### 9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.

Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of

the transmit frequency band ( $f_c$ ) for:

a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),

b) all configurations for each device position in a), e.g., antenna extended and retracted, and

c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e.,  $N_c > 3$ ), then all

frequencies, configurations and modes shall be tested for all of the above test conditions.

**Step 2**: For the condition providing highest peak spatial-average SAR determined in Step 1,perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

**Step 3**: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Preparation of system







#### 9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

			$\leq$ 3 GHz	> 3 GHz		
Maximum distance from (geometric center of pro	closest me be sensors)	asurement point to phantom surface	$5 \pm 1 \text{ mm}$	$\frac{1}{2}\cdot\delta\cdot\ln(2)\pm0.5~mm$		
Maximum probe angle fi normal at the measureme	rom probe a ent location	xis to phantom surface	30°±1°	20°±1°		
			$\leq 2 \text{ GHz:} \leq 15 \text{ mm}$ $2 - 3 \text{ GHz:} \leq 12 \text{ mm}$	$\begin{array}{l} 3-4 \ \mathrm{GHz:} \leq 12 \ \mathrm{mm} \\ 4-6 \ \mathrm{GHz:} \leq 10 \ \mathrm{mm} \end{array}$		
Maximum area scan spa	tial resolutio	on: Δx <sub>Area</sub> , Δy <sub>Area</sub>	When the x or y dimension of the measurement plane orientation, measurement resolution must be dimension of the test device with point on the test device.	he test device, in the is smaller than the above, the $e \le $ the corresponding x or y th at least one measurement		
Maximum zoom scan sp	atial resolut	ion: Δx <sub>Zoom</sub> , Δy <sub>Zoom</sub>	$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ 2 - 3 GHz: $\leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz:} \le 5 \text{ mm}^4$ $4 - 6 \text{ GHz:} \le 4 \text{ mm}^4$		
	uniform g	nid: ∆z <sub>Zoom</sub> (n)	$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz} \le 4 \text{ mm}$ $4 - 5 \text{ GHz} \le 3 \text{ mm}$ $5 - 6 \text{ GHz} \le 2 \text{ mm}$		
Maximum zoom scan spatial resolution, normal to phantom surface	graded	$\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	≤4 mm	$3 - 4 \text{ GHz:} \le 3 \text{ mm}$ $4 - 5 \text{ GHz:} \le 2.5 \text{ mm}$ $5 - 6 \text{ GHz:} \le 2 \text{ mm}$		
	grid	∆z <sub>Zoom</sub> (n>1): between subsequent points	$\leq 1.5 \cdot \Delta z$	Zoom(n-1)		
Minimum zoom scan volume	x, y, z	·	≥ 30 mm	$3 - 4 \text{ GHz} \ge 28 \text{ mm}$ $4 - 5 \text{ GHz} \ge 25 \text{ mm}$ $5 - 6 \text{ GHz} \ge 22 \text{ mm}$		
Note: δ is the penetration 2011 for details.	n depth of a	plane-wave at normal inc	ridence to the tissue medium; see	draft standard IEEE P1528-		

\* When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.



#### 9.3 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

#### 9.4 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in section14 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.



## 10 Area Scan Based 1-g SAR

#### 10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-gSAR is  $\leq$  1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

#### **10.2 Fast SAR Algorithms**

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz)and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm mare 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.



## 11 Wi-Fi and BT Measurement result

The maximum output power of BT channel 64 is 5.13dBm. The maximum tune up of BT is 6.5dBm.

There are two sets of tune-up power, Normal power and Low power, for all band by proximity sensor.

#### The Normal power for WiFi is as following:

802.11b (dBm)

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
11	/	/	16.80	/
6	/	/	17.16	/
1	16.70	16.68	17.30	16.76
Tune up	18.50	18.50	18.50	18.50

802.11g (dBm)

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1	16.29	/	/	/	/	/	/	/
6	15.83	/	/	/	/	/	/	/
11	16.29	15.75	15.29	14.82	14.31	13.82	13.32	13.31
Tune up	17.50	17.00	17.00	16.00	15.50	15.00	14.50	14.50

802.11n (dBm) - HT20 (2.4G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1	15.38	/	/	/	/	/	/	/
6	15.09	/	/	/	/	/	/	/
11	15.38	14.91	14.90	14.37	14.35	13.95	13.84	13.35
Tune up	16.50	16.00	16.00	15.50	15.50	15.00	15.00	14.50

## No.I19Z60737-SEM02 Page 21 of 91



802.11a (dBm)										
Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps		
36(5180 MHz)	15.75	15.36	15.35	14.81	14.82	14.34	14.33	13.75		
40(5200 MHz)	15.67	/	/	/	/	/	/	/		
44(5220 MHz)	15.66	/	/	/	/	/	/	/		
48(5240 MHz)	15.66	/	/	/	/	/	/	/		
52(5260 MHz)	15.51	/	/	/	/	/	/	/		
56(5280 MHz)	15.52	/	/	/	/	/	/	/		
60(5300 MHz)	15.60	/	/	/	/	/	/	/		
64(5320 MHz)	15.84	15.48	15.47	15.02	15.00	14.39	14.35	13.78		
Tune up	17.50	17.00	16.50	16.50	16.50	15.50	15.50	15.00		
100(5500 MHz)	16.56	/	/	/	/	/	/	/		
104(5520 MHz)	16.63	/	/	/	/	/	/	/		
108(5540 MHz)	16.48	/	/	/	/	/	/	/		
112(5560 MHz)	16.18	/	/	/	/	/	/	/		
116(5580 MHz)	16.12	/	/	/	/	/	/	/		
120(5600 MHz)	15.99	/	/	/	/	/	/	/		
124(5620 MHz)	16.28	/	/	/	/	/	/	/		
128(5640 MHz)	16.56	/	/	/	/	/	/	/		
132(5660 MHz)	16.80	/	/	/	/	/	/	/		
136(5680 MHz)	16.98	16.31	16.30	15.81	15.76	15.37	15.35	15.34		
140(5700 MHz)	16.63	/	/	/	/	/	/	/		
144(5720 MHz)	16.47	/	/	/	/	/	/	/		
Tune up	17.50	17.00	17.00	16.50	16.50	16.00	16.00	16.00		

802.11n-40MHz (dBm)												
151(5755 MHz)	13.12	/	/	/	/	/	/	/				
159(5795 MHz)	13.63	13.59	13.57	13.56	13.38	13.34	13.40	13.32				
Tune up	Tune up         14.00         14.00         14.00         14.00         14.00         14.00         14.00         14.00											

No.I19Z60737-SEM02 Page 22 of 91



Tune up

#### The Low power for WiFi is as following:

9.00

9.00

	802.11b (dl	Bm)														
	Channel\dat	a rate	1Mbps			2Mb	ps		5.5	Mbp	S	11	11Mbps			
	11			/			/			7.33			/			
	6		8	8.10			8.03			8	.11		8.0	08		
	1			/				/		7	.73		1	/		
	Tune up		9	.00			9	.00		9	.00		9.0	00		
	802.11g (dB															
Chann	nannel\data rate 6Mbps		9Mbps	6	12Mb		s 18Mbps		24Mb	4Mbps 36Mbps		4	48Mbps		54Mb	ps
1		7.41	/	/		/		/	/		/		/		/	
6		7.36	/	/ /		/		/	/		/		/		/	
11		7.68	7.42	2	7.4	43		7.40	7.3	5	7.34	7.32			7.3	31
Tune u	р	9.00	9.00	)	9.0	00		9.00	9.0	)	9.00		9.00		9.0	)0
	802.11n (dB	m) - HT20	) (2.4G)													
	Channel\data rate		MCS0	MC	CS1 MC		2	MCS3	MC	S4	MCS5	MC	CS6	MC	CS7	
	1		7.38	/	/	/		/	/		/		/		/	
	6		7.33	/	/	/		/	/		/		/		/	
	11		7.67	7.6	66	7.6	5	7.61	7.6	50	7.58	7	.56	7	.56	

9.00

9.00

9.00

9.00

9.00

9.00

802.11a (dBm)											
Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps			
36(5180 MHz)	12.88	12.87	12.86	12.86	12.82	12.82	12.81	12.80			
40(5200 MHz)	12.45	/	/	/	/	/	/	/			
44(5220 MHz)	12.18	/	/	/	/	/	/	/			
48(5240 MHz)	12.01	/	/	/	/	/	/	/			
52(5260 MHz)	12.00	/	/	/	/	/	/	/			
56(5280 MHz)	12.01	/	/	/	/	/	/	/			
60(5300 MHz)	12.48	/	/	/	/	/	/	/			
64(5320 MHz)	12.99	12.98	12.98	12.96	12.94	12.91	12.90	12.88			
Tune up	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
100(5500 MHz)	13.33	/	/	/	/	/	/	/			
104(5520 MHz)	13.33	/	/	/	/	/	/	/			
108(5540 MHz)	13.20	/	/	/	/	/	/	/			
112(5560 MHz)	12.87	/	/	/	/	/	/	/			
116(5580 MHz)	12.74	/	/	/	/	/	/	/			
120(5600 MHz)	12.84	/	/	/	/	/	/	/			
124(5620 MHz)	13.03	/	/	/	/	/	/	/			
128(5640 MHz)	13.38	/	/	/	/	/	/	/			
132(5660 MHz)	13.50	/	/	/	/	/	/	/			
136(5680 MHz)	13.53	13.52	13.51	13.51	13.48	13.49	13.45	13.44			
140(5700 MHz)	13.32	/	/	/	/	/	/	/			
144(5720 MHz)	13.06	/	/	/	/	/	/	/			



No.I19Z60737-SEM02 Page 23 of 91

Tune up	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
		ł	802.11n-40	)MHz (dBr	n)			
151(5755 MHz)	12.64	/	/	/	/	/	/	/
159(5795 MHz)	12.98	12.97	12.81	12.75	12.74	12.84	12.82	12.65
Tune up	13.50	13.50	13.50	13.50	13.50	13.50	13.50	13.50



## **12 Simultaneous TX SAR Considerations**

#### **12.1 Introduction**

The following procedures adopted from "FCC SAR Considerations for Cell Phones with Multiple Transmitters" are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

#### **12.2 Transmit Antenna Separation Distances**



Antenna	Band	Conducted power reduced (dB)
3# (WIFI 2.4G)	2.4G	9.5
4# (WIFI 5G)	5G	3.5

Antenna	Trigger position	Trigger distance (mm)
NEED INFORMATION PROVIDENT	Back	10
3# (WIFI 2.4G)	Тор	5
and a second second	Front	8
	Back	10
4# (WIFI 5G)	Тор	5
	Front	8

**Picture 12.1 Antenna Locations** 



#### **12.3 SAR Measurement Positions**

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

SAR measurement positions							
Mode Front Rear Left edge Right edge Top edge Bottom edge							
WLAN 2.4G	WLAN 2.4G No Yes No Yes Yes No						
WLAN 5G         No         Yes         No         Yes         No							

## 12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot$  [ $\sqrt{f(GHz)}$ ]  $\leq$  3.0 for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Pand/Mada	P <sub>ref</sub> power	RF output p	oower (mW)	SAD toot evolucion
Band/Mode	(mW)	dBm	mW	SAR lest exclusion
Bluetooth	20	6.5	4.47	Yes
2.4GHz WLAN 802.11 b/g/n	20	18.5	70.79	No
5GHz WLAN 802.11 a/n/ac	20	17.5	56.23	No

#### Table 12.1: Summary of Transmitters

According to the conducted power measurement result, we can draw the conclusion that: stand-alone SAR for WiFi should be performed. Then, simultaneous transmission SAR for WiFi is considered with measurement results of main antenna and WiFi.

Stand-alone SAR and simultaneous transmission SAR for Bluetooth should not be performed



## 13 SAR Test Result

#### 13.1 WLAN Evaluation for 2.4G

According to the KDB248227 D01, SAR is measured for 2.4GHz 802.11b DSSS using the <u>initial</u> test position procedure.

#### **Body Evaluation**

#### Table 13.1-1: SAR Values(WLAN - Body)–2.4G (Fast SAR)

	Ambient Temperature: 22.9 °C						nperature: 2	22.5°C		
Freque	encv	Teet	Figure	Conducted	Conducted		Reported	Measured	Reported	Power
		Desition	No./	Power	Nax. tune-up	SAR(10g)	SAR(10g)	SAR(1g)	SAR(1g)(	Drift
MHz	Ch.	Position	Note	(dBm)	Power (aBm)	(W/kg)	(W/kg)	(W/kg)	W/kg)	(dB)
2437	6	Top 0mm	/	8.11	9.00	0.024	0.03	0.063	0.08	0.02
2412	1	Top 4mm	/	17.30	18.50	0.133	0.18	0.367	0.48	0.03
2437	6	Rear 0mm	/	8.11	9.00	0.180	0.22	0.552	0.68	-0.07
2412	1	Rear 9mm	/	17.30	18.50	0.149	0.20	0.508	0.67	-0.05
2412	1	Right 0mm	/	17.30	18.50	0.066	0.09	0.127	0.17	0.19
2437	6	Rear 0mm	B2	8.11	9.00	0.154	0.19	0.503	0.62	-0.06

As shown above table, the <u>initial test position</u> for body is "Rear 0mm". So the body SAR of WLAN is presented as below:

Table 13.1-2: SAR Values(WLAN - Body)-2.4G (Full SAR)

Ambient Temperature: 22.9 °C					Liquid Tem	nperature: 2	22.5°C			
Freque	encv	Toot	Figure	Conducted	Max tupo up	Measured	Reported	Measured	Reported	Power
		Desition	No./	Power		SAR(10g)	SAR(10g)	SAR(1g)	SAR(1g)(	Drift
MHz	Ch.	Position	Note	(dBm)	Power (aBm)	(W/kg)	(W/kg)	(W/kg)	W/kg)	(dB)
2412	1	Rear	,	17.20	19 50	0 1 4 1	0.10	0 472	0.62	0.05
2412	1	9mm	/	17.50	16.50	0.141	0.19	0.475	0.02	-0.05
2427	6	Rear		0.11	0.00	0.165	0.20	0.510	0.62	0.07
2437	ю	0mm	Fig.1	8.11	9.00	0.165	0.20	0.512	0.63	-0.07

Note1: When the <u>reported</u> SAR of the <u>initial test position</u> is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the <u>initial test position</u> using subsequent highest estimated 1-g SAR conditions determined by area scans, on the highest maximum output power channel, until the <u>reported</u> SAR is  $\leq 0.8$  W/kg.

Note2: For all positions/configurations tested using the <u>initial test position</u> and subsequent test positions, when the <u>reported</u> SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the <u>reported</u> SAR is  $\leq$  1.2 W/kg or all required channels are tested.



2437

6

Rear

## No.I19Z60737-SEM02 Page 27 of 91

0.66

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. The scaled reported SAR is presented as below.

Ambient Temperature: 22.9 °C Liquid Temperature: 22.5°C							
Freque	ency	Test	Actual duty	maximum duty	Reported SAR	Scaled reported SAR	
MHz	Ch.	Position	factor	factor	(1g)(W/kg)	(1g)(W/kg)	

100%

0.63

#### Table 13.1-3: SAR Values (WLAN - Body) – 802.11b (Scaled Reported SAR)

SAR is not required for OFDM because the 802.11b adjusted SAR  $\leq$  1.2 W/kg.

96.10%



Picture 13.1 Duty factor plot for CH6



## 13.2 WLAN Evaluation For 5G

#### Table 13.2-1: OFDM mode specified maximum output power of WLAN antenna

802.11 mode	а	g	n			
Ch. BW(MHz)	20	20	20	40		
U-NII-1	Х		Х	Х		
U-NII-2A	Х		Х	Х		
U-NII-2C	Х		Х	Х		
U-NII-3	Х		Х	Х		
§ 15.247 (5.8 GHz)	§ 15.247 (5.8 GHz)					
X: maximum(conducted) output power(mW), including tolerance, specified for						
production units						

#### Table 13.2-2: Maximum output power specified of WLAN antenna Normal Power

802.11 mode	а	g	n	
Ch. BW(MHz)	20	20	20	40
U-NII-1	56		45	28
U-NII-2A	56		45	28
U-NII-2C	56		50	35
U-NII-3	25		25	25
§ 15.247 (5.8 GHz)				

• The maximum output power specified for production units is the same for all channels, modulations and data rates in each channel bandwidth configuration of the 802.11a/g/n/ac modes.

• The blue highlighted cells represent highest output configurations in each standalone or aggregated frequency band, with tune-up tolerance included.

#### able 13.2-3: Maximum output power specified of WLAN antenna Low Power

802.11 mode	а	g	n	
Ch. BW(MHz)	20	20	20	40
U-NII-1	25		25	22
U-NII-2A	25		25	22
U-NII-2C	25		25	22
U-NII-3	22		22	22
§ 15.247 (5.8 GHz)				

- The maximum output power specified for production units is the same for all channels, modulations and data rates in each channel bandwidth configuration of the 802.11a/g/n/ac modes.
- The blue highlighted cells represent highest output configurations in each standalone or aggregated frequency band, with tune-up tolerance included.



Table 13.2-4: Maximum output power measured of WLAN antenna, for the applicable OFDM configurations according to the default power measurement procedures for selection initial test configurations Normal Power

802.11 mode	а	n					
BW(MHz)	20	20	40				
	<mark>36</mark> /40/44/48	36/40/44/48	38/46				
U-INII-1	<mark>38</mark> /37/37/37	Lower power	Lower power				
	52/56/60/ <mark>64</mark>	52/56/60/64	54/62				
U-INII-ZA	34/35/36/ <mark>38</mark>	Lower power	Lower power				
U-NII-2C	100/104/108/112 <b>45/46/44/41</b> 116/132/ <mark>136</mark> /140/144 <b>41/48/<mark>50</mark>/46/44</b>	100/104/108/112 116/132/136/140 Lower power	102/110/134 Lower power				
U-NII-3 149/153/157/161/165 Lower power		149/153/157/161 /165 Lower power	151/ <mark>159</mark> <b>21/23</b>				
• Channels with measured maximum power within 0.25dB are considered to have the same							
	measured output.						
Channels selected for initial test configuration are highlighted in yellow.							

Table 13.2-5: Maximum output power measured of WLAN antenna, for the applicable OFDM configurations according to the default power measurement procedures for selection initial test configurations Low Power

802.11 mode	а	n								
BW(MHz)	20	20	40							
	<mark>36</mark> /40/44/48	36/40/44/48	38/46							
U-INII-I	<mark>19</mark> /18/17/16	Lower power	Lower power							
	52/56/60/ <mark>64</mark>	52/56/60/64	54/62							
U-MI-ZA	16/16/18/ <mark>20</mark>	Lower power	Lower power							
U-NII-2C	100/104/108/112 <b>22/22/21/19</b> 116/132/ <mark>136</mark> /140/144 <b>19/22/<mark>23</mark>/21/20</b>	100/104/108/112 116/132/136/140 Lower power	102/110/134 Lower power							
U-NII-3	149/153/157/161/165 Lower power	149/153/157/161 /165 Lower power	151/ <mark>159</mark> <b>18/20</b>							
• Channels with measured maximum power within 0.25dB are considered to have the same										
	measured output.									
Cha	nnels selected for initial	test configuration ar	e <mark>highlighted in yellow</mark> .							



		nai toot ooningalaa		
802.11 mode	а	n		
BW(MHz)	20	20	40	
U-NII-1	<mark>36</mark> /40/44/48	36/40/44/48	38/46	
U-NII-2A	52/56/60/ <mark>64</mark> <b>0.54</b>	52/56/60/64	54/62	
U-NII-2C	100/104/108/112 116/132/ <mark>136</mark> /140/144 <b>0.80</b>	100/104/108/112 116/132/136/140	102/110/118/ 126/134	
U-NII-3	149/153/157/161/165	149/153/157/161 /165	151/ <mark>159</mark> <b>0.79</b>	
U-NII-1 and	U-NII-2A bands have the	same specified max	ximum output	
and toleranc	e; SAR is measured for l	J-NII-2A band first. A	Adjusted SAR	
of U-NII-2A b	band is $\leq$ 1.2W/kg, SAF	R is not required for	U-NII-1 band.	

 Table 13.2-6: Reported SAR of initial test configuration for Body

		A	mbient T	emperature:	22.9 °C	Liquid Temperature: 22.5 °C				
Frequ	ency	Test	Figure	Conducted	Max. tune-up	Measured	Reported	Measured	Reported	Power
		Position	No	Power	Power (dBm)	SAR(10g)	SAR(10g)	SAR(1g)	SAR(1g)	Drift
MHz	Ch.	1 Collion	110.	(dBm)		(W/kg)	(W/kg)	(W/kg)	(W/kg)	(dB)
5320	64	Тор	Note1	15.84	17.50	0.067	0.10	0.247	0.36	0.08
5320	64	Rear	Note2	15.84	17.50	0.045	0.07	0.080	0.12	0.03
5320	64	Тор	/	12.99	14.00	0.042	0.05	0.172	0.22	0.07
5320	64	Rear	/	12.99	14.00	0.104	0.13	0.430	0.54	0.09
5680	136	Тор	Note1	16.98	17.50	0.060	0.07	0.215	0.24	0.03
5680	136	Rear	Note2	16.98	17.50	0.041	0.05	0.069	0.08	0.18
5680	136	Тор	/	13.53	14.00	0.036	0.04	0.137	0.15	0.11
5680	136	Rear	Fig.2	13.53	14.00	0.145	0.16	0.717	0.80	0.03
5795	159	Тор	Note1	13.63	14.00	0.058	0.06	0.250	0.27	0.12
5795	159	Rear	Note2	13.63	14.00	0.043	0.05	0.072	0.08	-0.06
5795	159	Тор	/	12.98	13.50	0.033	0.04	0.124	0.14	0.03
5795	159	Rear	/	12.98	13.50	0.142	0.16	0.699	0.79	0.19
5680	136	Rear	B2	13.53	14.00	0.143	0.16	0.701	0.78	-0.04

Note: The distance between the EUT and the phantom bottom is 0mm.

Note1: The distance between the EUT and the phantom bottom is 4mm.

Note2: The distance between the EUT and the phantom bottom is 9mm.



## No.I19Z60737-SEM02 Page 31 of 91

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. The scaled reported SAR is presented as below.

Frequ	ency	Test	D	Actual	maximum	Reported	Scaled reported
MHz	Ch.	Position	(mm)	duty factor	duty factor	(1g) (W/kg)	SAR (1g) (W/kg)
5680	136	Rear	0	100%	100%	0.80	0.80





Picture 13.2-1 The plot of duty factor for U-NII-2C (Body)



## 14 SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required. 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps2) through 4) do not apply.

2) When the original highest measured SAR is  $\geq$  0.80 W/kg, repeat that measurement once.

3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is  $\geq$  1.45W/kg (~ 10% from the 1-g SAR limit).

4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq$ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.



## **15 Measurement Uncertainty**

## 16.1 Measurement Uncertainty for Normal SAR Tests (300MHz~3GHz)

No.	Error Description	Туре	Uncertainty	Probably	Div.	(Ci)	(Ci)	Std.	Std.	Degree		
			value Distributi			1g	10g	Unc.	Unc.	of		
								(1g)	(10g)	freedom		
Mea	Measurement system											
1	Probe calibration	В	6.0	N	1	1	1	6.0	6.0	8		
2	Isotropy	В	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	8		
3	Boundary effect	В	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	8		
4	Linearity	В	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞		
5	Detection limit	В	1.0	N	1	1	1	0.6	0.6	∞		
6	Readout electronics	В	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	$\infty$		
7	Response time	В	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	$\infty$		
8	Integration time	В	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	~		
9	RF ambient conditions-noise	В	0	R	$\sqrt{3}$	1	1	0	0	œ		
10	RFambient conditions-reflection	В	0	R	$\sqrt{3}$	1	1	0	0	8		
11	Probe positioned mech. restrictions	В	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	œ		
12	Probe positioning with respect to phantom shell	В	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	œ		
13	Post-processing	В	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	8		
			Test	sample related	ł							
14	Test sample positioning	А	3.3	Ν	1	1	1	3.3	3.3	71		
15	Device holder uncertainty	А	3.4	N	1	1	1	3.4	3.4	5		
16	Drift of output power	В	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	œ		
			Phan	tom and set-u	р					•		
17	Phantom uncertainty	В	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	8		
18	Liquid conductivity (target)	В	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	8		
19	Liquid conductivity (meas.)	А	2.06	N	1	0.64	0.43	1.32	0.89	43		
20	Liquid permittivity (target)	В	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	œ		
21	Liquid permittivity (meas.)	А	1.6	N	1	0.6	0.49	1.0	0.8	521		

TTL

No.I19Z60737-SEM02 Page 34 of 91

(	Combined standard uncertainty	<i>u</i> <sub>c</sub> =	$= \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$					9.55	9.43	257
Expa (cont 95 %	inded uncertainty fidence interval of	1	$u_e = 2u_c$					19.1	18.9	
16.	2 Measurement U	ncerta	ninty for No	ormal SAR	Tests	(3~6	GHz)			
No.	Error Description	Туре	Uncertainty	Probably	Div.	(Ci)	(Ci)	Std.	Std.	Degree
			value	Distribution		1g	10g	Unc.	Unc.	of
								(1g)	(10g)	freedom
Mea	surement system		I	I	1	1	1		1	
1	Probe calibration	В	6.55	Ν	1	1	1	6.55	6.55	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
2	Isotropy	В	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	$\infty$
3	Boundary effect	В	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	∞
4	Linearity	В	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	В	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	$\infty$
6	Readout electronics	В	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	$\infty$
7	Response time	В	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	$\infty$
8	Integration time	В	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	$\infty$
9	RF ambient conditions-noise	В	0	R	$\sqrt{3}$	1	1	0	0	8
10	RFambient conditions-reflection	В	0	R	$\sqrt{3}$	1	1	0	0	œ
11	Probe positioned mech. restrictions	В	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	œ
12	Probe positioning with respect to phantom shell	В	6.7	R	$\sqrt{3}$	1	1	3.9	3.9	œ
13	Post-processing	В	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	$\infty$
	T		Test	sample related	d	1		1	1	T
14	Test sample positioning	Α	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	А	3.4	Ν	1	1	1	3.4	3.4	5
16	Drift of output power	В	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	œ
			Phan	tom and set-u	р					1
17	Phantom uncertainty	В	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	$\infty$
18	Liquid conductivity (target)	В	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	œ
19	Liquid conductivity (meas.)	А	2.06	N	1	0.64	0.43	1.32	0.89	43
20	Liquid permittivity	В	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~

No.I19Z60737-SEM02 Page 35 of 91



	(target)									
21	Liquid permittivity (meas.)	А	1.6	Ν	1	0.6	0.49	1.0	0.8	521
(	Combined standard uncertainty	$u_{c} = \sqrt{\sum_{i=1}^{21} c_{i}^{2} u_{i}^{2}}$						10.7	10.6	257
Expa (conf 95 %	nded uncertainty fidence interval of	1	$u_e = 2u_c$					21.4	21.1	
16.	3 Measurement U	ncerta	inty for Fa	st SAR Tes	ts (30	DOMH:	z~3G	Hz)		
No.	Error Description	Туре	Uncertainty	Probably	Div.	(Ci)	(Ci)	Std.	Std.	Degree
			value	Distribution		1g	10g	Unc.	Unc.	of
								(1g)	(10g)	freedom
Mea	surement system									
1	Probe calibration	В	6.0	Ν	1	1	1	6.0	6.0	8
2	Isotropy	В	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	8
3	Boundary effect	В	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	8
4	Linearity	В	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	œ
5	Detection limit	В	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	8
6	Readout electronics	В	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	8
7	Response time	В	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	8
8	Integration time	В	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	8
9	RF ambient conditions-noise	В	0	R	$\sqrt{3}$	1	1	0	0	8
10	RFambient conditions-reflection	В	0	R	$\sqrt{3}$	1	1	0	0	œ
11	Probe positioned mech. Restrictions	В	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	œ
12	Probe positioning with respect to phantom shell	В	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Post-processing	В	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	8
14	Fast SAR z-Approximation	В	7.0	R	$\sqrt{3}$	1	1	4.0	4.0	8
	Test sample related									
15	Test sample positioning	А	3.3	N	1	1	1	3.3	3.3	71
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
17	Drift of output power	В	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
			Phan	tom and set-u	р					
18	Phantom uncertainty	В	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	$\infty$



## No.I19Z60737-SEM02 Page 36 of 91

r										
19	Liquid conductivity (target)	В	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	$\infty$
20	Liquid conductivity (meas.)	A 2.06		Ν	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	В	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	~
22	Liquid permittivity (meas.)	А	1.6	Ν	1	0.6	0.49	1.0	0.8	521
(	Combined standard uncertainty	u <sub>c</sub> =	$=\sqrt{\sum_{i=1}^{22}c_i^2u_i^2}$					10.4	10.3	257
Expa (cont 95 %	nded uncertainty fidence interval of	1	$u_e = 2u_c$					20.8	20.6	
16.	4 Measurement U	ncerta	inty for Fa	st SAR Tes	ts (3-	-6GH	z)			
No.	Error Description	Туре	Uncertainty	Probably	Div.	(Ci)	(Ci)	Std.	Std.	Degree
			value	Distribution		1g	10g	Unc.	Unc.	of
						0	0	(1g)	(10g)	freedom
Mea	surement system			I					ς υ,	
1	Probe calibration	В	6 5 5	N	1	1	1	6 5 5	6 55	œ
2	Isotropy	B	47	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
3	Boundary effect	B	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
4	Linearity	B	2.0 A 7	R	$\sqrt{3}$	1	1	2.7	2.7	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.0	0.0	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
9	RF ambient	В	0	R	$\sqrt{3}$	1	1	0	0	~
10	RFambient conditions-reflection	В	0	R	$\sqrt{3}$	1	1	0	0	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
11	Probe positioned mech. Restrictions	В	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	8
12	Probe positioning with respect to phantom shell	В	6.7	R	$\sqrt{3}$	1	1	3.9	3.9	œ
13	Post-processing	В	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	$\infty$
14	Fast SAR z-Approximation	В	14.0	R	$\sqrt{3}$	1	1	8.1	8.1	8
Test sample related										
15	Test sample positioning	А	3.3	N	1	1	1	3.3	3.3	71
16	Device holder	Α	3.4	N	1	1	1	3.4	3.4	5





	uncertainty									
17	Drift of output power	В	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	8
	Phantom and set-up									
18	Phantom uncertainty	В	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	8
19	Liquid conductivity (target)	В	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	8
20	Liquid conductivity (meas.)	А	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	В	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	8
22	Liquid permittivity (meas.)	А	1.6	Ν	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		<i>u</i> <sub>c</sub> =	$= \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$					13.5	13.4	257
Expa (cont 95 %	nded uncertainty fidence interval of	1	$u_e = 2u_c$					27.0	26.8	

## **16 MAIN TEST INSTRUMENTS**

#### Table 17.1: List of Main Instruments

No.	Name	Туре	Serial Number	Calibration Date	Valid Period	
01	Network analyzer	E5071C	MY46110673	January 24, 2019	One year	
02	Power meter	NRVD	102083	October 24, 2018		
03	Power sensor	NRV-Z5	100542	October 24, 2018	One year	
04	Signal Generator	E4438C	MY49070393	January 4, 2019	One Year	
05	Amplifier	60S1G4	0331848	No Calibration Requested		
07	E-field Probe	SPEAG EX3DV4	7514	August 27, 2018	One year	
08	DAE	SPEAG DAE4	1525	September 18, 2018	One year	
09	Dipole Validation Kit	SPEAG D2450V2	853	July 24, 2018	One year	
10	Dipole Validation Kit	SPEAG D5GHzV2	1262	January 31, 2019	One year	

\*\*\*END OF REPORT BODY\*\*\*



## ANNEX A Graph Result

Wifi 802.11b Body Rear Channel 6 Date: 2019-6-19 Electronics: DAE4 Sn1525 Medium: Body 2450 MHz Medium parameters used (interpolated): f = 2437 MHz;  $\sigma = 1.96$  mho/m;  $\varepsilon_r = 52.16$ ;  $\rho = 1000$  kg/m<sup>3</sup> Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C Communication System: WLan 2450 Frequency: 2437 MHz Duty Cycle: 1:1 Probe: EX3DV4 – SN7514 ConvF(7.13, 7.13, 7.13)

Area Scan (161x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.20 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.186 V/m; Power Drift = -0.07 dB Peak SAR (extrapolated) = 1.82 W/kg SAR(1 g) = 0.512 W/kg; SAR(10 g) = 0.165 W/kg Maximum value of SAR (measured) = 1.26 W/kg



Fig.1 2450 MHz





Fig. 1-1 Z-Scan at power reference point (2450 MHz)



#### Wifi 802.11a Rear Channel 136

Date: 2019-6-20 Electronics: DAE4 Sn1525 Medium: Body 5 GHz Medium parameters used: f = 5680 MHz;  $\sigma = 5.719$  mho/m;  $\epsilon_r = 47.14$ ;  $\rho = 1000$  kg/m<sup>3</sup> Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C Communication System: WLan 5G Frequency: 5680 MHz Duty Cycle: 1:1 Probe: EX3DV4 –SN7514 ConvF(4.00, 4.00, 4.00)

Area Scan (191x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 1.46 W/kg

Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 2.683 V/m; Power Drift = 0.03 dBPeak SAR (extrapolated) = 6.58 W/kgSAR(1 g) = 0.717 W/kg; SAR(10 g) = 0.145 W/kgMaximum value of SAR (measured) = 3.05 W/kg











Fig. 26-1 Z-Scan at power reference point (5GHz)



## ANNEX B System Verification Results

## 2450 MHz

Date: 2019-6-19 Electronics: DAE4 Sn1525 Medium: Body2450 MHz Medium parameters used: f = 2450 MHz;  $\sigma = 1.96$  mho/m;  $\varepsilon_r = 52.16$ ;  $\rho = 1000$  kg/m<sup>3</sup> Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C Communication System: CW Frequency: 2450 MHz Duty Cycle: 1:1 Probe: EX3DV4 – SN7514 ConvF(7.13,7.13,7.13) System Validation/Area Scan (81x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Reference Value = 90.35 V/m; Power Drift = 0.04 dB SAR(1 g) = 12.8 W/kg; SAR(10 g) = 6.01 W/kg Maximum value of SAR (interpolated) = 14.4 W/kg

System Validation/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 90.35 V/m; Power Drift = 0.04 dB Peak SAR (extrapolated) = 24.61 W/kg

SAR(1 g) = 13.0 W/kg; SAR(10 g) = 6.19 W/kg

Maximum value of SAR (measured) = 14.6 W/kg



0~dB = 14.6~W/kg = 11.64~dB~W/kg Fig.B.1 validation 2450 MHz 250mW



## 5250MHz

Date: 2019-6-20 Electronics: DAE4 Sn1525 Medium: Body 5 GHz Medium parameters used: f = 5250 MHz;  $\sigma = 5.274$  mho/m;  $\epsilon_r = 47.09$ ;  $\rho = 1000$  kg/m<sup>3</sup> Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C Communication System: CW Frequency: 5250 MHz Duty Cycle: 1:1 Probe: EX3DV4 – SN7514 ConvF(4.54, 4.54, 4.54)

**System Validation /Area Scan (91x91x1):** Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (interpolated) = 18.3 W/kg

System Validation /Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 55.68 V/m; Power Drift = 0.00 dB Peak SAR (extrapolated) = 29.84 W/kg SAR(1 g) = 7.11 W/kg; SAR(10 g) = 2.08 W/kgMaximum value of SAR (measured) = 18.1 W/kg



0 dB = 18.1 W/kg = 12.58 dBW/kg

Fig.B.2 validation 5250MHz 100mW



## 5600MHz

Date: 2019-6-20 Electronics: DAE4 Sn1525 Medium: Body 5 GHz Medium parameters used: f = 5600 MHz;  $\sigma = 5.719$  mho/m;  $\epsilon_r = 47.14$ ;  $\rho = 1000$  kg/m<sup>3</sup> Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C Communication System: CW Frequency: 5600 MHz Duty Cycle: 1:1 Probe: EX3DV4 – SN7514 ConvF(4.00, 4.00, 4.00)

**System Validation /Area Scan (91x91x1):** Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (interpolated) = 20.23 W/kg

System Validation /Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 68.62 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 37.33 W/kg SAR(1 g) = 8.13 W/kg; SAR(10 g) = 2.43 W/kg

Maximum value of SAR (measured) = 20.21 W/kg



0 dB = 20.21 W/kg = 13.06 dBW/kg

Fig.B.3 validation 5600MHz 100mW



## 5750MHz

Date: 2019-6-20 Electronics: DAE4 Sn1525 Medium: Body 5 GHz Medium parameters used: f = 5750 MHz;  $\sigma = 5.856$  mho/m;  $\epsilon_r = 46.25$ ;  $\rho = 1000$  kg/m<sup>3</sup> Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C Communication System: CW Frequency: 5750 MHz Duty Cycle: 1:1 Probe: EX3DV4 – SN7514 ConvF(3.98, 3.98, 3.98)

**System Validation /Area Scan (91x91x1):** Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (interpolated) = 18.7 W/kg

System Validation /Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 68.02 V/m; Power Drift = 0.05 dB Peak SAR (extrapolated) = 35.71 W/kg SAR(1 g) = 7.73 W/kg; SAR(10 g) = 2.04 W/kg Maximum value of SAR (measured) = 18.9 W/kg



0 dB = 18.9 W/kg = 12.76 dBW/kg

#### Fig.B.4 validation 5750MHz 100mW

The SAR system verification must be required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR.

Table B.1 C	omparison	between	area scan	and zoo	om scan	for sy	stem v	verification
-------------	-----------	---------	-----------	---------	---------	--------	--------	--------------

Date	Band	Position	Area scan (1g)	Zoom scan (1g)	Drift (%)
2019-6-19	2450	Body	12.8	13	-1.54



## ANNEX C SAR Measurement Setup

#### C.1 Measurement Set-up

The Dasy4 or DASY5 system for performing compliance tests is illustrated above graphically. This system consists of the following items:



Picture C.1SAR Lab Test Measurement Set-up

- A standard high precision 6-axis robot (StäubliTX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY4 or DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as
- warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.



#### C.2 Dasy4 or DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 or DASY5 software reads the reflection durning a software approach and looks for the maximum using 2<sup>nd</sup> ord curve fitting. The approach is stopped at reaching the maximum.

#### **Probe Specifications:**

Model:	ES3DV3, EX3DV4					
Frequency	10MHz — 6.0GHz(EX3DV4)					
Range:	10MHz — 4GHz(ES3DV3)					
Calibration:	In head and body simulating tissue at					
	Frequencies from 835 up to 5800MHz					
Linearity:	± 0.2 dB(30 MHz to 6 GHz) for EX3DV4					
± 0.2 dB(30 MHz	to 4 GHz) for ES3DV3					
DynamicRange:	10 mW/kg — 100W/kg					
Probe Length:	330 mm					
Probe Tip						
Length:	20 mm					
Body Diameter:	12 mm					
Tip Diameter:	2.5 mm (3.9 mm for ES3DV3)					
Tip-Center:	1 mm (2.0mm for ES3DV3)					
Application:SAF	R Dosimetry Testing					
	Compliance tests of mobile phones					
	Dosimetry in strong gradient fields					
Picture C.3E-fiel	d Probe					



Picture C.2Near-field Probe



## C.3 E-field Probe Calibration

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm<sup>2</sup>) using an RF Signal generator, TEM cell, and RF Power Meter.

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and inn a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed ©Copyright. All rights reserved by CTTL.



in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm<sup>2</sup>.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

 $\Delta t$  = Exposure time (30 seconds), C = Heat capacity of tissue (brain or muscle),  $\Delta T$  = Temperature increase due to RF exposure.

$$SAR = \frac{\left|E\right|^2 \cdot \sigma}{\rho}$$

Where:  $\sigma$  = Simulated tissue conductivity,  $\rho$  = Tissue density (kg/m<sup>3</sup>).

## C.4 Other Test Equipment

## C.4.1 Data Acquisition Electronics(DAE)

The data acquisition electronics consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



PictureC.4: DAE

#### No.I19Z60737-SEM02 Page 49 of 91



#### C.4.2 Robot

The SPEAG DASY system uses the high precision robots (DASY4: RX90XL; DASY5: RX160L) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- > Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchron motors; no stepper motors)
- > Low ELF interference (motor control fields shielded via the closed metallic construction shields)



Picture C.5DASY 4

Picture C.6DASY 5

#### C.4.3 Measurement Server

The Measurement server is based on a PC/104 CPU broad with CPU (dasy4: 166 MHz, Intel Pentium; DASY5: 400 MHz, Intel Celeron), chipdisk (DASY4: 32 MB; DASY5: 128MB), RAM (DASY4: 64 MB, DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O broad, which is directly connected to the PC/104 bus of the CPU broad.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.



Picture C.7 Server for DASY 4

#### Picture C.8 Server for DASY 5

#### C.4.4 Device Holder for Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of  $\pm 0.5$ mm would produce a SAR uncertainty of  $\pm 20\%$ . Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\ell = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

<Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin-SAM and ELI phantoms.



Picture C.9-1: Device Holder



Picture C.9-2: Laptop Extension Kit



## C.4.5 Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to

Represent the 90<sup>th</sup> percentile of the population. The phantom enables the dissymmetric evaluation of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

Shell Thickness:2±0. 2 mmFilling Volume:Approx. 25 litersDimensions:810 x 1000 x 500 mm (H x L x W)Available:Special



Picture C.10: SAM Twin Phantom



## ANNEX D Position of the wireless device in relation to the phantom

#### D.1 Body-worn device

A typical example of a body-worn device is a mobile phone, wireless enabled PDA or other battery operated wireless device with the ability to transmit while mounted on a person's body using a carry accessory approved by the wireless device manufacturer.



Picture D.4Test positions for body-worn devices

#### D.2 Desktop device

A typical example of a desktop device is a wireless enabled desktop computer placed on a table or desk when used.

The DUT shall be positioned at the distance and in the orientation to the phantom that corresponds to the intended use as specified by the manufacturer in the user instructions. For devices that employ an external antenna with variable positions, tests shall be performed for all antenna positions specified. Picture8.5 show positions for desktop device SAR tests. If the intended use is not specified, the device shall be tested directly against the flat phantom.





Picture D.5 Test positions for desktop devices

D.3 DUT Setup Photos



Picture D.6



## ANNEX E Equivalent Media Recipes

The liquid used for the frequency range of 800-3000 MHz consisted of water, sugar, salt, preventol, glycol monobutyl and Cellulose. The liquid has been previously proven to be suited for worst-case. The Table E.1 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528 and IEC 62209.

Fraguanay		-	1000	1000	2450	2450	E000	E000		
Frequency	835Head	835Body	1900	1900	2450	2450	5800	5800		
(MHz)	ooonicaa	COODCUY	Head	Body	Head	Body	Head	Body		
Ingredients (% by weight)										
Water	41.45	52.5	55.242	69.91	58.79	72.60	65.53	65.53		
Sugar	56.0	45.0	١	١	١	١	١	١		
Salt	1.45	1.4	0.306	0.13	0.06	0.18	١	١		
Preventol	0.1	0.1	١	١	١	١	١	١		
Cellulose	1.0	1.0	١	١	١	١	١	١		
Glycol	1	1	44 450	20.00	11 1E	07.00	1	N		
Monobutyl	۸	١	44.452	29.90	41.15	21.22	۸	١		
Diethylenglycol	``	,	,	,	,	,	47.04	47.04		
monohexylether	Λ	١	١	١	١	١	17.24	17.24		
Triton X-100	١	١	١	١	١	١	17.24	17.24		
Dielectric			10.0							
Parameters	ε=41.5	ε=55.Z	ε=40.0	8=53.3	ε=39.2	ε=52.7	8=35.3	ε=48.2		
	σ=0.90	σ=0.97	σ=1.40	σ=1.52	σ=1.80	σ=1.95	σ=5.27	σ=6.00		
Target Value										

#### TableE.1: Composition of the Tissue Equivalent Matter

Note: There are a little adjustment respectively for 750, 1750, 2600, 5200, 5300 and 5600 based on the recipe of closest frequency in table E.1.



## ANNEX F System Validation

The SAR system must be validated against its performance specifications before it is deployed. When SAR probes, system components or software are changed, upgraded or recalibrated, these must be validated with the SAR system(s) that operates with such components.

Probe SN.	Liquid name	Validation date	Frequency point	Status (OK or Not)
7514	Head 750MHz	Sep.10,2018	750 MHz	OK
7514	Head 850MHz	Sep.10,2018	835 MHz	OK
7514	Head 900MHz	Sep.10,2018	900 MHz	OK
7514	Head 1750MHz	Sep.10,2018	1750 MHz	OK
7514	Head 1810MHz	Sep.10,2018	1810 MHz	OK
7514	Head 1900MHz	Sep.11,2018	1900 MHz	OK
7514	Head 2000MHz	Sep.11,2018	2000 MHz	OK
7514	Head 2100MHz	Sep.11,2018	2100 MHz	OK
7514	Head 2300MHz	Sep.11,2018	2300 MHz	OK
7514	Head 2450MHz	Sep.11,2018	2450 MHz	OK
7514	Head 2600MHz	Sep.12,2018	2600 MHz	OK
7514	Head 3500MHz	Sep.12,2018	3500 MHz	OK
7514	Head 3700MHz	Sep.12,2018	3700 MHz	OK
7514	Head 5200MHz	Sep.12,2018	5250 MHz	OK
7514	Head 5500MHz	Sep.12,2018	5600 MHz	OK
7514	Head 5800MHz	Sep.12,2018	5800 MHz	OK
7514	Body 750MHz	Sep.12,2018	750 MHz	OK
7514	Body 850MHz	Sep.9,2018	835 MHz	OK
7514	Body 900MHz	Sep.9,2018	900 MHz	OK
7514	Body 1750MHz	Sep.9,2018	1750 MHz	OK
7514	Body 1810MHz	Sep.9,2018	1810 MHz	OK
7514	Body 1900MHz	Sep.9,2018	1900 MHz	OK
7514	Body 2000MHz	Sep.13,2018	2000 MHz	OK
7514	Body 2100MHz	Sep.13,2018	2100 MHz	OK
7514	Body 2300MHz	Sep.13,2018	2300 MHz	OK
7514	Body 2450MHz	Sep.13,2018	2450 MHz	OK
7514	Body 2600MHz	Sep.13,2018	2600 MHz	OK
7514	Body 3500MHz	Sep.8,2018	3500 MHz	OK
7514	Body 3700MHz	Sep.8,2018	3700 MHz	OK
7514	Body 5200MHz	Sep.8,2018	5250 MHz	OK
7514	Body 5500MHz	Sep.8,2018	5600 MHz	OK
7514	Body 5800MHz	Sep.8,2018	5800 MHz	OK

Table F.1: System Validation for 7514



## ANNEX G Probe Calibration Certificate

#### **Probe 7514 Calibration Certificate**

Engineering AG Engineering AG eughausstrasse 43, 8004 Zur	D <b>ry Of</b> ich, Switzerland	S C S	Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura Swiss Calibration Service
ccredited by the Swiss Accredine Swiss Accredine Swiss Accreditation Servi	tation Service (SAS) ce is one of the signatories	to the EA	reditation No.: SCS 0108
ultilateral Agreement for the lient CTTL-BJ (Aud	recognition of calibration c den)	ertificates Certificate No:	EX3-7514_Aug18
CALIBRATION	CERTIFICATE		
Dbject	EX3DV4 - SN:751	4	
Calibration procedure(s)	QA CAL-01.v9, Q/ QA CAL-25.v6 Calibration proceed	A CAL-12.v9, QA CAL-14.v4, QA lure for dosimetric E-field probes	CAL-23.v5,
Calibration date:	August 27, 2018		
This calibration certificate docur The measurements and the und All calibrations have been cond Calibration Equipment used (M.	ments the traceability to nation certainties with confidence pro ucted in the closed laboratory &TE critical for calibration)	nal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a	of measurements (SI). are part of the certificate. and humidity < 70%.
This calibration certificate docur The measurements and the und All calibrations have been cond Calibration Equipment used (M- Primary Standards	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration)	nal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.)	of measurements (SI). are part of the certificate. and humidity < 70%.
This calibration certificate docur The measurements and the unous All calibrations have been cond Calibration Equipment used (Me Primary Standards Power meter NRP	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration)	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19
his calibration certificate docur he measurements and the und ll calibrations have been cond Calibration Equipment used (Me Primary Standards Power meter NRP Power sensor NRP-Z91 Power Sensor NRP-Z91	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19
This calibration certificate docur The measurements and the unor All calibrations have been cond Calibration Equipment used (Me Primary Standards Power sensor NRP-Z91 Power sensor NRP-Z91 Powers sensor NRP-Z91 Powers 20 dB Attenuetor	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 25277 (20x)	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Apr-19
This calibration certificate docu The measurements and the und All calibrations have been cond Calibration Equipment used (Me Primary Standards Power sensor NRP-Z91 Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3D/2	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103244 SN: 103245 SN: S5277 (20x) SN: 3013	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 230-Dec-17 (No. ES3-3013, Dec17)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Apr-19 Dec-18
This calibration certificate docu The measurements and the und All calibrations have been cond Calibration Equipment used (M- Primary Standards Power Sensor NRP- Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: S5277 (20x) SN: 3013 SN: 660	nal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 30-Dec-17 (No. ES3-3013_Dec17) 21-Dec-17 (No. DAE4-660_Dec17)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Apr-19 Dec-18 Dec-18
This calibration certificate docu The measurements and the und All calibrations have been cond Calibration Equipment used (Me Primary Standards Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103244 SN: 103245 SN: S5277 (20x) SN: 3013 SN: 660 ID	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 30-Dec-17 (No. ES3-3013_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) Check Date (in house)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Scheduled Check
This calibration certificate docur The measurements and the unor All calibrations have been cond Calibration Equipment used (Me Primary Standards Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Power meter E4419B	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 55277 (20x) SN: 3013 SN: 660 ID SN: 6B41293874	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 30-Dec-17 (No. ES3-3013_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) Check Date (in house) 06-Apr-16 (in house check Jun-18)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Dec-18 In house check: Jun-20
This calibration certificate docur The measurements and the unor All calibrations have been cond Calibration Equipment used (Me Primary Standards Power meter NRP Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Power meter E4419B Power sensor E4412A	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 55277 (20x) SN: 3013 SN: 660 ID SN: 6B41293874 SN: MY41498087	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 30-Dec-17 (No. ES3-3013_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) - Check Date (in house) 06-Apr-16 (in house check Jun-18)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Scheduled Check In house check: Jun-20 In house check: Jun-20
This calibration certificate docu The measurements and the und All calibrations have been cond Calibration Equipment used (Me Primary Standards Power meter NRP Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Power meter E4419B Power sensor E4412A Power sensor E4412A	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 55277 (20x) SN: 3013 SN: 660 ID SN: 6B41293874 SN: GB41293874 SN: WY41498087 SN: 000110210	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02672) 21-Dec-17 (No. DAE4-660_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) Check Date (in house) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Scheduled Check In house check: Jun-20 In house check: Jun-20
This calibration certificate docu The measurements and the und All calibrations have been cond Calibration Equipment used (Me Primary Standards Power meter NRP Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Power meter E4419B Power sensor E4412A Power sensor E4412A RF generator HP 8648C	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 3013 SN: 3013 SN: 660 ID SN: GB41293874 SN: MY41498087 SN: 000110210 SN: US3642U01700	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 30-Dec-17 (No. ES3-3013_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) Check Date (in house) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 04-Aug-99 (in house check Jun-18)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Scheduled Check In house check: Jun-20 In house check: Jun-20 In house check: Jun-20
This calibration certificate docu The measurements and the und All calibrations have been cond Calibration Equipment used (M- Primary Standards Power meter NRP Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Power sensor E44198 Power sensor E4412A Power sensor E4412A Power sensor E4412A RF generator HP 8648C Network Analyzer E8358A	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 55277 (20x) SN: 3013 SN: 660 ID SN: 6B41293874 SN: MY41498087 SN: 000110210 SN: US3642U01700 SN: US3642U01700 SN: US41080477	nal standards, which realize the physical units         bability are given on the following pages and         facility: environment temperature (22 ± 3)°C a         Cal Date (Certificate No.)         04-Apr-18 (No. 217-02672/02673)         04-Apr-18 (No. 217-02672)         05-Apr-16 (in house check Jun-18)         06-Apr-16 (in house check Jun-18)         06-Apr-16 (in house check Jun-18)         04-Aug-99 (in house check Jun-18)         04-Aug-99 (in house check Oct-17)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Scheduled Check In house check: Jun-20 In house check: Jun-20
This calibration certificate docur The measurements and the und All calibrations have been cond Calibration Equipment used (Me Primary Standards Power meter NRP Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Power meter E44198 Power sensor E4412A Power sensor E4412A RF generator HP 8648C Network Analyzer E8358A	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 3013 SN: 660 ID SN: 660 ID SN: 6B41293874 SN: MY41498087 SN: 000110210 SN: US3642U01700 SN: US3642U01700 SN: US41080477	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 30-Dec-17 (No. ES3-3013_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 04-Aug-99 (in house check Jun-18) 31-Mar-14 (in house check Oct-17) Function	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Scheduled Check In house check: Jun-20 In house check: Jun-20 In house check: Jun-20 In house check: Jun-20 In house check: Jun-20 Signature
This calibration certificate docu The measurements and the und All calibrations have been cond Calibration Equipment used (Me Primary Standards Power meter NRP Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Power meter E4419B Power sensor E4412A Power sensor E4412A RF generator HP 8648C Network Analyzer E8358A Calibrated by:	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 3013 SN: 3013 SN: 660 ID SN: GB41293874 SN: MY41498087 SN: 000110210 SN: US3642U01700 SN: US3642U01700 SN: US41080477 Name Jeton Kastrati	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 30-Dec-17 (No. ES3-3013_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) 06-Apr-16 (in house) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 04-Aug-99 (in house check Jun-18) 31-Mar-14 (in house check Oct-17) Function	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Scheduled Check In house check: Jun-20 In house check: Jun-20 Signature
This calibration certificate docu The measurements and the und All calibrations have been cond Calibration Equipment used (Me Primary Standards Power meter NRP Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Power meter E44198 Power sensor E4412A RF generator HP 8648C Network Analyzer E8358A Calibrated by: Approved by:	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 03245 SN: 03245 SN: 55277 (20x) SN: 3013 SN: 660 ID SN: 660 ID SN: 6B41293874 SN: MY41498087 SN: 00110210 SN: US3642U01700 SN: US3642U01700 SN: US41080477 Name Jeton Kastrati Katja Pokovic	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 30-Dec-17 (No. ES3-3013_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) 06-Apr-16 (in house) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 04-Aug-99 (in house check Jun-18) 31-Mar-14 (in house check Oct-17) Function Laboratory Technician	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Scheduled Check In house check: Jun-20 In house check: Jun-20 Signature
This calibration certificate docu The measurements and the und All calibrations have been cond Calibration Equipment used (Me Primary Standards Power meter NRP Power sensor NRP-Z91 Power sensor NRP-Z91 Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Power meter E44198 Power sensor E4412A RF generator HP 8648C Network Analyzer E8358A Calibrated by: Approved by:	ments the traceability to nation certainties with confidence pro- ucted in the closed laboratory &TE critical for calibration) ID SN: 104778 SN: 103244 SN: 103245 SN: 103245 SN: 55277 (20x) SN: 3013 SN: 660 ID SN: 660 ID SN: 6B41293874 SN: 00110210 SN: US3642U01700 SN: US3642U01700 SN: US3642U01700 SN: US41080477 Name Jeton Kastrati Katja Pokovic	hal standards, which realize the physical units bability are given on the following pages and facility: environment temperature (22 ± 3)°C a Cal Date (Certificate No.) 04-Apr-18 (No. 217-02672/02673) 04-Apr-18 (No. 217-02672) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02673) 04-Apr-18 (No. 217-02682) 30-Dec-17 (No. ES3-3013_Dec17) 21-Dec-17 (No. DAE4-660_Dec17) 06-Apr-16 (in house) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 06-Apr-16 (in house check Jun-18) 04-Aug-99 (in house check Jun-18) 31-Mar-14 (in house check Oct-17) Function Laboratory Technician	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Apr-19 Apr-19 Apr-19 Dec-18 Dec-18 Dec-18 Scheduled Check In house check: Jun-20 In house check: Jun-20 Signature



#### No.I19Z60737-SEM02 Page 57 of 91

#### Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst C Service suisse d'étalonnage

Servizio svizzero di taratura

Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

#### Glossary:

TSL	tissue simulating liquid
NORMx,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORMx,y,z
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization 9	9 rotation around an axis that is in the plane normal to probe axis (at measurement center),
	i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

- ----

- Calibration is Performed According to the Following Standards:

   a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
  - Techniques", June 2013
    b) IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from handheld and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
  - c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
  - d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Methods Applied and Interpretation of Parameters:

- NORMx, y,z: Assessed for E-field polarization 9 = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx, y,z are only intermediate values, i.e., the uncertainties of NORMx, y,z does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)x,y,z = NORMx,y,z \* frequency\_response (see Frequency Response Chart). This linearization is
  implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included
  in the stated uncertainty of ConvF.
- *DCPx,y,z*: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx,y,z \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORMx (no uncertainty required).

Certificate No: EX3-7514\_Aug18

Page 2 of 39



EX3DV4 - SN:7514

August 27, 2018

# Probe EX3DV4

# SN:7514

Manufactured: Calibrated:

November 13, 2017 August 27, 2018

Calibrated for DASY/EASY Systems (Note: non-compatible with DASY2 system!)

Certificate No: EX3-7514\_Aug18

Page 3 of 39



EX3DV4-SN:7514

August 27, 2018

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:7514

#### **Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm $(\mu V/(V/m)^2)^A$	0.46	0.44	0.39	± 10.1 %
DCP (mV) <sup>B</sup>	96.5	101.1	97.9	

#### **Modulation Calibration Parameters**

UID	Communication System Name		A dB	B dB√μV	С	D dB	VR mV	Unc <sup>t</sup> (k=2)
0	CW	X	0.0	0.0	1.0	0.00	179.1	±3.5 %
		Y	0.0	0.0	1.0		177.3	
		Z	0.0	0.0	1.0		158.1	

Note: For details on UID parameters see Appendix.

#### **Sensor Model Parameters**

	C1 fF	C2 fF	α V <sup>-1</sup>	T1 ms.V <sup>-2</sup>	T2 ms.V <sup>-1</sup>	T3 ms	T4 V⁻²	T5 V <sup>-1</sup>	Т6
Х	31.17	241.1	37.77	3.625	0.025	5.031	0.000	0.325	1.005
Y	34.86	259.7	35.41	7.412	0.000	5.026	0.323	0.291	1.002
Z	33.14	259.6	38.65	3.827	0.264	5.046	0.000	0.373	1.008

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

 <sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).
 <sup>B</sup> Numerical linearization parameter: uncertainty not required.
 <sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Certificate No: EX3-7514\_Aug18

Page 4 of 39



EX3DV4- SN:7514

August 27, 2018

#### DASY/EASY - Parameters of Probe: EX3DV4 - SN:7514

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unc (k=2)
150	52.3	0.76	12.79	12.79	12.79	0.00	1.00	± 13.3 %
300	45.3	0.87	11.57	11.57	11.57	0.07	1.20	± 13.3 %
450	43.5	0.87	10.68	10.68	10.68	0.14	1.20	± 13.3 %
750	41.9	0.89	9.47	9.47	9.47	0.45	0.89	<u>±</u> 12.0 %
835	41.5	0.90	9.09	9.09	9.09	0.53	0.85	± 12.0 %
900	41.5	0.97	9.03	9.03	9.03	0.49	0.85	± 12.0 %
1450	40.5	1.20	8.24	8.24	8.24	0.35	0.80	± 12.0 %
1640	40.2	1.31	8.22	8.22	8.22	0.38	0.81	± 12.0 %
1750	40.1	1.37	8.10	8.10	8.10	0.36	0.83	± 12.0 %
1810	40.0	1.40	7.82	7.82	7.82	0.35	0.81	± 12.0 %
1900	40.0	1.40	7.73	7.73	7.73	0.31	0.80	± 12.0 %
2000	40.0	1.40	7.64	7.64	7.64	0.30	0.84	± 12.0 %
2100	39.8	1.49	7.57	7.57	7.57	0.27	0.85	± 12.0 %
2300	39.5	1.67	7.42	7.42	7.42	0.31	0.80	± 12.0 %
2450	39.2	1.80	6.95	6.95	6.95	0.38	0.98	± 12.0 %
2600	39.0	1.96	6.92	6.92	6.92	0.25	1.05	± 12.0 %
3500	37.9	2.91	6.78	6.78	6.78	0.79	0.64	± 13.1 %
3700	37.7	3.12	6.61	6.61	6.61	0.42	0.93	± 13.1 %
5200	36.0	4.66	5.05	5.05	5.05	0.40	1.80	± 13.1 %
5250	35.9	4.71	5.02	5.02	5.02	0.40	1.80	± 13.1 %
5300	35.9	4.76	4.99	4.99	4.99	0.40	1.80	± 13.1 %
5500	35.6	4.96	4.59	4.59	4.59	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.41	4.41	4.41	0.40	1.80	± 13.1 %
5750	35.4	5.22	4.47	4.47	4.47	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.42	4.42	4.42	0.40	1.80	± 13.1 %

<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below at 150 MHz is ± 50 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.
<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters (s and o) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (s and o) is restricted to ± 5%. The uncertainty is the RSS of the ConvF.

The control of the c

Certificate No: EX3-7514\_Aug18

Page 5 of 39



EX3DV4-SN:7514

August 27, 2018

#### DASY/EASY - Parameters of Probe: EX3DV4 - SN:7514

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) <sup>c</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unc (k=2)
150	61.9	0.80	12.43	12.43	12.43	0.00	1.00	± 13.3 %
300	58.2	0.92	11.39	11.39	11.39	0.05	1.20	± 13.3 %
450	56.7	0.94	11.34	11.34	11.34	0.08	1.20	± 13.3 %
750	55.5	0.96	9.68	9.68	9.68	0.31	1.04	± 12.0 %
835	55.2	0.97	9.47	9.47	9.47	0.46	0.80	± 12.0 %
900	55.0	1.05	9.34	9.34	9.34	0.46	0.83	± 12.0 %
1450	54.0	1.30	8.02	8.02	8.02	0.31	0.80	± 12.0 %
1640	53.7	1.42	7.85	7.85	7.85	0.42	0.81	± 12.0 %
1750	53.4	1.49	7.82	7.82	7.82	0.39	0.83	± 12.0 %
1810	53.3	1.52	7.69	7.69	7.69	0.32	0.92	± 12.0 %
1900	53.3	1.52	7.53	7.53	7.53	0.35	0.83	± 12.0 %
2000	53.3	1.52	7.45	7.45	7.45	0.39	0.80	± 12.0 %
2100	53.2	1.62	7.39	7.39	7.39	0.32	0.94	± 12.0 %
2300	52.9	1.81	7.25	7.25	7.25	0.37	0.85	± 12.0 %
2450	52.7	1.95	7.13	7.13	7.13	0.32	0.97	± 12.0 %
2600	52.5	2.16	7.06	7.06	7.06	0.24	1.10	± 12.0 %
3500	51.3	3.31	6.85	6.85	6.85	0.00	1.00	± 13.1 % _
3700	51.0	3.55	6.75	6.75	6.75	0.00	1.00	± 13.1 %
5200	49.0	5.30	4.59	4.59	4.59	0.50	1.90	<u>± 13.1 %</u>
5250	48.9	5.36	4.54	4.54	4.54	0.50	1.90	± 13.1 %
5300	48.9	5.42	4.49	4.49	4.49	0.50	1.90	± 13.1 %
5500	48.6	5.65	4.17	4.17	4.17	0.50	1.90	± 13.1 %
5600	48.5	5.77	4.00	4.00	4.00	0.50	1.90	± 13.1 %
5750	48.3	5.94	3.98	3.98	3.98	0.50	1.90	± 13.1 %
5800	48.2	6.00	3.94	3.94	3.94	0.50	1.90	± 13.1 %

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below at 150 MHz is ± 50 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.
<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters (s and o) can be relaxed to ± 10% if liquid compensation formula is applied to

The operations below 3 GHz, the value of the value parameters is and of can be relaxed to ± 10% if induit compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (s and o) is restricted to ± 5%. The uncertainty is the RSS of the Convert uncertainty for indicated target tissue parameters. <sup>6</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Certificate No: EX3-7514\_Aug18

Page 6 of 39



EX3DV4- SN:7514

August 27, 2018

Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

Certificate No: EX3-7514\_Aug18

Page 7 of 39



EX3DV4- SN:7514

August 27, 2018



## Receiving Pattern ( $\phi$ ), $\vartheta = 0^{\circ}$

Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

Certificate No: EX3-7514\_Aug18

Page 8 of 39



EX3DV4-- SN:7514

August 27, 2018



Dynamic Range f(SAR<sub>head</sub>) (TEM cell , f<sub>eval</sub>= 1900 MHz)

Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Certificate No: EX3-7514\_Aug18

Page 9 of 39



EX3DV4- SN:7514

August 27, 2018



## **Conversion Factor Assessment**

Certificate No: EX3-7514\_Aug18

Page 10 of 39



EX3DV4-SN:7514

August 27, 2018

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:7514

#### **Other Probe Parameters**

Canada Anna Anna Anna Anna Anna Anna Anna	
Sensor Arrangement	Triangular
Connector Angle (°)	-19.8
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm
	100

Certificate No: EX3-7514\_Aug18

Page 11 of 39