

# FCC RF EXPOSURE REPORT CERTIFICATION TEST REPORT

For

IEEE 802.11b/g/n 2T2R USB WiFi Module

**MODEL NUMBER: SKI.W7603.1** 

FCC ID: 2AR82-SKIW7603101

REPORT NUMBER: 4789631992-2

**ISSUE DATE: November 05, 2020** 

Prepared for

Guangzhou Shikun Electronics Co., Ltd NO.6 Liankun Road, Huangpu District, Guangzhou, China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com




REPORT NO.: 4789631992-2

Page 2 of 7

## **Revision History**

Rev.	Issue Date	Revisions	Revised By
V0	11/05/2020	Initial Issue	





## **TABLE OF CONTENTS**

1.	ATTESTATION OF TEST RESULTS	.4
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	.5
-		
4	REQUIREMENT	F



REPORT NO.: 4789631992-2 Page 4 of 7

#### 1. ATTESTATION OF TEST RESULTS

**Applicant Information** 

Company Name: Guangzhou Shikun Electronics Co., Ltd

Address: NO.6 Liankun Road, Huangpu District, Guangzhou, China

**Manufacturer Information** 

Company Name: Guangzhou Shikun Electronics Co., Ltd

Address: NO.6 Liankun Road, Huangpu District, Guangzhou, China

**EUT Information** 

EUT Name: IEEE 802.11b/g/n 2T2R USB WiFi Module

Model: SKI.W7603.1

Sample Received Date: September 18, 2020

Sample Status: Normal Sample ID: 3331747

Date of Tested: September 18, 2020~ September 30, 2020

APPLICABLE STANDARDS				
STANDARD		TEST RESULTS		
FCC 47CFR§2.1091		PASS		
Prepared By:	Checked By	:		
Mick. Zhong	Shema	lier		
Mick Zhang Project Engineer	Shawn Wen Laboratory L	eader		
Approved By:				
Lephenbus				
Stanban Cua	<del></del>			

Stephen Guo

Laboratory Manager



#### 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

#### 3. FACILITIES AND ACCREDITATION

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.

#### 4. REQUIREMENT

#### **LIMIT AND CALCULATION METHOD**

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

### RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E ²,  H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

#### **CALCULATION METHOD**

 $S=PG/4\pi R^2$ 

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



REPORT NO.: 4789631992-2 Page 7 of 7

#### **CALCULATED RESULTS**

WIFI Mode						
Operating	Max. Tune up Power		Power Density	Power Density Limit	Test Result	
Mode	dBm	mW	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>		
802.11n HT20	17	50.12	0.01823	1.0	Complies	

Note: 1. Antenna Gain=-2.62dBi (Numeric 1.83),  $\pi$ =3.141.

- 2. The Power comes from the operation description.
- 3. The minimum separation distance of the device is greater than 20 cm.
- 4. Calculate by WORST-CASE mode.

**END OF REPORT**