

ALARM DEVICE MANUFACTURING COMPANY				EXHIBIT 5-3				
165 EILEEN WAY								
SYOSSET, NY 11791				FCC ID # <u>CFS8DL5815MN</u>				
Date : 04/10/02 Tested by : _Yasseen Mohammed_ Approved by : Ken Addy_								
Test Sample (model) : 5815MN TRANSMITTER								
Test method: ANSI C63.4 - 1992								
Test specification: FCC Part 15, Sub-part C								
Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.								
Emissions not reported were more than 20dB below the specified unit.								
[(Meter reading + Cable/Amp factor + Antenna factor) / 20]								
(4) Conv. Reading = 10								
(5) Corr. Reading = Conv. Reading X Duty Cycle								
(6) Six Highest Emissions Recorded								
Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Am p Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								729
345	H	64.50	1.7	16.67	13915.5	10%	1391.6	7292
690	H	36.21	2.3	21.57	1009.3	10%	100.9	729
1035	H	34.17	3.2	25.39	1374.0	10%	137.4	500
1380	H	32.50	3.5	25.51	1189.9	10%	119.0	500
1725	H	34.50	3.8	26.83	1805.1	10%	180.5	729
2070	H	25.00	4.3	28.48	774.5	10%	77.4	729
2415	H	25.00	4.5	28.96	837.5	10%	83.8	729
2760	H	23.00	4.6	29.76	737.9	10%	73.8	729
3105	H	22.00	4.6	30.55	720.3	10%	72.0	729
3405	H	22.00	5.1	31.05	808.2	10%	80.8	729
4000								