

Advanced
Compliance Laboratory

6 Randolph Way
Hillsborough, NJ 08844
Tel: (908) 927 9288
Fax: (908) 927 0728

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT of

SINGLE USE PATIENT TAG
MODEL: IT-725/IT-725P/IT-725S
FCC ID: ST2-IT725 IC:6012A-IT725

May 14, 2014

This report concerns (check one): Original grant ☒ Class II change ☐
Equipment type: Low Power Intentional Radiator

Test Specifications:

☐ FCC Part 15C Sec. 15.249

☐ Industry Canada RSS-210 (Issue 8) & RSS-Gen (Issue 3)

Deferred grant requested per 47 CF 0.457(d)(1)(ii)? yes ☐ no ☒

If yes, defer until: _____ (date)

Company agrees to notify the Commission by _____ (date)
of the intended date of announcement of the product so that the grant can be
issued on that date.

Report prepared for:

CENTRAK, INC.

Report prepared by:

Advanced Compliance Lab

Report number:

0048-140502-02



Lab Code: 200101

The test result in this report IS supported and covered by the NVLAP accreditation

Table of Contents

Report Cover Page	1
Table of Contents	2
Figures	3
1. GENERAL INFORMATION	4
1.1 Verification of Compliance	4
1.2 Equipment Modifications.....	5
1.3 Product Information	6
1.4 Test Methodology	6
1.5 Test Facility	6
1.6 Test Equipment	6
1.7 Statement for the Document Use.....	7
2. PRODUCT LABELING.....	8
3. SYSTEM TEST CONFIGURATION.....	9
3.1 Justification	9
3.2 Special Accessories	9
3.3 Configuration of Tested System.....	9
4. SYSTEM SCHEMATICS	13
5. RADIATED EMISSION DATA	14
5.1 Field Strength Calculation	14
5.2 Test Methods and Conditions	14
5.3 Test Data	14
6. EUT RECEIVING MODE VERIFICATION	20
7. PHOTOS OF TESTED EUT	22

Figures

Figure 2.1 FCC/IC ID Label	8
Figure 2.2 Location of Label	8
Figure 3.1 Radiated Test Setup.....	10
Figure 4.1 EUT Schematics.....	12
Figure 7.1 Front View	21
Figure 7.2 Back View	22
Figure 7.3 PCB Component Side View.....	24
Figure 7.4 PCB Foil Side View.....	25

1. GENERAL INFORMATION

1.1 Verification of Compliance

EUT: SINGLE USE PATIENT TAG

Model: IT-725/IT-725P/IT-725S
(all models are electrical identical)

Applicant: CENTRAK, INC.

Test Type: FCC Part 15.249 &
IC RSS-210 (Issue 8) A2.9 & RSS-Gen (Issue 3)

Result: PASS

Tested by: ADVANCED COMPLIANCE LABORATORY


Test Date: May 14, 2014

Report Number: 0048-140502-02

The above equipment was tested by Compliance Laboratory, Advanced Technologies, Inc. for compliance with the requirement set forth in the FCC rules and regulations Part 15 subpart C. This said equipment in the configuration described in the report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

	Prob. Dist.	Uncertainty(dB)	Uncertainty(dB)	Uncertainty(dB)
		30-1000MHz	1-6.5GHz	Conducted
Combined Std. Uncertainty u_c	norm.	± 2.36	± 2.99	± 1.83



Wei Li
Lab Manager
Advanced Compliance Lab

Date May 14, 2014

1.2 Equipment Modifications

N/A

1.3 Product Information

System Configuration

ITEM	DESCRIPTION	FCC/IC ID	CABLE
Product	SINGLE USE PATIENT TAG IT-725/IT-725P/IT-725S (1)	ST2-IT725 6012A-IT725	
Housing	PLASTICS		
Power Supply	3V DC Battery		
Operation Freq.	904MHz ~ 926MHz		
Receiver	IT-725(RX)	Verification	

(1) EUT submitted for grant.

1.4 Test Methodology

Radiated tests were performed according to the procedures in ANSI C63.4-2003 at an antenna to EUT distance of 3 meters.

1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated and conducted data are located at Hillsborough, New Jersey, USA. This site is accepted by FCC to perform measurements under Part 15 or 18 (Registration # 90601) and also designated by IC as “site IC 3130”. This site The NVLAP Lab code for accreditation of FCC EMC Test Method is: 200101-0.

1.6 Test Equipment

Manufacture	Model	Serial No.	Description	Cal Due dd/mm/yy
Hewlett-Packard	HP8546A	3448A00290	EMI Receiver	15/10/14
EMCO	3104C	9307-4396	20-300MHz Biconical Antenna	15/01/15
EMCO	3146	9008-2860	200-1000MHz Log-Periodic Antenna	15/01/15
Electro-Meterics	ALR-25M/30	289	10KHz-30MHz Active Loop Antenna	28/05/14
Fischer Custom	LISN-2	900-4-0008	Line Impedance Stabilization Networks	18/03/15
Fischer Custom	LISN-2	900-4-0009	Line Impedance Stabilization Networks	24/03/15
EMCO	3115	4945	Double Ridge Guide Horn Antenna	22/01/15

All Test Equipment Used are Calibrated Traceable to NIST Standards. Calibration interval: 2 year.

1.7 Statement for the Document Use

This report shall not be reproduced except in full, without the written approval of the laboratory. And this report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. & Canada Government.

2. PRODUCT LABELING

Centrak SINGLE USE PATIENT TAG
Model No.: IT-725 /IT-725P/ IT-725S
FCC ID: ST2-IT725 IC: 6012A-IT725

This device complies with part 15 of the FCC Rules and IC RSS-210 & RSS-Gen Rules.. Operating is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Figure 2.1 FCC/IC ID Label
(Only ID show on the EUT)




Figure 2.2 Location of the Label

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it). Customized antenna on PCB was used.

Testing was performed as EUT was continuously operated at the following frequency channels: Low=904MHz, Middle= 915MHz, High=926MHz.

Fresh external battery was used for extended operating time.

3.2 Special Accessories

N/A

3.3 Configuration of Tested System

Figure 3.1 to Figure 3.3 illustrate this system, which is tested standing along.







Figure 3.1 Radiated Test Setup

4. SYSTEM SCHEMATICS

See Attachment.

Figure 4.1 System Schematics

5. RADIATED EMISSION DATA

5.1 Field Strength Calculation

The corrected field strength is automatically calculated by EMI Receiver using following:

$$FS = RA + AF + CF + AG$$

where FS: Corrected Field Strength in dB μ V/m

RA: Amplitude of EMI Receiver before correction in dB μ V

AF: Antenna Factor in dB/m

CF: Cable Attenuation Factor in dB

AG: Built-in Preamplifier Gain in dB (Stored in receiver as part of the calibration data)

THE "DUTY CYCLE CORRECTION FACTOR" FOR SPURIOUS RADIATED EMISSIONS IS;
 $20 \log * (4 \text{ ms} / 100 \text{ ms}) = -28 \text{ dB}$, WHICH WAS USED TO CORRECT THE AVERAGE RADIATED EMISSION READINGS.

5.2 Test Methods and Conditions

The initial step in collecting radiated data is a EMI Receiver scan of the measurement range below 30MHz using peak detector and 9KHz IF bandwidth / 30KHz video bandwidth. For the range 30MHz - 1GHz, 100KHz IF bandwidth / 100KHz video bandwidth are used. Both bandwidths are 1MHz for above 1GHz measurement. Up to 10th harmonics were investigated.

5.3 Test Data

The following data lists the significant emission frequencies, polarity and position, peak reading of the EMI Receiver, the FCC limit, and the difference between the peak reading and the limit. Explanation of the correction and calculation are given in section 5.1.

Test Personnel:



Typed/Printed Name: Edward Lee

Date: May 14, 2014

Radiated Test Data (CH-904MHz/915MHz/926MHz)

Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Peak /QP Reading at 3m (2) (dBuV/m)	FCC/IC 3m Peak Limit (3) (dBuV/m)	Difference To Peak Limit (dBuV/m)	Average Reading with Correction (>1GHz) (dBuV/m)	FCC/IC 3m QP/Average Limit (1) (dBuV/m)	Difference To AVG Limit (dBuV/m)
904	V/X	1.1	180	85.8				94	-8.2
1808	V/X	1.1	270	53.4	74	-20.6	25.4	54	-28.6
2712	V/X	1.1	250	46.4	74	-27.6	18.4	54	-35.6
904	H/X	1.0	135	91.1			91.1	94	-2.9
1808	H/X	1.0	135	54.7	74	-19.3	26.7	54	-27.3
2712	H/X	1.0	235	49.0	74	-25	21	54	-33
915	V/X	1.1	270	83.0				94	-11
1830	V/X	1.1	090	54.6	74	-19.4	26.6	54	-27.4
2745	V/X	1.1	135	46.5	74	-27.5	18.5	54	-35.5
915	H/X	1.0	090	90.1			90.1	94	-3.9
1828	H/X	1.0	180	54.0	74	-20	26	54	-28
2745	H/X	1.0	235	48.5	74	-25.5	20.5	54	-33.5
926	V/X	1.1	135	80.0				94	-14
1852	V/X	1.1	180	55.6	74	-18.4	27.6	54	-26.4
2778	V/X	1.1	235	46.5	74	-27.5	18.5	54	-35.5
926	H/X	1.0	045	87.9			87.9	94	-6.1
1852	H/X	1.0	330	54.7	74	-19.3	26.7	54	-27.3
2778	H/X	1.0	135	48.3	74	-25.7	20.3	54	-33.7
904	V/Y	1.1	180	86.1				94	-7.9
1808	V/Y	1.1	235	53.9	74	-20.1	25.9	54	-28.1
2712	V/Y	1.1	270	46.3	74	-27.7	18.3	54	-35.7
904	H/Y	1.0	135	90.9			90.9	94	-3.1
1808	H/Y	1.0	170	55.5	74	-18.5	27.5	54	-26.5
2712	H/Y	1.0	180	54.3	74	-19.7	26.3	54	-27.7
915	V/Y	1.1	000	85.5				94	-8.5
1830	V/Y	1.1	330	54.3	74	-19.7	26.3	54	-27.7
2745	V/Y	1.1	045	45.7	74	-28.3	17.7	54	-36.3
915	H/Y	1.0	235	89.2			89.2	94	-4.8
1828	H/Y	1.0	090	55.9	74	-18.1	27.9	54	-26.1
2745	H/Y	1.0	180	49.9	74	-24.1	21.9	54	-32.1
926	V/Y	1.1	135	84.5				94	-9.5

1852	V/Y	1.1	180	55.3	74	-18.7	27.3	54	-26.7
2778	V/Y	1.1	180	46.1	74	-27.9	18.1	54	-35.9
926	H/Y	1.0	090	88.8			88.8	94	-5.2
1852	H/Y	1.0	270	53.3	74	-20.7	25.3	54	-28.7
2778	H/Y	1.0	135	47.3	74	-26.7	19.3	54	-34.7
904	V/Z	1.1	135	92.3				94	-1.7
1808	V/Z	1.1	045	51.3	74	-22.7	23.3	54	-30.7
2712	V/Z	1.1	180	46.8	74	-27.2	18.8	54	-35.2
904	H/Z	1.0	045	92.1			92.1	94	-1.9
1808	H/Z	1.0	270	49.4	74	-24.6	21.4	54	-32.6
2712	H/Z	1.0	090	47.8	74	-26.2	19.8	54	-34.2
915	V/Z	1.1	045	90.6				94	-3.4
1830	V/Z	1.1	330	54.0	74	-20	26	54	-28
2745	V/Z	1.1	000	46.3	74	-27.7	18.3	54	-35.7
915	H/Z	1.0	315	89.7			89.7	94	-4.3
1830	H/Z	1.0	090	48.8	74	-25.2	20.8	54	-33.2
2745	H/Z	1.0	150	46.4	74	-27.6	18.4	54	-35.6
926	V/Z	1.1	000	88.3				94	-5.7
1852	V/Z	1.1	330	55.3	74	-18.7	27.3	54	-26.7
2778	V/Z	1.1	000	46.4	74	-27.6	18.4	54	-35.6
926	H/Z	1.0	270	87.8			87.8	94	-6.2
1852	H/Z	1.0	090	48.0	74	-26	20	54	-34
2778	H/Z	1.0	135	46.2	74	-27.8	18.2	54	-35.8

- (1) The limit for emissions within the 902-928MHz band is 50mV(94dB) per FCC Sec. 15.249 & IC RSS-210 Annex 2.9. The limit for its harmonics is 500uV (54dB). Other spurious emissions shall be lower than either its fundamental by 50dB or the limit defined in Sec. 15.209, whichever is higher.
- (2) If the peak reading is less than the FCC/IC quasi-peak or average limit, it'll be not necessary to show the measured/ calculated quasi-peak or average reading.
- (3) For above 1GHz range, peak reading shall meet the limit: average Limit+20dB.

Other Spurious outside of the band 902-928MHz

Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Peak Reading at 3m (2) (dBuV/m)	Peak Reading After Correction (dBuV/m)	FCC/IC 3m Limit (1) (dBuV/m)	Difference (dBuV/m)
720	H/X	1.0	135	39.4		46.5	-7.1
793	H/X	1.0	180	39.9		46.5	-6.6
940	H/X	1.0	240	41.8		46.5	-4.7
945	H/X	1.0	235	41.7		46.5	-4.8
468	V/Z	1.1	180	35.1		46.5	-11.4
876	V/Z	1.1	045	41.3		46.5	-5.2
936	V/Z	1.1	090	41.2		46.5	-5.3
940	V/Z	1.1	180	40.9		46.5	-5.6

Comparing to the limit defined in FCC Sec. 15.209/IC RSS-Gen, emissions below the limit by 20dB were not recorded.

