

FCC 47 CFR MPE REPORT

Continental Aftermarket & Services GmbH

Car Radio

Model Number: ACR313UBA-IVE

Additional Model: CR313UBA-IVE, TR313UBA-IVE, TRDW312UB-PIA,
TRDW313UB-BO, CRDW312UB-WH, CR313UB-MAN, TRDW311U-OR,
TRDW312UB-OR, TRDW312UB-BU, TRDW312UB-OR/WAN

FCC ID: 2AVAW-ACR313UBA-IVE

Applicant:	Continental Aftermarket & Services GmbH
Address:	Sodener Strasse 9, Schwalbach am Taunus, Germany
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2212024
Date of Test:	Nov. 10-30, 2022
Date of Report:	Dec. 02, 2022

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	-1.44	0.7178
	2441	-1.9	0.6457
	2480	-1.83	0.6561
$\pi/4$ DQPSK	2402	-2.73	0.5333
	2441	-3.17	0.4819
	2480	-3.03	0.4977
8-DPSK	2402	-2.4	0.5754
	2441	-2.71	0.5358
	2480	-2.79	0.5260

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	-1.44	-1±1	0	1.06	1.276	0.000254	1	Complies
$\pi/4$ DQPSK	-2.73	-2±1	-1	1.06	1.276	0.000202	1	Complies
8-DPSK	-2.4	-2±1	-1	1.06	1.276	0.000202	1	Complies

End of Test Report