

FCC Test Report

Report No.: AGC10232230103FE05

FCC ID : 2AEAN-RCDUO

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: Integrated Audio Production Studio

BRAND NAME : RØDE

MODEL NAME : RODECASTER DUO

APPLICANT : Rode Microphones

DATE OF ISSUE : Feb. 16, 2023

STANDARD(S)

TEST PROCEDURE(S) : FCC Part 15.247

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 80


REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Feb. 16, 2023	Valid	Initial Release	




TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	7
2.3. IEEE 802.11N MODULATION SCHEME	8
2.4. RELATED SUBMITTAL(S) / GRANT (S)	8
2.5. TEST METHODOLOGY	
2.6. SPECIAL ACCESSORIES	
2.7. EQUIPMENT MODIFICATIONS	
2.8. ANTENNA REQUIREMENT	9
3. MEASUREMENT UNCERTAINTY	10
4. DESCRIPTION OF TEST MODES	11
5. SYSTEM TEST CONFIGURATION	12
5.1. CONFIGURATION OF EUT SYSTEM	12
5.2. EQUIPMENT USED IN EUT SYSTEM	12
5.3. SUMMARY OF TEST RESULTS	12
6. TEST FACILITY	13
7. OUTPUT POWER	14
7.1. MEASUREMENT PROCEDURE	14
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	14
7.3. LIMITS AND MEASUREMENT RESULT	15
8. BANDWIDTH	16
8.1. MEASUREMENT PROCEDURE	16
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	16
8.3. LIMITS AND MEASUREMENT RESULTS	17
9. CONDUCTED SPURIOUS EMISSION	30
9.1. MEASUREMENT PROCEDURE	
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
9.3. MEASUREMENT EQUIPMENT USEDJN	
9.4 LIMITS AND MEASUREMENT RESULT	30





10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	45
10.1 MEASUREMENT PROCEDURE	45
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	45
10.3 MEASUREMENT EQUIPMENT USED	45
10.4 LIMITS AND MEASUREMENT RESULT	45
11. RADIATED EMISSION	52
11.1. MEASUREMENT PROCEDURE	52
11.2. TEST SETUP	53
11.3. LIMITS AND MEASUREMENT RESULT	54
11.4. TEST RESULT	54
12. LINE CONDUCTED EMISSION TEST	76
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	76
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	76
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	77
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	77
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	78
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	80
APPENDIX B: PHOTOGRAPHS OF EUT	80





1. VERIFICATION OF CONFORMITY

Applicant	Rode Microphones		
Address	107 Carnarvon Street, Silverwater 2128, Australia		
manufacturer	Rode Microphones		
Address	107 Carnarvon Street, Silverwater 2128, Australia		
Factory	Rode Microphones		
Address	107 Carnarvon Street, Silverwater 2128, Australia		
Product Designation	Integrated Audio Production Studio		
Brand Name	RØDE		
Test Model	RODECASTER DUO		
Date of receipt of test item	Jan. 04, 2023		
Date of test	Jan. 05, 2023 to Feb. 16, 2023		
Deviation	No any deviation from the test method		
Condition of Test Sample	Normal		
Test Result	Pass		
Report Template	AGCRT-US-BGN/RF		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Prepared By	Alan Duan	
	Alan Duan (Project Engineer)	Feb. 16, 2023
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Feb. 16, 2023
Approved By	Max Zhang	
-	Max Zhang (Authorized Officer)	Feb. 16, 2023



Report No.: AGC10232230103FE05 Page 6 of 80

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as "Integrated Audio Production Studio". It is designed by way of utilizing the DSSS and OFDM technology to achieve the system operation.

A major technical description of EUT is described as following

Equipment Type	WLAN 2.4G			
Frequency Band	2400MHz ~ 2483.5MHz			
Operation Frequency	2412MHz ~ 2462MHz			
Output Power (Average)	IEEE 802.11b:15.69dBm; IEEE 802.11g:15.36dBm;			
Output Power (Average)	IEEE 802.11n(HT20):15.03dBm; IEEE 802.11n(HT40):15.57dBm			
Output Power (Peak)	IEEE 802.11b:18.02dBm; IEEE 802.11g:22.68dBm;			
Output Fower (Feak)	IEEE 802.11n(HT20):22.45dBm; IEEE 802.11n(HT40):23.05dBm			
Modulation	802.11b:DQPSK, DBPSK, CCK			
Woddiation	802.11g/n: 64-QAM, 16-QAM, QPSK, BPSK			
	802.11b: 1/2/5.5/11Mbps			
Data Rate	802.11g: 6/9/12/18/24/36/48/54Mbps			
	802.11n: up to 300Mbps			
Number of channels	11			
Hardware Version	V1.0			
Software Version	V1.0			
Antenna Designation	PCB antenna (Comply with requirements of the FCC part 15.203)			
Antenna Gain	-1.56dBi			
Power Supply	DC 9V, 3A			



Page 7 of 80

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	1	2412 MHZ
	2	2417 MHZ
	3	2422 MHZ
	4	2427 MHZ
	5	2432 MHZ
2400~2483.5MHZ	6	2437 MHZ
	7	2442 MHZ
	8	2447 MHZ
	9	2452 MHZ
	10	2457 MHZ
	11	2462 MHZ

Note: For 20MHZ bandwidth system use Channel 1 to Channel 11. For 40MHZ bandwidth system use Channel 3 to Channel 9



Report No.: AGC10232230103FE05 Page 8 of 80

2.3. IEEE 802.11N MODULATION SCHEME

MCS Index	Nss	Modulation	R	NBPSC	NCBPS NDBPS rate(MI 800ns		NDBPS		Mbps)	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval

2.4. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AEAN-RCDUO** filing to comply with the FCC Part 15 requirements.

2.5. TEST METHODOLOGY

KDB 558074 D01 15.247 Meas Guidance v05: Guidance for compliance measurements on Digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

ANSI C63.10:2013: American National Standard for Testing Unlicensed Wireless Devices

2.6. SPECIAL ACCESSORIES

Refer to section 5.2.

2.7. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.



Page 9 of 80

2.8. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.




Page 10 of 80

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2.7 \%$
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %





4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel transmitting (TX)
2	Middle channel transmitting (TX)
3	High channel transmitting (TX)
Transm Transm	it by 802.11b with Date rate (1/2/5.5/11) it by 802.11g with Date rate (6/9/12/18/24/36/48/54) it by 802.11n (20MHz) with Date rate (6.5/13/19.5/26/39/52/58.5/65) it by 802.11n (40MHz) with Date rate (13.5/27/40.5/54/81/108/121.5/135)

Note:

1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency Individually, and the EUT is operating at its maximum duty cycle>or equal 98%

The test channel for 20MHZ bandwidth system is channel 1, 6 and 11. The test channel for 40MHZ bandwidth system is channel 3, 6 and 9.

2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.

Software Setting

```
■ C:\Users\Administrator\Desktop\RODE-2.4G定频步骤视频\88888\windows工具labtoo\DutA... 👝 📵 🖂
Enter option: 80
Dut_Bt_ResetBt: 0x000000000
Enter option: 116 1
 Dut_Bt_SetBtDisableBtuPwrCt1: 0x000000000
Enter option: 114 0
114 0
 Dut_Bt_SetBtPvrControlClass: 0x00000000
Enter option: 16 7 1
16 7 1
Dut_Bt_SetBtPwrLv1Value: 0x000000001
Enter option: 12 78
 Dut_Bt_SetBtChannel: 0x000000000
Enter option: 225 1 25
225 1 25
 Dut_Bt_TxBtDutyCycleHop: 0x000000000
Enter option:
```




Page 12 of 80

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure:




5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Integrated Audio Production Studio	RODECASTER DUO	2AEAN-RCDUO	EUT
2	Microphone	dh6	USB-TTL	AE
3	Black wired headset	HF130		AE
4	Bluetooth speaker	SRS-XB01	DC5V/0.5A	AE
5	Adapter	YDS-PD030	Input: AC 100-240V 1.5A 50/60Hz; Output: DC 5V3A/9V3A/12V2.5A/ 15V2A/20V1.5A	AE

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT	
§15.247(b)(3)	Output Power	Compliant	
§15.247(a)(2)	6 dB Bandwidth	Compliant	
§15.247	Conducted Spurious Emission	Compliant	
§15.247(e)	Maximum Conducted Output Power Spectral Density	Compliant	
§15.209	Radiated Emission	Compliant	
§15.247(d)	Band Edges	Compliant	
§15.207	Line Conduction Emission	Compliant	





6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023
LISN	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test software	R&S	ES-K1(Ver.V1.71)	N/A	N/A	N/A

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Agilent	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Signal Analyzer	Aglient	N9020A	MY52090123	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	N/A	N/A	Mar. 18, 2022	Mar. 19, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn Antenna	SCHWARZBEC	BBHA9170	768	Oct. 31, 2021	Oct. 30, 2023
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Double-Ridged Waveguide Horn	ETS	3117	00154520	Sep. 06, 2021	Sep. 05, 2023
Preamplifier Assembly	ETS	3117PA	00225134	Sep. 01, 2022	Sep. 02, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 05, 2023	Jan. 04, 2025
Test Software	Tonscend	JS32-RE	Ver.2.5	N/A	N/A



Page 14 of 80

7. OUTPUT POWER


7.1. MEASUREMENT PROCEDURE

For average power test:

- 1. Connect EUT RF output port to power sensor through an RF attenuator.
- 2. Connect the power sensor to the PC.
- 3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Record the maximum power from the software.

Note: The EUT was tested according to ANSI C63.10 (2013) for compliance to FCC 47CFR 15.247 requirements.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)






Page 15 of 80

7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power					
Test Mode	Test Channel (MHz)	Average Power (dBm)	Peak Power (dBm)	Limits (dBm)	Pass or Fail
	2412	15.27	17.99	≤30	Pass
802.11b	2437	15.69	18.02	≤30	Pass
	2462	15.25	17.75	≤30	Pass
	2412	14.89	22.36	≤30	Pass
802.11g	2437	15.36	22.68	≤30	Pass
	2462	14.93	22.28	≤30	Pass
	2412	14.99	22.25	≤30	Pass
802.11n20	2437	15.03	22.45	≤30	Pass
	2462	14.98	22.27	≤30	Pass
802.11n40	2422	15.44	23.01	≤30	Pass
	2437	15.57	23.05	≤30	Pass
	2452	15.07	22.68	≤30	Pass





8. BANDWIDTH

8.1. MEASUREMENT PROCEDURE

6dB bandwidth:


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW≥3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
 The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video
 bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)






Page 17 of 80

8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail
	2412	13.134	8.542	≥0.5	Pass
802.11b	2437	13.312	8.103	≥0.5	Pass
	2462	13.129	8.541	≥0.5	Pass
	2412	16.516	15.32	≥0.5	Pass
802.11g	2437	16.585	15.13	≥0.5	Pass
	2462	16.532	15.12	≥0.5	Pass
	2412	17.561	15.12	≥0.5	Pass
802.11n20	2437	17.636	15.13	≥0.5	Pass
	2462	17.574	15.11	≥0.5	Pass
802.11n40	2422	35.969	35.02	≥0.5	Pass
	2437	36.067	35.11	≥0.5	Pass
	2452	35.915	35.01	≥0.5	Pass




Test Graphs of Occupied Bandwidth



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.











Test_Graph_802.11g_ANT1_2462_6Mbps_OBW






Test_Graph_802.11n20_ANT1_2437_MCS0_OBW













Test Graphs of DTS Bandwidth



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.





Test_Graph_802.11g_ANT1_2412_6Mbps_DTSBW






Test_Graph_802.11g_ANT1_2462_6Mbps_DTSBW

0 Hz





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11n20_ANT1_2437_MCS0_DTSBW

OBW Power

x dB

99.00 %


-6.00 dB

14.879 kHz

15.13 MHz

Transmit Freq Error x dB Bandwidth





Test Graph 802.11n40 ANT1 2422 MCS0 DTSBW

x dB


-6.00 dB

x dB Bandwidth

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

35.02 MHz







Page 30 of 80

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 (2013) for compliance to FCC 47CFR 15.247 requirements. Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW>RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW>RBW) are conform to the requirement.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2.

9.3. MEASUREMENT EQUIPMENT USEDJN

The same as described in section 6.

9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT				
Applicable Limite	Measurement Result			
Applicable Limits	Test Data	Criteria		
In any 100 KHz Bandwidth Outside the	At least -20dBc than the limit			
frequency band in which the spread spectrum	Specified on the BOTTOM	PASS		
intentional radiator is operating, the radio frequency	Channel			
power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the TOP Channel	PASS		


Note: The limits reference level is according to the test plot of -6dB bandwidth.




Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands




Test_Graph_802.11b_ANT1_2412_1Mbps_Lower Band Emissions






































Test_Graph_802.11g_ANT1_2462_6Mbps_Lower Band Emissions ent Spectrum Analyzer - Swept SA Frequency Avg Type: Log-Pwi Avg|Hold: 8/10 Center Freq 13.750000000 GHz Trig: Free Run #Atten: 30 dB IFGain:Low **Auto Tune** Mkr1 24.969 2 GHz -50.267 dBm 10 dB/div Ref 20.00 dBm Center Freq 13.750000000 GHz Start Freq 2.500000000 GHz Stop Freq 25.000000000 GHz CF Step 2.250000000 GHz <u>Auto</u> Freq Offset 0 Hz Start 2.50 GHz #Res BW 100 kHz Stop 25.00 GHz Sweep 2.152 s (30000 pts) #VBW 300 kHz Test_Graph_802.11g_ANT1_2462_6Mbps_Higher Band Emissions







Test_Graph_802.11n20_ANT1_2412_MCS0_Lower Band Emissions














Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/











Web: http://www.agccert.com/









Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/















Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands









Note: Emissions from 2483.5-2500MHz which fall in the restricted bands had been considered with the radiated emission limits specified.



Page 45 of 80

10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

10.1 MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the ANSI C63.10 (2013) item 11.10 was used in this testing.

10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer to Section 8.2.

10.3 MEASUREMENT EQUIPMENT USED

Refer to Section 6.

10.4 LIMITS AND MEASUREMENT RESULT

	Test Data of Conducted Output Power Spectral Density								
Test Mode	Test Channel (MHz)	Power density (dBm/20kHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail				
	2412	0.344	-7.895		Pass				
802.11b	2437	0.232	-8.007	- ₹8	Pass				
	2462	0.061	-8.178	- ≪8	Pass				
	2412	-1.603	-9.842	- ₹8	Pass				
802.11g	2437	-0.935	-9.174		Pass				
	2462	-1.175	-9.414	- ₹8	Pass				
	2412	-1.234	-9.473		Pass				
802.11n20	2437	-1.126	-9.365	- ₹8	Pass				
	2462	-1.434	-9.673	- \$8	Pass				
	2422	-4.197	-12.436	- ₹8	Pass				
802.11n40	2437	-4.841	-13.08	- \$8	Pass				
	2452	-4.562	-12.801	- ₹8	Pass				

Note: Power density(dBm/3kHz) = Power density(dBm/20kHz) - 10*log(20/3).



Test Graphs of Conducted Output Power Spectral Density



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11b_ANT1_2437_1Mbps_PSD

#VBW 62 kHz

Span 12.15 MHz Sweep 29.04 ms (1000 pts)

Center 2.437000 GHz #Res BW 20 kHz
























Test_Graph_802.11n20_ANT1_2437_MCS0_PSD
















Report No.: AGC10232230103FE05 Page 52 of 80

11. RADIATED EMISSION


11.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.




11.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 54 of 80

11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission.

the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT


Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



Radiated emission from 30MHz to 1000MHz

EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHz	Antenna	Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		135.0319	13.90	18.37	32.27	43.50	-11.23	peak
2		233.3487	12.58	21.40	33.98	46.00	-12.02	peak
3	;	375.9384	10.63	24.28	34.91	46.00	-11.09	peak
4		400.4318	11.65	23.47	35.12	46.00	-10.88	peak
5		601.4265	7.71	26.18	33.89	46.00	-12.11	peak
6	*	912.8619	6.22	30.93	37.15	46.00	-8.85	peak

RESULT: PASS



EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHz	Antenna	Vertical



No	. Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		40.4172	9.40	16.90	26.30	40.00	-13.70	peak
2		61.3462	6.99	17.02	24.01	40.00	-15.99	peak
3	*	135.0319	15.96	16.32	32.28	43.50	-11.22	peak
4		233.3487	12.59	16.29	28.88	46.00	-17.12	peak
5		601.4265	8.10	25.96	34.06	46.00	-11.94	peak
6		726.8052	6.49	28.15	34.64	46.00	-11.36	peak

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

- 2. The "Factor" value can be calculated automatically by software of measurement system.
- 3. All test modes had been pre-tested. The 802.11b at middle channel is the worst case and recorded in the report.



Page 57 of 80

Radiated emission above 1GHz

EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	- Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type			
4824.000	55.63	0.08	55.71	74	-18.29	peak			
4824.000	46.29	0.08	46.37	54	-7.63	AVG			
7236.000	50.12	2.21	52.33	74	-21.67	peak			
7236.000	41.35	2.21	43.56	54	-10.44	AVG			
Remark:									
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO	
Temperature	25°C	Relative Humidity	58%	
Pressure	960hPa	Test Voltage	Normal Voltage	
Test Mode	802.11b with date rate 1	Antenna	Vertical	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4824.000	56.34	0.08	56.42	74	-17.58	peak	
4824.000	46.25	0.08	46.33	54	-7.67	AVG	
7236.000	50.15	2.21	52.36	74	-21.64	peak	
7236.000	42.69	2.21	44.9	54	-9.1	AVG	
Remark:							
Factor = Antenna Factor + Cable Loss – Pre-amplifier.							



Page 58 of 80

EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHz	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type			
4874.000	57.14	0.14	57.28	74	-16.72	peak			
4874.000	46.39	0.14	46.53	54	-7.47	AVG			
7311.000	51.03	2.36	53.39	74	-20.61	peak			
7311.000	42.57	2.36	44.93	54	-9.07	AVG			
Remark:									
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHz	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4874.000	55.29	0.14	55.43	74	-18.57	peak
4874.000	46.38	0.14	46.52	54	-7.48	AVG
7311.000	50.12	2.36	52.48	74	-21.52	peak
7311.000	40.24	2.36	42.6	54	-11.4	AVG
emark:						



Page 59 of 80

EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHz	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4924.000	55.36	0.22	55.58	74	-18.42	peak
4924.000	43.24	0.22	43.46	54	-10.54	AVG
7386.000	49.67	2.64	52.31	74	-21.69	peak
7386.000	41.02	2.64	43.66	54	-10.34	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHz	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4924.000	56.35	0.22	56.57	74	-17.43	peak
4924.000	46.28	0.22	46.5	54	-7.5	AVG
7386.000	51.03	2.64	53.67	74	-20.33	peak
7386.000	42.57	2.64	45.21	54	-8.79	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

RESULT: PASS

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been pre-tested. The 802.11b mode is the worst case and recorded in the report.



Test result for band edge emission at restricted bands

EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHz	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS



EUT	Integrated Audio Production Studio	Model Name	RODECASTER DUO
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHz	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS