



TW-1160 HANDHELD U/L/S MULTI-BAND ANTENNA

FUNCTIONAL DESCRIPTION

- Housed in a thick UV stable radome and constructed from corrosion-resistant material for reliability in the harshest environments, this gooseneck antenna has consistent gain across the band
- Compatible with TW-135, TW-900/950, TW-875, TW-860

SPECIFICATIONS

Physical	
Design	Dipole
Length	11.38 in (0.29 m)
Width	2.25 in (57 mm)
Weight	6 oz (170g)
Radome	Xenoy®
Water Resistant	IP68

Electrical	
Frequency Range	675-2600 MHz
VSWR	3.0:1 Max
Nominal Impedance	50 Ω
Power Rating	20 Watts PEP
Pattern	Omni Directional Azimuth 360° Elevation 45°
Gain	-1 ~ +2dBi
Polarization	Vertical
Connector	TNC-M

Specifications subject to change without notice.



Please access the most recent digital version of this datasheet on the TrellisWare Customer Support Site (site registration required).

When Nothing Else Works

TrellisWare Technologies, Inc.
10641 Scripps Summit Court, Suite 100, San Diego, CA 92131
Tel: 858.753.1600 | info@trellisware.com | www.trellisware.com

To place an order, please contact your account manager.
For more information, email sales@trellisware.com

TrellisWare, the TrellisWare logo, and When Nothing Else Works are trademarks or registered trademarks of TrellisWare Technologies, Inc. in the United States and other countries. All other trademarks contained herein are the property of their respective owners and their use herein does not imply sponsorship or endorsement of their products or services.
Copyright © 2022 TrellisWare Technologies, Inc. All Rights Reserved DS-TW-1160-001r2