



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.org.cn

Maximum Permissible Exposure Evaluation

FCC ID: 2AR24-AIBOX30XS

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

EUT Specification

Product Name:	LED Multimedia Processor
Trade Mark:	/
Model/Type reference:	Ai Box3.0 XS
Listed Model(s):	/
Model Difference:	/
Frequency band (Operating)	<input checked="" type="checkbox"/> BT: 2.402GHz ~ 2.480GHz <input checked="" type="checkbox"/> BLE: 2.402GHz ~ 2.480GHz <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> RLAN: 5.150GHz ~ 5.250GHz <input checked="" type="checkbox"/> RLAN: 5.725GHz ~ 5.850GHz <input type="checkbox"/> Others _____
Device category	<input type="checkbox"/> Portable (<5mm separation) <input type="checkbox"/> Mobile (>20cm separation) <input checked="" type="checkbox"/> fixed (>20cm separation) <input type="checkbox"/> Others _____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S=5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antenna <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Antenna gain (Max)	5dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Only show the value of the worst antenna

BLE - Worst case						
Type	Channel frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
GFSK	2402	5.21	6	5	0.00251	1

EDR - Worst case						
Type	Channel frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
8-DPSK	2441	7.97	9	5	0.00500	1

2.4GHz WIFI - Worst case								
Type	Channel frequency (MHz)	Antenna	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm^2)	Total Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
802.11 n40	2437	Ant1	16.92	18	5	0.03970	0.07940	1
	2437	Ant2	17.36	18	5	0.03970		1



5G WIFI U-NII-1(5150-5250MHz) - Worst case							
Type	Antenna	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Total Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11 ac20	Ant1	13.36	14	5	0.01580	0.03160	1
	Ant2	11.72	14	5	0.01580		1

5G WIFI U-NII-3(5745-5850MHz) - Worst case							
Type	Antenna	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Total Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11 ac20	Ant1	13.99	15	5	0.01990	0.03980	1
	Ant2	14.26	15	5	0.01990		1

The WiFi and BT can transmit simultaneously.

Worst case					
Type	Frequency (MHz)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	BT+WIFI Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
8-DPSK	2441	5	0.00500	0.08439	1
802.11 n40	2437	5	0.07939		

Note:

1. Calculate by Worst-case mode
2. Max. Tune Up Power by Manufacturer's Declaration, and Max. Tune Up Power is used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.
4. RF Modules ZK-7668U and ZK-7612U cannot transmit simultaneously.

*****THE END*****