



FCC ID: 2BK3WLS1433602FA

According to KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1

At 100 MHz to 6 GHz and for test separation distances ≤ 50 mm, the SAR test exclusion threshold is determined according to the following

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \times [\sqrt{f(\text{GHz})}] \leq 3.0$$

1. SAR test exclusion threshold

Frequency: 433.92 MHz (min. separation distances = 5 mm)

$$\text{SAR test exclusion thresholds (5 mm)} = 3 \times 5 / (\sqrt{0.43392}) = 22.77 \text{ mW}$$

Max. Tune-up Tolerance (mW)	SAR Test Exclusion Thresholds (5mm) (mW)
1	22.77

$$\text{Calculation Value: } 1 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{0.43392} = 0.132$$

So, Calculation value ≤ 3.0

Remark:

- Based on field strength 61.54 dBuV/m at 3m transmit power(eirp) of the device was calculated as 0.0004 mW using free space formula.
- Max. conducted power 0.0004 mW is closet 1 mW, so 1 mW was calculated.
- When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. Conclusion: No SAR is required.