

SMD CERAMIC ANTENNA

Data Sheet

CS-2450-31-L


For 2400-2480MHz

3.2x1.6mm [EIA1206]

Shenzhen silicon electrical equipment Co., LTD
Shenzhen Baoan District Gushu community Haibin Science and technology building 501

Feature


- Light weight, compact
- Wide bandwidth, low cost
- Built-in antenna with high gain



Application

- Bluetooth
- IEEE802.11g/b
- Zigbee systems
- etc...

Shapes And Dimensions Dimensions in mm



L	W	A	H
3.10±0.10	1.55±0.10	0.40±0.20	0.55±0.1




Electrical Characteristics per line(TA=25°C)

Parameter	Specification	Units
Frequency Band	2400~2480	MHz
Polarization	Line	
*Peak Gain	2.6	dBi
* Efficiency	72.30	%
Impedance	50	Ω


■ Part Numbering System

CS - 2450 - 31 - L
Material Frequency Size Type


Unit: mm




Evaluation Board



- ANT
- PAD
- TOP
- BOTTOM
- VIA




- ANT
- PAD
- TOP
- BOTTOM



■ Radiation Patterns



□ 2.4GHz WLAN BAND

⊙ 3D Gain Pattern (2441 MHz)




■ Frequency Characteristics

□ EFFICIENCY AND VSWR




■ RECOMMENDED REFLOW PROFILE




■ Packaging Style

□ REEL DIMENSIONS



□ TAPE DIMENSIONS



Feature	Specifications	Tolerances
W	8.00	±0.30
P	4.00	±0.10
E	1.75	±0.10
F	3.50	±0.10
P2	2.00	±0.10
D	1.50	+0.10 -0.00
P0	4.00	±0.10
10P0	40.00	±0.20

Quantity:5000pieces per 7 reel