

FCC Test Report

Product Name	TABLET PC
Model No.	PA-501
FCC ID	2ABTU-PA-501

Applicant	RuggON Corporation
Address	3F., No.10, Ln. 181, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City , Taiwan

Date of Receipt	Apr. 10, 2015
Issued Date	Jul. 08, 2015
Report No.	1540249R-RFUSP17V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

Test Report

Issued Date: Jul. 08, 2015

Report No.: 1540249R-RFUSP17V00



Product Name	TABLET PC
Applicant	RuggON Corporation
Address	3F., No.10, Ln. 181, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City , Taiwan
Manufacturer	Ubiqconn Technology, Inc.
Model No.	PA-501
FCC ID.	2ABTU-PA-501
EUT Rated Voltage	AC 100-240V, 50-60Hz
EUT Test Voltage	AC 120V/60Hz
Trade Name	RuggON
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2014 ANSI C63.4: 2014, ANSI C63.10: 2013
Test Result	Complied

Documented By :

Jinn Chen

(Senior Adm. Specialist / Jinn Chen)

Tested By :

Eason chen

(Engineer / Eason Chen)

Approved By :

Vincent Lin

(Director / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	4
1.1. EUT Description.....	4
1.2. Operational Description	5
1.3. Tested System Details.....	6
1.4. Configuration of tested System	6
1.5. EUT Exercise Software	6
1.6. Test Facility	7
2. Conducted Emission.....	8
2.1. Test Equipment.....	8
2.2. Test Setup	8
2.3. Limits	9
2.4. Test Procedure	9
2.5. Uncertainty	9
2.6. Test Result of Conducted Emission.....	10
3. Radiated Emission.....	12
3.1. Test Equipment.....	12
3.2. Test Setup	12
3.3. Limits	13
3.4. Test Procedure	14
3.5. Uncertainty	15
3.6. Test Result of Radiated Emission.....	16
4. Band Edge	19
4.1. Test Equipment.....	19
4.2. Test Setup	19
4.3. Limits	20
4.4. Test Procedure	20
4.5. Uncertainty	20
4.6. Test Result of Band Edge	21
5. Frequency Tolerance	22
5.1. Test Equipment.....	22
5.2. Test Setup	22
5.3. Limits	22
5.4. Test Procedure	22
5.5. Uncertainty	22
5.6. Test Result of Frequency Stability.....	23
6. EMI Reduction Method During Compliance Testing	25
Attachment 1: EUT Test Photographs	
Attachment 2: EUT Detailed Photographs	

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	TABLET PC
Trade Name	RuggON
Model No.	PA-501
FCC ID	2ABTU-PA-501
Frequency Range	13.56MHz
Modulation	ASK
Antenna Type	Loop Antenna
Power Adapter	MFR: FSP, M/N: FSP065-REB Input: 100-240V~1.5A, 50-60Hz Output: 19V ---3.42A Cable Out: Non-shielded, 1.8m

Frequency of Each Channel:

Channel	Frequency
Channel 1:	13.56 MHz

Note:

1. This device is a TABLET PC with a built-in 13.56MHz NFC transceiver.
2. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.225
3. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

Test Mode	Mode 1: Transmit mode
-----------	-----------------------


1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	Power Cord
(1)	Notebook PC	DELL	PPT	N/A	Non-Shielded, 0.8m
(2)	Monitor	DELL	ST2320L	N/A	N/A
(3)	FLASH	Transcend	JetFlash110	155422-2931	Non-Shielded, 1.8m
(4)	Earphone	AIWA	N/A	N/A	N/A

Signal Cable Type	Signal cable Description
A RS-232 Cable	Shielded, 1.8m
B HDMI Cable	Shielded, 1.8m
C Earphone Cable	Non-Shielded, 1.8m
D Micro USB Cable	Shielded, 0.6m
E RJ45 Cable	Non-Shielded, 2.0m

1.4. Configuration of tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in Section 1.4
- (2) Execute Software on the EUT.
- (3) Start the continuous transmitter.
- (4) Verify that the EUT works properly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from
QuieTek Corporation's Web Site: <http://www.quietek.com/chinese/about/certificates.aspx?bval=5>

The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site:
<http://www.quietek.com/>

Site Description: File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Registration Number: 92195

Site Name: Quietek Corporation
Site Address: No.5-22, Ruishukeng,
Linkou Dist. New Taipei City 24451,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com

FCC Accreditation Number: TW1014

2. Conducted Emission


2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2014	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2015	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2015	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar, 2015	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2015	
	No.1 Shielded Room				

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBUV) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56 _(註)	56-46 _(註)
0.50-5.0	56	46
5.0 - 30	60	50

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Uncertainty

± 2.26 dB

2.6. Test Result of Conducted Emission

Product : TABLET PC
Test Item : Conducted Emission Test
Power Line : Line 1
Test Mode : Mode 1: Transmit mode

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV	dB	dBuV
LINE 1					
Quasi-Peak					
0.162	9.761	37.480	47.241	-18.416	65.657
0.205	9.755	28.010	37.765	-26.664	64.429
0.236	9.758	24.550	34.308	-29.235	63.543
0.275	9.761	19.570	29.331	-33.098	62.429
3.138	9.947	21.930	31.877	-24.123	56.000
21.615	10.188	17.560	27.748	-32.252	60.000
Average					
0.162	9.761	25.370	35.131	-20.526	55.657
0.205	9.755	19.200	28.955	-25.474	54.429
0.236	9.758	4.480	14.238	-39.305	53.543
0.275	9.761	8.690	18.451	-33.978	52.429
3.138	9.947	12.450	22.397	-23.603	46.000
21.615	10.188	12.240	22.428	-27.572	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. “ ” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : TABLET PC
Test Item : Conducted Emission Test
Power Line : Line 2
Test Mode : Mode 1: Transmit mode

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV	dB	dBuV
LINE 2					
Quasi-Peak					
0.166	9.760	37.320	47.080	-18.463	65.543
0.212	9.756	28.630	38.386	-25.843	64.229
0.259	9.759	22.740	32.499	-30.387	62.886
0.314	9.764	18.430	28.194	-33.120	61.314
3.076	9.946	23.230	33.176	-22.824	56.000
18.853	10.316	17.670	27.986	-32.014	60.000
Average					
0.166	9.760	18.060	27.820	-27.723	55.543
0.212	9.756	17.240	26.996	-27.233	54.229
0.259	9.759	7.110	16.869	-36.017	52.886
0.314	9.764	11.610	21.374	-29.940	51.314
3.076	9.946	14.720	24.666	-21.334	46.000
18.853	10.316	12.870	23.186	-26.814	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. “ ” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

3. Radiated Emission

3.1. Test Equipment

The following test equipments are used during the radiated emission test:


Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X	Magnetic Loop Antenna	Teseq	HLA6121/ 37133	Sep, 2014
	X	Bilog Antenna	Schaffner Chase	CBL6112B/ 2707	Jun, 2015
	X	EMI Test Receiver	R&S	ESCS 30/838251/ 001	Jun, 2015
	X	Coaxial Cable	QTK(Arnist)	RG 214/ LC003-RG	Jun, 2015
	X	Coaxial signal switch	Arnist	MP59B/ 6200798682	Jun, 2015

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ CB # 8	X	Spectrum Analyzer	R&S	FSP40/ 100339	Oct, 2014
	X	Horn Antenna	ETS-Lindgren	3117/ 35205	Mar, 2015
	X	Horn Antenna	Schwarzbeck	BBHA9170/209	Jan, 2015
	X	Horn Antenna	TRC	AH-0801/95051	Aug, 2014
	X	Pre-Amplifier	EMCI	EMC012630SE/980210	Jan, 2015
	X	Pre-Amplifier	MITEQ	JS41-001040000-58-5P/153945	Jul, 2015
	X	Pre-Amplifier	NARDA	DBL-1840N506/013	Jul, 2015


- Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

3.2. Test Setup

9kHz~30MHz



30MHz~1GHz



3.3. Limits

► Fundamental electric field strength Limit

FCC Part 15 Subpart C Paragraph 15.225 Limits				
Fundamental Frequency MHz	Field strength of fundamental			
	uV/m	Distance (meter)	dBuV/m	Distance (meter)
13.553 – 13.567	15848	30	124	3
13.410 – 13.553 and 13.567 – 13.710	334	30	90.47	3
13.110 – 13.410 and 13.710 – 14.010	106	30	80.50	3
Outside of the 13.110 – 14.010	See 15.209 Limits			

Remarks : 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)

- Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

➤ Spurious electric field strength Limit

FCC Part 15 Subpart C Paragraph 15.209 Limits			
Frequency MHz	uV/m	dBuV/m	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	See Remark ¹	300
0.490-1.705	24000/F(kHz)	See Remark ¹	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Remarks : 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
 2. In the Above Table, the tighter limit applies at the band edges.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3.4. Test Procedure

Fundamental electric field strength:

The EUT and its simulators are placed on a turn table which is 1 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum electric field strength. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna which is 1 meter above ground. All X-axis, Y-axis and Z-axis polarization of the antenna are set on measurement.

Spurious electric field strength:

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C6310: 2013 on radiated measurement.

On any frequency the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurement are included emission measurement below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

The bandwidth below 30MHz setting on the field strength meter is 9kHz and above 30MHz is 120kHz.

The frequency range from 9kHz to 10th harmonics is checked.

3.5. Uncertainty

± 2.6 dB below 30MHz

± 3.8 dB above 30MHz

3.6. Test Result of Radiated Emission

Product : TABLET PC
Test Item : Fundamental Radiated Emission
Test Site : No.3 OATS
Test Mode : Mode 1: Transmit mode

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
X-axis					
Quasi-Peak					
Horizontal					
13.560	20.410	20.230	40.640	-83.360	124.000
Vertical					
13.560	20.410	21.290	41.700	-82.300	124.000
Y-axis					
Quasi-Peak					
Horizontal					
13.560	20.410	22.310	42.720	-81.280	124.000
Vertical					
13.560	20.410	23.910	44.320	-79.680	124.000
Z-axis					
Quasi-Peak					
Horizontal					
13.560	20.410	20.190	40.600	-83.400	124.000
Vertical					
13.560	20.410	21.180	41.590	-82.410	124.000

Note:

1. Limit=84dBuV/m + 40*Log (30(m)/3(m))=124dBuV/m
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : TABLET PC
 Test Item : General Radiated Emission Data (below 30MHz)
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit mode

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
27.120	19.950	10.810	30.760	-38.780	69.540
Vertical					
27.120	19.950	10.920	30.870	-38.670	69.540

Note:

1. $\text{Limit} = 29.54 \text{ dBuV/m} + 40 * \text{Log} (30(\text{m})/3(\text{m})) = 69.54 \text{ dBuV/m}$
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. “ ” means the worst emission level.
4. $\text{Measurement Level} = \text{Reading Level} + \text{Correct Factor}.$

Product : TABLET PC
Test Item : General Radiated Emission Data (above 30MHz)
Test Site : No.3 OATS
Test Mode : Mode 1: Transmit mode

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
QP Detector					
263.362	-5.004	31.191	26.186	-19.814	46.000
360.362	-1.631	41.260	39.630	-6.370	46.000
455.957	-0.437	37.619	37.182	-8.818	46.000
575.449	2.962	38.235	41.197	-4.803	46.000
791.942	5.212	28.884	34.096	-11.904	46.000
960.638	6.391	25.879	32.270	-21.730	54.000
Vertical					
QP Detector					
257.739	-7.542	43.407	35.866	-10.134	46.000
342.087	-3.588	35.691	32.103	-13.897	46.000
517.812	-0.719	37.791	37.072	-8.928	46.000
575.449	-5.622	39.634	34.012	-11.988	46.000
755.391	3.286	35.138	38.424	-7.576	46.000
922.681	5.533	28.047	33.580	-12.420	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor


4. Band Edge

4.1. Test Equipment

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 3	X	Magnetic Loop Antenna	Teseq	HLA6121/ 37133	Sep, 2014
	X	Bilog Antenna	Schaffner Chase	CBL6112B/ 2707	Jun, 2015
	X	EMI Test Receiver	R&S	ESCS 30/838251/ 001	Jun, 2015
	X	Coaxial Cable	QTK(Arnist)	RG 214/ LC003-RG	Jun, 2015
	X	Coaxial signal switch	Arnist	MP59B/ 6200798682	Jun, 2015

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with "X" are used to measure the final test results.

4.2. Test Setup



4.3. Limits

In any 9 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50 dB below that in the 9 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

4.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.

The bandwidth below 30MHz setting on the field strength meter is 9kHz and above 30MHz is 120kHz.

4.5. Uncertainty

Radiated is ± 2.6 dB

4.6. Test Result of Band Edge

Product : TABLET PC
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmit mode

RF Radiated Measurement

(Horizontal)

Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	QP Limit (dBuV/m)	Result
13.110	20.430	16.290	36.720	69.540	Pass
13.360	20.420	15.210	35.630	69.540	Pass
13.410	20.420	15.290	35.710	69.540	Pass
14.010	20.400	15.080	35.480	69.540	Pass

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. “ ” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

(Vertical)

Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	QP Limit (dBuV/m)	Result
13.110	20.430	15.090	35.520	69.540	Pass
13.360	20.420	15.110	35.530	69.540	Pass
13.410	20.420	14.210	34.630	69.540	Pass
14.010	20.400	14.390	34.790	69.540	Pass

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. “ ” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor


5. Frequency Tolerance

5.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2015
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2015
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015
X	Temperature Chamber	TDE	CHM 150CT	March, 2015

Note: All equipments are calibrated every one year.

5.2. Test Setup



5.3. Limits

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency.

5.4. Test Procedure

The over operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

5.5. Uncertainty

± 150 Hz

5.6. Test Result of Frequency Stability

Product : TABLET PC
Test Item : Frequency Tolerance
Test Site : Temperature Chamber
Test Mode : Mode 1: Transmit mode

Temperature (°C)	Voltage (V)	Observe Time	Declared Frequency (MHz)	Read Frequency (MHz)	Tolerance (%)	Limit (%)
20	120	start	13.56	13.56004	0.000295	± 0.01 %
		2mins	13.56	13.56004	0.000295	
		5mins	13.56	13.56004	0.000295	
		10mins	13.56	13.56004	0.000295	
20	138	start	13.56	13.56004	0.000295	± 0.01 %
		2mins	13.56	13.56004	0.000295	
		5mins	13.56	13.56004	0.000295	
		10mins	13.56	13.56004	0.000295	
20	102	start	13.56	13.56004	0.000295	± 0.01 %
		2mins	13.56	13.56004	0.000295	
		5mins	13.56	13.56004	0.000295	
		10mins	13.56	13.56004	0.000295	
50	120	start	13.56	13.56001	0.000074	± 0.01 %
		2mins	13.56	13.56001	0.000074	
		5mins	13.56	13.56001	0.000074	
		10mins	13.56	13.56001	0.000074	
40	120	start	13.56	13.56007	0.000516	± 0.01 %
		2mins	13.56	13.56007	0.000516	
		5mins	13.56	13.56007	0.000516	
		10mins	13.56	13.56007	0.000516	
30	120	start	13.56	13.56002	0.000147	± 0.01 %
		2mins	13.56	13.56002	0.000147	
		5mins	13.56	13.56002	0.000147	
		10mins	13.56	13.56002	0.000147	

10	120	start	13.56	13.56004	0.000295	± 0.01 %
		2mins	13.56	13.56004	0.000295	
		5mins	13.56	13.56004	0.000295	
		10mins	13.56	13.56004	0.000295	
0	120	start	13.56	13.56003	0.000221	± 0.01 %
		2mins	13.56	13.56003	0.000221	
		5mins	13.56	13.56003	0.000221	
		10mins	13.56	13.56003	0.000221	
-10	120	start	13.56	13.56002	0.000147	± 0.01 %
		2mins	13.56	13.56002	0.000147	
		5mins	13.56	13.56002	0.000147	
		10mins	13.56	13.56002	0.000147	
-20	120	start	13.56	13.56002	0.000147	± 0.01 %
		2mins	13.56	13.56002	0.000147	
		5mins	13.56	13.56002	0.000147	
		10mins	13.56	13.56002	0.000147	

6. EMI Reduction Method During Compliance Testing

No modification was made during testing.