FCC&IC Radio Test Report

FCC ID: SIB-BGTAB-NV24A

IC: 6719D-BGTABNV24A

This report concerns (check one): ■ **Original Grant** □ **Class II Change**

Project No.	:	1406C178
Equipment	:	dreamtab
Model Name	:	BGTAB-NV24A
Applicant	:	Foxconn International Inc
Address	:	NO 2 ZIYOU ST TUCHENG DISTRICT NEW TAIPEI,236 Taiwan

Date of Receipt	:	Jun. 24, 2014
Date of Test	:	Jun. 24, 2014~ Aug. 08, 2014
Issued Date	:	Aug. 11, 2014
Tested by	:	BTL Inc.

Testing Engineer : David Mao
(David Mao)

Technical Manager : Leo Hung
(Leo Hung)

Authorized Signatory : Steven Lu
(Steven Lu)

BTL INC.

No.3,Jinshagang 1st Road, Shixia,Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000FAX: +86-769-8319-6000

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL**'s authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents Page

1 . CERTIFICATION 6

2 . SUMMARY OF TEST RESULTS 7

2.1 TEST FACILITY 8

2.2 MEASUREMENT UNCERTAINTY 8

3 . GENERAL INFORMATION 9

3.1 GENERAL DESCRIPTION OF EUT 9

3.2 DESCRIPTION OF TEST MODES 11

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING 12

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 13

3.5 DESCRIPTION OF SUPPORT UNITS 14

4 . EMC EMISSION TEST 15

4.1 CONDUCTED EMISSION MEASUREMENT 15

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS 15

4.1.2 TEST PROCEDURE 15

4.1.3 DEVIATION FROM TEST STANDARD 15

4.1.4 TEST SETUP 16

4.1.5 EUT OPERATING CONDITIONS 16

4.1.6 EUT TEST CONDITIONS 16

4.1.7 TEST RESULTS 16

4.2 RADIATED EMISSION MEASUREMENT 17

4.2.1 RADIATED EMISSION LIMITS 17

4.2.2 TEST PROCEDURE 18

4.2.3 DEVIATION FROM TEST STANDARD 18

4.2.4 TEST SETUP 19

4.2.5 EUT OPERATING CONDITIONS 20

4.2.6 EUT TEST CONDITIONS 20

4.2.7 TEST RESULTS (9K TO 30MHZ) 20

4.2.8 TEST RESULTS (BETWEEN 30 TO 1000 MHZ) 20

4.2.9 TEST RESULTS (ABOVE 1000 MHZ) 21

5 . BANDWIDTH TEST 22

5.1 APPLIED PROCEDURES 22

5.1.1 TEST PROCEDURE 22

5.1.2 DEVIATION FROM STANDARD 22

5.1.3 TEST SETUP 22

5.1.4 EUT OPERATION CONDITIONS 22

5.1.5 EUT TEST CONDITIONS 22

5.1.6 TEST RESULTS 22

6 . MAXIMUM OUTPUT POWER TEST 23

Table of Contents	Page
6.1 APPLIED PROCEDURES / LIMIT	23
6.1.1 TEST PROCEDURE	23
6.1.2 DEVIATION FROM STANDARD	23
6.1.3 TEST SETUP	23
6.1.4 EUT OPERATION CONDITIONS	23
6.1.5 EUT TEST CONDITIONS	23
6.1.6 TEST RESULTS	23
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	24
7.1 APPLIED PROCEDURES / LIMIT	24
7.1.1 TEST PROCEDURE	24
7.1.2 DEVIATION FROM STANDARD	24
7.1.3 TEST SETUP	24
7.1.4 EUT OPERATION CONDITIONS	24
7.1.5 EUT TEST CONDITIONS	24
7.1.6 TEST RESULTS	24
8 . POWER SPECTRAL DENSITY TEST	25
8.1 APPLIED PROCEDURES / LIMIT	25
8.1.1 TEST PROCEDURE	25
8.1.2 DEVIATION FROM STANDARD	25
8.1.3 TEST SETUP	25
8.1.4 EUT OPERATION CONDITIONS	25
8.1.5 EUT TEST CONDITIONS	25
8.1.6 TEST RESULTS	25
9 . MEASUREMENT INSTRUMENTS LIST	26
10 . EUT TEST PHOTO	28
ATTACHMENT A - CONDUCTED EMISSION	32
ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)	35
ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)	37
ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)	44
ATTACHMENT E - BANDWIDTH	77
ATTACHMENT F - MAXIMUM OUTPUT POWER	88
ATTACHMENT G – ANTENNA CONDUCTED SPURIOUS EMISSION	91
ATTACHMENT H – POWER SPECTRAL DENSITY	110

REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FICP-4-1406C178	Original Issue.	Aug. 11, 2014

1. CERTIFICATION

Equipment	:	dreamtab
Brand Name	:	FUHU
Model Name	:	BGTAB-NV24A
Applicant		Foxconn International Inc.
Manufacturer	:	FUHU INC
Address	:	909N., Sepulveda Blvd., Suite 540, E1 Segundo, CA 90245
Factory	:	HONGFUJIN Precision Electronics (Chong Qing) Co., Ltd.
Address	:	No.1, 1st E District RD., Shapingba District, Chongqing 401332, P.R. China
Date of Test	:	Jun. 24, 2014~ Aug. 08, 2014
Test Item	:	ENGINEERING SAMPLE
Standard(s)	:	FCC Part15, Subpart C(15.247) / ANSI C63.4-2009 Canada RSS-210:2010 RSS-GEN Issue 3, Dec 2010

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc..
The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FICP-4-1406C178) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247) , Subpart C **Canada RSS-210:2010; RSS-GEN Issue 3, Dec 2010**				
Standard(s) Section		Test Item	Judgment	Remark
FCC	**IC**			
15.207	RSS-GEN 7.2.2	Conducted Emission	PASS	
15.247(d)	RSS-210 Annex 8 (A8.5)	Antenna conducted Spurious Emission	PASS	
15.247(a)(2)	RSS-210 Annex 8 (A8.2(a))	6dB Bandwidth	PASS	
15.247(b)(3)	RSS-210 Annex 8 (A8.4(4))	Peak Output Power	PASS	
15.247(e)	RSS-210 Annex 8 (A8.2(b))	Power Spectral Density	PASS	
15.203	-	Antenna Requirement	PASS	
15.209/15.205	RSS-210 Annex 8 (A8.5)	Transmitter Radiated Emissions	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this test report.

(2) The test follows FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r02 (Measurement Guidelines of DTS)

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792
BTL's test firm number for FCC: 319330
BTL's test firm number for IC: 4428B-1

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U，(dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U，(dB)	NOTE
DG-CB03	CISPR	9KHz~30MHz	V	3.79	
		9KHz~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	dreamtab	
Brand Name	FUHU	
Model Name	BGTAB-NV24A	
Model Difference	N/A	
Product Description	Operation Frequency	5745~5825 MHz
	Modulation Technology	802.11a/n:OFDM
	Bit Rate of Transmitter	300Mbps
	Output Power (Max.)	802.11a: 21.73 dBm 802.11n(20MHz): 23.50 dBm 802.11n(40MHz):23.30 dBm
Power Source	#1 DC supplied from AC Adapter. Model: ADS-65LSI-19-3 19065G #2 Supplied from rechargeable Li-ion polymer battery. Brand / Model: McNair / MLP2462113-4S	
Power Rating	#1 I/P AC 100-240V~ 50/60Hz 1.5A O/P: DC 19V 3.42A #2 14.8V 1650mAh 24.42Wh	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

802.11a / 802.11n 20M					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	**5745**	153	5765	**157**	**5785**
161	5805	**165**	**5825**		

802.11n 40M			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	**5755**	**159**	**5795**

3. Table for Filed Antenna

Group 1

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1	FOXCONN	PCA-3007-25GC1-A2	Integral	N/A	-1.31	360mm
2	FOXCONN	PCA-3007-25GC1-A5	Integral	N/A	-3.46	65mm

Group 2

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1	MAG Corporation	PCA-3007-25GC1-A2	Integral	N/A	2.24	360mm
2	MAG Corporation	PCA-3007-25GC1-A5	Integral	N/A	1.92	65mm

Note:
1.The EUT incorporates a MIMO function. Physically, the EUT provides two completed two transmitters and two receivers (2T2R).
2. ANT 1 for 1TX was found to be the worst case and recorded.
3. Two groups of antenna were used with the same type, only differ in manufacturer and gain. Group 2 was tested and recorded as the worst case in this report.

Operating Mode / TX Mode	1TX	2TX
802.11a	V (ANT 1)	-
802.11n(20MHz)	-	V (ANT 1 + ANT 2)
802.11n(40MHz)	-	V (ANT 1 + ANT 2)

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX A MODE CHANNEL 149/157/165
Mode 2	TX N-20MHZ MODE CHANNEL 149/157/165
Mode 3	TX N-40MHZ MODE CHANNEL 151/159
Mode 4	TX MODE

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 4	TX MODE

For Radiated Test	
Final Test Mode	Description
Mode 1	TX A MODE CHANNEL 149/157/165
Mode 2	TX N-20MHZ MODE CHANNEL 149/157/165
Mode 3	TX N-40MHZ MODE CHANNEL 151/159

Note:

(1) For radiated below 1G test, the 802.11a is found to be the worst case and recorded.

(2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis. The worst case was found positioned on Z-plane. Therefore only the test data of this Z-plane was used for radiated emission measurement test.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test software version	N/A		
Frequency	**5745 MHz**	**5785 MHz**	**5825 MHz**
IEEE 802.11a	14	14	14
IEEE 802.11 n (20MHz)	13	13	13

Test software version	N/A	
Frequency	**5755 MHz**	**5795 MHz**
IEEE 802.11 n (40MHz)	14	13

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
-	-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
-	-	-	-	-

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d. LISN at least 80 cm from nearest part of EUT chassis.

e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

(1) All readings are QP Mode value unless otherwise stated AVG in column of『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform。In this case, a " * " marked in AVG Mode column of Interference Voltage Measured。

(2) Measuring frequency range from 150KHz to 30MHz。

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz-1000MHz)

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) & RSS-210 section 2.2& Annex 8 (A8.5), then the 15.209(a)& RSS-Gen limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2.2 TEST PROCEDURE

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz

(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **4.1.6** Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: DC14.8V

4.2.7 TEST RESULTS (9K TO 30MHZ)

Please refer to the Attachment B

4.2.8 TEST RESULTS (BETWEEN 30 TO 1000 MHZ)

Please refer to the Attachment C

Remark:

(1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
(2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
(3) Measuring frequency range from 30MHz to 1000MHz.
(4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

4.2.9 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

Remark:

(1) All readings are Peak unless otherwise stated QP in column of『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.

(2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.

(3) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

(4) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.

(5) EUT Orthogonal Axis:
"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand

(6) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

5. BANDWIDTH TEST

5.1 Applied procedures

FCC Part15 (15.247) , Subpart C/ RSS-GEN and RSS-210			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(2) RSS-GEN section 4.6.1 RSS-210 Annex 8 (A8.2(a))	Bandwidth	5725 - 5825	PASS

5.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: DC14.8V

5.1.6 TEST RESULTS

Please refer to the Attachment E.

6. MAXIMUM OUTPUT POWER TEST

6.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C/ RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3) RSS-210 Annex 8.4(4)	Maximum Output Power	1 Watt or 30dBm	5725 - 5825	PASS

6.1.1 TEST PROCEDURE

a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
b. The maximum peak conducted output power was performed in accordance with method 9.1.3 of FCC KDB 558074 D01 DTS Meas Guidance v03r02.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP

6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.
Transmit output power was measured while the host equipment supply voltage was varied from 85 % to 115 % of the nominal rated supply voltage. No change in transmit output power was observed.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: DC14.8V

6.1.6 TEST RESULTS

Please refer to the Attachment F.

7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 Applied procedures / limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

7.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: DC14.8V

7.1.6 TEST RESULTS

Please refer to the Attachment G.

8. POWER SPECTRAL DENSITY TEST

8.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C / RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e) RSS-210 Annex 8(A8.2(b))	Power Spectral Density	8 dBm (in any 3KHz)	5745 - 5825	PASS

8.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting: RBW=3KHz, VBW=10KHz, Sweep time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP

8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: DC14.8V

8.1.6 TEST RESULTS

Please refer to the Attachment H.

9. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	Mar. 29, 2015
2	LISN	R&S	ENV216	101447	Mar. 29, 2015
3	Test Cable	N/A	C_17	N/A	Mar. 14, 2015
4	EMI TEST RECEIVER	R&S	ESCS30	833364/017	Mar. 29, 2015
5	50Ω Terminator	SHX	TF2-3G-A	08122902	Mar. 29, 2015

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	EMCO	3142C	00066462	Mar. 29, 2015
2	Antenna	EMCO	3142C	00066464	Mar. 29, 2015
3	Amplifier	Agilent	8447D	2944A11203	Nov. 11, 2014
4	Amplifier	Agilent	8447D	2944A11204	Nov. 11, 2014
5	Spectrum Analyzer	Agilent	E4443A	MY48250370	Nov. 11, 2014
6	RF Pre-selector	Agilent	N9039A	MY46520201	Nov. 11, 2014
7	Test Cable	N/A	Cable_5m_8m_15m	N/A	Jan. 14, 2015
8	Test Cable	N/A	Cable_5m_11m_15m	N/A	Jan. 14, 2015
9	Spectrum Analyzer	Agilent	E4447A	MY48250208	Nov. 11, 2014
10	RF Pre-selector	Agilent	N9039A	MY46520214	Nov. 11, 2014
11	Multi-Device Controller	ETS-Lindgren	2090	N/A	N/A
12	Horn Antenna	EMCO	3115	9605-4803	Mar. 29, 2015
13	Amplifier	Agilent	8449B	3008A02584	Nov. 11, 2014
14	Spectrum Analyzer	Agilent	E4447A	MY48250208	Nov. 11, 2014
15	Test Cable	Huber+Suhner	SUCOFLEX_15m_4m	N/A	Jan. 14, 2015
16	Multi-Device Controller	ETS-Lindgren	2090	N/A	N/A

6dB Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

Peak Output Power Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	P-series Power meter	Agilent	N1911A	MY45100473	Mar. 29, 2015
2	Wireband Power sensor	Agilent	N1921A	MY51100041	Mar. 29, 2015

Antenna Conducted Spurious Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

Power Spectral Density Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

Remark: ”N/A” denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.

10. EUT TEST PHOTO

Conducted Measurement Photos



Radiated Measurement Photos

9KHz to 30MHz

Radiated Measurement Photos

30MHz to 1000MHz



Radiated Measurement Photos

Above 1000MHz



ATTACHMENT A - CONDUCTED EMISSION

Test Mode:	TX Mode

Line



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1540	36.49	9.52	46.01	65.78	-19.77	peak	
2		0.1930	32.31	9.54	41.85	63.91	-22.06	peak	
3		0.2242	28.33	9.54	37.87	62.66	-24.79	peak	
4		0.4898	22.97	9.59	32.56	56.17	-23.61	peak	
5		11.0897	28.87	10.15	39.02	60.00	-20.98	peak	
6		12.9961	26.90	10.25	37.15	60.00	-22.85	peak	

Test Mode:	TX Mode

Neutral



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1540	37.38	9.52	46.90	65.78	-18.88	peak	
2		0.1970	32.13	9.53	41.66	63.74	-22.08	peak	
3		0.2281	27.45	9.53	36.98	62.52	-25.54	peak	
4		0.4977	23.11	9.58	32.69	56.04	-23.35	peak	
5		11.0897	29.01	10.22	39.23	60.00	-20.77	peak	
6	*	13.2110	34.39	10.36	44.75	60.00	-15.25	peak	

ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)

Test Mode ：	TX Mode

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0156	0°	13.43	24.58	38.01	103.74	-65.73	AVG
0.0156	0°	14.27	24.58	38.85	123.74	-84.89	PEAK
0.0311	0°	6.81	23.60	30.41	97.75	-67.34	AVG
0.0311	0°	8.03	23.60	31.63	117.75	-86.12	PEAK
0.0385	0°	4.32	23.13	27.45	95.90	-68.45	AVG
0.0385	0°	5.73	23.13	28.86	115.90	-87.04	PEAK
0.0470	0°	3.14	22.59	25.73	94.16	-68.43	AVG
0.0470	0°	4.81	22.59	27.40	114.16	-86.76	PEAK
2.0604	0°	28.74	19.46	48.20	69.54	-21.34	QP
3.3738	0°	20.39	18.94	39.33	69.54	-30.21	QP

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0155	90°	13.18	24.30	37.48	123.80	-86.32	AVG
0.0155	90°	14.17	24.30	38.47	143.80	-105.33	PEAK
0.0311	90°	6.87	23.60	30.47	117.75	-87.28	AVG
0.0311	90°	7.79	23.60	31.39	137.75	-106.36	PEAK
0.0373	90°	5.93	23.20	29.13	116.17	-87.04	AVG
0.0373	90°	6.84	23.20	30.04	136.17	-106.13	PEAK
0.0470	90°	5.14	22.59	27.73	114.16	-86.43	AVG
0.0470	90°	6.09	22.59	28.68	134.16	-105.48	PEAK
2.0604	90°	29.63	19.46	49.09	69.54	-20.45	QP
3.2842	90°	17.12	18.93	36.05	69.54	-33.49	QP

Remark:

(1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
(2) Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
(3) Limit line = specific limits (dBuV) + distance extrapolation factor.

ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode:	TX A MODE 5745MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		184.2300	48.09	13.57	34.52	43.50	8.98	peak	
2	*	203.6300	52.91	-15.14	37.77	43.50	-5.73	peak	
3		618.7900	40.47	-6.88	33.59	46.00	-12.41	peak	
4		687.6600	38.34	-4.98	33.36	46.00	-12.64	peak	
5		756.5300	38.67	-4.40	34.27	46.00	-11.73	peak	
6		960.2300	38.01	-0.25	37.76	54.00	-16.24	peak	

Test Mode:	TX A MODE 5745MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		120.2100	47.57	-14.19	33.38	43.50	-10.12	peak	
2		184.2300	50.06	-13.57	36.49	43.50	-7.01	peak	
3	*	203.6300	53.80	-15.14	38.66	43.50	-4.84	peak	
4		239.5200	50.23	-14.05	36.18	46.00	-9.82	peak	
5		275.4100	46.94	-12.72	34.22	46.00	-11.78	peak	
6		960.2300	37.51	-0.25	37.26	54.00	-16.74	peak	

Test Mode:	TX A MODE 5785MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		120.2100	48.46	-14.19	34.27	43.50	-9.23	peak	
2		184.2300	49.09	-13.57	35.52	43.50	-7.98	peak	
3	*	203.6300	52.91	-15.14	37.77	43.50	-5.73	peak	
4		618.7900	41.47	-6.88	34.59	46.00	-11.41	peak	
5		756.5300	39.67	-4.40	35.27	46.00	-10.73	peak	
6		960.2300	39.01	-0.25	38.76	54.00	-15.24	peak	

Test Mode:	TX A MODE 5785MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		184.2300	49.95	-13.57	36.38	43.50	-7.12	peak	
2	*	203.6300	53.79	-15.14	38.65	43.50	-4.85	peak	
3		240.4900	49.05	-14.04	35.01	46.00	-10.99	peak	
4		338.4600	45.62	-11.60	34.02	46.00	-11.98	peak	
5		756.5300	39.54	-4.40	35.14	46.00	-10.86	peak	
6		960.2300	35.67	-0.25	35.42	54.00	-18.58	peak	

Test Mode:	TX A MODE 5825MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		120.2100	47.46	-14.19	33.27	43.50	-10.23	peak	
2		184.2300	47.59	-13.57	34.02	43.50	-9.48	peak	
3	*	203.6300	52.41	-15.14	37.27	43.50	-6.23	peak	
4		618.7900	40.47	-6.88	33.59	46.00	-12.41	peak	
5		756.5300	38.17	-4.40	33.77	46.00	-12.23	peak	
6		960.2300	37.51	-0.25	37.26	54.00	-16.74	peak	

Test Mode:	TX A MODE 5825MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		184.2300	49.95	-13.57	36.38	43.50	-7.12	peak	
2	*	203.6300	53.79	-15.14	38.65	43.50	-4.85	peak	
3		240.4900	48.55	-14.04	34.51	46.00	-11.49	peak	
4		275.4100	45.63	-12.72	32.91	46.00	-13.09	peak	
5		756.5300	38.04	-4.40	33.64	46.00	-12.36	peak	
6		960.2300	34.67	-0.25	34.42	54.00	-19.58	peak	

ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)

Orthogonal Axis :	X
Test Mode :	TX A Mode 5745MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5725.000	19.35	44.58	63.93	74.00	-10.07	peak	
2		5725.000	5.42	44.58	50.00	54.00	-4.00	AVG	
3	*	5742.400	49.60	44.67	94.27	54.00	40.27	AVG	Fundamental frequency, no limit
4	X	5747.900	57.80	44.70	102.50	74.00	28.50	peak	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX A Mode 5745MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11490.17	35.34	16.47	51.81	74.00	-22.19	peak	
2	*	11490.17	23.57	16.47	40.04	54.00	-13.96	AVG	

Orthogonal Axis :	X
Test Mode :	TX A Mode 5745MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5725.000	19.30	44.58	63.88	74.00	-10.12	peak	
2		5725.000	5.21	44.58	49.79	54.00	-4.21	AVG	
3	X	5741.900	59.11	44.66	103.77	74.00	29.77	peak	Fundamental frequency, no limit
4	*	5742.100	51.05	44.67	95.72	54.00	41.72	AVG	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX A Mode 5745MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11489.32	32.90	16.47	49.37	74.00	-24.63	peak	
2	*	11490.56	21.67	16.47	38.14	54.00	-15.86	AVG	

Orthogonal Axis :	X
Test Mode :	TX A Mode 5785MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	5783.600	49.08	44.89	93.97	54.00	39.97	AVG	Fundamental frequency, no limit
2	X	5785.600	57.00	44.90	101.90	74.00	27.90	peak	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX A Mode 5785MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11569.13	36.07	16.44	52.51	74.00	-21.49	peak	
2	*	11570.81	23.89	16.44	40.33	54.00	-13.67	AVG	

Orthogonal Axis :	X
Test Mode :	TX A Mode 5785MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	5782.200	52.64	44.87	97.51	54.00	43.51	AVG	Fundamental frequency, no limit
2	X	5790.400	60.51	44.92	105.43	74.00	31.43	peak	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX A Mode 5785MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11568.97	34.89	16.44	51.33	74.00	-22.67	peak	
2	*	11570.89	23.53	16.44	39.97	54.00	-14.03	AVG	

Orthogonal Axis :	X
Test Mode :	TX A Mode 5825MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	5822.100	49.03	45.08	94.11	54.00	40.11	AVG	Fundamental frequency, no limit
2	X	5823.000	57.97	45.09	103.06	74.00	29.06	peak	Fundamental frequency, no limit
3		5850.000	15.04	45.23	60.27	74.00	-13.73	peak	
4		5850.000	1.87	45.23	47.10	54.00	6.90	AVG	

Orthogonal Axis :	X
Test Mode :	TX A Mode 5825MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11650.81	36.20	16.40	52.60	74.00	-21.40	peak	
2	*	11650.97	23.86	16.40	40.26	54.00	-13.74	AVG	

Orthogonal Axis :	X
Test Mode :	TX A Mode 5825MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	5821.200	61.01	45.07	106.08	74.00	32.08	peak	Fundamental frequency, no limit
2	*	5821.700	53.11	45.08	98.19	54.00	44.19	AVG	Fundamental frequency, no limit
3		5850.000	18.42	45.23	63.65	74.00	-10.35	peak	
4		5850.000	5.84	45.23	51.07	54.00	-2.93	AVG	

Orthogonal Axis :	X
Test Mode :	TX A Mode 5825MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11649.22	35.90	16.40	52.30	74.00	-21.70	peak	
2	*	11650.75	23.67	16.40	40.07	54.00	-13.93	AVG	

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5745MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5725.000	15.71	44.58	60.29	74.00	-13.71	peak	
2		5725.000	4.33	44.58	48.91	54.00	-5.09	AVG	
3	X	5742.800	59.15	44.67	103.82	74.00	29.82	peak	Fundamental frequency, no limit
4	*	5742.800	50.03	44.67	94.70	54.00	40.70	AVG	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5745MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11489.16	36.34	16.47	52.81	74.00	-21.19	peak	
2	*	11490.83	25.17	16.47	41.64	54.00	-12.36	AVG	

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5745MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5725.000	17.98	44.58	62.56	74.00	-11.44	peak	
2		5725.000	5.84	44.58	50.42	54.00	-3.58	AVG	
3	*	5742.200	51.26	44.67	95.93	54.00	41.93	AVG	Fundamental frequency, no limit
4	X	5746.300	61.14	44.69	105.83	74.00	31.83	peak	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5745MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11489.31	34.43	16.47	50.90	74.00	-23.10	peak	
2	*	11490.64	22.26	16.47	38.73	54.00	-15.27	AVG	

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5785MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	5782.900	58.03	44.88	102.91	74.00	28.91	peak	Fundamental frequency, no limit
2	*	5782.900	50.57	44.88	95.45	54.00	41.45	AVG	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5785MHz

Vertical



No	Mk	Freq	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11570.36	36.37	16.44	52.81	74.00	-21.19	peak	
2	*	11570.75	24.65	16.44	41.09	54.00	-12.91	AVG	

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5785MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	5783.600	60.84	44.89	105.73	74.00	31.73	peak	Fundamental frequency, no limit
2	*	5783.600	52.42	44.89	97.31	54.00	43.31	AVG	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5785MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11570.76	35.70	16.44	52.14	74.00	-21.86	peak	
2	*	11571.12	24.07	16.44	40.51	54.00	-13.49	AVG	

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5825MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	5822.400	60.36	45.09	105.45	74.00	31.45	peak	Fundamental frequency, no limit
2	*	5822.500	51.04	45.09	96.13	54.00	42.13	AVG	Fundamental frequency, no limit
3		5850.000	17.73	45.23	62.96	74.00	-11.04	peak	
4		5850.000	5.25	45.23	50.48	54.00	-3.52	AVG	

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5825MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Dctcctor	Commcnt
1		11649.21	36.36	16.40	52.76	74.00	-21.24	peak	
2	*	11650.63	24.87	16.40	41.27	54.00	-12.73	AVG	

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5825MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	5821.500	52.97	45.07	98.04	54.00	44.04	AVG	Fundamental frequency, no limit
2	X	5822.800	61.75	45.09	106.84	74.00	32.84	peak	Fundamental frequency, no limit
3		5850.000	21.98	45.23	67.21	74.00	-6.79	peak	
4		5850.000	6.40	45.23	51.63	54.00	-2.37	AVG	

Orthogonal Axis :	X
Test Mode :	TX N20 Mode 5825MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11650.47	35.02	16.40	51.42	74.00	-22.58	peak	
2	*	11650.91	23.61	16.40	40.01	54.00	-13.99	AVG	

Orthogonal Axis :	X
Test Mode :	TX N40 Mode 5755MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	5725.000	11.18	44.58	55.76	54.00	1.76	AVG	
2	*	5742.400	47.21	44.67	91.88	54.00	37.88	AVG	Fundamental frequency, no limit
3		5725.000	26.88	44.58	71.46	74.00	-2.54	peak	
4	X	5747.600	57.27	44.70	101.97	74.00	27.97	peak	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX N40 Mode 5755MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11510.27	34.07	16.49	50.56	74.00	-23.44	peak	
2	*	11510.83	22.62	16.48	39.10	54.00	-14.90	AVG	

Orthogonal Axis :	X
Test Mode :	TX N40 Mode 5755MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	5725.000	13.83	44.58	58.41	54.00	4.41	AVG	
2	*	5758.600	50.12	44.76	94.88	54.00	40.88	AVG	Fundamental frequency, no limit
3	X	5725.000	32.73	44.58	77.31	74.00	3.31	peak	
4	X	5743.200	60.47	44.67	105.14	74.00	31.14	peak	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX N40 Mode 5755MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11509.41	33.09	16.49	49.58	74.00	-24.42	peak	
2	*	11510.38	21.97	16.49	38.46	54.00	-15.54	AVG	

Orthogonal Axis :	X
Test Mode :	TX N40 Mode 5795MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5850.000	4.08	45.23	49.31	54.00	-4.69	AVG	
2	*	5797.800	47.47	44.96	92.43	54.00	38.43	AVG	Fundamental frequency, no limit
3		5850.000	14.70	45.23	59.93	74.00	-14.07	peak	
4	X	5797.800	57.67	44.96	102.63	74.00	28.63	peak	Fundamental frequency, no limit

Orthogonal Axis :	X
Test Mode :	TX N40 Mode 5795MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11588.58	35.28	16.44	51.72	74.00	-22.28	peak	
2	*	11590.83	24.12	16.43	40.55	54.00	-13.45	AVG	

Orthogonal Axis :	X
Test Mode :	TX N40 Mode 5795MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	5786.800	60.38	44.90	105.28	74.00	31.28	peak	Fundamental frequency, no limit
2	*	5798.800	49.90	44.96	94.86	54.00	40.86	AVG	Fundamental frequency, no limit
3		5850.000	21.46	45.23	66.69	74.00	-7.31	peak	
4		5850.000	5.78	45.23	51.01	54.00	-2.99	AVG	

Orthogonal Axis :	X
Test Mode :	TX N40 Mode 5795MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11590.84	34.09	16.43	50.52	74.00	-23.48	peak	
2	*	11590.91	23.11	16.43	39.54	54.00	-14.46	AVG	

ATTACHMENT E - BANDWIDTH

Test Mode : TX A Mode_CH149/157/165

Test Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	LIMIT (MHz)
CH149	5745	16.00	16.35	>=500KHz
CH157	5785	16.25	16.35	>=500KHz
CH165	5825	16.25	16.35	>=500KHz

TX CH 149



Date: 29.JUL.2014 20:44:36

TX CH 157



Date: 29.JUL.2014 20:48:14

TX CH 165



Date: 29.JUL.2014 21:00:41