

Page: 1 of 32

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT





CLASS II & IV PC REPORT

Applicant: Acer Incorporated

8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi, New Taipei City

22181, Taiwan (R.O.C)

Product Name: 2TX 11ax (WiFi6) + BLE Combo Card

Brand Name: acer

Model No.: MT7921

Model Difference: N/A

Report Number: E2/2021/80018

FCC ID HLZMT7921

IC: 1754F-MT7921

Issue Date: October 7, 2021

Date of Test: August 20, 2021 ~ September 10, 2021

Date of EUT Received: August 13, 2021

Approved By Jazz Huang

Jazz Huang

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. Central RF Lab The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10:2013 and the energy emitted by the sample EUT comply with FCC rule part §15.247, ISED RSS-247.

The results of this report relate only to the sample identified in this report.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 2 of 32

Revision History					
Report Number Revision Description Issue Date Revised By					
E2/2021/80018	00	Original	October 7, 2021	Ariel Chang	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號



Page: 3 of 32

Table of Contents

1	GENERAL INFORMATION	4
2	SYSTEM TEST CONFIGURATION	6
3	SUMMARY OF TEST RESULTS	9
4	DESCRIPTION OF TEST MODES	. 10
5	MEASUREMENT UNCERTAINTY	. 12
6	PEAK OUTPUT POWER MEASUREMENT	. 13
7	SPLIDIOUS EMISSION MEASUPEMENT	16

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號t (886-2) 2299-3279 f (886-2) 2298-0488 www.sgs.com.tw



Page: 4 of 32

GENERAL INFORMATION

1.1 **Product Description**

Product Name	Notebook Computer
Brand Name	acer
Model No. of FCC Host	N21Q5
Model No. of IC Host	CB514-2H,CB514-2HT
Model Difference	For the marketing purpose, only different model designations on the marking plate for different markets. No RF concern.
Hardware Version	N/A
Software Version	N/A
EUT Series No.	N8AS2WW0011190E3B17600
Model No. of BT/WLAN Module	MT7921
Class II & Class IV	2TX 11ax (WiFi6) + BLE Combo Card installed in Notebook Com-
Permissive change	puter
Power Supply	11.25Vdc from Rechargeable Li-polymer Battery or 19Vdc from AC/DC Adapter

1.2 **RF Specification**

Radio Technology	BLE
Frequency Range	2402 – 2480MHz
Channel number	40 channels
Modulation type	GFSK
Transmit Power	BLE 1M: 10.32 dBm BLE 2M: 10.30 dBm

1.3 Antenna Designation

Bluetooth Low Energy							
Antenna	Cupplier	Antenna	Freq.	Peak Antenna			
Type	Supplier	Part No.	(MHz)	Gain (dBi)			
PIFA	WNC	DQ6K15G5900(81EABK15.G59)	2400~2500	1.15			
Note:							
1. Antenna info	Antenna information is provided by the applicant.						

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 5 of 32

1.4 Test Methodology of Applied Standards

FCC Part 15, Subpart C §15.247 FCC KDB 558074 D01 15.247 Meas Guidance v05r02 RSS-247 issue 2 Feb. 2017 RSS-Gen, Issue 5 (Amendment 2, February 2021) ANSI C63.10:2013

1.5 Test Facility

Laboratory	Test Site Address	Test Site Name	FCC Designa- tion number	IC CAB identifier
		SAC 1		
		SAC 3		
		Conduction 1		
	No.134, Wu Kung Road, New Taipei	Conducted 1		
	Industrial Park, Wuku District, New	Conducted 2	TW0027	TW3702
	Taipei City, Taiwan.	Conducted 3		
		Conducted 4	_	
		Conducted 5		
SGS Taiwan Ltd.		Conducted 6		
Central RF Lab.		Conduction C	TW0028	
(TAF code 3702)		SAC C		
(1A1 COUC 57 02)		SAC D		
		SAC G		
	No.2, Keji 1st Rd., Guishan District,	Conducted A		
	Taoyuan City, Taiwan 333	Conducted B		
	ladyddir Oity, Taiwaii 555	Conducted C		
		Conducted D		
		Conducted E		
		Conducted F		
		Conducted G		

Note: Test site name is remarked on the equipment list in each section of this report as an indication where measurements occurred in specific test site and address.

1.6 Special Accessories

There are no special accessories used while test was conducted.

1.7 Equipment Modifications

There was no modification incorporated into the EUT.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 6 of 32

SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

An engineering test mode (software/firmware) that applicant provided was utilized to manipulate the EUT into transmit, selection of the test channel, and modulation scheme.

2.3 Test Procedure

2.3.1 **Conducted Emissions**

The EUT is a placed on a table which is 0.8 m above ground plane. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz. The CISPR Quasi-Peak and Average detector mode is employed. The two LISNs provide 50uH/50 ohm of coupling impedance for the measuring instrument. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

2.3.2 Conducted Test (RF)

The active antenna port of the unlicensed wireless device is connected to the spectrum analyzer with attenuator to protect the instrumentation. If a second antenna port is available, it is tested at one operating frequency, with other port(s) appropriately terminated, to verify it has similar output characteristics as the fully tested port.

2.3.3 **Radiated Emissions**

The EUT is a placed on a turn table. For emissions testing at or below 1 GHz, the table height shall be 0.8 m above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max, emission, the relative positions of this transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indem-

nification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

f (886-2) 2298-0488



Page: 7 of 32

2.4 **Measurement Results Explanation Example**

2.4.1 Radiated Emission Test Sites For Measurements From 9 kHz To 30 MHz

Radiated emission below 30MHz is measured in a 9m*6m*6m semi-anechoic chamber, the measurements correspond to those obtained at an open-field test site.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

2.4.2 For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuation factor between EUT conducted port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly EUT RF output level.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 www.sgs.com.tw



Page: 8 of 32

2.5 Test Configuration

Fig. 2-1 Radiated Emission



Fig. 2-2 Conducted (Antenna Port)

Configuration



2.6 Control Unit(s)

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Data Cable	Power Cord
1	Bluetooth Test Software	N/A	N/A	N/A	N/A	N/A
2	Adapter	N/A	N/A	N/A	N/A	N/A

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indem-nification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

Member of SGS Group



Page: 9 of 32

SUMMARY OF TEST RESULTS

FCC Rules	ISED Rules	Description Of Test	Result
§15.247(b) (3)	RSS-247 §5.4(4)	Peak Output Power	Compliant
§15.247(d) §15.209	RSS-247 §5.5 RSS-Gen §8.9	Radiated Spurious Emission	Compliant

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 f (886-2) 2298-0488



Page: 10 of 32

DESCRIPTION OF TEST MODES

4.1 Operating Frequencies

	-				
ITEM	FREQUENCY	ITEM	FREQUENCY	ITEM	FREQUENCY
1	2402 MHz	15	2430 MHz	29	2458 MHz
2	2404 MHz	16	2432 MHz	30	2460 MHz
3	2406 MHz	17	2434 MHz	31	2462 MHz
4	2408 MHz	18	2436 MHz	32	2464 MHz
5	2410 MHz	19	2438 MHz	33	2466 MHz
6	2412 MHz	20	2440 MHz	34	2468 MHz
7	2414 MHz	21	2442 MHz	35	2470 MHz
8	2416MHz	22	2444 MHz	36	2472 MHz
9	2418 MHz	23	2446 MHz	37	2474 MHz
10	2420 MHz	24	2448 MHz	38	2476 MHz
11	2422 MHz	25	2450 MHz	39	2478 MHz
12	2424 MHz	26	2452 MHz	40	2480 MHz
13	2426 MHz	27	2454 MHz		
14	2428 MHz	28	2456 MHz		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279 f (886-2) 2298-0488



Page: 11 of 32

4.2 The Worst Test Modes and Channel Details

- 1. The EUT has been tested under operating condition.
- 2. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.
- 3. The field strength of radiation emission was measured as EUT three orthogonal planes, E1 / E2 / H, are positioned to pre-scan the emission generating the highest one. The worst position is tested and recorded.
- 4. Investigation has been done on all the possible configurations for searching the worst case.

RADIATED EMISSION TEST (ABOVE 1 GHz)							
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)			
Bluetooth LE	0 to 39	0,19,39	GFSK	1			
Bluetooth LE	0 to 39	0,19,39	GFSK	2			

Note: The field strength of radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for channel Low, Mid and High, the worst case E2 position was reported.

CONDUCTED TEST							
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)			
Bluetooth LE	0 to 39	0,19,39	GFSK	1			
Bluetooth LE	0 to 39	0,19,39	GFSK	2			

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 12 of 32

MEASUREMENT UNCERTAINTY

Test Items	Ur	ncertaint	Э
AC Power Line Conducted Emission	+/-	2.34	dB
Peak Output Power		1	dB
6dB Bandwidth & 99% Bandwidth	+/-	1.53	Hz
100 kHz Bandwidth Of Frequency Band Edges		1.69	dB
Peak Power Density		1.53	dB
Temperature	+/-	0.4	°C
Humidity	+/-	3.5	%
DC / AC Power Source	+/-	1	%

Radiated Spurious Emission Measurement Uncertainty								
	+/-	2.64	dB	9kHz~30MHz				
Polarization: Vertical	+/-	4.93	dB	30MHz - 1000MHz				
Polarization, vertical	+/-	4.81	dB	1GHz - 18GHz				
	+/-	4.52	dB	18GHz - 40GHz				
	+/-	2.64	dB	9kHz~30MHz				
Polarization: Horizontal	+/-	4.45	dB	30MHz - 1000MHz				
Polarization. Horizontal	+/-	4.81	dB	1GHz - 18GHz				
	+/-	4.52	dB	18GHz - 40GHz				

Note:

- 1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
- 2. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 13 of 32

6 PEAK OUTPUT POWER MEASUREMENT

6.1 Standard Applicable:

For systems using digital modulation in the 2400-2483.5 MHz bands, the limit for peak output power is 1Watt and the e.i.r.p. shall not exceed 4 W.


If the transmitting antenna of directional gain greater than 6dBi are used the peak output power form the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6dBi.

In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of Antenna exceeds 6dBi.

6.2 Measurement Equipment Used:

Conducted Emission Test Site: Conducted G								
EQUIPMENT TYPE	MFR	MODEL NUM- BER	SERIAL NUMBER	LAST CAL.	CAL DUE.			
Power Meter	Anritsu	ML2496A	1326001	08/12/2021	08/11/2022			
Power Sensor	Anritsu	MA2411B	1315048	08/12/2021	08/11/2022			
Power Sensor	Anritsu	MA2411B	1315049	08/12/2021	08/11/2022			
Attenuator	Marvelous	WATT-218FS-10	RF18	11/19/2020	11/18/2021			
Attenuator	Marvelous	WATT-218FS-10	RF23	11/19/2020	11/18/2021			

6.3 Test Set-up:



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 14 of 32

6.4 Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. The testing follows the Measurement Procedure of FCC KDB 558074 D01 DTS Meas. Guidance.
- 3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.
- 4. Record the max. Reading as observed from Power Meter.
- 5. Repeat above procedures until all test default channel measured was complete.



Page: 15 of 32

Output Power:

6.5.1 Peak & Avg

BLE 1M mode:

DLL IIVI				
СН	Frequency (MHz)	Power set	Peak Power Output (dBm)	Required Limit (dBm)
Low	2402	default	9.28	30
Mid	2440	default	9.94	30
High	2480	default	10.32	30
	_	D	Max. Avg. Output include	Do avviso al Lissit
СН	Frequency (MHz)	Power set	tune up tolerance Power (dBm)	Required Limit (dBm)
CH Low			•	-
	(MHz)	set	(dBm)	(dBm)
Low	(MHz) 2402	set default	(dBm) 9.19	(dBm) 30

^{*}Note: Measured by power meter, cable loss 11.1 dB + Duty cycle factor has been offseted to the power meter for Avg. power and cable loss has been offseted for Peak power measurement.

BLE 2M mode:

	oao.			
СН	Frequency (MHz)	Power set	Peak Power Output (dBm)	Required Limit (dBm)
Low	2402	default	9.23	30
Mid	2440	default	9.90	30
High	2480	default	10.30	30
СН	Frequency (MHz)	Power set	Max. Avg. Output include tune up tolerance Power (dBm)	Required Limit (dBm)
Low	2402	default	9.16	30
Mid	2440	default	9.84	30
High	2480	default	10.20	30

^{*}Note: Measured by power meter, cable loss 11.1 dB + Duty cycle factor has been offseted to the power meter for Avg. power and cable loss has been offseted for Peak power measurement.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 16 of 32

6.5.2 **EIRP**

EIRP BLE 1M mode

СН	Frequency (MHz)	Power set	Max. Avg. Output include tune up tolerance Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit		
Low	2402	default	9.19	1.15	10.34	4W=	36	dBm
Mid	2440	default	9.86	1.15	11.01	4W=	36	dBm
High	2480	default	10.22	1.15	11.37	4W=	36	dBm

^{*} Note: EIRP = Average Power + Gain

EIRP BLE 2M mode

СН	Frequency (MHz)	Power set	Max. Avg. Output include tune up tolerance Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit		
Low	2402	default	9.16	1.15	10.31	4W=	36	dBm
Mid	2440	default	9.84	1.15	10.99	4W=	36	dBm
High	2480	default	10.20	1.15	11.35	4W=	36	dBm

^{*} Note: EIRP = Average Power + Gain

SPURIOUS EMISSION MEASUREMENT

7.1 Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands must also comply with the §15.209 and RSS-Gen §8.9 Table 5 and 6 limit as below.

And according to §15.33(a) (1) & RSS-Gen §6.13.2.a for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

Frequency (MHz)	Field strength (microvolts/meter)	Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 www.sgs.com.tw



Page: 17 of 32

Measurement Equipment Used

	Radiated Emission Test Site: SAC G								
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.				
Broadband Antenna	SCHWAZBECK	VULB 9168	1206	02/22/2021	02/21/2022				
Horn Anten- na	Schwarzbeck	DRH18-E	210105A18E	04/09/2021	04/08/2022				
Horn Anten- na Schwarzbeck BBHA9170		184	12/11/2020	12/10/2021					
Loop Anten- na	ETS.LINDGREN	6502	143303	05/07/2021	05/06/2022				
3m Site NSA	SGS	966 chamber G	N/A	03/30/2021	03/29/2022				
Spectrum Analyzer	KEYSIGHT	N9010A	MY57120290	04/06/2021	04/05/2022				
FMC Instru-		EMC0011830	980199	11/19/2020	11/18/2021				
		EMC330N	980781	03/15/2021	03/14/2022				
Pre-Amplifier	EMC Instru- ments	EMC118A45SE	980815	03/15/2021	03/14/2022				
Attenuator	Marvelous	MVE2213-30	RF04	11/19/2020	11/18/2021				
High Pass Filter	R&S	F13 HPF 3GHz	RF175	11/19/2020	11/18/2021				
Lowpass Fil- ter	Woken	EWT-56-0019	RF173	11/19/2020	11/18/2021				
High Pass Filter	R&S	HPF7.0	RF176	11/19/2020	11/18/2021				
Notch Filter	Woken	EWT-54-0037	RF204	11/19/2020	11/18/2021				
Coaxial Cable	Huber+Suhner	RG 214/U	W21.01	11/19/2020	11/18/2021				
Test Soft- ware	audix	e3	20923 sgs Ver.9	N.C.R	N.C.R				
Coaxial Cable	EMC Instru- ments	EMC104-SM-SM-8000-5000-5000	210219 \ 210220 \ 210221	03/15/2021	03/14/2022				

Note: N.C.R refers to Not Calibrated Required.


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Page: 18 of 32

Test SET-UP


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz.



(B) Radiated Emission Test Set-Up, Frequency From 30MHz to 1000MHz.



(C) Radiated Emission Test Set-Up, Frequency Above 1GHz.



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is dr Attention is drawn to the limitation of liability, indemelectronic format documents, subject to Terms and Conditions for Electronic Documents at https://www.sgs.com.tw/1erms-ano-Conditions. Attention is grawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279 f (886-2) 2298-0488 www.sgs.com.tw



Page: 19 of 32

7.4 Measurement Procedure

- 1. The testing follows the Measurement Procedure of FCC KDB 558074 D01 DTS Meas. Guidance.
- 2. The EUT was placed on a turn table with 0.8m for frequency< 1GHz and 1.5m for frequency> 1GHz above ground plane.
- 3. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 4. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 5. Set the spectrum analyzer as RBW=100 kHz and VBW=300 kHz for Peak Detector (PK) at frequency between 30MHz and 1 GHz.
- 6. Use receiver mode as RBW=120 kHz for Quasi-peak (QP) at frequency between 30MHz and 1 GHz.
- 7. Set the spectrum analyzer as RBW=1 MHz, VBW=3 MHz for Maximum Emission Measurements at frequency above 1 GHz.
- 8. Set the spectrum analyzer as RBW=1 MHz, VBW=10 Hz (Duty cycle > 98%) or VBW ≥ 1/T (Duty cycle < 98%) for Average Emission Measurements at frequency above 1 GHz.
- 9. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 10. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 11. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 12. Repeat above procedures until all default test channel measured were complete.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 20 of 32

7.5 **Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

The limit of the emission level is expressed in dBuV/m, which converts 20*log(uV/m)

Actual $FS(dB\mu V/m) = SPA$. Reading level $(dB\mu V) + Factor(dB)$

 $Factor(dB) = Antenna\ Factor(dB\mu V/m) + Cable\ Loss(dB) - Pre\ Amplifier\ Gain(dB)$

7.6 Test Results of Radiated Spurious Emissions from 9 kHz to 30 MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit per 15.31(o) & RSS-GEN §6.13.2 was not reported.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

f (886-2) 2298-0488



Page: 21 of 32

7.7Measurement Result:


7.7.1 Radiated Spurious Emission

Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 1M Test Date :2021-08-20

Test Frequency :2402 MHz Temp./Humi. :24.4/59
Test Mode :TX CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



	Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	MHz	Mode PK/QP/AV	Reading Level dBuV	dB	FS dBµV/m	@3m dBµV/m	dB
_	IVII IZ	FTVQF/AV	αυμν	ub	αυμ ν/π	αυμ ν/π	ub
	4804.000	Average	27.68	3.14	30.82	54.00	-23.18
	4804.000	Peak	36.44	3.14	39.57	74.00	-34.43
	7206.000	Average	25.29	7.22	32.50	54.00	-21.50
	7206.000	Peak	35.02	7.22	42.24	74.00	-31.76

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indem-nification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號t (886-2) 2299-3279 f (886-2) 2298-0488 www.sgs.com.tw



Page: 22 of 32


Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 1M Test Date :2021-08-20

Test Frequency :2402 MHz Temp./Humi. :24.4/59

Antenna Pol. :Horizontal Test Mode :TX CH LOW

EUT Pol :NB Plane Engineer :Jack Tseng



	Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	•	Mode	Reading Level		FS	@3m	_
	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
_			•		•	•	
	4004.000	A	07.45	2.44	20.50	E4.00	00.44
	4804.000	Average	27.45	3.14	30.59	54.00	-23.41
	4804.000	Peak	37.21	3.14	40.35	74.00	-33.65
	7206.000	Average	25.04	7.22	32.26	54.00	-21.74
	7206.000	Peak	33.27	7.22	40.49	74.00	-33.51

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Page: 23 of 32

Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 1M Test Date :2021-08-20

Test Frequency :2440 MHz Temp./Humi. :24.4/59 Test Mode :TX CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
				•	•	
4880.000	Average	26.09	3.33	29.42	54.00	-24.58
4880.000	Peak	35.93	3.33	39.26	74.00	-34.74
7320.000	Average	25.20	7.66	32.86	54.00	-21.14
7320.000	Peak	34.09	7.66	41.75	74.00	-32.25

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 24 of 32


Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 1M Test Date :2021-08-20

Test Frequency :2440 MHz Temp./Humi. :24.4/59

Test Mode :TX CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
- 1	Mode	Reading Level		FS	@3m	- 3
		•		_	_	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
		•				
4880.000	Average	25.98	3.33	29.31	54.00	-24.69
4880.000	Peak	37.06	3.33	40.39	74.00	-33.61
7320.000	Average	25.04	7.66	32.70	54.00	-21.30
7320 000	Peak	35 13	7 66	42 79	74 00	-31.21
4880.000 7320.000 7320.000	Peak Average Peak	37.06 25.04 35.13	3.33 7.66 7.66	40.39 32.70 42.79	74.00 54.00 74.00	-21

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Page: 25 of 32

Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 1M Test Date :2021-08-20

Test Frequency :2480 MHz Temp./Humi. :24.4/59 Test Mode :TX CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
4960.000	Average	26.95	3.42	30.37	54.00	-23.63
4960.000	Peak	36.34	3.42	39.76	74.00	-34.24
7440.000	Average	24.85	8.11	32.96	54.00	-21.04
7440.000	Peak	32.91	8.11	41.02	74.00	-32.98

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 26 of 32


Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 1M Test Date :2021-08-20

Test Frequency :2480 MHz Temp./Humi. :24.4/59

Test Mode :TX CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4960.000	Average	26.80	3.42	30.22	54.00	-23.78
4960.000	Peak	35.19	3.42	38.61	74.00	-35.39
7440.000	Average	24.83	8.11	32.94	54.00	-21.06
7440.000	Peak	35.17	8.11	43.28	74.00	-30.72

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Page: 27 of 32

Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 2M Test Date :2021-08-20

Test Frequency :2402 MHz Temp./Humi. :24.4/59 Test Mode :TX CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



	Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	·	Mode	Reading Level		FS	@3m	Ū
	MHz	PK/QP/AV	dBuV	dB	dBµV/m	dBµV/m	dB
_	IVIIIZ	PN/QP/AV	иьμν	uБ	αБμν/П	ασμν/π	uБ
	4804.000	Average	27.75	3.14	30.89	54.00	-23.11
	4804.000	Peak	37.30	3.14	40.43	74.00	-33.57
	7206.000	Average	25.11	7.22	32.32	54.00	-21.68
	7206.000	Peak	34.45	7.22	41.67	74.00	-32.33

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 28 of 32


Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 2M Test Date :2021-08-20

Test Frequency :2402 MHz Temp./Humi. :24.4/59

Test Mode :TX CH LOW Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
4804.000	Average	27.88	3.14	31.02	54.00	-22.98
4804.000	Peak	36.70	3.14	39.84	74.00	-34.16
7206.000	Average	25.14	7.22	32.36	54.00	-21.64
7206.000	Peak	33.18	7.22	40.39	74.00	-33.61

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Page: 29 of 32

Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 2M Test Date :2021-08-20

Test Frequency :2440 MHz Temp./Humi. :24.4/59
Test Mode :TX CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
4880.000	Average	25.93	3.33	29.26	54.00	-24.74
4880.000	Peak	35.94	3.33	39.27	74.00	-34.73
7320.000	Average	25.11	7.66	32.77	54.00	-21.23
7320.000	Peak	33.95	7.66	41.61	74.00	-32.39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 30 of 32


Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 2M Test Date :2021-08-20

Test Frequency :2440 MHz Temp./Humi. :24.4/59

Test Mode :TX CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
4880.000	Average	26.30	3.33	29.63	54.00	-24.37
4880.000	Peak	35.66	3.33	38.99	74.00	-35.01
7320.000	Average	25.27	7.66	32.93	54.00	-21.07
7320.000	Peak	32.70	7.66	40.36	74.00	-33.64

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Page: 31 of 32

Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 2M Test Date :2021-08-20

Test Frequency :2480 MHz Temp./Humi. :24.4/59 Test Mode :TX CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dΒμV/m	dBµV/m	dB
4960.000	Average	27.05	3.42	30.47	54.00	-23.53
4960.000	Peak	36.21	3.42	39.63	74.00	-34.37
7440.000	Average	24.86	8.11	32.97	54.00	-21.03
7440.000	Peak	33.58	8.11	41.69	74.00	-32.31

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 32 of 32


Report Number :E2/2021/80018 Test Site :SAC G

Operation Mode :BLE 2M Test Date :2021-08-20

Test Frequency :2480 MHz Temp./Humi. :24.4/59

Test Mode :TX CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
4960.000	Average	26.69	3.42	30.11	54.00	-23.89
4960.000	Peak	35.20	3.42	38.62	74.00	-35.38
7440.000	Average	24.99	8.11	33.10	54.00	-20.90
7440.000	Peak	34.39	8.11	42.50	74.00	-31.50

~ End of Report ~

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。