

## SAR TEST REPORT



The following samples were submitted and identified on behalf of the client as:

**Equipment Under Test** Smartphone  
**Brand Name** HTC  
**Model No.** 2PYR200 / 2PYR210  
**Company Name** HTC Corporation  
**Company Address** No.23, Xinghua Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C)  
**Standards** IEEE/ANSI C95.1-1992, IEEE 1528-2013, KDB248227D01v02r02, KDB865664D01v01r04, KDB865664D02v01r02, KDB941225D01v03r01, KDB941225D05v02r05, KDB941225D06v02r01, KDB447498D01v06, KDB648474D04v01r03,  
**FCC ID** NM82PYR200  
**Date of Receipt** Dec. 01, 2016  
**Date of Test(s)** Dec. 21, 2016 ~ Dec. 30, 2016  
**Date of Issue** Feb. 08, 2017

In the configuration tested, the EUT complied with the standards specified above.

**Remarks:**

This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS Taiwan Electronic & Communication Laboratory or testing done by SGS Taiwan Electronic & Communication Laboratory in connection with distribution or use of the product described in this report must be approved by SGS Taiwan Electronic & Communication Laboratory in writing.

**Signed on behalf of SGS****Engineer****Bond Tsai****Date: Feb. 08, 2017****Supervisor****John Yeh****Date: Feb. 08, 2017**



## Revision History

| Report Number | Revision | Description                  | Issue Date    |
|---------------|----------|------------------------------|---------------|
| E5/2016/C0001 | Rev.00   | Initial creation of document | Jan. 11, 2017 |
| E5/2016/C0001 | Rev.01   | 1 <sup>st</sup> modification | Jan. 24, 2017 |
| E5/2016/C0001 | Rev.02   | 2 <sup>nd</sup> modification | Feb. 08, 2017 |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |

## Contents

|                                                                    |            |
|--------------------------------------------------------------------|------------|
| <b>1. General Information.....</b>                                 | <b>4</b>   |
| 1.1 Testing Laboratory .....                                       | 4          |
| 1.2 Details of Applicant.....                                      | 4          |
| 1.3 Description of EUT .....                                       | 5          |
| 1.4 Test Environment .....                                         | 37         |
| 1.5 Operation Description .....                                    | 37         |
| 1.6 Positioning Procedure .....                                    | 40         |
| 1.7 Evaluation Procedures .....                                    | 42         |
| 1.8 Probe Calibration Procedures .....                             | 44         |
| 1.9 The SAR Measurement System.....                                | 47         |
| 1.10 System Components.....                                        | 49         |
| 1.11 SAR System Verification .....                                 | 51         |
| 1.12 Tissue Simulant Fluid for the Frequency Band .....            | 53         |
| 1.13 Test Standards and Limits .....                               | 55         |
| <b>2. Summary of Results .....</b>                                 | <b>57</b>  |
| <b>3. Simultaneous Transmission Analysis.....</b>                  | <b>63</b>  |
| 3.1 Estimated SAR calculation.....                                 | 64         |
| 3.2 SPLSR evaluation and analysis .....                            | 64         |
| <b>4. Instruments List .....</b>                                   | <b>69</b>  |
| <b>5. Measurements .....</b>                                       | <b>71</b>  |
| <b>6. SAR System Performance Verification .....</b>                | <b>93</b>  |
| <b>7. DAE &amp; Probe Calibration Certificate .....</b>            | <b>103</b> |
| <b>8. Uncertainty Budget.....</b>                                  | <b>119</b> |
| <b>9. Phantom Description.....</b>                                 | <b>120</b> |
| <b>10. System Validation from Original Equipment Supplier.....</b> | <b>121</b> |



# 1. General Information

## 1.1 Testing Laboratory

|                                                                      |                                                             |
|----------------------------------------------------------------------|-------------------------------------------------------------|
| SGS Taiwan Ltd. Electronics & Communication Laboratory               |                                                             |
| No. 2, Keji 1st Rd., Guishan Township, Taoyuan County, 33383, Taiwan |                                                             |
| Tel                                                                  | +886-2-2299-3279                                            |
| Fax                                                                  | +886-2-2298-0488                                            |
| Internet                                                             | <a href="http://www.tw.sgs.com/">http://www.tw.sgs.com/</a> |

## 1.2 Details of Applicant

|                 |                                                                     |
|-----------------|---------------------------------------------------------------------|
| Company Name    | HTC Corporation                                                     |
| Company Address | No.23, Xinghua Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C) |

### 1.3 Description of EUT

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                          |                                  |        |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|--------|
| EUT Name                    | Smartphone                                                                                                                                                                                                                                                                                                                                                                                                               |                                  |        |
| Brand Name                  | HTC                                                                                                                                                                                                                                                                                                                                                                                                                      |                                  |        |
| Model No.                   | 2PYR200 / 2PYR210                                                                                                                                                                                                                                                                                                                                                                                                        |                                  |        |
| FCC ID                      | NM82PYR200                                                                                                                                                                                                                                                                                                                                                                                                               |                                  |        |
| Mode of Operation           | <input checked="" type="checkbox"/> GSM <input checked="" type="checkbox"/> GPRS <input checked="" type="checkbox"/> EDGE<br><input checked="" type="checkbox"/> WCDMA <input checked="" type="checkbox"/> HSDPA <input checked="" type="checkbox"/> HSUPA<br><input checked="" type="checkbox"/> LTE FDD <input checked="" type="checkbox"/> WLAN802.11 b/g/n(20M/40M)<br><input checked="" type="checkbox"/> Bluetooth |                                  |        |
| Duty Cycle                  | GSM<br>(DTM multi class B)                                                                                                                                                                                                                                                                                                                                                                                               | 1/8.3                            |        |
|                             | GPRS<br>(support multi class 10 max)                                                                                                                                                                                                                                                                                                                                                                                     | 1/4.1 (1Dn2UP)<br>1/8.3 (1Dn1UP) |        |
|                             | EDGE<br>(support multi class 10 max)                                                                                                                                                                                                                                                                                                                                                                                     | 1/4.1 (1Dn2UP)<br>1/8.3 (1Dn1UP) |        |
|                             | LTE FDD<br>(LTE Release Version: R10)                                                                                                                                                                                                                                                                                                                                                                                    | 1                                |        |
|                             | WCDMA<br>(HSDPA Category 14)<br>(HSUPA Category 6)                                                                                                                                                                                                                                                                                                                                                                       | 1                                |        |
|                             | WLAN802.11 b/g/n(20M/40M)                                                                                                                                                                                                                                                                                                                                                                                                | 1                                |        |
|                             | Bluetooth                                                                                                                                                                                                                                                                                                                                                                                                                | 1                                |        |
| TX Frequency Range<br>(MHz) | GSM850                                                                                                                                                                                                                                                                                                                                                                                                                   | 824                              | — 849  |
|                             | GSM1900                                                                                                                                                                                                                                                                                                                                                                                                                  | 1850                             | — 1910 |
|                             | WCDMA Band II                                                                                                                                                                                                                                                                                                                                                                                                            | 1850                             | — 1910 |
|                             | WCDMA Band IV                                                                                                                                                                                                                                                                                                                                                                                                            | 1710                             | — 1755 |
|                             | WCDMA Band V                                                                                                                                                                                                                                                                                                                                                                                                             | 824                              | — 849  |
|                             | LTE FDD Band 2                                                                                                                                                                                                                                                                                                                                                                                                           | 1850                             | — 1910 |
|                             | LTE FDD Band 4                                                                                                                                                                                                                                                                                                                                                                                                           | 1710                             | — 1755 |
|                             | LTE FDD Band 5                                                                                                                                                                                                                                                                                                                                                                                                           | 824                              | — 849  |
|                             | LTE FDD Band 12                                                                                                                                                                                                                                                                                                                                                                                                          | 699                              | — 716  |
|                             | WLAN802.11 b/g/n(20M)                                                                                                                                                                                                                                                                                                                                                                                                    | 2412                             | — 2462 |
|                             | WLAN802.11 n(40M)                                                                                                                                                                                                                                                                                                                                                                                                        | 2422                             | — 2452 |
|                             | Bluetooth                                                                                                                                                                                                                                                                                                                                                                                                                | 2402                             | — 2480 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

|                           |                       |       |   |       |
|---------------------------|-----------------------|-------|---|-------|
| Channel Number<br>(ARFCN) | GSM850                | 128   | — | 251   |
|                           | GSM1900               | 512   | — | 810   |
|                           | WCDMA Band II         | 9262  | — | 9538  |
|                           | WCDMA Band IV         | 1312  | — | 1513  |
|                           | WCDMA Band V          | 4132  | — | 4233  |
|                           | LTE FDD Band 2        | 18607 | — | 19193 |
|                           | LTE FDD Band 4        | 19957 | — | 20393 |
|                           | LTE FDD Band 5        | 20407 | — | 20643 |
|                           | LTE FDD Band 12       | 23017 | — | 23173 |
|                           | WLAN802.11 b/g/n(20M) | 1     | — | 11    |
|                           | WLAN802.11 n(40M)     | 3     | — | 9     |
|                           | Bluetooth             | 0     | — | 78    |

| Max. SAR (1 g) (Unit: W/Kg) |                 |          |          |                                                                                                                                                                     |
|-----------------------------|-----------------|----------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mode                        | Band            | Measured | Reported | Position / Channel                                                                                                                                                  |
| Head                        | GSM 850         | 0.132    | 0.169    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>251 Channel   |
|                             | GSM 1900        | 0.062    | 0.074    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>661 Channel   |
|                             | WCDMA Band II   | 0.176    | 0.181    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>9262 Channel  |
|                             | WCDMA Band IV   | 0.191    | 0.196    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>1412 Channel  |
|                             | WCDMA Band V    | 0.151    | 0.172    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>4183 Channel  |
|                             | LTE FDD Band 2  | 0.156    | 0.175    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>18700 Channel |
|                             | LTE FDD Band 4  | 0.174    | 0.196    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>20300 Channel |
|                             | LTE FDD Band 5  | 0.116    | 0.131    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>20600 Channel |
|                             | LTE FDD Band 12 | 0.045    | 0.052    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>23095 Channel |
|                             | WLAN802.11 b    | 0.089    | 0.090    | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>11 Channel    |

| Max. SAR (1 g) (Unit: W/Kg) |          |          |          |                                                                                        |
|-----------------------------|----------|----------|----------|----------------------------------------------------------------------------------------|
| Mode                        | Band     | Measured | Reported | Position / Channel                                                                     |
| Body-worn                   | GSM 850  | 0.193    | 0.247    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br>251 Channel |
|                             | GSM 1900 | 0.119    | 0.142    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br>661 Channel |

| Max. SAR (1 g) (Unit: W/Kg) |                    |          |          |                                                                                                                                                                                            |
|-----------------------------|--------------------|----------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mode                        | Band               | Measured | Reported | Position / Channel                                                                                                                                                                         |
| Hotspot mode                | GPRS 850 (1Dn2UP)  | 0.305    | 0.394    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>251 Channel  |
|                             | GPRS 1900 (1Dn2UP) | 0.173    | 0.206    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>661 Channel  |
|                             | WCDMA Band II      | 0.271    | 0.279    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>9262 Channel |
|                             | WCDMA Band IV      | 0.282    | 0.290    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>1412 Channel |

| Max. SAR (1 g) (Unit: W/Kg) |                 |          |          |                                                                                                                                                                                             |
|-----------------------------|-----------------|----------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mode                        | Band            | Measured | Reported | Position / Channel                                                                                                                                                                          |
| Hotspot mode                | WCDMA Band V    | 0.238    | 0.271    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>4183 Channel  |
|                             | LTE FDD Band 2  | 0.265    | 0.298    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>18700 Channel |
|                             | LTE FDD Band 4  | 0.266    | 0.300    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>20300 Channel |
|                             | LTE FDD Band 5  | 0.209    | 0.236    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>20600 Channel |
|                             | LTE FDD Band 12 | 0.144    | 0.165    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>23095 Channel |
|                             | WLAN802.11 b    | 0.118    | 0.120    | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Right<br><input type="checkbox"/> Left<br>11 Channel    |

### GSM 850 - conducted power table:

| EUT mode                                                   | Frequency (MHz) | CH  | Max. Rated Avg. Power + Max. Tolerance (dBm) | Burst average power | Source-based time average power |
|------------------------------------------------------------|-----------------|-----|----------------------------------------------|---------------------|---------------------------------|
|                                                            |                 |     |                                              | Avg. (dBm)          | Avg. (dBm)                      |
| GSM850 (GMSK)                                              | 824.2           | 128 | 33.5                                         | 32.27               | 23.24                           |
|                                                            | 836.6           | 190 | 33.5                                         | 32.38               | 23.35                           |
|                                                            | 848.8           | 251 | 33.5                                         | 32.42               | 23.39                           |
| The division factor compared to the number of TX time slot |                 |     |                                              |                     |                                 |
| Division factor                                            |                 |     |                                              | 1 TX time slot      |                                 |
|                                                            |                 |     |                                              |                     | -9.03                           |

### GPRS 850 - conducted power table:

| Burst average power                                        |                 |     |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 33.5           | 32             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     |
| GPRS 850                                                   | 824.2           | 128 | 32.27          | 30.79          |
|                                                            | 836.6           | 190 | 32.38          | 30.87          |
|                                                            | 848.8           | 251 | 32.42          | 30.89          |
| Source-based time average power                            |                 |     |                |                |
| GPRS 850                                                   | 824.2           | 128 | 23.24          | 24.77          |
|                                                            | 836.6           | 190 | 23.35          | 24.85          |
|                                                            | 848.8           | 251 | 23.39          | 24.87          |
| The division factor compared to the number of TX time slot |                 |     |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          |

### EDGE 850 - conducted power table:

| Burst average power                                        |                    |     |                |                |
|------------------------------------------------------------|--------------------|-----|----------------|----------------|
| Max. Rated Avg. Power +<br>Max. Tolerance (dBm)            |                    |     | 27.5           | 27             |
|                                                            |                    |     | 1Dn1UP         | 1Dn2UP         |
| EUT mode                                                   | Frequency<br>(MHz) | CH  | Avg.<br>(dBm)  | Avg.<br>(dBm)  |
| EDGE 850<br>(MCS5)                                         | 824.2              | 128 | 26.39          | 25.71          |
|                                                            | 836.6              | 190 | 26.41          | 25.85          |
|                                                            | 848.8              | 251 | 26.44          | 25.86          |
| Source-based time average power                            |                    |     |                |                |
| EDGE 850<br>(MCS5)                                         | 824.2              | 128 | 17.36          | 19.69          |
|                                                            | 836.6              | 190 | 17.38          | 19.83          |
|                                                            | 848.8              | 251 | 17.41          | 19.84          |
| The division factor compared to the number of TX time slot |                    |     |                |                |
| Division factor                                            |                    |     | 1 TX time slot | 2 TX time slot |
|                                                            |                    |     | -9.03          | -6.02          |

### GSM 1900 - conducted power table:

| EUT mode                                                   | Frequency<br>(MHz) | CH  | Max. Rated<br>Avg.<br>Power +<br>Max.<br>Tolerance<br>(dBm) | Burst<br>average<br>power | Source<br>-based<br>time<br>average<br>power |
|------------------------------------------------------------|--------------------|-----|-------------------------------------------------------------|---------------------------|----------------------------------------------|
|                                                            |                    |     |                                                             | Avg.<br>(dBm)             | Avg.<br>(dBm)                                |
| GSM1900<br>(GMSK)                                          | 1850.2             | 512 | 30.5                                                        | 29.43                     | 20.4                                         |
|                                                            | 1800               | 661 | 30.5                                                        | 29.72                     | 20.69                                        |
|                                                            | 1909.8             | 810 | 30.5                                                        | 29.65                     | 20.62                                        |
| The division factor compared to the number of TX time slot |                    |     |                                                             |                           |                                              |
| Division factor                                            |                    |     |                                                             | 1 TX time slot            |                                              |
|                                                            |                    |     |                                                             | -9.03                     |                                              |

### GPRS 1900 - conducted power table:

| Burst average power                                        |                    |     |                |                |
|------------------------------------------------------------|--------------------|-----|----------------|----------------|
| Max. Rated Avg. Power +<br>Max. Tolerance (dBm)            |                    |     | 30.5           | 29.5           |
|                                                            |                    |     | 1Dn1UP         | 1Dn2UP         |
| EUT mode                                                   | Frequency<br>(MHz) | CH  | Avg.<br>(dBm)  | Avg.<br>(dBm)  |
| GPRS<br>1900                                               | 1850.2             | 512 | 29.43          | 28.54          |
|                                                            | 1880               | 661 | 29.72          | 28.74          |
|                                                            | 1909.8             | 810 | 29.65          | 28.55          |
| Source-based time average power                            |                    |     |                |                |
| GPRS<br>1900                                               | 1850.2             | 512 | 20.40          | 22.52          |
|                                                            | 1880               | 661 | 20.69          | 22.72          |
|                                                            | 1909.8             | 810 | 20.62          | 22.53          |
| The division factor compared to the number of TX time slot |                    |     |                |                |
| Division factor                                            |                    |     | 1 TX time slot | 2 TX time slot |
|                                                            |                    |     | -9.03          | -6.02          |

### EDGE 1900 - conducted power table:

| Burst average power                                        |                    |     |                |                |
|------------------------------------------------------------|--------------------|-----|----------------|----------------|
| Max. Rated Avg. Power +<br>Max. Tolerance (dBm)            |                    |     | 26.5           | 26             |
|                                                            |                    |     | 1Dn1UP         | 1Dn2UP         |
| EUT mode                                                   | Frequency<br>(MHz) | CH  | Avg.<br>(dBm)  | Avg.<br>(dBm)  |
| EDGE<br>1900<br>(MCS5)                                     | 1850.2             | 512 | 25.52          | 25.03          |
|                                                            | 1880               | 661 | 25.70          | 25.12          |
|                                                            | 1909.8             | 810 | 25.60          | 25.09          |
| Source-based time average power                            |                    |     |                |                |
| EDGE<br>1900<br>(MCS5)                                     | 1850.2             | 512 | 16.49          | 19.01          |
|                                                            | 1880               | 661 | 16.67          | 19.10          |
|                                                            | 1909.8             | 810 | 16.57          | 19.07          |
| The division factor compared to the number of TX time slot |                    |     |                |                |
| Division factor                                            |                    |     | 1 TX time slot | 2 TX time slot |
|                                                            |                    |     | -9.03          | -6.02          |

### WCDMA Band II - HSDPA / HSUPA conducted power table (Unit: dBm):

| Band                                       |                 | WCDMA II |       |        |
|--------------------------------------------|-----------------|----------|-------|--------|
| TX Channel                                 |                 | 9262     | 9400  | 9538   |
| Frequency (MHz)                            |                 | 1852.4   | 1880  | 1907.6 |
| Max. Rated Avg. Power+Max. Tolerance (dBm) |                 | 24.00    |       |        |
| 3GPP Rel 99                                | RMC 12.2Kbps    | 23.87    | 23.79 | 23.83  |
| 3GPP Rel 5                                 | HSDPA Subtest-1 | 23.69    | 23.54 | 23.49  |
|                                            | HSDPA Subtest-2 | 23.74    | 23.51 | 23.46  |
|                                            | HSDPA Subtest-3 | 22.71    | 22.57 | 22.69  |
|                                            | HSDPA Subtest-4 | 22.69    | 22.55 | 22.58  |
| 3GPP Rel 6                                 | HSUPA Subtest-1 | 22.61    | 22.56 | 23.36  |
|                                            | HSUPA Subtest-2 | 21.44    | 21.39 | 21.32  |
|                                            | HSUPA Subtest-3 | 21.53    | 21.61 | 21.54  |
|                                            | HSUPA Subtest-4 | 21.43    | 22.11 | 21.43  |
|                                            | HSUPA Subtest-5 | 23.50    | 23.40 | 23.50  |

### WCDMA Band IV - HSDPA / HSUPA conducted power table (Unit: dBm):

| Band                                       |                 | WCDMA IV |        |        |
|--------------------------------------------|-----------------|----------|--------|--------|
| TX Channel                                 |                 | 1312     | 1412   | 1513   |
| Frequency (MHz)                            |                 | 1712.4   | 1732.4 | 1752.6 |
| Max. Rated Avg. Power+Max. Tolerance (dBm) |                 | 24.00    |        |        |
| 3GPP Rel 99                                | RMC 12.2Kbps    | 23.86    | 23.88  | 23.84  |
| 3GPP Rel 5                                 | HSDPA Subtest-1 | 23.34    | 23.50  | 23.39  |
|                                            | HSDPA Subtest-2 | 23.33    | 23.48  | 23.36  |
|                                            | HSDPA Subtest-3 | 22.35    | 22.41  | 22.33  |
|                                            | HSDPA Subtest-4 | 22.37    | 22.45  | 22.34  |
| 3GPP Rel 6                                 | HSUPA Subtest-1 | 22.40    | 22.57  | 23.06  |
|                                            | HSUPA Subtest-2 | 21.19    | 21.43  | 21.30  |
|                                            | HSUPA Subtest-3 | 21.38    | 21.53  | 21.49  |
|                                            | HSUPA Subtest-4 | 21.88    | 21.41  | 21.98  |
|                                            | HSUPA Subtest-5 | 23.20    | 23.50  | 23.20  |

### WCDMA Band V - HSDPA / HSUPA conducted power table (Unit: dBm):

| Band                                       |                 | WCDMA V |       |       |
|--------------------------------------------|-----------------|---------|-------|-------|
| TX Channel                                 |                 | 4132    | 4183  | 4233  |
| Frequency (MHz)                            |                 | 826.4   | 836.6 | 846.6 |
| Max. Rated Avg. Power+Max. Tolerance (dBm) |                 | 24.00   |       |       |
| 3GPP Rel 99                                | RMC 12.2Kbps    | 23.37   | 23.44 | 23.31 |
| 3GPP Rel 5                                 | HSDPA Subtest-1 | 23.26   | 23.29 | 23.21 |
|                                            | HSDPA Subtest-2 | 23.26   | 23.29 | 23.17 |
|                                            | HSDPA Subtest-3 | 22.21   | 22.28 | 22.29 |
|                                            | HSDPA Subtest-4 | 22.20   | 22.26 | 22.27 |
| 3GPP Rel 6                                 | HSUPA Subtest-1 | 22.05   | 22.27 | 22.04 |
|                                            | HSUPA Subtest-2 | 21.29   | 21.28 | 21.05 |
|                                            | HSUPA Subtest-3 | 21.40   | 21.32 | 21.35 |
|                                            | HSUPA Subtest-4 | 22.02   | 22.00 | 21.86 |
|                                            | HSUPA Subtest-5 | 23.30   | 23.30 | 23.00 |

### Subtests for WCDMA Release 5 HSDPA

| SUB-TEST | $\beta_c$ | $\beta_d$ | $\beta_d$<br>(SF) | $\beta_c/\beta_d$ | $\beta_{HS}$<br>(Note 1, Note 2) | CM (dB)<br>(Note 3) | MPR (dB)<br>(Note 3) |
|----------|-----------|-----------|-------------------|-------------------|----------------------------------|---------------------|----------------------|
| 1        | 2/15      | 15/15     | 64                | 2/15              | 4/15                             | 0.0                 | 0.0                  |
| 2        | 12/15     | 15/15     | 64                | 12/15             | 24/15                            | 1.0                 | 0.0                  |
| 3        | 15/15     | 8/15      | 64                | 15/8              | 30/15                            | 1.5                 | 0.5                  |
| 4        | 15/15     | 4/15      | 64                | 15/4              | 30/15                            | 1.5                 | 0.5                  |

### Subtests for WCDMA Release 6 HSUPA

| SUB-TEST | $\beta_c$ | $\beta_d$ | $\beta_d$<br>(SF) | $\beta_c/\beta_d$ | $\beta_{HS}$<br>(Note 1) | $\beta_{ec}$ | $\beta_{ed}$<br>(Note 5)<br>(Note 6)           | $\beta_{ed}$<br>(SF) | $\beta_{ed}$<br>(Codes) | CM<br>(dB)<br>(Note 2) | MPR<br>(dB)<br>(Note 2) | AG<br>Index<br>(Note 6) | E-TFCI |
|----------|-----------|-----------|-------------------|-------------------|--------------------------|--------------|------------------------------------------------|----------------------|-------------------------|------------------------|-------------------------|-------------------------|--------|
| 1        | 11/15     | 15/15     | 64                | 11/15             | 22/15                    | 209/225      | 1309/225                                       | 4                    | 1                       | 1.0                    | 0.0                     | 20                      | 75     |
| 2        | 6/15      | 15/15     | 64                | 6/15              | 12/15                    | 12/15        | 94/75                                          | 4                    | 1                       | 3.0                    | 2.0                     | 12                      | 67     |
| 3        | 15/15     | 9/15      | 64                | 15/9              | 30/15                    | 30/15        | $\beta_{ed1}$ : 47/15<br>$\beta_{ed2}$ : 47/15 | 4<br>4               | 2                       | 2.0                    | 1.0                     | 15                      | 92     |
| 4        | 2/15      | 15/15     | 64                | 2/15              | 4/15                     | 2/15         | 56/75                                          | 4                    | 1                       | 3.0                    | 2.0                     | 17                      | 71     |
| 5        | 15/15     | 15/15     | 64                | 15/15             | 30/15                    | 24/15        | 134/15                                         | 4                    | 1                       | 1.0                    | 0.0                     | 21                      | 81     |

### LTE FDD Band 2 - conducted power table:

| FDD Band 2 |            |         |           |                 |         |                       |                                     |                          |     |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|-----|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |     |
| 20         | QPSK       | 1 RB    | 0         | 1860            | 18700   | 22.97                 | 23.5                                | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.93                 | 23.5                                | 0                        |     |
|            |            |         |           | 1900            | 19100   | 22.91                 | 23.5                                | 0                        |     |
|            |            |         | 50        | 1860            | 18700   | 22.99                 | 23.5                                | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.95                 | 23.5                                | 0                        |     |
|            |            |         |           | 1900            | 19100   | 22.92                 | 23.5                                | 0                        |     |
|            |            |         | 99        | 1860            | 18700   | 22.89                 | 23.5                                | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.80                 | 23.5                                | 0                        |     |
|            |            |         |           | 1900            | 19100   | 22.87                 | 23.5                                | 0                        |     |
|            |            | 50 RB   | 0         | 1860            | 18700   | 21.92                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.99                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1900            | 19100   | 21.91                 | 22.5                                | 0-1                      |     |
|            |            |         | 25        | 1860            | 18700   | 21.88                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.96                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1900            | 19100   | 21.97                 | 22.5                                | 0-1                      |     |
|            |            |         | 50        | 1860            | 18700   | 21.94                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.87                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1900            | 19100   | 21.85                 | 22.5                                | 0-1                      |     |
|            |            | 100RB   |           |                 | 1860    | 18700                 | 21.94                               | 22.5                     | 0-1 |
|            |            |         |           |                 | 1880    | 18900                 | 21.99                               | 22.5                     | 0-1 |
|            |            |         |           |                 | 1900    | 19100                 | 21.96                               | 22.5                     | 0-1 |
|            | 16-QAM     | 1 RB    | 0         | 1860            | 18700   | 21.88                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.89                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1900            | 19100   | 21.85                 | 22.5                                | 0-1                      |     |
|            |            |         | 50        | 1860            | 18700   | 21.81                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.55                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1900            | 19100   | 21.63                 | 22.5                                | 0-1                      |     |
|            |            |         | 99        | 1860            | 18700   | 21.76                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.74                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1900            | 19100   | 21.81                 | 22.5                                | 0-1                      |     |
|            |            | 50 RB   | 0         | 1860            | 18700   | 20.98                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1880            | 18900   | 20.94                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1900            | 19100   | 20.95                 | 21.5                                | 0-2                      |     |
|            |            |         | 25        | 1860            | 18700   | 20.91                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1880            | 18900   | 20.98                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1900            | 19100   | 20.97                 | 21.5                                | 0-2                      |     |
|            |            |         | 50        | 1860            | 18700   | 20.95                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1880            | 18900   | 20.88                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1900            | 19100   | 20.90                 | 21.5                                | 0-2                      |     |
|            |            | 100RB   |           |                 | 1860    | 18700                 | 20.97                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 1880    | 18900                 | 20.96                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 1900    | 19100                 | 20.91                               | 21.5                     | 0-2 |

| FDD Band 2 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 15         | QPSK       | 1 RB    | 0         | 1857.5          | 18675   | 22.90                 | 23.5                                | 0                        |
|            |            |         |           | 1880            | 18900   | 22.91                 | 23.5                                | 0                        |
|            |            |         |           | 1902.5          | 19125   | 22.81                 | 23.5                                | 0                        |
|            |            |         | 36        | 1857.5          | 18675   | 22.77                 | 23.5                                | 0                        |
|            |            |         |           | 1880            | 18900   | 22.92                 | 23.5                                | 0                        |
|            |            |         |           | 1902.5          | 19125   | 22.81                 | 23.5                                | 0                        |
|            |            |         | 74        | 1857.5          | 18675   | 22.82                 | 23.5                                | 0                        |
|            |            |         |           | 1880            | 18900   | 22.94                 | 23.5                                | 0                        |
|            |            |         |           | 1902.5          | 19125   | 22.90                 | 23.5                                | 0                        |
|            |            | 36 RB   | 0         | 1857.5          | 18675   | 22.00                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.92                 | 22.5                                | 0-1                      |
|            |            |         |           | 1902.5          | 19125   | 21.96                 | 22.5                                | 0-1                      |
|            |            |         | 18        | 1857.5          | 18675   | 21.91                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.85                 | 22.5                                | 0-1                      |
|            |            |         |           | 1902.5          | 19125   | 21.91                 | 22.5                                | 0-1                      |
|            |            |         | 37        | 1857.5          | 18675   | 21.94                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.79                 | 22.5                                | 0-1                      |
|            |            |         |           | 1902.5          | 19125   | 21.92                 | 22.5                                | 0-1                      |
|            |            | 75RB    |           | 1857.5          | 18675   | 22.00                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.92                 | 22.5                                | 0-1                      |
|            |            |         |           | 1902.5          | 19125   | 21.86                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 1857.5          | 18675   | 21.58                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.97                 | 22.5                                | 0-1                      |
|            |            |         |           | 1902.5          | 19125   | 21.98                 | 22.5                                | 0-1                      |
|            |            |         | 36        | 1857.5          | 18675   | 21.85                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.79                 | 22.5                                | 0-1                      |
|            |            |         |           | 1902.5          | 19125   | 21.81                 | 22.5                                | 0-1                      |
|            |            |         | 74        | 1857.5          | 18675   | 21.51                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.75                 | 22.5                                | 0-1                      |
|            |            |         |           | 1902.5          | 19125   | 21.79                 | 22.5                                | 0-1                      |
|            |            | 36 RB   | 0         | 1857.5          | 18675   | 20.62                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.68                 | 21.5                                | 0-2                      |
|            |            |         |           | 1902.5          | 19125   | 20.77                 | 21.5                                | 0-2                      |
|            |            |         | 18        | 1857.5          | 18675   | 20.97                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.98                 | 21.5                                | 0-2                      |
|            |            |         |           | 1902.5          | 19125   | 20.91                 | 21.5                                | 0-2                      |
|            |            |         | 37        | 1857.5          | 18675   | 20.93                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.98                 | 21.5                                | 0-2                      |
|            |            |         |           | 1902.5          | 19125   | 20.98                 | 21.5                                | 0-2                      |
|            |            | 75RB    |           | 1857.5          | 18675   | 20.97                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.86                 | 21.5                                | 0-2                      |
|            |            |         |           | 1902.5          | 19125   | 20.96                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

| FDD Band 2 |            |         |           |                 |         |                        |                                      |                          |     |
|------------|------------|---------|-----------|-----------------|---------|------------------------|--------------------------------------|--------------------------|-----|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted pow er (dBm) | Target Pow er + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |     |
| 10         | QPSK       | 1 RB    | 0         | 1855            | 18650   | 22.96                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.81                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1905            | 19150   | 22.92                  | 23.5                                 | 0                        |     |
|            |            |         | 25        | 1855            | 18650   | 22.96                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.98                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1905            | 19150   | 22.91                  | 23.5                                 | 0                        |     |
|            |            |         | 49        | 1855            | 18650   | 22.93                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.79                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1905            | 19150   | 22.90                  | 23.5                                 | 0                        |     |
|            |            | 25 RB   | 0         | 1855            | 18650   | 21.97                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.92                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1905            | 19150   | 21.94                  | 22.5                                 | 0-1                      |     |
|            |            |         | 12        | 1855            | 18650   | 21.95                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.98                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1905            | 19150   | 21.99                  | 22.5                                 | 0-1                      |     |
|            |            |         | 25        | 1855            | 18650   | 21.93                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.97                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1905            | 19150   | 21.94                  | 22.5                                 | 0-1                      |     |
|            |            | 50RB    |           |                 | 1855    | 18650                  | 21.99                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1880    | 18900                  | 21.83                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1905    | 19150                  | 21.98                                | 22.5                     | 0-1 |
|            | 16-QAM     | 1 RB    | 0         | 1855            | 18650   | 21.85                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.99                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1905            | 19150   | 21.84                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 25              | 1855    | 18650                  | 21.91                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1880    | 18900                  | 21.83                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1905    | 19150                  | 21.81                                | 22.5                     | 0-1 |
|            |            |         | 49        | 1855            | 18650   | 21.87                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.88                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1905            | 19150   | 21.92                  | 22.5                                 | 0-1                      |     |
|            |            |         | 25 RB     | 0               | 1855    | 18650                  | 20.91                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1880    | 18900                  | 21.00                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1905    | 19150                  | 21.00                                | 21.5                     | 0-2 |
|            |            |         |           | 12              | 1855    | 18650                  | 20.95                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1880    | 18900                  | 20.91                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1905    | 19150                  | 20.94                                | 21.5                     | 0-2 |
|            |            |         |           | 25              | 1855    | 18650                  | 20.93                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1880    | 18900                  | 20.97                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1905    | 19150                  | 20.89                                | 21.5                     | 0-2 |
|            |            | 50RB    |           |                 | 1855    | 18650                  | 20.85                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1880    | 18900                  | 20.83                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1905    | 19150                  | 20.96                                | 21.5                     | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

| FDD Band 2 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5          | QPSK       | 1 RB    | 0         | 1852.5          | 18625   | 22.91                 | 23.5                                | 0                        |
|            |            |         |           | 1880            | 18900   | 22.92                 | 23.5                                | 0                        |
|            |            |         |           | 1907.5          | 19175   | 22.90                 | 23.5                                | 0                        |
|            |            |         | 12        | 1852.5          | 18625   | 22.83                 | 23.5                                | 0                        |
|            |            |         |           | 1880            | 18900   | 22.84                 | 23.5                                | 0                        |
|            |            |         |           | 1907.5          | 19175   | 22.89                 | 23.5                                | 0                        |
|            |            |         | 24        | 1852.5          | 18625   | 22.81                 | 23.5                                | 0                        |
|            |            |         |           | 1880            | 18900   | 22.87                 | 23.5                                | 0                        |
|            |            |         |           | 1907.5          | 19175   | 22.97                 | 23.5                                | 0                        |
|            |            | 12 RB   | 0         | 1852.5          | 18625   | 21.96                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.93                 | 22.5                                | 0-1                      |
|            |            |         |           | 1907.5          | 19175   | 21.91                 | 22.5                                | 0-1                      |
|            |            |         | 6         | 1852.5          | 18625   | 21.97                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.94                 | 22.5                                | 0-1                      |
|            |            |         |           | 1907.5          | 19175   | 21.81                 | 22.5                                | 0-1                      |
|            |            |         | 13        | 1852.5          | 18625   | 21.99                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.98                 | 22.5                                | 0-1                      |
|            |            |         |           | 1907.5          | 19175   | 21.87                 | 22.5                                | 0-1                      |
|            |            | 25RB    |           | 1852.5          | 18625   | 21.90                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.99                 | 22.5                                | 0-1                      |
|            |            |         |           | 1907.5          | 19175   | 21.83                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 1852.5          | 18625   | 21.58                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.61                 | 22.5                                | 0-1                      |
|            |            |         |           | 1907.5          | 19175   | 21.98                 | 22.5                                | 0-1                      |
|            |            |         | 12        | 1852.5          | 18625   | 21.49                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.69                 | 22.5                                | 0-1                      |
|            |            |         |           | 1907.5          | 19175   | 21.68                 | 22.5                                | 0-1                      |
|            |            |         | 24        | 1852.5          | 18625   | 21.64                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.87                 | 22.5                                | 0-1                      |
|            |            |         |           | 1907.5          | 19175   | 21.64                 | 22.5                                | 0-1                      |
|            |            | 12 RB   | 0         | 1852.5          | 18625   | 20.73                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.95                 | 21.5                                | 0-2                      |
|            |            |         |           | 1907.5          | 19175   | 20.79                 | 21.5                                | 0-2                      |
|            |            |         | 6         | 1852.5          | 18625   | 20.98                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.90                 | 21.5                                | 0-2                      |
|            |            |         |           | 1907.5          | 19175   | 20.92                 | 21.5                                | 0-2                      |
|            |            |         | 13        | 1852.5          | 18625   | 20.93                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.90                 | 21.5                                | 0-2                      |
|            |            |         |           | 1907.5          | 19175   | 20.90                 | 21.5                                | 0-2                      |
|            |            | 25RB    |           | 1852.5          | 18625   | 20.97                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.83                 | 21.5                                | 0-2                      |
|            |            |         |           | 1907.5          | 19175   | 20.77                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

| FDD Band 2 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 3          | QPSK       | 1 RB    | 0         | 1851.5          | 18615   | 22.89                 | 23.5                                | 0                        |
|            |            |         |           | 1880            | 18900   | 22.96                 | 23.5                                | 0                        |
|            |            |         |           | 1908.5          | 19185   | 22.94                 | 23.5                                | 0                        |
|            |            |         | 7         | 1851.5          | 18615   | 22.91                 | 23.5                                | 0                        |
|            |            |         |           | 1880            | 18900   | 22.94                 | 23.5                                | 0                        |
|            |            |         |           | 1908.5          | 19185   | 22.92                 | 23.5                                | 0                        |
|            |            |         | 14        | 1851.5          | 18615   | 22.87                 | 23.5                                | 0                        |
|            |            |         |           | 1880            | 18900   | 22.88                 | 23.5                                | 0                        |
|            |            |         |           | 1908.5          | 19185   | 22.87                 | 23.5                                | 0                        |
|            |            | 8 RB    | 0         | 1851.5          | 18615   | 21.95                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.97                 | 22.5                                | 0-1                      |
|            |            |         |           | 1908.5          | 19185   | 21.93                 | 22.5                                | 0-1                      |
|            |            |         | 4         | 1851.5          | 18615   | 21.95                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.91                 | 22.5                                | 0-1                      |
|            |            |         |           | 1908.5          | 19185   | 21.94                 | 22.5                                | 0-1                      |
|            |            |         | 7         | 1851.5          | 18615   | 21.95                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.78                 | 22.5                                | 0-1                      |
|            |            |         |           | 1908.5          | 19185   | 21.93                 | 22.5                                | 0-1                      |
|            |            | 15RB    |           | 1851.5          | 18615   | 21.93                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.91                 | 22.5                                | 0-1                      |
|            |            |         |           | 1908.5          | 19185   | 21.83                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 1851.5          | 18615   | 21.94                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.85                 | 22.5                                | 0-1                      |
|            |            |         |           | 1908.5          | 19185   | 21.69                 | 22.5                                | 0-1                      |
|            |            |         | 7         | 1851.5          | 18615   | 21.77                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.81                 | 22.5                                | 0-1                      |
|            |            |         |           | 1908.5          | 19185   | 21.75                 | 22.5                                | 0-1                      |
|            |            |         | 14        | 1851.5          | 18615   | 21.72                 | 22.5                                | 0-1                      |
|            |            |         |           | 1880            | 18900   | 21.69                 | 22.5                                | 0-1                      |
|            |            |         |           | 1908.5          | 19185   | 21.53                 | 22.5                                | 0-1                      |
|            |            | 8 RB    | 0         | 1851.5          | 18615   | 20.86                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.58                 | 21.5                                | 0-2                      |
|            |            |         |           | 1908.5          | 19185   | 20.66                 | 21.5                                | 0-2                      |
|            |            |         | 4         | 1851.5          | 18615   | 20.79                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.49                 | 21.5                                | 0-2                      |
|            |            |         |           | 1908.5          | 19185   | 20.58                 | 21.5                                | 0-2                      |
|            |            |         | 7         | 1851.5          | 18615   | 20.93                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.38                 | 21.5                                | 0-2                      |
|            |            |         |           | 1908.5          | 19185   | 20.42                 | 21.5                                | 0-2                      |
|            |            | 15RB    |           | 1851.5          | 18615   | 20.66                 | 21.5                                | 0-2                      |
|            |            |         |           | 1880            | 18900   | 20.26                 | 21.5                                | 0-2                      |
|            |            |         |           | 1908.5          | 19185   | 20.72                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

| FDD Band 2 |            |         |           |                 |         |                        |                                      |                          |     |
|------------|------------|---------|-----------|-----------------|---------|------------------------|--------------------------------------|--------------------------|-----|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted pow er (dBm) | Target Pow er + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |     |
| 1.4        | QPSK       | 1 RB    | 0         | 1850.7          | 18607   | 22.71                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.61                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1909.3          | 19193   | 22.78                  | 23.5                                 | 0                        |     |
|            |            |         | 2         | 1850.7          | 18607   | 22.66                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.74                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1909.3          | 19193   | 22.56                  | 23.5                                 | 0                        |     |
|            |            |         | 5         | 1850.7          | 18607   | 22.63                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.61                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1909.3          | 19193   | 22.50                  | 23.5                                 | 0                        |     |
|            |            | 3 RB    | 0         | 1850.7          | 18607   | 22.69                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.70                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1909.3          | 19193   | 22.56                  | 23.5                                 | 0                        |     |
|            |            |         | 2         | 1850.7          | 18607   | 22.70                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.72                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1909.3          | 19193   | 22.59                  | 23.5                                 | 0                        |     |
|            |            |         | 3         | 1850.7          | 18607   | 22.81                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1880            | 18900   | 22.78                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1909.3          | 19193   | 22.59                  | 23.5                                 | 0                        |     |
|            |            | 6RB     |           |                 | 1850.7  | 18607                  | 21.76                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1880    | 18900                  | 21.71                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1909.3  | 19193                  | 21.58                                | 22.5                     | 0-1 |
|            | 16-QAM     | 1 RB    | 0         | 1850.7          | 18607   | 21.69                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.85                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1909.3          | 19193   | 21.28                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1850.7          | 18607   | 21.75                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.70                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1909.3          | 19193   | 21.31                  | 22.5                                 | 0-1                      |     |
|            |            |         | 5         | 1850.7          | 18607   | 21.18                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.01                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1909.3          | 19193   | 21.10                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1850.7          | 18607   | 21.58                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1880            | 18900   | 21.59                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1909.3          | 19193   | 21.63                  | 22.5                                 | 0-1                      |     |
|            |            |         | 3 RB      | 2               | 1850.7  | 18607                  | 21.78                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1880    | 18900                  | 21.48                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1909.3  | 19193                  | 21.61                                | 22.5                     | 0-1 |
|            |            |         |           | 3               | 1850.7  | 18607                  | 21.76                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1880    | 18900                  | 21.49                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1909.3  | 19193                  | 21.71                                | 22.5                     | 0-1 |
|            |            | 6RB     |           |                 | 1850.7  | 18607                  | 20.59                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1880    | 18900                  | 20.33                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1909.3  | 19193                  | 20.43                                | 21.5                     | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

### LTE FDD Band 4 - conducted power table:

| FDD Band 4 |            |         |           |                 |         |                       |                                     |                          |     |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|-----|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |     |
| 20         | QPSK       | 1 RB    | 0         | 1720            | 20050   | 22.94                 | 23.5                                | 0                        |     |
|            |            |         |           | 1732.5          | 20175   | 22.83                 | 23.5                                | 0                        |     |
|            |            |         |           | 1745            | 20300   | 22.98                 | 23.5                                | 0                        |     |
|            |            |         | 50        | 1720            | 20050   | 22.91                 | 23.5                                | 0                        |     |
|            |            |         |           | 1732.5          | 20175   | 22.95                 | 23.5                                | 0                        |     |
|            |            |         |           | 1745            | 20300   | 22.94                 | 23.5                                | 0                        |     |
|            |            |         | 99        | 1720            | 20050   | 22.54                 | 23.5                                | 0                        |     |
|            |            |         |           | 1732.5          | 20175   | 22.57                 | 23.5                                | 0                        |     |
|            |            |         |           | 1745            | 20300   | 22.85                 | 23.5                                | 0                        |     |
|            |            | 50 RB   | 0         | 1720            | 20050   | 21.82                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.92                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1745            | 20300   | 21.94                 | 22.5                                | 0-1                      |     |
|            |            |         | 25        | 1720            | 20050   | 21.83                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.86                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1745            | 20300   | 21.92                 | 22.5                                | 0-1                      |     |
|            |            |         | 50        | 1720            | 20050   | 21.78                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.72                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1745            | 20300   | 21.82                 | 22.5                                | 0-1                      |     |
|            |            | 100RB   |           |                 | 1720    | 20050                 | 21.89                               | 22.5                     | 0-1 |
|            |            |         |           |                 | 1732.5  | 20175                 | 21.82                               | 22.5                     | 0-1 |
|            |            |         |           |                 | 1745    | 20300                 | 21.88                               | 22.5                     | 0-1 |
|            | 16-QAM     | 1 RB    | 0         | 1720            | 20050   | 21.96                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.94                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1745            | 20300   | 21.92                 | 22.5                                | 0-1                      |     |
|            |            |         | 50        | 1720            | 20050   | 21.91                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.65                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1745            | 20300   | 21.97                 | 22.5                                | 0-1                      |     |
|            |            |         | 99        | 1720            | 20050   | 21.62                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.44                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 1745            | 20300   | 21.93                 | 22.5                                | 0-1                      |     |
|            |            | 50 RB   | 0         | 1720            | 20050   | 20.49                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1732.5          | 20175   | 20.61                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1745            | 20300   | 20.66                 | 21.5                                | 0-2                      |     |
|            |            |         | 25        | 1720            | 20050   | 20.92                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1732.5          | 20175   | 20.89                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1745            | 20300   | 20.99                 | 21.5                                | 0-2                      |     |
|            |            |         | 50        | 1720            | 20050   | 20.77                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1732.5          | 20175   | 20.86                 | 21.5                                | 0-2                      |     |
|            |            |         |           | 1745            | 20300   | 20.88                 | 21.5                                | 0-2                      |     |
|            |            | 100RB   |           |                 | 1720    | 20050                 | 20.81                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 1732.5  | 20175                 | 20.84                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 1745    | 20300                 | 20.83                               | 21.5                     | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

| FDD Band 4 |            |         |           |                 |         |                        |                                      |                          |     |
|------------|------------|---------|-----------|-----------------|---------|------------------------|--------------------------------------|--------------------------|-----|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted pow er (dBm) | Target Pow er + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |     |
| 15         | QPSK       | 1 RB    | 0         | 1717.5          | 20025   | 22.85                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1732.5          | 20175   | 22.81                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1747.5          | 20325   | 22.83                  | 23.5                                 | 0                        |     |
|            |            |         | 36        | 1717.5          | 20025   | 22.56                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1732.5          | 20175   | 22.65                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1747.5          | 20325   | 22.82                  | 23.5                                 | 0                        |     |
|            |            |         | 74        | 1717.5          | 20025   | 22.76                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1732.5          | 20175   | 22.85                  | 23.5                                 | 0                        |     |
|            |            |         |           | 1747.5          | 20325   | 22.85                  | 23.5                                 | 0                        |     |
|            |            | 36 RB   | 0         | 1717.5          | 20025   | 21.88                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.93                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1747.5          | 20325   | 21.97                  | 22.5                                 | 0-1                      |     |
|            |            |         | 18        | 1717.5          | 20025   | 21.86                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.79                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1747.5          | 20325   | 21.87                  | 22.5                                 | 0-1                      |     |
|            |            |         | 37        | 1717.5          | 20025   | 21.83                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.81                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1747.5          | 20325   | 21.90                  | 22.5                                 | 0-1                      |     |
|            |            | 75RB    |           |                 | 1717.5  | 20025                  | 21.79                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1732.5  | 20175                  | 21.79                                | 22.5                     | 0-1 |
|            |            |         |           |                 | 1747.5  | 20325                  | 21.84                                | 22.5                     | 0-1 |
|            | 16-QAM     | 1 RB    | 0         | 1717.5          | 20025   | 21.73                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.92                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1747.5          | 20325   | 21.62                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1717.5          | 20025   | 21.71                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.81                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1747.5          | 20325   | 21.67                  | 22.5                                 | 0-1                      |     |
|            |            |         | 36        | 1717.5          | 20025   | 21.74                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1732.5          | 20175   | 21.64                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1747.5          | 20325   | 21.83                  | 22.5                                 | 0-1                      |     |
|            |            |         |           | 1717.5          | 20025   | 20.88                  | 21.5                                 | 0-2                      |     |
|            |            |         |           | 1732.5          | 20175   | 20.81                  | 21.5                                 | 0-2                      |     |
|            |            |         |           | 1747.5          | 20325   | 20.98                  | 21.5                                 | 0-2                      |     |
|            |            |         | 36 RB     | 0               | 1717.5  | 20025                  | 20.84                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1732.5  | 20175                  | 20.73                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1747.5  | 20325                  | 20.86                                | 21.5                     | 0-2 |
|            |            |         |           | 18              | 1717.5  | 20025                  | 20.84                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1732.5  | 20175                  | 20.73                                | 21.5                     | 0-2 |
|            |            |         |           |                 | 1747.5  | 20325                  | 20.86                                | 21.5                     | 0-2 |
|            |            | 37      | 1717.5    | 20025           | 20.81   | 21.5                   | 0-2                                  |                          |     |
|            |            |         | 1732.5    | 20175           | 20.68   | 21.5                   | 0-2                                  |                          |     |
|            |            |         | 1747.5    | 20325           | 20.90   | 21.5                   | 0-2                                  |                          |     |
| 75RB       |            |         | 1717.5    | 20025           | 20.90   | 21.5                   | 0-2                                  |                          |     |
|            |            |         | 1732.5    | 20175           | 20.85   | 21.5                   | 0-2                                  |                          |     |
|            |            |         | 1747.5    | 20325           | 20.89   | 21.5                   | 0-2                                  |                          |     |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

| FDD Band 4 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 10         | QPSK       | 1 RB    | 0         | 1715            | 20000   | 22.71                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.64                 | 23.5                                | 0                        |
|            |            |         |           | 1750            | 20350   | 22.64                 | 23.5                                | 0                        |
|            |            |         | 25        | 1715            | 20000   | 22.88                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.68                 | 23.5                                | 0                        |
|            |            |         |           | 1750            | 20350   | 22.88                 | 23.5                                | 0                        |
|            |            |         | 49        | 1715            | 20000   | 22.61                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.69                 | 23.5                                | 0                        |
|            |            |         |           | 1750            | 20350   | 22.82                 | 23.5                                | 0                        |
|            |            | 25 RB   | 0         | 1715            | 20000   | 21.75                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.94                 | 22.5                                | 0-1                      |
|            |            |         |           | 1750            | 20350   | 21.88                 | 22.5                                | 0-1                      |
|            |            |         | 12        | 1715            | 20000   | 21.81                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.83                 | 22.5                                | 0-1                      |
|            |            |         |           | 1750            | 20350   | 21.92                 | 22.5                                | 0-1                      |
|            |            |         | 25        | 1715            | 20000   | 21.66                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.82                 | 22.5                                | 0-1                      |
|            |            |         |           | 1750            | 20350   | 21.76                 | 22.5                                | 0-1                      |
|            |            | 50RB    |           | 1715            | 20000   | 21.73                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.83                 | 22.5                                | 0-1                      |
|            |            |         |           | 1750            | 20350   | 21.88                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 1715            | 20000   | 21.68                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.64                 | 22.5                                | 0-1                      |
|            |            |         |           | 1750            | 20350   | 21.80                 | 22.5                                | 0-1                      |
|            |            |         | 25        | 1715            | 20000   | 21.71                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.81                 | 22.5                                | 0-1                      |
|            |            |         |           | 1750            | 20350   | 21.90                 | 22.5                                | 0-1                      |
|            |            |         | 49        | 1715            | 20000   | 21.37                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.92                 | 22.5                                | 0-1                      |
|            |            |         |           | 1750            | 20350   | 21.87                 | 22.5                                | 0-1                      |
|            |            | 25 RB   | 0         | 1715            | 20000   | 20.97                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.94                 | 21.5                                | 0-2                      |
|            |            |         |           | 1750            | 20350   | 20.87                 | 21.5                                | 0-2                      |
|            |            |         | 12        | 1715            | 20000   | 20.69                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.78                 | 21.5                                | 0-2                      |
|            |            |         |           | 1750            | 20350   | 20.86                 | 21.5                                | 0-2                      |
|            |            |         | 25        | 1715            | 20000   | 20.93                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.72                 | 21.5                                | 0-2                      |
|            |            |         |           | 1750            | 20350   | 20.67                 | 21.5                                | 0-2                      |
|            |            | 50RB    |           | 1715            | 20000   | 20.75                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.87                 | 21.5                                | 0-2                      |
|            |            |         |           | 1750            | 20350   | 20.85                 | 21.5                                | 0-2                      |

| FDD Band 4 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5          | QPSK       | 1 RB    | 0         | 1712.5          | 19975   | 22.83                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.89                 | 23.5                                | 0                        |
|            |            |         |           | 1752.5          | 20375   | 22.68                 | 23.5                                | 0                        |
|            |            |         | 12        | 1712.5          | 19975   | 22.85                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.71                 | 23.5                                | 0                        |
|            |            |         |           | 1752.5          | 20375   | 22.95                 | 23.5                                | 0                        |
|            |            |         | 24        | 1712.5          | 19975   | 22.81                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.67                 | 23.5                                | 0                        |
|            |            |         |           | 1752.5          | 20375   | 22.97                 | 23.5                                | 0                        |
|            |            | 12 RB   | 0         | 1712.5          | 19975   | 21.81                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.78                 | 22.5                                | 0-1                      |
|            |            |         |           | 1752.5          | 20375   | 21.67                 | 22.5                                | 0-1                      |
|            |            |         | 6         | 1712.5          | 19975   | 21.71                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.77                 | 22.5                                | 0-1                      |
|            |            |         |           | 1752.5          | 20375   | 21.60                 | 22.5                                | 0-1                      |
|            |            |         | 13        | 1712.5          | 19975   | 21.67                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.85                 | 22.5                                | 0-1                      |
|            |            |         |           | 1752.5          | 20375   | 21.83                 | 22.5                                | 0-1                      |
|            |            | 25RB    |           | 1712.5          | 19975   | 21.75                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.79                 | 22.5                                | 0-1                      |
|            |            |         |           | 1752.5          | 20375   | 21.73                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 1712.5          | 19975   | 21.73                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.92                 | 22.5                                | 0-1                      |
|            |            |         |           | 1752.5          | 20375   | 21.51                 | 22.5                                | 0-1                      |
|            |            |         | 12        | 1712.5          | 19975   | 21.99                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.91                 | 22.5                                | 0-1                      |
|            |            |         |           | 1752.5          | 20375   | 21.66                 | 22.5                                | 0-1                      |
|            |            |         | 24        | 1712.5          | 19975   | 21.49                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.87                 | 22.5                                | 0-1                      |
|            |            |         |           | 1752.5          | 20375   | 21.97                 | 22.5                                | 0-1                      |
|            |            | 12 RB   | 0         | 1712.5          | 19975   | 20.79                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.80                 | 21.5                                | 0-2                      |
|            |            |         |           | 1752.5          | 20375   | 20.97                 | 21.5                                | 0-2                      |
|            |            |         | 6         | 1712.5          | 19975   | 20.69                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.71                 | 21.5                                | 0-2                      |
|            |            |         |           | 1752.5          | 20375   | 20.94                 | 21.5                                | 0-2                      |
|            |            |         | 13        | 1712.5          | 19975   | 20.85                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.67                 | 21.5                                | 0-2                      |
|            |            |         |           | 1752.5          | 20375   | 20.71                 | 21.5                                | 0-2                      |
|            |            | 25RB    |           | 1712.5          | 19975   | 20.78                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.81                 | 21.5                                | 0-2                      |
|            |            |         |           | 1752.5          | 20375   | 20.79                 | 21.5                                | 0-2                      |

| FDD Band 4 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 3          | QPSK       | 1 RB    | 0         | 1711.5          | 19965   | 22.96                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.67                 | 23.5                                | 0                        |
|            |            |         |           | 1753.5          | 20385   | 22.91                 | 23.5                                | 0                        |
|            |            |         | 7         | 1711.5          | 19965   | 22.91                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.89                 | 23.5                                | 0                        |
|            |            |         |           | 1753.5          | 20385   | 22.95                 | 23.5                                | 0                        |
|            |            |         | 14        | 1711.5          | 19965   | 22.62                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.61                 | 23.5                                | 0                        |
|            |            |         |           | 1753.5          | 20385   | 22.81                 | 23.5                                | 0                        |
|            |            | 8 RB    | 0         | 1711.5          | 19965   | 21.85                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.76                 | 22.5                                | 0-1                      |
|            |            |         |           | 1753.5          | 20385   | 21.87                 | 22.5                                | 0-1                      |
|            |            |         | 4         | 1711.5          | 19965   | 21.77                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.73                 | 22.5                                | 0-1                      |
|            |            |         |           | 1753.5          | 20385   | 21.87                 | 22.5                                | 0-1                      |
|            |            |         | 7         | 1711.5          | 19965   | 21.80                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.84                 | 22.5                                | 0-1                      |
|            |            |         |           | 1753.5          | 20385   | 21.75                 | 22.5                                | 0-1                      |
|            |            | 15RB    |           | 1711.5          | 19965   | 21.78                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.76                 | 22.5                                | 0-1                      |
|            |            |         |           | 1753.5          | 20385   | 21.84                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 1711.5          | 19965   | 21.90                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.86                 | 22.5                                | 0-1                      |
|            |            |         |           | 1753.5          | 20385   | 21.37                 | 22.5                                | 0-1                      |
|            |            |         | 7         | 1711.5          | 19965   | 21.99                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.88                 | 22.5                                | 0-1                      |
|            |            |         |           | 1753.5          | 20385   | 21.69                 | 22.5                                | 0-1                      |
|            |            |         | 14        | 1711.5          | 19965   | 21.75                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.53                 | 22.5                                | 0-1                      |
|            |            |         |           | 1753.5          | 20385   | 21.68                 | 22.5                                | 0-1                      |
|            |            | 8 RB    | 0         | 1711.5          | 19965   | 20.88                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.52                 | 21.5                                | 0-2                      |
|            |            |         |           | 1753.5          | 20385   | 20.77                 | 21.5                                | 0-2                      |
|            |            |         | 4         | 1711.5          | 19965   | 20.88                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.43                 | 21.5                                | 0-2                      |
|            |            |         |           | 1753.5          | 20385   | 20.83                 | 21.5                                | 0-2                      |
|            |            |         | 7         | 1711.5          | 19965   | 20.76                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.93                 | 21.5                                | 0-2                      |
|            |            |         |           | 1753.5          | 20385   | 20.83                 | 21.5                                | 0-2                      |
|            |            | 15RB    |           | 1711.5          | 19965   | 20.75                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.86                 | 21.5                                | 0-2                      |
|            |            |         |           | 1753.5          | 20385   | 20.51                 | 21.5                                | 0-2                      |

| FDD Band 4 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 1.4        | QPSK       | 1 RB    | 0         | 1710.7          | 19957   | 22.75                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.73                 | 23.5                                | 0                        |
|            |            |         |           | 1754.3          | 20393   | 22.80                 | 23.5                                | 0                        |
|            |            |         | 2         | 1710.7          | 19957   | 22.61                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.94                 | 23.5                                | 0                        |
|            |            |         |           | 1754.3          | 20393   | 22.88                 | 23.5                                | 0                        |
|            |            |         | 5         | 1710.7          | 19957   | 22.60                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.67                 | 23.5                                | 0                        |
|            |            |         |           | 1754.3          | 20393   | 22.84                 | 23.5                                | 0                        |
|            |            | 3 RB    | 0         | 1710.7          | 19957   | 22.88                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.91                 | 23.5                                | 0                        |
|            |            |         |           | 1754.3          | 20393   | 22.92                 | 23.5                                | 0                        |
|            |            |         | 2         | 1710.7          | 19957   | 22.89                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.89                 | 23.5                                | 0                        |
|            |            |         |           | 1754.3          | 20393   | 22.96                 | 23.5                                | 0                        |
|            |            |         | 3         | 1710.7          | 19957   | 22.82                 | 23.5                                | 0                        |
|            |            |         |           | 1732.5          | 20175   | 22.95                 | 23.5                                | 0                        |
|            |            |         |           | 1754.3          | 20393   | 22.82                 | 23.5                                | 0                        |
|            |            | 6RB     |           | 1710.7          | 19957   | 21.89                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.89                 | 22.5                                | 0-1                      |
|            |            |         |           | 1754.3          | 20393   | 21.86                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 1710.7          | 19957   | 21.67                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.95                 | 22.5                                | 0-1                      |
|            |            |         |           | 1754.3          | 20393   | 21.34                 | 22.5                                | 0-1                      |
|            |            |         | 2         | 1710.7          | 19957   | 21.84                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.49                 | 22.5                                | 0-1                      |
|            |            |         |           | 1754.3          | 20393   | 21.90                 | 22.5                                | 0-1                      |
|            |            |         | 5         | 1710.7          | 19957   | 21.54                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.96                 | 22.5                                | 0-1                      |
|            |            |         |           | 1754.3          | 20393   | 21.87                 | 22.5                                | 0-1                      |
|            |            | 3 RB    | 0         | 1710.7          | 19957   | 21.46                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.74                 | 22.5                                | 0-1                      |
|            |            |         |           | 1754.3          | 20393   | 21.32                 | 22.5                                | 0-1                      |
|            |            |         | 2         | 1710.7          | 19957   | 21.48                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.49                 | 22.5                                | 0-1                      |
|            |            |         |           | 1754.3          | 20393   | 21.46                 | 22.5                                | 0-1                      |
|            |            |         | 3         | 1710.7          | 19957   | 21.44                 | 22.5                                | 0-1                      |
|            |            |         |           | 1732.5          | 20175   | 21.49                 | 22.5                                | 0-1                      |
|            |            |         |           | 1754.3          | 20393   | 21.43                 | 22.5                                | 0-1                      |
|            |            | 6RB     |           | 1710.7          | 19957   | 20.49                 | 21.5                                | 0-2                      |
|            |            |         |           | 1732.5          | 20175   | 20.10                 | 21.5                                | 0-2                      |
|            |            |         |           | 1754.3          | 20393   | 20.54                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

### LTE FDD Band 5 - conducted power table:

| FDD Band 5 |            |         |           |                 |         |                       |                                     |                          |     |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|-----|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |     |
| 10         | QPSK       | 1 RB    | 0         | 829             | 20450   | 22.75                 | 23.5                                | 0                        |     |
|            |            |         |           | 836.5           | 20525   | 22.78                 | 23.5                                | 0                        |     |
|            |            |         |           | 844             | 20600   | 22.89                 | 23.5                                | 0                        |     |
|            |            |         | 25        | 829             | 20450   | 22.71                 | 23.5                                | 0                        |     |
|            |            |         |           | 836.5           | 20525   | 22.70                 | 23.5                                | 0                        |     |
|            |            |         |           | 844             | 20600   | 22.97                 | 23.5                                | 0                        |     |
|            |            |         | 49        | 829             | 20450   | 22.91                 | 23.5                                | 0                        |     |
|            |            |         |           | 836.5           | 20525   | 22.65                 | 23.5                                | 0                        |     |
|            |            |         |           | 844             | 20600   | 22.56                 | 23.5                                | 0                        |     |
|            |            | 25 RB   | 0         | 829             | 20450   | 21.74                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 836.5           | 20525   | 21.78                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 844             | 20600   | 21.86                 | 22.5                                | 0-1                      |     |
|            |            |         | 12        | 829             | 20450   | 21.60                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 836.5           | 20525   | 21.68                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 844             | 20600   | 21.85                 | 22.5                                | 0-1                      |     |
|            |            |         | 25        | 829             | 20450   | 21.60                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 836.5           | 20525   | 21.73                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 844             | 20600   | 21.68                 | 22.5                                | 0-1                      |     |
|            |            | 50RB    |           |                 | 829     | 20450                 | 21.67                               | 22.5                     | 0-1 |
|            |            |         |           |                 | 836.5   | 20525                 | 21.85                               | 22.5                     | 0-1 |
|            |            |         |           |                 | 844     | 20600                 | 21.88                               | 22.5                     | 0-1 |
|            | 16-QAM     | 1 RB    | 0         | 829             | 20450   | 21.41                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 836.5           | 20525   | 21.94                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 844             | 20600   | 21.72                 | 22.5                                | 0-1                      |     |
|            |            |         | 25        | 829             | 20450   | 20.92                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 836.5           | 20525   | 21.78                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 844             | 20600   | 21.81                 | 22.5                                | 0-1                      |     |
|            |            |         | 49        | 829             | 20450   | 20.51                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 836.5           | 20525   | 21.58                 | 22.5                                | 0-1                      |     |
|            |            |         |           | 844             | 20600   | 21.99                 | 22.5                                | 0-1                      |     |
|            |            |         | 25 RB     | 0               | 829     | 20450                 | 20.77                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 836.5   | 20525                 | 20.83                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 844     | 20600                 | 20.87                               | 21.5                     | 0-2 |
|            |            |         |           | 12              | 829     | 20450                 | 20.74                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 836.5   | 20525                 | 20.83                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 844     | 20600                 | 20.68                               | 21.5                     | 0-2 |
|            |            | 25      | 829       | 20450           | 20.77   | 21.5                  | 0-2                                 |                          |     |
|            |            |         | 836.5     | 20525           | 20.67   | 21.5                  | 0-2                                 |                          |     |
|            |            |         | 844       | 20600           | 20.67   | 21.5                  | 0-2                                 |                          |     |
|            |            | 500RB   |           |                 | 829     | 20450                 | 20.60                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 836.5   | 20525                 | 20.58                               | 21.5                     | 0-2 |
|            |            |         |           |                 | 844     | 20600                 | 20.68                               | 21.5                     | 0-2 |

| FDD Band 5 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5          | QPSK       | 1 RB    | 0         | 826.5           | 20425   | 22.58                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.91                 | 23.5                                | 0                        |
|            |            |         |           | 846.5           | 20625   | 22.70                 | 23.5                                | 0                        |
|            |            |         | 12        | 826.5           | 20425   | 22.52                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.81                 | 23.5                                | 0                        |
|            |            |         |           | 846.5           | 20625   | 22.71                 | 23.5                                | 0                        |
|            |            |         | 24        | 826.5           | 20425   | 22.58                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.85                 | 23.5                                | 0                        |
|            |            |         |           | 846.5           | 20625   | 22.38                 | 23.5                                | 0                        |
|            |            | 12 RB   | 0         | 826.5           | 20425   | 21.75                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.71                 | 22.5                                | 0-1                      |
|            |            |         |           | 846.5           | 20625   | 21.57                 | 22.5                                | 0-1                      |
|            |            |         | 6         | 826.5           | 20425   | 21.72                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.64                 | 22.5                                | 0-1                      |
|            |            |         |           | 846.5           | 20625   | 21.64                 | 22.5                                | 0-1                      |
|            |            |         | 13        | 826.5           | 20425   | 21.62                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.61                 | 22.5                                | 0-1                      |
|            |            |         |           | 846.5           | 20625   | 21.51                 | 22.5                                | 0-1                      |
|            |            | 25RB    |           | 826.5           | 20425   | 21.67                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.52                 | 22.5                                | 0-1                      |
|            |            |         |           | 846.5           | 20625   | 21.55                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 826.5           | 20425   | 21.71                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.89                 | 22.5                                | 0-1                      |
|            |            |         |           | 846.5           | 20625   | 21.73                 | 22.5                                | 0-1                      |
|            |            |         | 12        | 826.5           | 20425   | 21.69                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.51                 | 22.5                                | 0-1                      |
|            |            |         |           | 846.5           | 20625   | 21.89                 | 22.5                                | 0-1                      |
|            |            |         | 24        | 826.5           | 20425   | 21.83                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.68                 | 22.5                                | 0-1                      |
|            |            |         |           | 846.5           | 20625   | 21.41                 | 22.5                                | 0-1                      |
|            |            | 12 RB   | 0         | 826.5           | 20425   | 20.63                 | 21.5                                | 0-2                      |
|            |            |         |           | 836.5           | 20525   | 20.53                 | 21.5                                | 0-2                      |
|            |            |         |           | 846.5           | 20625   | 20.60                 | 21.5                                | 0-2                      |
|            |            |         | 6         | 826.5           | 20425   | 20.64                 | 21.5                                | 0-2                      |
|            |            |         |           | 836.5           | 20525   | 20.47                 | 21.5                                | 0-2                      |
|            |            |         |           | 846.5           | 20625   | 20.64                 | 21.5                                | 0-2                      |
|            |            |         | 13        | 826.5           | 20425   | 20.65                 | 21.5                                | 0-2                      |
|            |            |         |           | 836.5           | 20525   | 20.60                 | 21.5                                | 0-2                      |
|            |            |         |           | 846.5           | 20625   | 20.61                 | 21.5                                | 0-2                      |
|            |            | 25RB    |           | 826.5           | 20425   | 20.71                 | 21.5                                | 0-2                      |
|            |            |         |           | 836.5           | 20525   | 20.55                 | 21.5                                | 0-2                      |
|            |            |         |           | 846.5           | 20625   | 20.57                 | 21.5                                | 0-2                      |

| FDD Band 5 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 3          | QPSK       | 1 RB    | 0         | 825.5           | 20415   | 22.81                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.63                 | 23.5                                | 0                        |
|            |            |         |           | 847.5           | 20635   | 22.75                 | 23.5                                | 0                        |
|            |            |         | 7         | 825.5           | 20415   | 22.87                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.88                 | 23.5                                | 0                        |
|            |            |         |           | 847.5           | 20635   | 22.48                 | 23.5                                | 0                        |
|            |            |         | 14        | 825.5           | 20415   | 22.91                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.73                 | 23.5                                | 0                        |
|            |            |         |           | 847.5           | 20635   | 22.44                 | 23.5                                | 0                        |
|            |            | 8 RB    | 0         | 825.5           | 20415   | 21.81                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.61                 | 22.5                                | 0-1                      |
|            |            |         |           | 847.5           | 20635   | 21.75                 | 22.5                                | 0-1                      |
|            |            |         | 4         | 825.5           | 20415   | 21.73                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.54                 | 22.5                                | 0-1                      |
|            |            |         |           | 847.5           | 20635   | 21.71                 | 22.5                                | 0-1                      |
|            |            |         | 7         | 825.5           | 20415   | 21.78                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.49                 | 22.5                                | 0-1                      |
|            |            |         |           | 847.5           | 20635   | 21.56                 | 22.5                                | 0-1                      |
|            |            | 15RB    |           | 825.5           | 20415   | 21.74                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.60                 | 22.5                                | 0-1                      |
|            |            |         |           | 847.5           | 20635   | 21.64                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 825.5           | 20415   | 21.59                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.74                 | 22.5                                | 0-1                      |
|            |            |         |           | 847.5           | 20635   | 21.86                 | 22.5                                | 0-1                      |
|            |            |         | 7         | 825.5           | 20415   | 21.93                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.82                 | 22.5                                | 0-1                      |
|            |            |         |           | 847.5           | 20635   | 21.67                 | 22.5                                | 0-1                      |
|            |            |         | 14        | 825.5           | 20415   | 21.48                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.36                 | 22.5                                | 0-1                      |
|            |            |         |           | 847.5           | 20635   | 21.55                 | 22.5                                | 0-1                      |
|            |            | 8 RB    | 0         | 825.5           | 20415   | 20.88                 | 21.5                                | 0-2                      |
|            |            |         |           | 836.5           | 20525   | 20.67                 | 21.5                                | 0-2                      |
|            |            |         |           | 847.5           | 20635   | 20.87                 | 21.5                                | 0-2                      |
|            |            |         | 4         | 825.5           | 20415   | 20.95                 | 21.5                                | 0-2                      |
|            |            |         |           | 836.5           | 20525   | 20.24                 | 21.5                                | 0-2                      |
|            |            |         |           | 847.5           | 20635   | 20.89                 | 21.5                                | 0-2                      |
|            |            |         | 7         | 825.5           | 20415   | 20.51                 | 21.5                                | 0-2                      |
|            |            |         |           | 836.5           | 20525   | 20.28                 | 21.5                                | 0-2                      |
|            |            |         |           | 847.5           | 20635   | 20.66                 | 21.5                                | 0-2                      |
|            |            | 15RB    |           | 825.5           | 20415   | 20.55                 | 21.5                                | 0-2                      |
|            |            |         |           | 836.5           | 20525   | 20.50                 | 21.5                                | 0-2                      |
|            |            |         |           | 847.5           | 20635   | 20.95                 | 21.5                                | 0-2                      |

| FDD Band 5 |            |         |           |                 |         |                       |                                     |                          |
|------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 1.4        | QPSK       | 1 RB    | 0         | 824.7           | 20407   | 22.74                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.49                 | 23.5                                | 0                        |
|            |            |         |           | 848.3           | 20643   | 22.57                 | 23.5                                | 0                        |
|            |            |         | 2         | 824.7           | 20407   | 22.84                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.65                 | 23.5                                | 0                        |
|            |            |         |           | 848.3           | 20643   | 22.62                 | 23.5                                | 0                        |
|            |            |         | 5         | 824.7           | 20407   | 22.80                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.55                 | 23.5                                | 0                        |
|            |            |         |           | 848.3           | 20643   | 22.58                 | 23.5                                | 0                        |
|            |            | 3 RB    | 0         | 824.7           | 20407   | 22.75                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.65                 | 23.5                                | 0                        |
|            |            |         |           | 848.3           | 20643   | 22.73                 | 23.5                                | 0                        |
|            |            |         | 2         | 824.7           | 20407   | 22.67                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.74                 | 23.5                                | 0                        |
|            |            |         |           | 848.3           | 20643   | 22.73                 | 23.5                                | 0                        |
|            |            |         | 3         | 824.7           | 20407   | 22.63                 | 23.5                                | 0                        |
|            |            |         |           | 836.5           | 20525   | 22.59                 | 23.5                                | 0                        |
|            |            |         |           | 848.3           | 20643   | 22.63                 | 23.5                                | 0                        |
|            |            | 6RB     |           | 824.7           | 20407   | 21.69                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.54                 | 22.5                                | 0-1                      |
|            |            |         |           | 848.3           | 20643   | 21.62                 | 22.5                                | 0-1                      |
|            | 16-QAM     | 1 RB    | 0         | 824.7           | 20407   | 21.88                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.81                 | 22.5                                | 0-1                      |
|            |            |         |           | 848.3           | 20643   | 21.79                 | 22.5                                | 0-1                      |
|            |            |         | 2         | 824.7           | 20407   | 21.74                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.99                 | 22.5                                | 0-1                      |
|            |            |         |           | 848.3           | 20643   | 21.89                 | 22.5                                | 0-1                      |
|            |            |         | 5         | 824.7           | 20407   | 21.79                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.92                 | 22.5                                | 0-1                      |
|            |            |         |           | 848.3           | 20643   | 21.82                 | 22.5                                | 0-1                      |
|            |            | 3 RB    | 0         | 824.7           | 20407   | 21.68                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.81                 | 22.5                                | 0-1                      |
|            |            |         |           | 848.3           | 20643   | 21.79                 | 22.5                                | 0-1                      |
|            |            |         | 2         | 824.7           | 20407   | 21.73                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.90                 | 22.5                                | 0-1                      |
|            |            |         |           | 848.3           | 20643   | 21.89                 | 22.5                                | 0-1                      |
|            |            |         | 3         | 824.7           | 20407   | 21.90                 | 22.5                                | 0-1                      |
|            |            |         |           | 836.5           | 20525   | 21.83                 | 22.5                                | 0-1                      |
|            |            |         |           | 848.3           | 20643   | 21.79                 | 22.5                                | 0-1                      |
|            |            | 6RB     |           | 824.7           | 20407   | 20.41                 | 21.5                                | 0-2                      |
|            |            |         |           | 836.5           | 20525   | 20.37                 | 21.5                                | 0-2                      |
|            |            |         |           | 848.3           | 20643   | 20.64                 | 21.5                                | 0-2                      |

### LTE FDD Band 12 - conducted power table:

| FDD Band 12 |            |         |           |                 |         |                       |                                     |                          |      |     |
|-------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|------|-----|
| BW(Mhz)     | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |      |     |
| 10          | QPSK       | 1 RB    | 0         | 704             | 23060   | 22.46                 | 23.5                                | 0                        |      |     |
|             |            |         |           | 707.5           | 23095   | 22.90                 | 23.5                                | 0                        |      |     |
|             |            |         |           | 711             | 23130   | 22.89                 | 23.5                                | 0                        |      |     |
|             |            |         | 25        | 704             | 23060   | 22.88                 | 23.5                                | 0                        |      |     |
|             |            |         |           | 707.5           | 23095   | 22.91                 | 23.5                                | 0                        |      |     |
|             |            |         |           | 711             | 23130   | 22.87                 | 23.5                                | 0                        |      |     |
|             |            |         | 49        | 704             | 23060   | 22.65                 | 23.5                                | 0                        |      |     |
|             |            |         |           | 707.5           | 23095   | 22.79                 | 23.5                                | 0                        |      |     |
|             |            |         |           | 711             | 23130   | 22.86                 | 23.5                                | 0                        |      |     |
|             |            | 25 RB   | 0         | 704             | 23060   | 21.62                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 707.5           | 23095   | 21.76                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 711             | 23130   | 21.90                 | 22.5                                | 0-1                      |      |     |
|             |            |         | 12        | 704             | 23060   | 21.72                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 707.5           | 23095   | 21.79                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 711             | 23130   | 21.94                 | 22.5                                | 0-1                      |      |     |
|             |            |         | 25        | 704             | 23060   | 21.79                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 707.5           | 23095   | 21.83                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 711             | 23130   | 21.92                 | 22.5                                | 0-1                      |      |     |
|             |            | 50RB    |           |                 | 704     | 23060                 | 21.69                               | 22.5                     | 0-1  |     |
|             |            |         |           |                 | 707.5   | 23095                 | 21.77                               | 22.5                     | 0-1  |     |
|             |            |         |           |                 | 711     | 23130                 | 21.89                               | 22.5                     | 0-1  |     |
|             | 16-QAM     | 1 RB    | 0         | 704             | 23060   | 21.74                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 707.5           | 23095   | 21.94                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 711             | 23130   | 21.60                 | 22.5                                | 0-1                      |      |     |
|             |            |         | 25        | 704             | 23060   | 21.80                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 707.5           | 23095   | 21.79                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 711             | 23130   | 21.75                 | 22.5                                | 0-1                      |      |     |
|             |            |         | 49        | 704             | 23060   | 21.57                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 707.5           | 23095   | 21.76                 | 22.5                                | 0-1                      |      |     |
|             |            |         |           | 711             | 23130   | 21.54                 | 22.5                                | 0-1                      |      |     |
|             |            |         | 25 RB     | 0               | 704     | 23060                 | 20.60                               | 21.5                     | 0-2  |     |
|             |            |         |           |                 | 707.5   | 23095                 | 20.66                               | 21.5                     | 0-2  |     |
|             |            |         |           |                 | 711     | 23130                 | 20.68                               | 21.5                     | 0-2  |     |
|             |            |         |           | 12              | 704     | 23060                 | 20.85                               | 21.5                     | 0-2  |     |
|             |            |         |           |                 | 707.5   | 23095                 | 20.52                               | 21.5                     | 0-2  |     |
|             |            |         |           |                 | 711     | 23130                 | 20.60                               | 21.5                     | 0-2  |     |
|             |            |         |           | 25              | 704     | 23060                 | 20.73                               | 21.5                     | 0-2  |     |
|             |            |         |           |                 | 707.5   | 23095                 | 20.45                               | 21.5                     | 0-2  |     |
|             |            |         |           |                 | 711     | 23130                 | 20.70                               | 21.5                     | 0-2  |     |
|             |            |         | 50RB      |                 |         | 704                   | 23060                               | 20.56                    | 21.5 | 0-2 |
|             |            |         |           |                 |         | 707.5                 | 23095                               | 20.53                    | 21.5 | 0-2 |
|             |            |         |           |                 |         | 711                   | 23130                               | 20.74                    | 21.5 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

| FDD Band 12 |            |         |           |                 |         |                       |                                     |                          |
|-------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)     | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5           | QPSK       | 1 RB    | 0         | 701.5           | 23035   | 22.49                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.55                 | 23.5                                | 0                        |
|             |            |         |           | 713.5           | 23155   | 22.45                 | 23.5                                | 0                        |
|             |            |         | 12        | 701.5           | 23035   | 22.60                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.73                 | 23.5                                | 0                        |
|             |            |         |           | 713.5           | 23155   | 22.80                 | 23.5                                | 0                        |
|             |            |         | 24        | 701.5           | 23035   | 22.76                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.45                 | 23.5                                | 0                        |
|             |            |         |           | 713.5           | 23155   | 22.74                 | 23.5                                | 0                        |
|             |            | 12 RB   | 0         | 701.5           | 23035   | 21.41                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.44                 | 22.5                                | 0-1                      |
|             |            |         |           | 713.5           | 23155   | 21.47                 | 22.5                                | 0-1                      |
|             |            |         | 6         | 701.5           | 23035   | 21.57                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.49                 | 22.5                                | 0-1                      |
|             |            |         |           | 713.5           | 23155   | 21.57                 | 22.5                                | 0-1                      |
|             |            |         | 13        | 701.5           | 23035   | 21.48                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.39                 | 22.5                                | 0-1                      |
|             |            |         |           | 713.5           | 23155   | 21.61                 | 22.5                                | 0-1                      |
|             |            | 25RB    |           | 701.5           | 23035   | 21.48                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.39                 | 22.5                                | 0-1                      |
|             |            |         |           | 713.5           | 23155   | 21.56                 | 22.5                                | 0-1                      |
|             | 16-QAM     | 1 RB    | 0         | 701.5           | 23035   | 21.87                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.94                 | 22.5                                | 0-1                      |
|             |            |         |           | 713.5           | 23155   | 21.77                 | 22.5                                | 0-1                      |
|             |            |         | 12        | 701.5           | 23035   | 21.26                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.81                 | 22.5                                | 0-1                      |
|             |            |         |           | 713.5           | 23155   | 21.75                 | 22.5                                | 0-1                      |
|             |            |         | 24        | 701.5           | 23035   | 21.68                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.53                 | 22.5                                | 0-1                      |
|             |            |         |           | 713.5           | 23155   | 21.46                 | 22.5                                | 0-1                      |
|             |            | 12 RB   | 0         | 701.5           | 23035   | 20.43                 | 21.5                                | 0-2                      |
|             |            |         |           | 707.5           | 23095   | 20.46                 | 21.5                                | 0-2                      |
|             |            |         |           | 713.5           | 23155   | 20.60                 | 21.5                                | 0-2                      |
|             |            |         | 6         | 701.5           | 23035   | 20.50                 | 21.5                                | 0-2                      |
|             |            |         |           | 707.5           | 23095   | 20.41                 | 21.5                                | 0-2                      |
|             |            |         |           | 713.5           | 23155   | 20.55                 | 21.5                                | 0-2                      |
|             |            |         | 13        | 701.5           | 23035   | 20.35                 | 21.5                                | 0-2                      |
|             |            |         |           | 707.5           | 23095   | 20.40                 | 21.5                                | 0-2                      |
|             |            |         |           | 713.5           | 23155   | 20.59                 | 21.5                                | 0-2                      |
|             |            | 25RB    |           | 701.5           | 23035   | 20.29                 | 21.5                                | 0-2                      |
|             |            |         |           | 707.5           | 23095   | 20.37                 | 21.5                                | 0-2                      |
|             |            |         |           | 713.5           | 23155   | 20.62                 | 21.5                                | 0-2                      |

| FDD Band 12 |            |         |           |                 |         |                       |                                     |                          |
|-------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)     | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 3           | QPSK       | 1 RB    | 0         | 700.5           | 23025   | 22.50                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.48                 | 23.5                                | 0                        |
|             |            |         |           | 714.5           | 23165   | 22.66                 | 23.5                                | 0                        |
|             |            |         | 7         | 700.5           | 23025   | 22.69                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.46                 | 23.5                                | 0                        |
|             |            |         |           | 714.5           | 23165   | 22.73                 | 23.5                                | 0                        |
|             |            |         | 14        | 700.5           | 23025   | 22.79                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.50                 | 23.5                                | 0                        |
|             |            |         |           | 714.5           | 23165   | 22.73                 | 23.5                                | 0                        |
|             |            | 8 RB    | 0         | 700.5           | 23025   | 21.53                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.58                 | 22.5                                | 0-1                      |
|             |            |         |           | 714.5           | 23165   | 21.62                 | 22.5                                | 0-1                      |
|             |            |         | 4         | 700.5           | 23025   | 21.59                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.66                 | 22.5                                | 0-1                      |
|             |            |         |           | 714.5           | 23165   | 21.57                 | 22.5                                | 0-1                      |
|             |            |         | 7         | 700.5           | 23025   | 21.55                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.70                 | 22.5                                | 0-1                      |
|             |            |         |           | 714.5           | 23165   | 21.59                 | 22.5                                | 0-1                      |
|             |            | 15RB    |           | 700.5           | 23025   | 21.49                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.53                 | 22.5                                | 0-1                      |
|             |            |         |           | 714.5           | 23165   | 21.57                 | 22.5                                | 0-1                      |
|             | 16-QAM     | 1 RB    | 0         | 700.5           | 23025   | 21.89                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.36                 | 22.5                                | 0-1                      |
|             |            |         |           | 714.5           | 23165   | 21.66                 | 22.5                                | 0-1                      |
|             |            |         | 7         | 700.5           | 23025   | 21.16                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.36                 | 22.5                                | 0-1                      |
|             |            |         |           | 714.5           | 23165   | 21.73                 | 22.5                                | 0-1                      |
|             |            |         | 14        | 700.5           | 23025   | 21.84                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.53                 | 22.5                                | 0-1                      |
|             |            |         |           | 714.5           | 23165   | 21.95                 | 22.5                                | 0-1                      |
|             |            | 8 RB    | 0         | 700.5           | 23025   | 20.36                 | 21.5                                | 0-2                      |
|             |            |         |           | 707.5           | 23095   | 20.44                 | 21.5                                | 0-2                      |
|             |            |         |           | 714.5           | 23165   | 20.76                 | 21.5                                | 0-2                      |
|             |            |         | 4         | 700.5           | 23025   | 20.31                 | 21.5                                | 0-2                      |
|             |            |         |           | 707.5           | 23095   | 20.68                 | 21.5                                | 0-2                      |
|             |            |         |           | 714.5           | 23165   | 20.72                 | 21.5                                | 0-2                      |
|             |            |         | 7         | 700.5           | 23025   | 20.58                 | 21.5                                | 0-2                      |
|             |            |         |           | 707.5           | 23095   | 20.91                 | 21.5                                | 0-2                      |
|             |            |         |           | 714.5           | 23165   | 20.81                 | 21.5                                | 0-2                      |
|             |            | 15RB    |           | 700.5           | 23025   | 20.40                 | 21.5                                | 0-2                      |
|             |            |         |           | 707.5           | 23095   | 20.78                 | 21.5                                | 0-2                      |
|             |            |         |           | 714.5           | 23165   | 20.79                 | 21.5                                | 0-2                      |

| FDD Band 12 |            |         |           |                 |         |                       |                                     |                          |
|-------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)     | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 1.4         | QPSK       | 1 RB    | 0         | 699.7           | 23017   | 22.53                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.59                 | 23.5                                | 0                        |
|             |            |         |           | 715.3           | 23173   | 22.56                 | 23.5                                | 0                        |
|             |            |         | 2         | 699.7           | 23017   | 22.53                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.66                 | 23.5                                | 0                        |
|             |            |         |           | 715.3           | 23173   | 22.61                 | 23.5                                | 0                        |
|             |            |         | 5         | 699.7           | 23017   | 22.58                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.49                 | 23.5                                | 0                        |
|             |            |         |           | 715.3           | 23173   | 22.44                 | 23.5                                | 0                        |
|             |            | 3 RB    | 0         | 699.7           | 23017   | 22.59                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.65                 | 23.5                                | 0                        |
|             |            |         |           | 715.3           | 23173   | 22.57                 | 23.5                                | 0                        |
|             |            |         | 2         | 699.7           | 23017   | 22.53                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.63                 | 23.5                                | 0                        |
|             |            |         |           | 715.3           | 23173   | 22.65                 | 23.5                                | 0                        |
|             |            |         | 3         | 699.7           | 23017   | 22.63                 | 23.5                                | 0                        |
|             |            |         |           | 707.5           | 23095   | 22.67                 | 23.5                                | 0                        |
|             |            |         |           | 715.3           | 23173   | 22.70                 | 23.5                                | 0                        |
|             |            | 6RB     |           | 699.7           | 23017   | 21.51                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.70                 | 22.5                                | 0-1                      |
|             |            |         |           | 715.3           | 23173   | 21.66                 | 22.5                                | 0-1                      |
|             | 16-QAM     | 1 RB    | 0         | 699.7           | 23017   | 21.65                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.82                 | 22.5                                | 0-1                      |
|             |            |         |           | 715.3           | 23173   | 21.63                 | 22.5                                | 0-1                      |
|             |            |         | 2         | 699.7           | 23017   | 21.52                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.77                 | 22.5                                | 0-1                      |
|             |            |         |           | 715.3           | 23173   | 21.51                 | 22.5                                | 0-1                      |
|             |            |         | 5         | 699.7           | 23017   | 21.44                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.86                 | 22.5                                | 0-1                      |
|             |            |         |           | 715.3           | 23173   | 21.71                 | 22.5                                | 0-1                      |
|             |            | 3 RB    | 0         | 699.7           | 23017   | 21.86                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.74                 | 22.5                                | 0-1                      |
|             |            |         |           | 715.3           | 23173   | 21.85                 | 22.5                                | 0-1                      |
|             |            |         | 2         | 699.7           | 23017   | 21.99                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.67                 | 22.5                                | 0-1                      |
|             |            |         |           | 715.3           | 23173   | 21.70                 | 22.5                                | 0-1                      |
|             |            |         | 3         | 699.7           | 23017   | 21.76                 | 22.5                                | 0-1                      |
|             |            |         |           | 707.5           | 23095   | 21.79                 | 22.5                                | 0-1                      |
|             |            |         |           | 715.3           | 23173   | 21.89                 | 22.5                                | 0-1                      |
|             |            | 6RB     |           | 699.7           | 23017   | 20.62                 | 21.5                                | 0-2                      |
|             |            |         |           | 707.5           | 23095   | 20.48                 | 21.5                                | 0-2                      |
|             |            |         |           | 715.3           | 23173   | 20.60                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

**WLAN802.11 b/g/n(20M/40M) conducted power table:**

| 802.11 b |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|----------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH       | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|          |                    |                                                    | 1                                       |
| 1        | 2412               | 18                                                 | 17.68                                   |
| 6        | 2437               | 18                                                 | 17.65                                   |
| 11       | 2462               | 18                                                 | 17.93                                   |

| 802.11 g |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|----------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH       | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|          |                    |                                                    | 6                                       |
| 1        | 2412               | 16                                                 | 15.83                                   |
| 6        | 2437               | 16                                                 | 15.97                                   |
| 11       | 2462               | 16                                                 | 15.68                                   |

| 802.11 n(20M) |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|---------------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH            | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|               |                    |                                                    | HT0                                     |
| 1             | 2412               | 15                                                 | 14.76                                   |
| 6             | 2437               | 15                                                 | 14.62                                   |
| 11            | 2462               | 15                                                 | 14.84                                   |

| 802.11 n(40M) |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|---------------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH            | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|               |                    |                                                    | HT0                                     |
| 3             | 2422               | 15                                                 | 14.78                                   |
| 6             | 2437               | 15                                                 | 14.86                                   |
| 9             | 2452               | 15                                                 | 14.75                                   |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

### Bluetooth conducted power table:

| Frequency<br>(MHz) | Data Rate | Max. tune-up<br>power | Average conducted output power |       |
|--------------------|-----------|-----------------------|--------------------------------|-------|
|                    |           |                       | dBm                            | mW    |
| 2402               | 1         | 8                     | 7.06                           | 5.082 |
| 2441               | 1         | 8                     | 7.98                           | 6.281 |
| 2480               | 1         | 8                     | 6.03                           | 4.009 |
| 2402               | 2         | 8                     | 5.47                           | 3.524 |
| 2441               | 2         | 8                     | 6.71                           | 4.688 |
| 2480               | 2         | 8                     | 4.62                           | 2.897 |
| 2402               | 3         | 8                     | 5.54                           | 3.581 |
| 2441               | 3         | 8                     | 6.84                           | 4.831 |
| 2480               | 3         | 8                     | 4.67                           | 2.931 |

| Frequency<br>(MHz) | BT4.0 Average conducted output power |       |
|--------------------|--------------------------------------|-------|
|                    | dBm                                  | mW    |
| 2402               | 2.94                                 | 1.968 |
| 2442               | 4.00                                 | 2.512 |
| 2480               | 2.03                                 | 1.596 |

## 1.4 Test Environment

Ambient Temperature:  $22 \pm 2^\circ \text{C}$   
Tissue Simulating Liquid:  $22 \pm 2^\circ \text{C}$

## 1.5 Operation Description

1. The EUT is controlled by using a Radio Communication Tester (Anritsu MT8820C), and the communication between the EUT and the tester is established by air link.
2. Measurements are performed respectively on the lowest, middle and highest channels of the operating band(s). The EUT is set to maximum power level during all tests, and at the beginning of each test the battery is fully charged.
3. During the SAR testing, the DASY 5 system checks power drift by comparing the e-field strength of one specific location measured at the beginning with that measured at the end of the SAR testing.
4. SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power. The data mode with highest specified time-averaged output power should be tested for SAR compliance. The GMSK EDGE configurations are grouped with GPRS and considered with respect to time-averaged maximum output power to determine compliance. The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode. Since the maximum output power in a secondary mode (8-PSK EDGE) is  $\leq \frac{1}{4}$  dB higher than the primary mode (GMSK GPRS/EDGE), SAR measurement is not required for the secondary mode (8-PSK EDGE).
5. The 3G SAR test reduction procedure is applied to HSDPA with 12.2 kbps RMC as the primary mode. Since the maximum output power in a secondary mode (HSDPA) is  $\leq \frac{1}{4}$  dB higher than the primary mode (WCDMA), SAR measurement is not required for the secondary mode (HSDPA).
6. The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) with 12.2 kbps RMC as the primary mode. Since the maximum output power in a secondary mode (HSPA) is  $\leq \frac{1}{4}$  dB higher than the primary mode (WCDMA), SAR measurement is not required for the secondary mode (HSPA).
7. LTE modes test according to **KDB 941225D05v02r05**.
  - a. Per Section 5.2.1, the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation.
    - Using the RB offset and required test channel combination with the highest

maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.

- When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel.

- When the reported SAR of a required test channel is  $> 1.45$  W/kg, SAR is required for all three RB offset configurations for that required test channel.

b. Per Section 5.2.2, the largest channel bandwidth and measure SAR for QPSK with 50% RB allocation

- The procedures required for 1 RB allocation in 5.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.

c. Per Section 5.2.3, the largest channel bandwidth and measure SAR for QPSK with 100% RB allocation

- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 5.2.1 and 5.2.2 are  $\leq 0.8$  W/kg.

- Otherwise, SAR is measured for the highest output power channel and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.

d. Per Section 5.2.4, Higher order modulations

- For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in sections 5.2.1, 5.2.2 and 5.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is  $> \frac{1}{2}$  dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is  $> 1.45$  W/kg.

e. Per Section 5.3, other channel bandwidth standalone SAR test requirements

- For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section 5.2 to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is  $> \frac{1}{2}$  dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is  $> 1.45$  W/kg. The equivalent channel configuration for the RB allocation, RB offset and modulation etc. is determined for the smaller channel bandwidth according to the same number of RB allocated in the largest channel bandwidth.

## WLAN802.11b DSSS SAR Test Requirements:

8. SAR is measured for 2.4 GHz 802.11b DSSS mode using the highest measured maximum output power channel, when the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
9. When the reported SAR is  $> 0.8$  W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

802.11g/n OFDM SAR Test Exclusion Requirements:

10. SAR is not required for 802.11g/n since the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.


Other

11. BT and WLAN 2.4GHz use the same antenna path and Bluetooth can't transmit simultaneously with WLAN 2.4GHz.
12. According to **KDB447498D01v06**, testing of other required channels is not required when the reported 1-g SAR for the highest output channel is  $\leq 0.8$  W/kg, when the transmission band is  $\leq 100$  MHz.
13. According to **KDB865664D01v01r04**, SAR measurement variability must be assessed for each frequency band. When the original highest measured SAR is  $\geq 0.8$  W/kg, repeated that measurement once. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit)
14. According to **KDB447498D01v06** – The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for product specific 10-g SAR.


| mode | position  | max. power (dB) | max. power (mW) | f(GHz) | calculation | SAR exclusion threshold | SAR test exclusion |
|------|-----------|-----------------|-----------------|--------|-------------|-------------------------|--------------------|
| BT   | body-worn | 8               | 6.31            | 2.48   | 0.994       | 3                       | yes                |

## 1.6 Positioning Procedure

### Head SAR measurement statement



Phone position 1, “cheek” or “touch” position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning.



Phone position 2, “tilted position.” The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning.

#### Cheek/Touch Position:

The handset was brought toward the mouth of the head phantom by pivoting against the ear reference point until any point of the mouthpiece or keypad touched the phantom.

#### Ear/Tilt Position:

With the phone aligned in the Cheek/Touch position, the handset was tilted away from the mouth with respect to the test device reference point by 15 degrees.

## Body SAR measurement statement

### 1. Body-worn exposure: 10mm

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative test separation distance configuration may be used to support both SAR conditions. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2 \text{ W/kg}$ , the highest reported SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.

### 2. Hotspot exposure: 10mm

A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge when the form factor of a handset is larger than  $9 \text{ cm} \times 5 \text{ cm}$ ,

Test configurations of WWAN

- (1) Front side
- (2) Back side
- (3) Bottom side.
- (4) Left side.

Test configurations of WLAN

- (1) Front side
- (2) Back side
- (3) Top side.
- (4) Right side

### 3. Phablet SAR test consideration

Since the device is not a phablet (overall diagonal dimension  $> 16.0 \text{ cm}$ ), phablet SAR procedure is not required for this device.

## 1.7 Evaluation Procedures

The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. The extraction of the measured data (grid and values) from the Zoom Scan.
2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters).
3. The generation of a high-resolution mesh within the measured volume.
4. The interpolation of all measured values from the measurement grid to the high-resolution grid.
5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface.
6. The calculation of the averaged SAR within masses of 1g and 10g.

The probe is calibrated at the center of the dipole sensors that is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated. The angle between the probe axis and the surface normal line is less than 30 degree.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extreme of the SAR distribution. The uncertainty on the locations of the extreme is less than 1/20 of the grid size. Only local maximum within -2 dB of the global maximum are searched and passed for the Cube Scan measurement. In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5mm.

The maximum search is automatically performed after each area scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the area scanning measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations. The 1g and 10g peak evaluations are only available for the predefined cube 7x7x7 scans.

The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30x30x30mm contains about 30g of tissue. The first procedure is an extrapolation (incl. Boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D



interpolation to get all points within the measured volume. In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is then moved around until the highest averaged SAR is found.

If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

## 1.8 Probe Calibration Procedures

For the calibration of E-field probes in lossy liquids, an electric field with an accurately known field strength must be produced within the measured liquid. For standardization purposes it would be desirable if all measurements which are necessary to assess the correct field strength would be traceable to standardized measurement procedures. In the following two different calibration techniques are summarized:

### 1.8.1 Transfer Calibration with Temperature Probes

In lossy liquids the specific absorption rate (SAR) is related both to the electric field ( $E$ ) and the temperature gradient ( $\delta T / \delta t$ ) in the liquid.

$$SAR = \frac{\sigma}{\rho} |E|^2 = c \frac{\delta T}{\delta t}$$

Whereby  $\sigma$  is the conductivity,  $\rho$  the density and  $c$  the heat capacity of the liquid.

Hence, the electric field in lossy liquid can be measured indirectly by measuring the temperature gradient in the liquid. Non-disturbing temperature probes (optical probes or thermistor probes with resistive lines) with high spatial resolution (<1-2 mm) and fast reaction time (<1 s) are available and can be easily calibrated with high precision [1]. The setup and the exciting source have no influence on the calibration; only the relative positioning uncertainties of the standard temperature probe and the E-field probe to be calibrated must be considered. However, several problems limit the available accuracy of probe calibrations with temperature probes:

1. The temperature gradient is not directly measurable but must be evaluated from temperature measurements at different time steps. Special precaution is necessary to avoid measurement errors caused by temperature gradients due to energy equalizing effects or convection currents in the liquid. Such effects cannot be completely avoided, as the measured field itself destroys the

thermal equilibrium in the liquid. With a careful setup these errors can be kept small.

2. The measured volume around the temperature probe is not well defined. It is difficult to calculate the energy transfer from a surrounding gradient temperature field into the probe. These effects must be considered, since temperature probes are calibrated in liquid with homogeneous temperatures. There is no traceable standard for temperature rise measurements.
3. The calibration depends on the assessment of the specific density, the heat capacity and the conductivity of the medium. While the specific density and heat capacity can be measured accurately with standardized procedures ( $\sim 2\%$  for  $c$ ; much better for  $\rho$ ), there is no standard for the measurement of the conductivity. Depending on the method and liquid, the error can well exceed  $\pm 5\%$ .
4. Temperature rise measurements are not very sensitive and therefore are often performed at a higher power level than the E-field measurements. The nonlinearities in the system (e.g., power measurements, different components, etc.) must be considered.

Considering these problems, the possible accuracy of the calibration of E-field probes with temperature gradient measurements in a carefully designed setup is about  $\pm 10\%$  (RSS) [2]. Recently, a setup which is a combination of the waveguide techniques and the thermal measurements was presented in [3]. The estimated uncertainty of the setup is  $\pm 5\%$  (RSS) when the same liquid is used for the calibration and for actual measurements and  $\pm 7-9\%$  (RSS) when not, which is in good agreement with the estimates given in [2].

### 1.8.2 Calibration with Analytical Fields

In this method a technical setup is used in which the field can be calculated analytically from measurements of other physical magnitudes (e.g., input power). This corresponds to the standard field method for probe calibration in air; however, there is no standard defined for fields in lossy liquids.

When using calculated fields in lossy liquids for probe calibration, several points must be considered in the assessment of the uncertainty:

1. The setup must enable accurate determination of the incident power.
2. The accuracy of the calculated field strength will depend on the assessment of the dielectric parameters of the liquid.
3. Due to the small wavelength in liquids with high permittivity, even small setups might be above the resonant cutoff frequencies. The field distribution in the setup must be carefully checked for conformity with the theoretical field distribution.

### References

- (1) N. Kuster, Q. Balzano, and J.C. Lin, Eds., *Mobile Communications Safety*, Chapman & Hall, London, 1997.
- (2) K. Meier, M. Burkhardt, T. Schmid, and N. Kuster, "Broadband calibration of E-field probes in lossy media", *IEEE Transactions on Microwave Theory and Techniques*, vol. 44, no. 10, pp. 1954-1962, Oct. 1996.
- (3) K. Jokela, P. Hyysalo, and L. Puranen, "Calibration of specific absorption rate (SAR) probes in waveguide at 900 MHz", *IEEE Transactions on Instrumentation and Measurements*, vol. 47, no. 2, pp. 432-438, Apr. 1998.

## 1.9 The SAR Measurement System

A block diagram of the SAR measurement system is given in Fig. a. This SAR measurement system uses a Computer-controlled 3-D stepper motor system (SPEAG DASY 5 professional system). Model EX3DV4 field probes are used to determine the internal electric fields. The SAR can be obtained from the equation  $SAR = \sigma (|E_i|^2) / \rho$  where  $\sigma$  and  $\rho$  are the conductivity and mass density of the tissue-simulant.




Fig. a A block diagram of the SAR measurement system

The DASY 5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Staubli RX family) with controller, teach pendant and software. An arm extension is for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. Data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
5. The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
6. A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
7. A computer operating Windows7
8. DASY 5 software.
9. Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
10. The SAM twin phantom enabling testing left-hand and right-hand usage.
11. The device holder for handheld mobile phones.
12. Tissue simulating liquid mixed according to the given recipes.
13. Validation dipole kits allowing to validate the proper functioning of the system.

## 1.10 System Components

### EX3DV4 E-Field Probe

|               |                                                                                                                                                                                                            |                                                                                     |  |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--|
| Construction  | Symmetrical design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE)                                                |  |  |
| Calibration   | Basic Broad Band Calibration in air<br>Conversion Factors (CF) for<br>HSL750/835/1750/1900/2450 MHz<br>Additional CF for other liquids and frequencies upon request                                        |                                                                                     |  |
| Frequency     | 10 MHz to > 6 GHz, Linearity: $\pm 0.6$ dB                                                                                                                                                                 |                                                                                     |  |
| Directivity   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in tissue material (rotation normal to probe axis)                                                                                        |                                                                                     |  |
| Dynamic Range | 10 $\mu$ W/g to > 100 mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)                                                                                                                     |                                                                                     |  |
| Dimensions    | Tip diameter: 2.5 mm                                                                                                                                                                                       |                                                                                     |  |
| Application   | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%. |                                                                                     |  |

## SAM PHANTOM V4.0C

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                     |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Construction:    | <p>The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209.</p> <p>It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.</p> |                                                                                     |
| Shell Thickness: | 2 ± 0.2 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |
| Filling Volume:  | Approx. 25 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                     |
| Dimensions:      | Height: 850 mm;<br>Length: 1000 mm;<br>Width: 500 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                     |

## DEVICE HOLDER

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                            |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| Construction | <p>In combination with the Twin SAM Phantom V4.0/V4.0C or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).</p> |  <p>Device Holder</p> |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|

## 1.11 SAR System Verification

The microwave circuit arrangement for system verification is sketched in Fig. b. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within  $\pm 10\%$  (according to KDB865664D01v01r04) from the target SAR values.

These tests were done at 750/835/1750/1900/2450 MHz. The tests were conducted on the same days as the measurement of the DUT. The obtained results from the system accuracy verification are displayed in the table 1. During the tests, the ambient temperature of the laboratory was 21.7°C, the relative humidity was 62% and the liquid depth above the ear reference points was above 15 cm ( $\leq 3G$ ) or 10 cm ( $> 3G$ ) in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.




Fig. b The block diagram of system verification



| Validation Kit | S/N   | Frequency (MHz) |      | 1W Target SAR-1g (mW/g) | Measured SAR-1g (mW/g) | Measured SAR-1g normalized to 1W (mW/g) | Deviation (%) | Measured Date |
|----------------|-------|-----------------|------|-------------------------|------------------------|-----------------------------------------|---------------|---------------|
| D750V3         | 1015  | 750             | Head | 8.32                    | 2.12                   | 8.48                                    | 1.92%         | Dec. 23, 2016 |
|                |       |                 | Body | 8.77                    | 2.18                   | 8.72                                    | -0.57%        | Dec. 23, 2016 |
| D835V2         | 4d063 | 835             | Head | 9.40                    | 2.34                   | 9.36                                    | -0.43%        | Dec. 21, 2016 |
|                |       |                 | Body | 9.57                    | 2.44                   | 9.76                                    | 1.99%         | Dec. 28, 2016 |
| D1750V2        | 1008  | 1750            | Head | 37.20                   | 9.25                   | 37.00                                   | -0.54%        | Dec. 27, 2016 |
|                |       |                 | Body | 37.30                   | 9.39                   | 37.56                                   | 0.70%         | Dec. 27, 2016 |
| D1900V2        | 5d027 | 1900            | Head | 38.70                   | 9.48                   | 37.92                                   | -2.02%        | Dec. 22, 2016 |
|                |       |                 | Body | 39.70                   | 9.82                   | 39.28                                   | -1.06%        | Dec. 29, 2016 |
| D2450V2        | 727   | 2450            | Head | 51.00                   | 13.10                  | 52.40                                   | 2.75%         | Dec. 30, 2016 |
|                |       |                 | Body | 49.60                   | 12.70                  | 50.80                                   | 2.42%         | Dec. 30, 2016 |

Table 1. Results of system validation

## 1.12 Tissue Simulant Fluid for the Frequency Band

The dielectric properties for this Head-simulant fluid were measured by using the Agilent Model 85070E Dielectric Probe (rates frequency band 200 MHz to 20 GHz) in conjunction with Network Analyzer.

All dielectric parameters of tissue simulates were measured within 24 hours of SAR measurements. The depth of the tissue simulant in the flat section of the phantom was at least 15 cm ( $\leq 3G$ ) or 10 cm ( $> 3G$ ) during all tests. (Appendix Fig. 2)

| Tissue Type | Measurement Date | Measured Frequency (MHz) | Target Dielectric Constant, $\epsilon_r$ ( $\pm 5\%$ ) | Target Conductivity, $\sigma$ ( $\pm 5\%$ ) | Measured Dielectric Constant, $\epsilon_r$ | Measured Conductivity, $\sigma$ (S/m) | % dev $\epsilon_r$ | % dev $\sigma$ |
|-------------|------------------|--------------------------|--------------------------------------------------------|---------------------------------------------|--------------------------------------------|---------------------------------------|--------------------|----------------|
| Head        | Dec. 23, 2016    | 707.5                    | 42.162                                                 | 0.890                                       | 42.560                                     | 0.892                                 | -0.94%             | -0.22%         |
|             |                  | 750                      | 41.942                                                 | 0.893                                       | 42.345                                     | 0.913                                 | -0.96%             | -2.20%         |
|             | Dec. 21, 2016    | 835                      | 41.500                                                 | 0.900                                       | 41.936                                     | 0.909                                 | -1.05%             | -1.00%         |
|             |                  | 836.6                    | 41.500                                                 | 0.902                                       | 41.836                                     | 0.911                                 | -0.81%             | -1.03%         |
|             |                  | 844                      | 41.500                                                 | 0.910                                       | 41.749                                     | 0.919                                 | -0.60%             | -1.02%         |
|             |                  | 848.8                    | 41.500                                                 | 0.915                                       | 41.711                                     | 0.921                                 | -0.51%             | -0.67%         |
|             | Dec. 27, 2016    | 1732.4                   | 40.107                                                 | 1.361                                       | 38.626                                     | 1.401                                 | 3.69%              | -2.95%         |
|             |                  | 1745                     | 40.087                                                 | 1.368                                       | 38.605                                     | 1.415                                 | 3.70%              | -3.42%         |
|             |                  | 1750                     | 40.079                                                 | 1.371                                       | 38.593                                     | 1.421                                 | 3.71%              | -3.64%         |
|             | Dec. 22, 2016    | 1852.4                   | 40.000                                                 | 1.400                                       | 38.876                                     | 1.388                                 | 2.81%              | 0.86%          |
|             |                  | 1860                     | 40.000                                                 | 1.400                                       | 38.807                                     | 1.393                                 | 2.98%              | 0.50%          |
|             |                  | 1880                     | 40.000                                                 | 1.400                                       | 38.737                                     | 1.408                                 | 3.16%              | -0.57%         |
|             |                  | 1900                     | 40.000                                                 | 1.400                                       | 38.677                                     | 1.417                                 | 3.31%              | -1.21%         |
|             | Dec. 30, 2016    | 2450                     | 39.200                                                 | 1.800                                       | 38.214                                     | 1.807                                 | 2.52%              | -0.39%         |
|             |                  | 2462                     | 39.185                                                 | 1.813                                       | 38.142                                     | 1.843                                 | 2.66%              | -1.65%         |
| Body        | Dec. 23, 2016    | 707.5                    | 55.697                                                 | 0.960                                       | 57.001                                     | 0.925                                 | -2.34%             | 3.65%          |
|             |                  | 750                      | 55.531                                                 | 0.963                                       | 56.872                                     | 0.946                                 | -2.41%             | 1.80%          |
|             | Dec. 28, 2016    | 835                      | 55.200                                                 | 0.970                                       | 55.866                                     | 0.981                                 | -1.21%             | -1.13%         |
|             |                  | 836.6                    | 55.195                                                 | 0.972                                       | 55.858                                     | 0.984                                 | -1.20%             | -1.24%         |
|             |                  | 844                      | 55.172                                                 | 0.981                                       | 55.824                                     | 0.998                                 | -1.18%             | -1.72%         |
|             |                  | 848.8                    | 55.158                                                 | 0.987                                       | 55.797                                     | 1.001                                 | -1.16%             | -1.42%         |
|             | Dec. 27, 2016    | 1732.4                   | 53.478                                                 | 1.477                                       | 53.859                                     | 1.428                                 | -0.71%             | 3.34%          |
|             |                  | 1745                     | 53.445                                                 | 1.485                                       | 53.845                                     | 1.441                                 | -0.75%             | 2.98%          |
|             |                  | 1750                     | 53.432                                                 | 1.488                                       | 53.832                                     | 1.445                                 | -0.75%             | 2.92%          |
|             | Dec. 29, 2016    | 1852.4                   | 53.300                                                 | 1.520                                       | 52.894                                     | 1.472                                 | 0.76%              | 3.16%          |
|             |                  | 1860                     | 53.300                                                 | 1.520                                       | 52.884                                     | 1.481                                 | 0.78%              | 2.57%          |
|             |                  | 1880                     | 53.300                                                 | 1.520                                       | 52.805                                     | 1.503                                 | 0.93%              | 1.12%          |
|             |                  | 1900                     | 53.300                                                 | 1.520                                       | 52.726                                     | 1.522                                 | 1.08%              | -0.13%         |
|             | Dec. 30, 2016    | 2450                     | 52.700                                                 | 1.950                                       | 52.541                                     | 2.009                                 | 0.30%              | -3.03%         |
|             |                  | 2462                     | 52.685                                                 | 1.967                                       | 52.525                                     | 2.017                                 | 0.30%              | -2.54%         |

Table 2. Dielectric Parameters of Tissue Simulant Fluid

The composition of the tissue simulating liquid:

| Frequency<br>(MHz) | Mode | Ingredient |          |         |                  |           |       | Total<br>amount |
|--------------------|------|------------|----------|---------|------------------|-----------|-------|-----------------|
|                    |      | DGMBE      | Water    | Salt    | Preventol<br>D-7 | Cellulose | Sugar |                 |
| 750                | Head | —          | 532.98 g | 18.3 g  | 2.4 g            | 3.2 g     | 766 g | 1.3L(Kg)        |
|                    | Body | —          | 631.68 g | 11.72 g | 1.2 g            | —         | 600 g | 1.0L(Kg)        |
| 850                | Head | —          | 532.98 g | 18.3 g  | 2.4 g            | 3.2 g     | 766 g | 1.3L(Kg)        |
|                    | Body | —          | 631.68 g | 11.72 g | 1.2 g            | —         | 600 g | 1.0L(Kg)        |
| 1750               | Head | 444.52 g   | 552.42 g | 3.06 g  | —                | —         | —     | 1.0L(Kg)        |
|                    | Body | 300.67 g   | 716.56 g | 4.0 g   | —                | —         | —     | 1.0L(Kg)        |
| 1900               | Head | 444.52 g   | 552.42 g | 3.06 g  | —                | —         | —     | 1.0L(Kg)        |
|                    | Body | 300.67 g   | 716.56 g | 4.0 g   | —                | —         | —     | 1.0L(Kg)        |
| 2450               | Head | 550ml      | 450ml    | —       | —                | —         | —     | 1.0L(Kg)        |
|                    | Body | 301.7ml    | 698.3ml  | —       | —                | —         | —     | 1.0L(Kg)        |

Table 3. Recipes for tissue simulating liquid

### 1.13 Test Standards and Limits

According to FCC 47CFR §2.1093(d) The limits to be used for evaluation are based generally on criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate ("SAR") in Section 4.2 of "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," ANSI/IEEE C95.1, By the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017.

These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86, Section 17.4.5. Copyright NCRP, 1986, Bethesda, Maryland 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards. The criteria to be used are specified in paragraphs (d)(1) and (d)(2) of this section and shall apply for portable devices transmitting in the frequency range from 100 kHz to 6 GHz. Portable devices that transmit at frequencies above 6 GHz are to be evaluated in terms of the MPE limits specified in § 1.1310 of this chapter.

Measurements and calculations to demonstrate compliance with MPE field strength or power density limits for devices operating above 6 GHz should be made at a minimum distance of 5 cm from the radiating source.

1. Limits for Occupational/Controlled exposure: 0.4 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 8 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 20 W/kg, as averaged over a 10 grams of tissue (defined as a tissue volume in the shape of a cube).

Occupational/Controlled limits apply when persons are exposed as a consequence of their employment provided these persons are fully aware of and exercise control over their exposure. Awareness of exposure can be accomplished by use of warning labels or by specific training or education through appropriate means, such as an RF safety program in a work environment.

2. Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube).

Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube).

General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure.

Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.(Table .6)

| Human Exposure                               | Uncontrolled Environment<br>General Population | Controlled Environment<br>Occupational |
|----------------------------------------------|------------------------------------------------|----------------------------------------|
| Spatial Peak SAR<br>(Brain)                  | 1.60 W/kg                                      | 8.00 W/kg                              |
| Spatial Average SAR<br>(Whole Body)          | 0.08 W/kg                                      | 0.40 W/kg                              |
| Spatial Peak SAR<br>(Hands/Feet/Ankle/Wrist) | 4.00 W/kg                                      | 20.00 W/kg                             |

Table 4. RF exposure limits

Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

## 2. Summary of Results

### GSM 850

| Mode                       | Position    | Distance (mm) | CH  | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|----------------------------|-------------|---------------|-----|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                            |             |               |     |             |                                              |                           |         | Measured                    | Reported |           |
| GSM850 (Head)              | Re Cheek    | -             | 251 | 848.8       | 33.50                                        | 32.42                     | 28.23%  | 0.094                       | 0.121    | -         |
|                            | Re Tilt     | -             | 251 | 848.8       | 33.50                                        | 32.42                     | 28.23%  | 0.079                       | 0.101    | -         |
|                            | Le Cheek    | -             | 251 | 848.8       | 33.50                                        | 32.42                     | 28.23%  | 0.132                       | 0.169    | 71        |
|                            | Le Tilt     | -             | 251 | 848.8       | 33.50                                        | 32.42                     | 28.23%  | 0.076                       | 0.097    | -         |
| GSM850 (Body-Worn)         | Front side  | 10            | 251 | 848.8       | 33.50                                        | 32.42                     | 28.23%  | 0.187                       | 0.240    | -         |
|                            | Back side   | 10            | 251 | 848.8       | 33.50                                        | 32.42                     | 28.23%  | 0.193                       | 0.247    | 72        |
| GPRS850 (Hotspot) (1Dn2UP) | Front side  | 10            | 251 | 848.8       | 32.00                                        | 30.89                     | 29.12%  | 0.238                       | 0.307    | -         |
|                            | Back side   | 10            | 251 | 848.8       | 32.00                                        | 30.89                     | 29.12%  | 0.305                       | 0.394    | 73        |
|                            | Bottom side | 10            | 251 | 848.8       | 32.00                                        | 30.89                     | 29.12%  | 0.101                       | 0.130    | -         |
|                            | Left side   | 10            | 251 | 848.8       | 32.00                                        | 30.89                     | 29.12%  | 0.162                       | 0.209    | -         |

### GSM 1900

| Mode                        | Position    | Distance (mm) | CH  | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------------------|-------------|---------------|-----|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                             |             |               |     |             |                                              |                           |         | Measured                    | Reported |           |
| GSM1900 (Head)              | Re Cheek    | -             | 661 | 1880        | 30.50                                        | 29.72                     | 19.67%  | 0.038                       | 0.045    | -         |
|                             | Re Tilt     | -             | 661 | 1880        | 30.50                                        | 29.72                     | 19.67%  | 0.016                       | 0.019    | -         |
|                             | Le Cheek    | -             | 661 | 1880        | 30.50                                        | 29.72                     | 19.67%  | 0.062                       | 0.074    | 74        |
|                             | Le Tilt     | -             | 661 | 1880        | 30.50                                        | 29.72                     | 19.67%  | 0.018                       | 0.022    | -         |
| GSM1900 (Body-Worn)         | Front side  | 10            | 661 | 1880        | 30.50                                        | 29.72                     | 19.67%  | 0.101                       | 0.121    | -         |
|                             | Back side   | 10            | 661 | 1880        | 30.50                                        | 29.72                     | 19.67%  | 0.119                       | 0.142    | 75        |
| GPRS1900 (Hotspot) (1Dn2UP) | Front side  | 10            | 661 | 1880        | 29.50                                        | 28.74                     | 19.12%  | 0.133                       | 0.158    | -         |
|                             | Back side   | 10            | 661 | 1880        | 29.50                                        | 28.74                     | 19.12%  | 0.173                       | 0.206    | 76        |
|                             | Bottom side | 10            | 661 | 1880        | 29.50                                        | 28.74                     | 19.12%  | 0.072                       | 0.086    | -         |
|                             | Left side   | 10            | 661 | 1880        | 29.50                                        | 28.74                     | 19.12%  | 0.039                       | 0.046    | -         |

### WCDMA Band II

| Mode       | Position    | Distance (mm) | CH   | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------|-------------|---------------|------|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|            |             |               |      |             |                                              |                           |         | Measured                    | Reported |           |
| R99 (Head) | RE Cheek    | -             | 9262 | 1852.4      | 24                                           | 23.87                     | 3.04%   | 0.090                       | 0.093    | -         |
|            | RE Tilt     | -             | 9262 | 1852.4      | 24                                           | 23.87                     | 3.04%   | 0.046                       | 0.047    | -         |
|            | LE Cheek    | -             | 9262 | 1852.4      | 24                                           | 23.87                     | 3.04%   | 0.176                       | 0.181    | 77        |
|            | LE Tilt     | -             | 9262 | 1852.4      | 24                                           | 23.87                     | 3.04%   | 0.046                       | 0.047    | -         |
| Hotspot    | Front side  | 10            | 9262 | 1852.4      | 24                                           | 23.87                     | 3.04%   | 0.212                       | 0.218    | -         |
|            | Back side   | 10            | 9262 | 1852.4      | 24                                           | 23.87                     | 3.04%   | 0.271                       | 0.279    | 78        |
|            | Bottom side | 10            | 9262 | 1852.4      | 24                                           | 23.87                     | 3.04%   | 0.122                       | 0.126    | -         |
|            | Left side   | 10            | 9262 | 1852.4      | 24                                           | 23.87                     | 3.04%   | 0.092                       | 0.095    | -         |

### WCDMA Band IV

| Mode       | Position    | Distance (mm) | CH   | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------|-------------|---------------|------|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|            |             |               |      |             |                                              |                           |         | Measured                    | Reported |           |
| R99 (Head) | RE Cheek    | -             | 1412 | 1732.4      | 24                                           | 23.88                     | 2.80%   | 0.054                       | 0.056    | -         |
|            | RE Tilt     | -             | 1412 | 1732.4      | 24                                           | 23.88                     | 2.80%   | 0.024                       | 0.025    | -         |
|            | LE Cheek    | -             | 1412 | 1732.4      | 24                                           | 23.88                     | 2.80%   | 0.191                       | 0.196    | 79        |
|            | LE Tilt     | -             | 1412 | 1732.4      | 24                                           | 23.88                     | 2.80%   | 0.028                       | 0.029    | -         |
| Hotspot    | Front side  | 10            | 1412 | 1732.4      | 24                                           | 23.88                     | 2.80%   | 0.221                       | 0.227    | -         |
|            | Back side   | 10            | 1412 | 1732.4      | 24                                           | 23.88                     | 2.80%   | 0.282                       | 0.290    | 80        |
|            | Bottom side | 10            | 1412 | 1732.4      | 24                                           | 23.88                     | 2.80%   | 0.132                       | 0.136    | -         |
|            | Left side   | 10            | 1412 | 1732.4      | 24                                           | 23.88                     | 2.80%   | 0.099                       | 0.102    | -         |

### WCDMA Band V

| Mode       | Position    | Distance (mm) | CH   | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------|-------------|---------------|------|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|            |             |               |      |             |                                              |                           |         | Measured                    | Reported |           |
| R99 (Head) | RE Cheek    | -             | 4183 | 836.6       | 24                                           | 23.44                     | 13.76%  | 0.113                       | 0.129    | -         |
|            | RE Tilt     | -             | 4183 | 836.6       | 24                                           | 23.44                     | 13.76%  | 0.052                       | 0.059    | -         |
|            | LE Cheek    | -             | 4183 | 836.6       | 24                                           | 23.44                     | 13.76%  | 0.151                       | 0.172    | 81        |
|            | LE Tilt     | -             | 4183 | 836.6       | 24                                           | 23.44                     | 13.76%  | 0.077                       | 0.088    | -         |
| Hotspot    | Front side  | 10            | 4183 | 836.6       | 24                                           | 23.44                     | 13.76%  | 0.213                       | 0.242    | -         |
|            | Back side   | 10            | 4183 | 836.6       | 24                                           | 23.44                     | 13.76%  | 0.238                       | 0.271    | 82        |
|            | Bottom side | 10            | 4183 | 836.6       | 24                                           | 23.44                     | 13.76%  | 0.078                       | 0.089    | -         |
|            | Left side   | 10            | 4183 | 836.6       | 24                                           | 23.44                     | 13.76%  | 0.149                       | 0.170    | -         |

## LTE FDD Band 2

| Mode                 | Bandwidth (MHz) | Modulation | RB Size | RB start | Position    | Distance (mm) | CH    | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|----------------------|-----------------|------------|---------|----------|-------------|---------------|-------|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                      |                 |            |         |          |             |               |       |             |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 2 (Head)    | 20MHz           | QPSK       | 1 RB    | 50       | RE Cheek    | -             | 18700 | 1860        | 23.5                                         | 22.99                     | 12.46%  | 0.074                       | 0.083    | -         |
|                      |                 |            |         |          | RE Tilt     | -             | 18700 | 1860        | 23.5                                         | 22.99                     | 12.46%  | 0.033                       | 0.037    | -         |
|                      |                 |            |         |          | LE Cheek    | -             | 18700 | 1860        | 23.5                                         | 22.99                     | 12.46%  | 0.156                       | 0.175    | 83        |
|                      |                 |            |         |          | LE Tilt     | -             | 18700 | 1860        | 23.5                                         | 22.99                     | 12.46%  | 0.039                       | 0.044    | -         |
|                      |                 |            | 50 RB   | 0        | RE Cheek    | -             | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.064                       | 0.072    | -         |
|                      |                 |            |         |          | RE Tilt     | -             | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.027                       | 0.030    | -         |
|                      |                 |            |         |          | LE Cheek    | -             | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.131                       | 0.147    | -         |
|                      |                 |            |         |          | LE Tilt     | -             | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.034                       | 0.038    | -         |
|                      |                 |            | 100 RB  |          | RE Cheek    | -             | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.064                       | 0.072    | -         |
|                      |                 |            |         |          | RE Tilt     | -             | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.027                       | 0.030    | -         |
|                      |                 |            |         |          | LE Cheek    | -             | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.13                        | 0.146    | -         |
|                      |                 |            |         |          | LE Tilt     | -             | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.032                       | 0.036    | -         |
| LTE Band 2 (Hotspot) | 20MHz           | QPSK       | 1 RB    | 50       | Front side  | 10            | 18700 | 1860        | 23.5                                         | 22.99                     | 12.46%  | 0.197                       | 0.222    | -         |
|                      |                 |            |         |          | Back side   | 10            | 18700 | 1860        | 23.5                                         | 22.99                     | 12.46%  | 0.265                       | 0.298    | 84        |
|                      |                 |            |         |          | Bottom side | 10            | 18700 | 1860        | 23.5                                         | 22.99                     | 12.46%  | 0.102                       | 0.115    | -         |
|                      |                 |            |         |          | Left side   | 10            | 18700 | 1860        | 23.5                                         | 22.99                     | 12.46%  | 0.087                       | 0.098    | -         |
|                      |                 |            | 50 RB   | 0        | Front side  | 10            | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.178                       | 0.200    | -         |
|                      |                 |            |         |          | Back side   | 10            | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.221                       | 0.249    | -         |
|                      |                 |            |         |          | Bottom side | 10            | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.077                       | 0.087    | -         |
|                      |                 |            |         |          | Left side   | 10            | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.049                       | 0.055    | -         |
|                      |                 |            | 100 RB  |          | Front side  | 10            | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.178                       | 0.200    | -         |
|                      |                 |            |         |          | Back side   | 10            | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.22                        | 0.247    | -         |
|                      |                 |            |         |          | Bottom side | 10            | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.075                       | 0.084    | -         |
|                      |                 |            |         |          | Left side   | 10            | 18900 | 1880        | 22.5                                         | 21.99                     | 12.46%  | 0.049                       | 0.055    | -         |

## LTE FDD Band 4

| Mode                 | Bandwidth (MHz) | Modulation | RB Size | RB start | Position    | Distance (mm) | CH    | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|----------------------|-----------------|------------|---------|----------|-------------|---------------|-------|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                      |                 |            |         |          |             |               |       |             |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 4 (Head)    | 20MHz           | QPSK       | 1 RB    | 0        | RE Cheek    | -             | 20300 | 1745        | 23.5                                         | 22.98                     | 12.72%  | 0.081                       | 0.091    | -         |
|                      |                 |            |         |          | RE Tilt     | -             | 20300 | 1745        | 23.5                                         | 22.98                     | 12.72%  | 0.037                       | 0.042    | -         |
|                      |                 |            |         |          | LE Cheek    | -             | 20300 | 1745        | 23.5                                         | 22.98                     | 12.72%  | 0.174                       | 0.196    | 85        |
|                      |                 |            |         |          | LE Tilt     | -             | 20300 | 1745        | 23.5                                         | 22.98                     | 12.72%  | 0.024                       | 0.027    | -         |
|                      |                 |            | 50 RB   | 0        | RE Cheek    | -             | 20300 | 1745        | 22.5                                         | 21.94                     | 13.76%  | 0.070                       | 0.080    | -         |
|                      |                 |            |         |          | RE Tilt     | -             | 20300 | 1745        | 22.5                                         | 21.94                     | 13.76%  | 0.034                       | 0.039    | -         |
|                      |                 |            |         |          | LE Cheek    | -             | 20300 | 1745        | 22.5                                         | 21.94                     | 13.76%  | 0.154                       | 0.175    | -         |
|                      |                 |            |         |          | LE Tilt     | -             | 20300 | 1745        | 22.5                                         | 21.94                     | 13.76%  | 0.022                       | 0.025    | -         |
|                      |                 |            | 100 RB  |          | RE Cheek    | -             | 20050 | 1720        | 22.5                                         | 21.89                     | 15.08%  | 0.068                       | 0.078    | -         |
|                      |                 |            |         |          | RE Tilt     | -             | 20050 | 1720        | 22.5                                         | 21.89                     | 15.08%  | 0.031                       | 0.036    | -         |
|                      |                 |            |         |          | LE Cheek    | -             | 20050 | 1720        | 22.5                                         | 21.89                     | 15.08%  | 0.154                       | 0.177    | -         |
|                      |                 |            |         |          | LE Tilt     | -             | 20050 | 1720        | 22.5                                         | 21.89                     | 15.08%  | 0.022                       | 0.025    | -         |
| LTE Band 4 (Hotspot) | 20MHz           | QPSK       | 1 RB    | 0        | Front side  | 10            | 20300 | 1745        | 23.5                                         | 22.98                     | 12.72%  | 0.229                       | 0.258    | -         |
|                      |                 |            |         |          | Back side   | 10            | 20300 | 1745        | 23.5                                         | 22.98                     | 12.72%  | 0.266                       | 0.300    | 86        |
|                      |                 |            |         |          | Bottom side | 10            | 20300 | 1745        | 23.5                                         | 22.98                     | 12.72%  | 0.123                       | 0.139    | -         |
|                      |                 |            |         |          | Left side   | 10            | 20300 | 1745        | 23.5                                         | 22.98                     | 12.72%  | 0.111                       | 0.125    | -         |
|                      |                 |            | 50 RB   | 0        | Front side  | 10            | 20300 | 1745        | 22.5                                         | 21.94                     | 13.76%  | 0.212                       | 0.241    | -         |
|                      |                 |            |         |          | Back side   | 10            | 20300 | 1745        | 22.5                                         | 21.94                     | 13.76%  | 0.242                       | 0.275    | -         |
|                      |                 |            |         |          | Bottom side | 10            | 20300 | 1745        | 22.5                                         | 21.94                     | 13.76%  | 0.105                       | 0.119    | -         |
|                      |                 |            |         |          | Left side   | 10            | 20300 | 1745        | 22.5                                         | 21.94                     | 13.76%  | 0.098                       | 0.111    | -         |
|                      |                 |            | 100 RB  |          | Front side  | 10            | 20050 | 1720        | 22.5                                         | 21.89                     | 15.08%  | 0.211                       | 0.243    | -         |
|                      |                 |            |         |          | Back side   | 10            | 20050 | 1720        | 22.5                                         | 21.89                     | 15.08%  | 0.239                       | 0.275    | -         |
|                      |                 |            |         |          | Bottom side | 10            | 20050 | 1720        | 22.5                                         | 21.89                     | 15.08%  | 0.104                       | 0.120    | -         |
|                      |                 |            |         |          | Left side   | 10            | 20050 | 1720        | 22.5                                         | 21.89                     | 15.08%  | 0.095                       | 0.109    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

## LTE FDD Band 5

| Mode                 | Bandwidth (MHz) | Modulation | RB Size | RB start | Position    | Distance (mm) | CH    | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|----------------------|-----------------|------------|---------|----------|-------------|---------------|-------|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                      |                 |            |         |          |             |               |       |             |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 5 (Head)    | 10MHz           | QPSK       | 1 RB    | 25       | RE Cheek    | -             | 20600 | 844         | 23.5                                         | 22.97                     | 12.98%  | 0.102                       | 0.115    | -         |
|                      |                 |            |         |          | RE Tilt     | -             | 20600 | 844         | 23.5                                         | 22.97                     | 12.98%  | 0.042                       | 0.047    | -         |
|                      |                 |            |         |          | LE Cheek    | -             | 20600 | 844         | 23.5                                         | 22.97                     | 12.98%  | 0.116                       | 0.131    | 87        |
|                      |                 |            |         |          | LE Tilt     | -             | 20600 | 844         | 23.5                                         | 22.97                     | 12.98%  | 0.056                       | 0.063    | -         |
|                      |                 |            | 25 RB   | 0        | RE Cheek    | -             | 20600 | 844         | 22.5                                         | 21.86                     | 15.88%  | 0.091                       | 0.105    | -         |
|                      |                 |            |         |          | RE Tilt     | -             | 20600 | 844         | 22.5                                         | 21.86                     | 15.88%  | 0.035                       | 0.041    | -         |
|                      |                 |            |         |          | LE Cheek    | -             | 20600 | 844         | 22.5                                         | 21.86                     | 15.88%  | 0.101                       | 0.117    | -         |
|                      |                 |            |         |          | LE Tilt     | -             | 20600 | 844         | 22.5                                         | 21.86                     | 15.88%  | 0.049                       | 0.057    | -         |
|                      |                 |            | 50 RB   |          | RE Cheek    | -             | 20600 | 844         | 22.5                                         | 21.88                     | 15.35%  | 0.092                       | 0.106    | -         |
|                      |                 |            |         |          | RE Tilt     | -             | 20600 | 844         | 22.5                                         | 21.88                     | 15.35%  | 0.035                       | 0.040    | -         |
|                      |                 |            |         |          | LE Cheek    | -             | 20600 | 844         | 22.5                                         | 21.88                     | 15.35%  | 0.104                       | 0.120    | -         |
|                      |                 |            |         |          | LE Tilt     | -             | 20600 | 844         | 22.5                                         | 21.88                     | 15.35%  | 0.051                       | 0.059    | -         |
| LTE Band 5 (Hotspot) | 10MHz           | QPSK       | 1 RB    | 25       | Front side  | 10            | 20600 | 844         | 23.5                                         | 22.97                     | 12.98%  | 0.189                       | 0.214    | -         |
|                      |                 |            |         |          | Back side   | 10            | 20600 | 844         | 23.5                                         | 22.97                     | 12.98%  | 0.209                       | 0.236    | 88        |
|                      |                 |            |         |          | Bottom side | 10            | 20600 | 844         | 23.5                                         | 22.97                     | 12.98%  | 0.131                       | 0.148    | -         |
|                      |                 |            |         |          | Left side   | 10            | 20600 | 844         | 23.5                                         | 22.97                     | 12.98%  | 0.141                       | 0.159    | -         |
|                      |                 |            | 25 RB   | 0        | Front side  | 10            | 20600 | 844         | 22.5                                         | 21.86                     | 15.88%  | 0.172                       | 0.199    | -         |
|                      |                 |            |         |          | Back side   | 10            | 20600 | 844         | 22.5                                         | 21.86                     | 15.88%  | 0.182                       | 0.211    | -         |
|                      |                 |            |         |          | Bottom side | 10            | 20600 | 844         | 22.5                                         | 21.86                     | 15.88%  | 0.119                       | 0.138    | -         |
|                      |                 |            |         |          | Left side   | 10            | 20600 | 844         | 22.5                                         | 21.86                     | 15.88%  | 0.127                       | 0.147    | -         |
|                      |                 |            | 50 RB   |          | Front side  | 10            | 20600 | 844         | 22.5                                         | 21.88                     | 15.35%  | 0.173                       | 0.200    | -         |
|                      |                 |            |         |          | Back side   | 10            | 20600 | 844         | 22.5                                         | 21.88                     | 15.35%  | 0.184                       | 0.212    | -         |
|                      |                 |            |         |          | Bottom side | 10            | 20600 | 844         | 22.5                                         | 21.88                     | 15.35%  | 0.12                        | 0.138    | -         |
|                      |                 |            |         |          | Left side   | 10            | 20600 | 844         | 22.5                                         | 21.88                     | 15.35%  | 0.129                       | 0.149    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

## LTE FDD Band 12

| Mode                  | Bandwidth (MHz) | Modulation | RB Size | RB start | Position    | Distance (mm) | CH    | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------------|-----------------|------------|---------|----------|-------------|---------------|-------|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                       |                 |            |         |          |             |               |       |             |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 12 (Head)    | 10MHz           | QPSK       | 1 RB    | 25       | RE Cheek    | -             | 23095 | 707.5       | 23.5                                         | 22.91                     | 14.55%  | 0.038                       | 0.044    | -         |
|                       |                 |            |         |          | RE Tilt     | -             | 23095 | 707.5       | 23.5                                         | 22.91                     | 14.55%  | 0.014                       | 0.016    | -         |
|                       |                 |            |         |          | LE Cheek    | -             | 23095 | 707.5       | 23.5                                         | 22.91                     | 14.55%  | 0.045                       | 0.052    | 89        |
|                       |                 |            |         |          | LE Tilt     | -             | 23095 | 707.5       | 23.5                                         | 22.91                     | 14.55%  | 0.028                       | 0.032    | -         |
|                       |                 |            | 25 RB   | 12       | RE Cheek    | -             | 23130 | 711         | 22.5                                         | 21.94                     | 13.76%  | 0.033                       | 0.038    | -         |
|                       |                 |            |         |          | RE Tilt     | -             | 23130 | 711         | 22.5                                         | 21.94                     | 13.76%  | 0.012                       | 0.014    | -         |
|                       |                 |            |         |          | LE Cheek    | -             | 23130 | 711         | 22.5                                         | 21.94                     | 13.76%  | 0.040                       | 0.046    | -         |
|                       |                 |            |         |          | LE Tilt     | -             | 23130 | 711         | 22.5                                         | 21.94                     | 13.76%  | 0.024                       | 0.027    | -         |
|                       |                 |            | 50 RB   |          | RE Cheek    | -             | 23130 | 711         | 22.5                                         | 21.89                     | 15.08%  | 0.031                       | 0.036    | -         |
|                       |                 |            |         |          | RE Tilt     | -             | 23130 | 711         | 22.5                                         | 21.89                     | 15.08%  | 0.012                       | 0.014    | -         |
|                       |                 |            |         |          | LE Cheek    | -             | 23130 | 711         | 22.5                                         | 21.89                     | 15.08%  | 0.039                       | 0.045    | -         |
|                       |                 |            |         |          | LE Tilt     | -             | 23130 | 711         | 22.5                                         | 21.89                     | 15.08%  | 0.022                       | 0.025    | -         |
| LTE Band 12 (Hotspot) | 10MHz           | QPSK       | 1 RB    | 25       | Front side  | 10            | 23095 | 707.5       | 23.5                                         | 22.91                     | 14.55%  | 0.108                       | 0.124    | -         |
|                       |                 |            |         |          | Back side   | 10            | 23095 | 707.5       | 23.5                                         | 22.91                     | 14.55%  | 0.144                       | 0.165    | 90        |
|                       |                 |            |         |          | Bottom side | 10            | 23095 | 707.5       | 23.5                                         | 22.91                     | 14.55%  | 0.039                       | 0.045    | -         |
|                       |                 |            |         |          | Left side   | 10            | 23095 | 707.5       | 23.5                                         | 22.91                     | 14.55%  | 0.093                       | 0.107    | -         |
|                       |                 |            | 25 RB   | 12       | Front side  | 10            | 23130 | 711         | 22.5                                         | 21.94                     | 13.76%  | 0.099                       | 0.113    | -         |
|                       |                 |            |         |          | Back side   | 10            | 23130 | 711         | 22.5                                         | 21.94                     | 13.76%  | 0.125                       | 0.142    | -         |
|                       |                 |            |         |          | Bottom side | 10            | 23130 | 711         | 22.5                                         | 21.94                     | 13.76%  | 0.028                       | 0.032    | -         |
|                       |                 |            |         |          | Left side   | 10            | 23130 | 711         | 22.5                                         | 21.94                     | 13.76%  | 0.075                       | 0.085    | -         |
|                       |                 |            | 50 RB   |          | Front side  | 10            | 23130 | 711         | 22.5                                         | 21.89                     | 15.08%  | 0.094                       | 0.108    | -         |
|                       |                 |            |         |          | Back side   | 10            | 23130 | 711         | 22.5                                         | 21.89                     | 15.08%  | 0.124                       | 0.143    | -         |
|                       |                 |            |         |          | Bottom side | 10            | 23130 | 711         | 22.5                                         | 21.89                     | 15.08%  | 0.027                       | 0.031    | -         |
|                       |                 |            |         |          | Left side   | 10            | 23130 | 711         | 22.5                                         | 21.89                     | 15.08%  | 0.073                       | 0.084    | -         |

## WLAN802.11 b

| Mode            | Position   | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------|------------|---------------|----|-------------|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                 |            |               |    |             |                                              |                           |         | Measured                    | Reported |           |
| 802.11 b (Head) | RE Cheek   | -             | 11 | 2462        | 18                                           | 17.93                     | 1.62%   | 0.038                       | 0.039    | -         |
|                 | RE Tilt    | -             | 11 | 2462        | 18                                           | 17.93                     | 1.62%   | 0.017                       | 0.017    | -         |
|                 | LE Cheek   | -             | 11 | 2462        | 18                                           | 17.93                     | 1.62%   | 0.089                       | 0.090    | 91        |
|                 | LE Tilt    | -             | 11 | 2462        | 18                                           | 17.93                     | 1.62%   | 0.040                       | 0.041    | -         |
| Hotspot         | Front side | 10            | 11 | 2462        | 18                                           | 17.93                     | 1.62%   | 0.024                       | 0.024    | -         |
|                 | Back side  | 10            | 11 | 2462        | 18                                           | 17.93                     | 1.62%   | 0.118                       | 0.120    | 92        |
|                 | Top side   | 10            | 11 | 2462        | 18                                           | 17.93                     | 1.62%   | 0.008                       | 0.008    | -         |
|                 | Right side | 10            | 11 | 2462        | 18                                           | 17.93                     | 1.62%   | 0.082                       | 0.083    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

### 3. Simultaneous Transmission Analysis

#### Simultaneous Transmission Scenarios:

| Simultaneous Transmit Configurations | Head | Body-Worn | Hotspot |
|--------------------------------------|------|-----------|---------|
| GSM + 2.4GHz Wi-Fi                   | Yes  | Yes       | No      |
| GPRS + 2.4GHz Wi-Fi                  | No   | No        | Yes     |
| WCDMA + 2.4GHz Wi-Fi                 | Yes  | Yes       | Yes     |
| LTE + 2.4GHz Wi-Fi                   | Yes  | Yes       | Yes     |
| GSM + BT                             | No   | Yes       | No      |
| GPRS + BT                            | No   | No        | No      |
| WCDMA + BT                           | No   | Yes       | No      |
| LTE + BT                             | No   | Yes       | No      |

1. WiFi 2.4G and BT can't transmit simultaneously.

2. The device does not support VoLTE.

3. The device does not support DTM function. Body-worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.

4. Based on KDB447498D01 note 36, when SAR test exclusion is allowed by other published RF exposure KDB procedures, such as the 2.5 cm hotspot mode SAR test exclusion for an edge or surface, then estimated SAR is not required to determine simultaneous SAR test exclusion.

5. Held to ear configurations are not applicable to Bluetooth and therefore were not considered for simultaneous transmission.

### 3.1 Estimated SAR calculation

According to KDB447498 D01v05 – When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$\text{Estimated SAR} = \frac{\text{Max.tune up power(mW)}}{\text{Min.test separation distance(mm)}} \times \frac{\sqrt{f(\text{GHz})}}{7.5}$$

If the minimum test separation distance is < 5mm, a distance of 5mm is used for estimated SAR calculation. When the test separation distance is >50mm, the 0.4W/kg is used for SAR-1g.

| mode | position  | max. power (dB) | max. power (mW) | f(GHz) | distance (mm) | x   | Estimated SAR |
|------|-----------|-----------------|-----------------|--------|---------------|-----|---------------|
| BT   | body-worn | 8               | 6.31            | 2.48   | 10            | 7.5 | 0.132 (1g)    |

### 3.2 SPLSR evaluation and analysis

Per KDB447498D01, when the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR sum to peak location separation ratio(SPLSR).

The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion.

The ratio is determined by  $(\text{SAR1} + \text{SAR2})^{1.5}/R_i$ , rounded to two decimal digits, and must be  $\leq 0.04$  for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

SAR1 and SAR2 are the highest reported or estimated SAR for each antenna in the pair, and  $R_i$  is the separation distance between the peak SAR locations for the antenna pair in mm.

When standalone test exclusion applies, SAR is estimated; the peak location is assumed to be at the feed-point or geometric center of the antenna.

### Simultaneous Transmission Combination

| reported SAR WWAN and WLAN 2.4GHz, $\Sigma$ SAR evaluation |          |             |                     |       |              |
|------------------------------------------------------------|----------|-------------|---------------------|-------|--------------|
| Frequency band                                             | Position |             | reported SAR / W/kg |       | $\Sigma$ SAR |
|                                                            |          |             | WWAN                | WLAN  | <1.6W/kg     |
| GSM 850                                                    | Head     | Right cheek | 0.121               | 0.039 | 0.160        |
|                                                            |          | Right tilt  | 0.101               | 0.017 | 0.118        |
|                                                            |          | Left cheek  | 0.169               | 0.090 | 0.259        |
|                                                            |          | Left tilt   | 0.097               | 0.041 | 0.138        |
| GPRS 850 (1Dn2UP)                                          | Hotspot  | Front       | 0.307               | 0.024 | 0.331        |
|                                                            |          | Back        | 0.394               | 0.120 | 0.514        |
|                                                            |          | Top         | -                   | 0.008 | -            |
|                                                            |          | Bottom      | 0.130               | -     | -            |
|                                                            |          | Right       | -                   | 0.083 | -            |
|                                                            |          | Left        | 0.209               | -     | -            |
| GSM 1900                                                   | Head     | Right cheek | 0.045               | 0.039 | 0.084        |
|                                                            |          | Right tilt  | 0.019               | 0.017 | 0.036        |
|                                                            |          | Left cheek  | 0.074               | 0.090 | 0.164        |
|                                                            |          | Left tilt   | 0.022               | 0.041 | 0.063        |
| GPRS 1900 (1Dn2UP)                                         | Hotspot  | Front       | 0.158               | 0.024 | 0.182        |
|                                                            |          | Back        | 0.206               | 0.120 | 0.326        |
|                                                            |          | Top         | -                   | 0.008 | -            |
|                                                            |          | Bottom      | 0.086               | -     | -            |
|                                                            |          | Right       | -                   | 0.083 | -            |
|                                                            |          | Left        | 0.046               | -     | -            |
| WCDMA Band II                                              | Head     | Right cheek | 0.093               | 0.039 | 0.132        |
|                                                            |          | Right tilt  | 0.047               | 0.017 | 0.064        |
|                                                            |          | Left cheek  | 0.181               | 0.090 | 0.271        |
|                                                            |          | Left tilt   | 0.047               | 0.041 | 0.088        |
|                                                            | Hotspot  | Front       | 0.218               | 0.024 | 0.242        |
|                                                            |          | Back        | 0.279               | 0.120 | 0.399        |
|                                                            |          | Top         | -                   | 0.008 | -            |
|                                                            |          | Bottom      | 0.126               | -     | -            |
|                                                            |          | Right       | -                   | 0.083 | -            |
|                                                            |          | Left        | 0.095               | -     | -            |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

| reported SAR WWAN and WLAN 2.4GHz, $\Sigma$ SAR evaluation |          |             |                     |       |              |
|------------------------------------------------------------|----------|-------------|---------------------|-------|--------------|
| Frequency band                                             | Position |             | reported SAR / W/kg |       | $\Sigma$ SAR |
|                                                            |          |             | WWAN                | WLAN  | <1.6W/kg     |
| WCDMA Band IV                                              | Head     | Right cheek | 0.056               | 0.039 | 0.095        |
|                                                            |          | Right tilt  | 0.025               | 0.017 | 0.042        |
|                                                            |          | Left cheek  | 0.196               | 0.090 | 0.286        |
|                                                            |          | Left tilt   | 0.029               | 0.041 | 0.070        |
|                                                            | Hotspot  | Front       | 0.227               | 0.024 | 0.251        |
|                                                            |          | Back        | 0.290               | 0.120 | 0.410        |
|                                                            |          | Top         | -                   | 0.008 | -            |
|                                                            |          | Bottom      | 0.136               | -     | -            |
|                                                            |          | Right       | -                   | 0.083 | -            |
|                                                            |          | Left        | 0.102               | -     | -            |
| WCDMA Band V                                               | Head     | Right cheek | 0.129               | 0.039 | 0.168        |
|                                                            |          | Right tilt  | 0.059               | 0.017 | 0.076        |
|                                                            |          | Left cheek  | 0.172               | 0.090 | 0.262        |
|                                                            |          | Left tilt   | 0.088               | 0.041 | 0.129        |
|                                                            | Hotspot  | Front       | 0.242               | 0.024 | 0.266        |
|                                                            |          | Back        | 0.271               | 0.120 | 0.391        |
|                                                            |          | Top         | -                   | 0.008 | -            |
|                                                            |          | Bottom      | 0.089               | -     | -            |
|                                                            |          | Right       | -                   | 0.083 | -            |
|                                                            |          | Left        | 0.170               | -     | -            |
| LTE FDD Band 2                                             | Head     | Right cheek | 0.083               | 0.039 | 0.122        |
|                                                            |          | Right tilt  | 0.037               | 0.017 | 0.054        |
|                                                            |          | Left cheek  | 0.175               | 0.090 | 0.265        |
|                                                            |          | Left tilt   | 0.044               | 0.041 | 0.085        |
|                                                            | Hotspot  | Front       | 0.222               | 0.024 | 0.246        |
|                                                            |          | Back        | 0.298               | 0.120 | 0.418        |
|                                                            |          | Top         | -                   | 0.008 | -            |
|                                                            |          | Bottom      | 0.115               | -     | -            |
|                                                            |          | Right       | -                   | 0.083 | -            |
|                                                            |          | Left        | 0.098               | -     | -            |

| reported SAR WWAN and WLAN 2.4GHz, $\Sigma$ SAR evaluation |          |             |                     |       |              |
|------------------------------------------------------------|----------|-------------|---------------------|-------|--------------|
| Frequency band                                             | Position |             | reported SAR / W/kg |       | $\Sigma$ SAR |
|                                                            |          |             | WWAN                | WLAN  | <1.6W/kg     |
| LTE FDD Band 4                                             | Head     | Right cheek | 0.091               | 0.039 | 0.130        |
|                                                            |          | Right tilt  | 0.042               | 0.017 | 0.059        |
|                                                            |          | Left cheek  | 0.196               | 0.090 | 0.286        |
|                                                            |          | Left tilt   | 0.027               | 0.041 | 0.068        |
|                                                            | Hotspot  | Front       | 0.258               | 0.024 | 0.282        |
|                                                            |          | Back        | 0.300               | 0.120 | 0.420        |
|                                                            |          | Top         | -                   | 0.008 | -            |
|                                                            |          | Bottom      | 0.139               | -     | -            |
|                                                            |          | Right       | -                   | 0.083 | -            |
|                                                            |          | Left        | 0.125               | -     | -            |
| LTE FDD Band 5                                             | Head     | Right cheek | 0.115               | 0.039 | 0.154        |
|                                                            |          | Right tilt  | 0.047               | 0.017 | 0.064        |
|                                                            |          | Left cheek  | 0.131               | 0.090 | 0.221        |
|                                                            |          | Left tilt   | 0.063               | 0.041 | 0.104        |
|                                                            | Hotspot  | Front       | 0.214               | 0.024 | 0.238        |
|                                                            |          | Back        | 0.236               | 0.120 | 0.356        |
|                                                            |          | Top         | -                   | 0.008 | -            |
|                                                            |          | Bottom      | 0.148               | -     | -            |
|                                                            |          | Right       | -                   | 0.083 | -            |
|                                                            |          | Left        | 0.159               | -     | -            |
| LTE FDD Band 12                                            | Head     | Right cheek | 0.044               | 0.039 | 0.083        |
|                                                            |          | Right tilt  | 0.016               | 0.017 | 0.033        |
|                                                            |          | Left cheek  | 0.052               | 0.090 | 0.142        |
|                                                            |          | Left tilt   | 0.032               | 0.041 | 0.073        |
|                                                            | Hotspot  | Front       | 0.124               | 0.024 | 0.148        |
|                                                            |          | Back        | 0.165               | 0.120 | 0.285        |
|                                                            |          | Top         | -                   | 0.008 | -            |
|                                                            |          | Bottom      | 0.045               | -     | -            |
|                                                            |          | Right       | -                   | 0.083 | -            |
|                                                            |          | Left        | 0.107               | -     | -            |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

| reported SAR WWAN and Bluetooth, $\Sigma$ SAR evaluation |           |       |                     |           |              |
|----------------------------------------------------------|-----------|-------|---------------------|-----------|--------------|
| Frequency band                                           | Position  |       | reported SAR / W/kg |           | $\Sigma$ SAR |
|                                                          |           |       | WWAN                | Bluetooth | <1.6W/kg     |
| GSM 850                                                  | Body-Worn | Front | 0.240               | 0.132     | 0.372        |
|                                                          |           | Back  | 0.247               | 0.132     | 0.379        |
| GSM 1900                                                 | Body-Worn | Front | 0.121               | 0.132     | 0.253        |
|                                                          |           | Back  | 0.142               | 0.132     | 0.274        |
| WCDMA Band II                                            | Body-Worn | Front | 0.218               | 0.132     | 0.35         |
|                                                          |           | Back  | 0.279               | 0.132     | 0.411        |
| WCDMA Band IV                                            | Body-Worn | Front | 0.227               | 0.132     | 0.359        |
|                                                          |           | Back  | 0.290               | 0.132     | 0.422        |
| WCDMA Band V                                             | Body-Worn | Front | 0.242               | 0.132     | 0.374        |
|                                                          |           | Back  | 0.271               | 0.132     | 0.403        |
| LTE FDD Band 2                                           | Body-Worn | Front | 0.222               | 0.132     | 0.354        |
|                                                          |           | Back  | 0.298               | 0.132     | 0.43         |
| LTE FDD Band 4                                           | Body-Worn | Front | 0.258               | 0.132     | 0.39         |
|                                                          |           | Back  | 0.300               | 0.132     | 0.432        |
| LTE FDD Band 5                                           | Body-Worn | Front | 0.214               | 0.132     | 0.346        |
|                                                          |           | Back  | 0.236               | 0.132     | 0.368        |
| LTE FDD Band 12                                          | Body-Worn | Front | 0.124               | 0.132     | 0.256        |
|                                                          |           | Back  | 0.165               | 0.132     | 0.297        |

#### 4. Instruments List

| Manufacturer                    | Device                       | Type            | Serial number | Date of last calibration | Date of next calibration |
|---------------------------------|------------------------------|-----------------|---------------|--------------------------|--------------------------|
| Schmid & Partner Engineering AG | Dosimetric E-Field Probe     | EX3DV4          | 3831          | Jan.27,2016              | Jan.26,2017              |
| Schmid & Partner Engineering AG | System Validation Dipole     | D750V3          | 1015          | Aug.30,2016              | Aug.29,2017              |
|                                 |                              | D835V2          | 4d063         | Aug.25,2016              | Aug.24,2017              |
|                                 |                              | D1750V2         | 1008          | Aug.31,2016              | Aug.30,2017              |
|                                 |                              | D1900V2         | 5d027         | Apr.25,2016              | Apr.24,2017              |
|                                 |                              | D2450V2         | 727           | Apr.19,2016              | Apr.18,2017              |
| Schmid & Partner Engineering AG | Data acquisition Electronics | DAE4            | 547           | Mar.21,2016              | Mar.20,2017              |
| Schmid & Partner Engineering AG | Software                     | DASY 52 V52.8.8 | N/A           | Calibration not required | Calibration not required |
| Schmid & Partner Engineering AG | Phantom                      | SAM             | N/A           | Calibration not required | Calibration not required |
| Manufacturer                    | Device                       | Type            | Serial number | Date of last calibration | Date of next calibration |
| Agilent                         | Network Analyzer             | E5071C          | MY46107530    | Jan.07,2016              | Jan.06,2017              |
| Agilent                         | Dielectric Probe Kit         | 85070E          | MY44300677    | Calibration not required | Calibration not required |
| Agilent                         | Dual-directional coupler     | 772D            | MY52180142    | Apr.13,2016              | Apr.12,2017              |
|                                 |                              | 778D            | MY52180302    | Apr.13,2016              | Apr.12,2017              |
| Agilent                         | RF Signal Generator          | N5181A          | MY50145142    | Feb.19,2016              | Feb.18,2017              |
| Agilent                         | Power Meter                  | E4417A          | MY51410006    | Jan.07,2016              | Jan.06,2017              |



| Manufacturer | Device                   | Type     | Serial number | Date of last calibration | Date of next calibration |
|--------------|--------------------------|----------|---------------|--------------------------|--------------------------|
| Agilent      | Power Sensor             | E9301H   | MY51470001    | Jan.07,2016              | Jan.06,2017              |
|              |                          | E9301H   | MY51470002    | Jan.07,2016              | Jan.06,2017              |
| Anritsu      | Radio Communication Test | MT8820C  | 6201061049    | Apr.08,2016              | Apr.07,2017              |
| TECPEL       | Digital thermometer      | DTM-303A | TP130075      | Mar.30,2016              | Mar.29,2017              |

## 5. Measurements

Date: 2016/12/21

### GSM 850\_Head\_Le Cheek\_CH 251

Communication System: GSM; Frequency: 848.8 MHz, Duty Cycle: 1:8.3

Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.921$  S/m;  $\epsilon_r = 41.711$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Ambient temperature: 22.8° C ; Liquid temperature: 21.9° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(8.84, 8.84, 8.84); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.153 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.355 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.172 W/kg

**SAR(1 g) = 0.132 W/kg; SAR(10 g) = 0.097 W/kg**

Maximum value of SAR (measured) = 0.154 W/kg



0 dB = 0.154 W/kg = -8.12 dBW/kg

Date: 2016/12/28

### GSM 850\_Body-worn\_Back side\_CH 251\_10mm

Communication System: GSM; Frequency: 848.8 MHz, Duty Cycle: 1:8.3

Medium parameters used:  $f = 849$  MHz;  $\sigma = 1.001$  S/m;  $\epsilon_r = 55.797$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.9° C ; Liquid temperature: 22.0° C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.08, 9.08, 9.08); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x131x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 1.43 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.68 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.92 W/kg

**SAR(1 g) = 0.193 W/kg; SAR(10 g) = 0.112 W/kg**

Maximum value of SAR (measured) = 1.37 W/kg



0 dB = 1.37 W/kg = 1.37 dBW/kg

Date: 2016/12/28

### GPRS 850\_Hotspot\_Back side\_CH 251\_10mm

Communication System: GPRS (1Dn2Up); Frequency: 848.8 MHz, Duty Cycle: 1:4.15

Medium parameters used:  $f = 849$  MHz;  $\sigma = 1.001$  S/m;  $\epsilon_r = 55.797$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.9° C ; Liquid temperature: 22.0° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.08, 9.08, 9.08); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.415 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.15 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.481 W/kg

**SAR(1 g) = 0.305 W/kg; SAR(10 g) = 0.194 W/kg**

Maximum value of SAR (measured) = 0.393 W/kg



0 dB = 0.393 W/kg = -4.06 dBW/kg

Date: 2016/12/22

**GSM 1900\_Head\_Le Cheek\_CH 661**

Communication System: GSM; Frequency: 1880 MHz, Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.408$  S/m;  $\epsilon_r = 38.737$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Ambient temperature: 22.8° C ; Liquid temperature: 22.2° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.66, 7.66, 7.66); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.0678 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.476 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.0990 W/kg

**SAR(1 g) = 0.062 W/kg; SAR(10 g) = 0.039 W/kg**

Maximum value of SAR (measured) = 0.0750 W/kg



0 dB = 0.0750 W/kg = -11.25 dBW/kg

Date: 2016/12/29

### GSM 1900 Body-worn Back side\_CH 661\_10mm

Communication System: GSM; Frequency: 1880 MHz, Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.503$  S/m;  $\epsilon_r = 52.805$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.4° C ; Liquid temperature: 22.0° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.54, 7.54, 7.54); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.167 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.207 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.199 W/kg

**SAR(1 g) = 0.119 W/kg; SAR(10 g) = 0.070 W/kg**

Maximum value of SAR (measured) = 0.162 W/kg



0 dB = 0.162 W/kg = -7.91 dBW/kg

Date: 2016/12/29

### GPRS 1900\_Hotspot\_Back side\_CH 661\_10mm

Communication System: GPRS (1Dn2Up); Frequency: 1880 MHz, Duty Cycle: 1:4.15  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.503$  S/m;  $\epsilon_r = 52.805$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section  
Ambient temperature: 22.4° C ; Liquid temperature: 22.0° C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.54, 7.54, 7.54); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.239 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.236 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.292 W/kg

**SAR(1 g) = 0.173 W/kg; SAR(10 g) = 0.102 W/kg**

Maximum value of SAR (measured) = 0.235 W/kg



0 dB = 0.235 W/kg = -6.29 dBW/kg

Date: 2016/12/22

**WCDMA Band II\_Head\_Le Cheek\_CH 9262**

Communication System: WCDMA; Frequency: 1852.4 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1852.4$  MHz;  $\sigma = 1.388$  S/m;  $\epsilon_r = 38.876$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Ambient temperature: 22.8° C ; Liquid temperature: 22.2° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.66, 7.66, 7.66); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.203 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.459 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.278 W/kg

**SAR(1 g) = 0.176 W/kg; SAR(10 g) = 0.109 W/kg**

Maximum value of SAR (measured) = 0.218 W/kg



0 dB = 0.218 W/kg = -6.61 dBW/kg

Date: 2016/12/29

### WCDMA Band II\_Hotspot\_Back side\_CH 9262\_10mm

Communication System: WCDMA; Frequency: 1852.4 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1852.4$  MHz;  $\sigma = 1.472$  S/m;  $\epsilon_r = 52.894$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.4° C ; Liquid temperature: 22.0° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.54, 7.54, 7.54); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.375 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.679 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.450 W/kg

**SAR(1 g) = 0.271 W/kg; SAR(10 g) = 0.163 W/kg**

Maximum value of SAR (measured) = 0.365 W/kg



0 dB = 0.365 W/kg = -4.37 dBW/kg

Date: 2016/12/27

**WCDMA Band IV\_Head\_Le Cheek\_CH 1412**

Communication System: WCDMA; Frequency: 1732.4 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1732.4$  MHz;  $\sigma = 1.401$  S/m;  $\epsilon_r = 38.626$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Ambient temperature: 22.5° C ; Liquid temperature: 21.9° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.92, 7.92, 7.92); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.233 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.569 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.302 W/kg

**SAR(1 g) = 0.191 W/kg; SAR(10 g) = 0.119 W/kg**

Maximum value of SAR (measured) = 0.245 W/kg



0 dB = 0.245 W/kg = -6.11 dBW/kg

Date: 2016/12/27

### WCDMA Band IV\_Body\_Back side\_CH 1412\_10mm

Communication System: WCDMA; Frequency: 1732.4 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1732.4$  MHz;  $\sigma = 1.428$  S/m;  $\epsilon_r = 53.859$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.4° C ; Liquid temperature: 21.9° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.74, 7.74, 7.74); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.366 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.790 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.432 W/kg

**SAR(1 g) = 0.282 W/kg; SAR(10 g) = 0.181 W/kg**

Maximum value of SAR (measured) = 0.359 W/kg



0 dB = 0.359 W/kg = -4.45 dBW/kg

Date: 2016/12/21

## WCDMA Band V\_Head\_Le Cheek\_CH 4183

Communication System: WCDMA; Frequency: 836.6 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.911$  S/m;  $\epsilon_r = 41.836$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Ambient temperature: 22.8° C ; Liquid temperature: 21.9° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(8.84, 8.84, 8.84); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.177 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.273 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.198 W/kg

**SAR(1 g) = 0.151 W/kg; SAR(10 g) = 0.113 W/kg**

Maximum value of SAR (measured) = 0.176 W/kg



0 dB = 0.176 W/kg = -7.54 dBW/kg

Date: 2016/12/28

### WCDMA Band V\_Hotspot\_Back side\_CH 4183\_10mm

Communication System: WCDMA; Frequency: 836.6 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.984$  S/m;  $\epsilon_r = 55.858$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.9° C ; Liquid temperature: 22.0° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.08, 9.08, 9.08); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.318 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.31 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.369 W/kg

**SAR(1 g) = 0.238 W/kg; SAR(10 g) = 0.151 W/kg**

Maximum value of SAR (measured) = 0.306 W/kg



0 dB = 0.306 W/kg = -5.15 dBW/kg

Date: 2016/12/22

### LTE Band 2 (20MHz)\_Head\_Le Cheek\_CH 18700\_QPSK\_1-50

Communication System: LTE; Frequency: 1860 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1860$  MHz;  $\sigma = 1.393$  S/m;  $\epsilon_r = 38.807$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Ambient temperature: 22.8° C ; Liquid temperature: 22.2° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.66, 7.66, 7.66); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.189 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.976 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.250 W/kg

**SAR(1 g) = 0.156 W/kg; SAR(10 g) = 0.098 W/kg**

Maximum value of SAR (measured) = 0.193 W/kg



0 dB = 0.193 W/kg = -7.14 dBW/kg

Date: 2016/12/29

**LTE Band 2 (20MHz)\_Hotspot\_Back side\_CH 18700\_QPSK\_1-50\_10mm**

Communication System: LTE; Frequency: 1860 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1860$  MHz;  $\sigma = 1.481$  S/m;  $\epsilon_r = 52.884$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.4° C ; Liquid temperature: 22.0° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.54, 7.54, 7.54); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.372 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.718 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.437 W/kg

**SAR(1 g) = 0.265 W/kg; SAR(10 g) = 0.161 W/kg**

Maximum value of SAR (measured) = 0.354 W/kg



0 dB = 0.354 W/kg = -4.51 dBW/kg

Date: 2016/12/27

**LTE Band 4 (20MHz)\_Head\_Le Cheek\_CH 20300\_QPSK\_1-0**

Communication System: LTE; Frequency: 1745 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.415$  S/m;  $\epsilon_r = 38.605$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Ambient temperature: 22.5° C ; Liquid temperature: 21.9° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.92, 7.92, 7.92); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.209 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.316 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.277 W/kg

**SAR(1 g) = 0.174 W/kg; SAR(10 g) = 0.107 W/kg**

Maximum value of SAR (measured) = 0.224 W/kg



0 dB = 0.224 W/kg = -6.51 dBW/kg

Date: 2016/12/27

**LTE Band 4 (20MHz)\_Body\_Back side\_CH 20300\_QPSK\_1-0\_10mm**

Communication System: LTE; Frequency: 1745 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.441$  S/m;  $\epsilon_r = 53.845$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.4° C ; Liquid temperature: 21.9° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.74, 7.74, 7.74); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.345 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.389 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.412 W/kg

**SAR(1 g) = 0.266 W/kg; SAR(10 g) = 0.169 W/kg**

Maximum value of SAR (measured) = 0.340 W/kg



0 dB = 0.340 W/kg = -4.69 dBW/kg

Date: 2016/12/21

### LTE Band 5 (10MHz)\_Head\_Le Cheek\_CH 20600\_QPSK\_1-25

Communication System: LTE; Frequency: 844 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 844$  MHz;  $\sigma = 0.919$  S/m;  $\epsilon_r = 41.749$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Ambient temperature: 22.8° C ; Liquid temperature: 21.9° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(8.84, 8.84, 8.84); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.143 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.645 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.151 W/kg

**SAR(1 g) = 0.116 W/kg; SAR(10 g) = 0.086 W/kg**

Maximum value of SAR (measured) = 0.134 W/kg



0 dB = 0.134 W/kg = -8.72 dBW/kg

Date: 2016/12/28

# **LTE Band 5 (10MHz)\_Hotspot\_Back side\_CH 20600\_QPSK\_1-25\_10mm**

Communication System: LTE; Frequency: 844 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 844 \text{ MHz}$ ;  $\sigma = 0.998 \text{ S/m}$ ;  $\epsilon_r = 55.824$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature:  $22.9^\circ \text{ C}$  ; Liquid temperature:  $22.0^\circ \text{ C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.08, 9.08, 9.08); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid:  $dx=15 \text{ mm}$ ,  $dy=15 \text{ mm}$

Maximum value of SAR (interpolated) =  $0.289 \text{ W/kg}$



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $11.06 \text{ V/m}$ ; Power Drift =  $-0.08 \text{ dB}$

Peak SAR (extrapolated) =  $0.334 \text{ W/kg}$

**SAR(1 g) =  $0.209 \text{ W/kg}$ ; SAR(10 g) =  $0.130 \text{ W/kg}$**

Maximum value of SAR (measured) =  $0.273 \text{ W/kg}$



$0 \text{ dB} = 0.273 \text{ W/kg} = -5.63 \text{ dBW/kg}$

Date: 2016/12/23

# **LTE Band 12 (10MHz)\_Head\_Le Cheek\_CH 23095\_QPSK\_1-25**

Communication System: LTE; Frequency: 707.5 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 707.5$  MHz;  $\sigma = 0.892$  S/m;  $\epsilon_r = 42.56$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Ambient temperature: 22.6° C ; Liquid temperature: 22.0° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.38, 9.38, 9.38); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.0485 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.970 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.0580 W/kg

**SAR(1 g) = 0.045 W/kg; SAR(10 g) = 0.034 W/kg**

Maximum value of SAR (measured) = 0.0528 W/kg



0 dB = 0.0528 W/kg = -12.77 dBW/kg

Date: 2016/12/23

# **LTE Band 12 (10MHz)\_Hotspot\_Back side\_CH 23095\_QPSK\_1-25\_10mm**

Communication System: LTE; Frequency: 707.5 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 707.5$  MHz;  $\sigma = 0.925$  S/m;  $\epsilon_r = 57.001$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.6° C ; Liquid temperature: 22.2° C

## **DASY5 Configuration:**

- Probe: EX3DV4 - SN3831; ConvF(9.25, 9.25, 9.25); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.187 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.44 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.215 W/kg

**SAR(1 g) = 0.144 W/kg; SAR(10 g) = 0.092 W/kg**

Maximum value of SAR (measured) = 0.178 W/kg



0 dB = 0.178 W/kg = -7.50 dBW/kg

Date: 2016/12/30

**WLAN 802.11b\_Head\_Le Cheek\_CH 11**

Communication System: WLAN(2.45G); Frequency: 2462 MHz, Duty Cycle: 1:1  
Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.843$  S/m;  $\epsilon_r = 38.142$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section  
Ambient temperature: 22.5° C ; Liquid temperature: 22.1° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(6.92, 6.92, 6.92); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (91x151x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.154 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.021 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.181 W/kg

**SAR(1 g) = 0.089 W/kg; SAR(10 g) = 0.043 W/kg**

Maximum value of SAR (measured) = 0.138 W/kg



0 dB = 0.138 W/kg = -8.60 dBW/kg

Date: 2016/12/30

### WLAN 802.11b\_Hotspot\_Back side\_CH 11\_10mm

Communication System: WLAN(2.45G); Frequency: 2462 MHz, Duty Cycle: 1:1  
Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.017$  S/m;  $\epsilon_r = 52.525$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section  
Ambient temperature: 22.4° C ; Liquid temperature: 22.1° C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.05, 7.05, 7.05); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Head/Area Scan (91x151x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.177 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.242 W/kg

**SAR(1 g) = 0.118 W/kg; SAR(10 g) = 0.052 W/kg**

Maximum value of SAR (measured) = 0.182 W/kg



0 dB = 0.182 W/kg = -7.40 dBW/kg

## 6. SAR System Performance Verification

Date: 2016/12/23

### Dipole 750 MHz\_SN:1015\_Head

Communication System: CW; Frequency: 750 MHz, Duty Cycle: 1:1



Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.913 \text{ S/m}$ ;  $\epsilon_r = 42.345$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Ambient temperature:  $22.6^\circ \text{ C}$  ; Liquid temperature:  $22.0^\circ \text{ C}$ 

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.38, 9.38, 9.38); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (51x121x1):** Interpolated grid:  $dx=15 \text{ mm}$ ,  $dy=15 \text{ mm}$ Maximum value of SAR (interpolated) =  $2.62 \text{ W/kg}$ **Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  
 $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $56.68 \text{ V/m}$ ; Power Drift =  $-0.01 \text{ dB}$ Peak SAR (extrapolated) =  $3.09 \text{ W/kg}$ **SAR(1 g) =  $2.12 \text{ W/kg}$ ; SAR(10 g) =  $1.41 \text{ W/kg}$** Maximum value of SAR (measured) =  $2.65 \text{ W/kg}$  $0 \text{ dB} = 2.65 \text{ W/kg} = 4.23 \text{ dBW/kg}$

Date: 2016/12/23

**Dipole 750 MHz\_SN:1015\_Body**

Communication System: CW; Frequency: 750 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.946$  S/m;  $\epsilon_r = 56.872$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.6° C ; Liquid temperature: 22.2° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.25, 9.25, 9.25); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 2.65 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.62 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 3.20 W/kg

**SAR(1 g) = 2.18 W/kg; SAR(10 g) = 1.45 W/kg**

Maximum value of SAR (measured) = 2.66 W/kg



0 dB = 2.66 W/kg = 4.25 dBW/kg

Date: 2016/12/21

**Dipole 835 MHz\_SN:4d063\_Head**

Communication System: CW; Frequency: 835 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.909$  S/m;  $\epsilon_r = 41.936$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.8° C ; Liquid temperature: 21.9° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(8.84, 8.84, 8.84); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (51x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 2.95 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 58.06 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.85 W/kg

**SAR(1 g) = 2.34 W/kg; SAR(10 g) = 1.53 W/kg**

Maximum value of SAR (measured) = 3.11 W/kg



0 dB = 3.11 W/kg = 4.93 dBW/kg

Date: 2016/12/28

### Dipole 835 MHz\_SN:4d063\_Body

Communication System: CW; Frequency: 835 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.981$  S/m;  $\epsilon_r = 55.866$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.9° C ; Liquid temperature: 22.0° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.08, 9.08, 9.08); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (51x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 3.12 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.76 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.61 W/kg

**SAR(1 g) = 2.44 W/kg; SAR(10 g) = 1.62 W/kg**

Maximum value of SAR (measured) = 3.09 W/kg



0 dB = 3.09 W/kg = 4.90 dBW/kg

Date: 2016/12/27

**Dipole 1750 MHz\_SN:1008\_Head**

Communication System: CW; Frequency: 1750 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.421$  S/m;  $\epsilon_r = 38.593$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.5° C ; Liquid temperature: 21.9° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.92, 7.92, 7.92); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (51x101x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 13.0 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 91.75 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 16.3 W/kg

**SAR(1 g) = 9.25 W/kg; SAR(10 g) = 4.84 W/kg**

Maximum value of SAR (measured) = 12.7 W/kg



0 dB = 12.7 W/kg = 11.04 dBW/kg

Date: 2016/12/27

### Dipole 1750 MHz\_SN:1008\_Body

Communication System: CW; Frequency: 1750 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.445$  S/m;  $\epsilon_r = 53.832$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.4° C ; Liquid temperature: 21.9° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.74, 7.74, 7.74); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (51x101x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 14.6 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 98.92 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 18.8 W/kg

**SAR(1 g) = 9.39 W/kg; SAR(10 g) = 4.97 W/kg**

Maximum value of SAR (measured) = 14.4 W/kg



0 dB = 14.4 W/kg = 11.58 dBW/kg

Date: 2016/12/22

**Dipole 1900 MHz\_SN:5d027\_Head**

Communication System: CW; Frequency: 1900 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.417$  S/m;  $\epsilon_r = 38.677$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.8° C ; Liquid temperature: 22.2° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.66, 7.66, 7.66); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (51x91x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 14.2 W/kg



**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 92.85 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 17.4 W/kg

**SAR(1 g) = 9.48 W/kg; SAR(10 g) = 4.98 W/kg**

Maximum value of SAR (measured) = 13.6 W/kg



0 dB = 13.6 W/kg = 11.33 dBW/kg

Date: 2016/12/29

**Dipole 1900 MHz\_SN:5d027\_Body**

Communication System: CW; Frequency: 1900 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.522$  S/m;  $\epsilon_r = 52.726$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.4° C ; Liquid temperature: 22.0° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.54, 7.54, 7.54); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (41x101x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 14.4 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.13 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 18.2 W/kg

**SAR(1 g) = 9.82 W/kg; SAR(10 g) = 5.18 W/kg**

Maximum value of SAR (measured) = 14.3 W/kg



0 dB = 14.3 W/kg = 11.55 dBW/kg

Date: 2016/12/30

### Dipole 2450 MHz\_SN:727\_Head

Communication System: CW; Frequency: 2450 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.807$  S/m;  $\epsilon_r = 38.214$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.5° C ; Liquid temperature: 22.1° C

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(6.92, 6.92, 6.92); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (51x101x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 20.9 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 103.1 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 28.0 W/kg

**SAR(1 g) = 13.1 W/kg; SAR(10 g) = 5.96 W/kg**

Maximum value of SAR (measured) = 20.0 W/kg



0 dB = 20.0 W/kg = 13.01 dBW/kg

Date: 2016/12/30

**Dipole 2450 MHz\_SN:727\_Body**

Communication System: CW; Frequency: 2450 MHz, Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2.009$  S/m;  $\epsilon_r = 52.541$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient temperature: 22.4° C ; Liquid temperature: 22.1° C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.05, 7.05, 7.05); Calibrated: 2016/1/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn547; Calibrated: 2016/3/21
- Phantom: Head
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

**Configuration/Pin=250mW/Area Scan (51x91x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 23.1 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 99.48 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 27.0 W/kg

**SAR(1 g) = 12.7 W/kg; SAR(10 g) = 5.87 W/kg**

Maximum value of SAR (measured) = 20.0 W/kg



0 dB = 20.0 W/kg = 13.01 dBW/kg

## 7. DAE & Probe Calibration Certificate

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **SGS-TW (Auden)**

Certificate No: **DAE4-547\_Mar16**

### CALIBRATION CERTIFICATE

Object **DAE4 - SD 000 D04 BM - SN: 547**

Calibration procedure(s) **QA CAL-06.V29**  
Calibration procedure for the data acquisition electronics (DAE)


Calibration date: **March 21, 2016**

This calibration certificate documents the traceability to national standards, which utilize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (MSTE critical for calibration)

| Primary Standards            | ID #               | Cal Date (Certificate No.) | Scheduled Calibration  |
|------------------------------|--------------------|----------------------------|------------------------|
| Kethley Multimeter Type 2001 | SN: 0810278        | 09-Sep-15 (No.17153)       | Sep-16                 |
| Secondary Standards          | ID #               | Check Date (in house)      | Scheduled Check        |
| Auto DAE Calibration Unit    | SE UWS 053 AA 1001 | 05-Jan-16 (in house check) | In house check: Jan-17 |
| Calibrator Box V2.1          | SE UMS 006 AA 1002 | 05-Jan-16 (in house check) | In house check: Jan-17 |

|                |                           |                               |                                                                                                    |
|----------------|---------------------------|-------------------------------|----------------------------------------------------------------------------------------------------|
| Calibrated by: | Name<br><b>H. Mayraz</b>  | Function<br><b>Technician</b> | Signature<br> |
| Approved by:   | Name<br><b>R. Bohnert</b> | Deputy Technical Manager      | Signature<br> |

Issued: March 21, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: **DAE4-547\_Mar16**

Page 1 of 1

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8604 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

## Glossary

**DAE** data acquisition electronics  
**Connector angle** information used in DASY system to align probe sensor X to the robot coordinate system.

## Methods Applied and Interpretation of Parameters

- **DC Voltage Measurement:** Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- **Connector angle:** The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
  - **DC Voltage Measurement Linearity:** Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
  - **Common mode sensitivity:** Influence of a positive or negative common mode voltage on the differential measurement.
  - **Channel separation:** Influence of a voltage on the neighbor channels not subject to an input voltage.
  - **AD Converter Values with inputs shorted:** Values on the internal AD converter corresponding to zero input voltage.
  - **Input Offset Measurement:** Output voltage and statistical results over a large number of zero voltage measurements.
  - **Input Offset Current:** Typical value for information; Maximum channel input offset current, not considering the input resistance.
  - **Input resistance:** Typical value for information; DAE input resistance at the connector, during internal auto-zeroing and during measurement.
  - **Low Battery Alarm Voltage:** Typical value for information. Below this voltage, a battery alarm signal is generated.
  - **Power consumption:** Typical value for information. Supply currents in various operating modes.



#### DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 $\mu$ V, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| Calibration Factors | X                         | Y                         | Z                         |
|---------------------|---------------------------|---------------------------|---------------------------|
| High Range          | 403.135 $\pm$ 0.02% (k=2) | 403.036 $\pm$ 0.02% (k=2) | 402.684 $\pm$ 0.02% (k=2) |
| Low Range           | 3.95305 $\pm$ 1.50% (k=2) | 3.90339 $\pm$ 1.50% (k=2) | 3.96094 $\pm$ 1.50% (k=2) |

#### Connector Angle

|                                           |                                     |
|-------------------------------------------|-------------------------------------|
| Connector Angle to be used in DASY system | 162.0 $^{\circ}$ $\pm$ 1 $^{\circ}$ |
|-------------------------------------------|-------------------------------------|

## Appendix (Additional assessments outside the scope of SCS0108)

### 1. DC Voltage Linearity

| High Range        | Reading ( $\mu\text{V}$ ) | Difference ( $\mu\text{V}$ ) | Error (%) |
|-------------------|---------------------------|------------------------------|-----------|
| Channel X + Input | 199994.21                 | 2.19                         | 0.00      |
| Channel X + Input | 20002.69                  | 2.01                         | 0.01      |
| Channel X - Input | -19996.82                 | 4.06                         | -0.02     |
| Channel Y + Input | 199993.69                 | 1.36                         | 0.00      |
| Channel Y + Input | 19998.39                  | -2.33                        | -0.01     |
| Channel Y - Input | -20002.28                 | -1.42                        | 0.01      |
| Channel Z + Input | 199992.57                 | 0.40                         | 0.00      |
| Channel Z + Input | 20001.18                  | 0.43                         | 0.00      |
| Channel Z - Input | -19999.63                 | 1.28                         | -0.01     |

| Low Range         | Reading ( $\mu\text{V}$ ) | Difference ( $\mu\text{V}$ ) | Error (%) |
|-------------------|---------------------------|------------------------------|-----------|
| Channel X + Input | 2000.74                   | 0.01                         | 0.00      |
| Channel X + Input | 200.98                    | -0.15                        | -0.08     |
| Channel X - Input | -198.85                   | -0.17                        | 0.09      |
| Channel Y + Input | 2000.55                   | -0.24                        | -0.01     |
| Channel Y + Input | 200.62                    | -0.63                        | -0.31     |
| Channel Y - Input | -199.16                   | -0.63                        | 0.32      |
| Channel Z + Input | 2000.92                   | 0.18                         | 0.01      |
| Channel Z + Input | 200.09                    | -1.21                        | -0.60     |
| Channel Z - Input | -199.88                   | -1.33                        | 0.67      |

### 2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

|           | Common mode Input Voltage (mV) | High Range Average Reading ( $\mu\text{V}$ ) | Low Range Average Reading ( $\mu\text{V}$ ) |
|-----------|--------------------------------|----------------------------------------------|---------------------------------------------|
| Channel X | 200                            | -3.77                                        | -5.74                                       |
|           | -200                           | 5.75                                         | 4.10                                        |
| Channel Y | 200                            | -0.86                                        | -1.19                                       |
|           | -200                           | -0.19                                        | -0.50                                       |
| Channel Z | 200                            | 5.38                                         | 5.39                                        |
|           | -200                           | -7.88                                        | -7.82                                       |

### 3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

|           | Input Voltage (mV) | Channel X ( $\mu\text{V}$ ) | Channel Y ( $\mu\text{V}$ ) | Channel Z ( $\mu\text{V}$ ) |
|-----------|--------------------|-----------------------------|-----------------------------|-----------------------------|
| Channel X | 200                | -                           | 3.23                        | -2.09                       |
| Channel Y | 200                | 9.86                        | -                           | 4.46                        |
| Channel Z | 200                | 4.46                        | 8.53                        | -                           |

#### 4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

|           | High Range (LSB) | Low Range (LSB) |
|-----------|------------------|-----------------|
| Channel X | 16360            | 14961           |
| Channel Y | 16477            | 16929           |
| Channel Z | 16075            | 16224           |

#### 5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10MΩ

|           | Average (μV) | min. Offset (μV) | max. Offset (μV) | Std. Deviation (μV) |
|-----------|--------------|------------------|------------------|---------------------|
| Channel X | 0.98         | 0.14             | 1.82             | 0.32                |
| Channel Y | -0.29        | -1.11            | 0.56             | 0.32                |
| Channel Z | -1.72        | -2.77            | -0.15            | 0.39                |

#### 6. Input Offset Current

Nominal input circuitry offset current on all channels: <25fA

#### 7. Input Resistance (Typical values for information)

|           | Zeroing (kOhm) | Measuring (MOhm) |
|-----------|----------------|------------------|
| Channel X | 200            | 200              |
| Channel Y | 200            | 200              |
| Channel Z | 200            | 200              |

#### 8. Low Battery Alarm Voltage (Typical values for information)

| Typical values | Alarm Level (VDC) |
|----------------|-------------------|
| Supply (+ Vcc) | +7.9              |
| Supply (- Vcc) | -7.6              |

#### 9. Power Consumption (Typical values for information)

| Typical values | Switched off (mA) | Stand by (mA) | Transmitting (mA) |
|----------------|-------------------|---------------|-------------------|
| Supply (+ Vcc) | +0.01             | +8            | +14               |
| Supply (- Vcc) | -0.01             | -8            | -9                |

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client: **SGS-TW (Auden)**

Certificate No: **EX3-3831 Jan16**

## CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3831**

Calibration procedure(s): **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6**  
Calibration procedure for dosimetric E-field probes

Calibration date: **January 27, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3) °C and humidity < 70%.

Calibration Equipment used (M&T critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | DB41293874      | 01-Apr-15 (No. 217-02128)         | Mar-16                 |
| Power sensor E4412A        | MY41499087      | 01-Apr-15 (No. 217-02128)         | Mar-16                 |
| Reference 3 dB Attenuator  | SN: S5054 (30)  | 01-Apr-15 (No. 217-02129)         | Mar-16                 |
| Reference 20 dB Attenuator | SN: S5277 (20a) | 01-Apr-15 (No. 217-02132)         | Mar-16                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 01-Apr-15 (No. 217-02133)         | Mar-16                 |
| Reference Probe ES3DV2     | SN: 3013        | 31-Dec-15 (No. ES3-3013_Dec15)    | Dec-16                 |
| DAE4                       | SN: 650         | 23-Dec-15 (No. DAE4-REC_Dec15)    | Dec-16                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8043C      | US3642U01700    | 4-Aug-15 (in house check Apr-15)  | in house check: Apr-16 |
| Network Analyzer HP 8753E  | US37390545      | 18-Oct-11 (in house check Oct-15) | in house check: Oct-16 |

|                          | Name           | Function              | Signature |
|--------------------------|----------------|-----------------------|-----------|
| Calibrated by:           | Jean Kacrali   | Laboratory Technician |           |
| Approved by:             | Krista Polovic | Technical Manager     |           |
| Issued: January 29, 2016 |                |                       |           |

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: EX3-3831 Jan16

Page 7 of 11

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates.

Accreditation No.: SCS 0108

## Glossary:

|                        |                                                                                                                                                   |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                    | tissue simulating liquid                                                                                                                          |
| $NORM_{x,y,z}$         | sensitivity in free space                                                                                                                         |
| $ConvF$                | sensitivity in TSL / $NORM_{x,y,z}$                                                                                                               |
| DCP                    | diode compression point                                                                                                                           |
| CF                     | crest factor (1/duty_cycle) of the RF signal                                                                                                      |
| A, B, C, D             | modulation dependent linearization parameters                                                                                                     |
| Polarization $\varphi$ | $\varphi$ rotation around probe axis                                                                                                              |
| Polarization $\theta$  | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle        | information used in DASY system to align probe sensor $\hat{x}$ to the robot coordinate system                                                    |

## Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 855664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Methods Applied and Interpretation of Parameters:

- $NORM_{x,y,z}$ : Assessed for E-field polarization  $\theta = 0$  ( $f < 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide).  $NORM_{x,y,z}$  are only intermediate values, i.e., the uncertainties of  $NORM_{x,y,z}$  does not affect the  $E^2$  field uncertainty inside TSL (see below  $ConvF$ ).
- $NORM(f)_{x,y,z} = NORM_{x,y,z} \cdot \text{frequency\_response}$  (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of  $ConvF$ .
- $DCP_{x,y,z}$ : DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- $A_{x,y,z}$ ,  $B_{x,y,z}$ ,  $C_{x,y,z}$ ,  $D_{x,y,z}$ ,  $VR_{x,y,z}$ : A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- $ConvF$  and Boundary Effect Parameters: Assessed in flat phantom using E-field for Temperature Transfer Standard for  $f < 800$  MHz and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to  $NORM_{x,y,z} \cdot ConvF$  whereby the uncertainty corresponds to that given for  $ConvF$ . A frequency dependent  $ConvF$  is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical Isotropy (3D deviation from isotropy): In a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the  $NORM_{x,y,z}$  (no uncertainty required).



EX3DV4 – SN:3831

January 27, 2016

# Probe EX3DV4

## SN:3831

Manufactured: September 6, 2011  
Calibrated: January 27, 2016

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

EX3DV4-SN:3831

January 27, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3831

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|-----------------------------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.45     | 0.42     | 0.43     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                                     | 100.7    | 102.6    | 99.9     |               |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>C</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 153.7    | $\pm 3.3 \%$              |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 139.5    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 143.5    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter; uncertainty not required.

<sup>C</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4- SN:3831

January 27, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3831

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>f</sup> | Conductivity (Sim) <sup>e</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>g</sup> | Depth <sup>h</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 750                  | 41.9                               | 0.89                            | 9.38    | 9.38    | 9.38    | 0.23               | 1.35                    | ± 12.0 %  |
| 835                  | 41.5                               | 0.90                            | 8.84    | 8.84    | 8.84    | 0.19               | 1.62                    | ± 12.0 %  |
| 900                  | 41.5                               | 0.97                            | 8.77    | 8.77    | 8.77    | 0.20               | 1.51                    | ± 12.0 %  |
| 1450                 | 40.5                               | 1.20                            | 8.17    | 8.17    | 8.17    | 0.28               | 0.97                    | ± 12.0 %  |
| 1750                 | 40.1                               | 1.37                            | 7.92    | 7.92    | 7.92    | 0.41               | 0.80                    | ± 12.0 %  |
| 1900                 | 40.0                               | 1.40                            | 7.66    | 7.66    | 7.66    | 0.37               | 0.80                    | ± 12.0 %  |
| 2000                 | 40.0                               | 1.40                            | 7.61    | 7.61    | 7.61    | 0.32               | 0.80                    | ± 12.0 %  |
| 2300                 | 39.5                               | 1.67                            | 7.33    | 7.33    | 7.33    | 0.31               | 0.96                    | ± 12.0 %  |
| 2450                 | 39.2                               | 1.80                            | 6.92    | 6.92    | 6.92    | 0.27               | 1.09                    | ± 12.0 %  |
| 2600                 | 39.0                               | 1.96                            | 6.71    | 6.71    | 6.71    | 0.40               | 0.89                    | ± 12.0 %  |
| 3500                 | 37.9                               | 2.91                            | 6.41    | 6.41    | 6.41    | 0.42               | 1.03                    | ± 13.1 %  |
| 5200                 | 36.0                               | 4.68                            | 4.76    | 4.76    | 4.76    | 0.35               | 1.80                    | ± 13.1 %  |
| 5300                 | 35.9                               | 4.76                            | 4.46    | 4.46    | 4.46    | 0.40               | 1.80                    | ± 13.1 %  |
| 5600                 | 35.5                               | 5.07                            | 4.08    | 4.08    | 4.08    | 0.50               | 1.80                    | ± 13.1 %  |
| 5800                 | 35.3                               | 5.27                            | 4.10    | 4.10    | 4.10    | 0.50               | 1.80                    | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 60 and 70 MHz for ConvF assessments at 30, 64, 128, 160 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>f</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> Alpha/Depth are determined during calibration. SPESAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3831

January 27, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3831

### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>f</sup> | Conductivity (S/m) <sup>f</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>g</sup> | Depth (mm) <sup>g</sup> | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 750                  | 55.5                               | 0.96                            | 9.25    | 9.25    | 9.25    | 0.26               | 1.29                    | ± 12.0 %  |
| 835                  | 55.2                               | 0.97                            | 9.08    | 9.08    | 9.08    | 0.35               | 1.04                    | ± 12.0 %  |
| 900                  | 55.0                               | 1.05                            | 9.05    | 8.05    | 9.05    | 0.30               | 1.12                    | ± 12.0 %  |
| 1750                 | 53.4                               | 1.49                            | 7.74    | 7.74    | 7.74    | 0.27               | 1.01                    | ± 12.0 %  |
| 1900                 | 53.3                               | 1.52                            | 7.54    | 7.54    | 7.54    | 0.35               | 0.85                    | ± 12.0 %  |
| 2000                 | 53.3                               | 1.52                            | 7.62    | 7.62    | 7.62    | 0.37               | 0.84                    | ± 12.0 %  |
| 2300                 | 52.9                               | 1.81                            | 7.06    | 7.06    | 7.06    | 0.35               | 0.80                    | ± 12.0 %  |
| 2450                 | 52.7                               | 1.95                            | 7.05    | 7.05    | 7.05    | 0.34               | 0.80                    | ± 12.0 %  |
| 2600                 | 52.5                               | 2.16                            | 6.71    | 6.71    | 6.71    | 0.37               | 0.80                    | ± 12.0 %  |
| 5200                 | 49.0                               | 5.30                            | 4.07    | 4.07    | 4.07    | 0.50               | 1.90                    | ± 13.1 %  |
| 5300                 | 48.9                               | 5.42                            | 3.81    | 3.81    | 3.81    | 0.55               | 1.90                    | ± 13.1 %  |
| 5600                 | 48.5                               | 5.77                            | 3.47    | 3.47    | 3.47    | 0.55               | 1.90                    | ± 13.1 %  |
| 5800                 | 48.2                               | 6.00                            | 3.52    | 3.52    | 3.52    | 0.60               | 1.90                    | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.


<sup>f</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3831

January 27, 2016

### Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)




Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

EX3DV4- SN:3831



January 27, 2016

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$



EX3DV4- SN:3831


January 27, 2016

**Dynamic Range f(SAR<sub>head</sub>)**  
(TEM cell , f<sub>eval</sub> = 1900 MHz)Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)


EX3DV4- SN:3831

January 27, 2016

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid Error ( $\phi$ , $\theta$ ), f = 900 MHz



EX3DV4- SN:3831

January 27, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3831

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -20.3      |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |



## 8. Uncertainty Budget

Measurement Uncertainty evaluation template for DUT SAR test (0.3-3G)

| A                                                 | c                         | D               | e          |           | f       | g        | h=c * f / e             | i=c * g / e             | k           |
|---------------------------------------------------|---------------------------|-----------------|------------|-----------|---------|----------|-------------------------|-------------------------|-------------|
| Source of Uncertainty                             | Tolerance/<br>Uncertainty | Probabilit<br>y | Div        | Div Value | ci (1g) | ci (10g) | Standard<br>uncertainty | Standard<br>uncertainty | vi, or Veff |
| <b>Measurement system</b>                         |                           |                 |            |           |         |          |                         |                         |             |
| Probe calibration                                 | 6.00%                     | N               | 1          | 1         | 1       | 1        | 6.00%                   | 6.00%                   | ∞           |
| <b>Isotropy , Axial</b>                           | 3.50%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 2.02%                   | 2.02%                   | ∞           |
| <b>Isotropy,<br/>Hemispherical</b>                | 9.60%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 5.54%                   | 5.54%                   | ∞           |
| Modulation Response                               | 2.40%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 1.40%                   | 1.40%                   | ∞           |
| Boundary Effect                                   | 1.00%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 0.58%                   | 0.58%                   | ∞           |
| Linearity                                         | 4.70%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 2.71%                   | 2.71%                   | ∞           |
| Detection Limits                                  | 1.00%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 0.58%                   | 0.58%                   | ∞           |
| Readout Electronics                               | 0.30%                     | N               | 1          | 1         | 1       | 1        | 0.30%                   | 0.30%                   | ∞           |
| Response time                                     | 0.80%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 0.46%                   | 0.46%                   | ∞           |
| Integration Time                                  | 2.60%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 1.50%                   | 1.50%                   | ∞           |
| <b>Measurement drift<br/>(class A evaluation)</b> | 1.75%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 1.01%                   | 1.01%                   | ∞           |
| RF ambient condition -<br>noise                   | 3.00%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 1.73%                   | 1.73%                   | ∞           |
| RF ambient conditions -<br>reflections            | 3.00%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 1.73%                   | 1.73%                   | ∞           |
| Probe positioner<br>Mechanical restrictions       | 0.40%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 0.23%                   | 0.23%                   | ∞           |
| Probe Positioning with<br>respect to phantom      | 2.90%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 1.67%                   | 1.67%                   | ∞           |
| Post-processing                                   | 1.00%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 0.58%                   | 0.58%                   | ∞           |
| Max SAR Eval                                      | 1.00%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 0.58%                   | 0.58%                   | ∞           |
| <b>Test Sample related</b>                        |                           |                 |            |           |         |          |                         |                         |             |
| Test sample positioning                           | 2.90%                     | N               | 1          | 1         | 1       | 1        | 2.90%                   | 2.90%                   | M-1         |
| Device Holder<br>Uncertainty                      | 3.60%                     | N               | 1          | 1         | 1       | 1        | 3.60%                   | 3.60%                   | M-1         |
| Drift of output power                             | 5.00%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 2.89%                   | 2.89%                   | ∞           |
| <b>Phantom and Setup</b>                          |                           |                 |            |           |         |          |                         |                         |             |
| Phantom Uncertainty                               | 4.00%                     | R               | $\sqrt{3}$ | 1.732     | 1       | 1        | 2.31%                   | 2.31%                   | ∞           |
| Liquid permittivity<br>(mea.)                     | 3.71%                     | N               | 1          | 1         | 0.64    | 0.43     | 2.37%                   | 1.60%                   | M           |
| Liquid Conductivity<br>(mea.)                     | 3.65%                     | N               | 1          | 1         | 0.6     | 0.49     | 2.19%                   | 1.79%                   | M           |
| Combined standard<br>uncertainty                  |                           | RSS             |            |           |         |          | 11.87%                  | 11.66%                  |             |
| Expant uncertainty<br>(95% confidence             |                           |                 |            |           |         |          | 23.73%                  | 23.31%                  |             |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

## 9. Phantom Description

Schmid & Partner Engineering AG

**s p e a g**

Zeughausstrasse 43, 8004 Zurich, Switzerland  
Phone: +41 1 245 9700, Fax: +41 1 245 9773  
info@speag.com, http://www.speag.com

### Certificate of Conformity / First Article Inspection

|              |                                                              |
|--------------|--------------------------------------------------------------|
| Item         | SAM Twin Phantom V4.0                                        |
| Type No      | QD 000 P40 C                                                 |
| Series No    | TP-1150 and higher                                           |
| Manufacturer | SPEAG<br>Zeughausstrasse 43<br>CH-8004 Zurich<br>Switzerland |

#### Tests

The series production process used allows the limitation to test of first articles.  
Complete tests were made on the pre-series Type No. QD 000 P40 AA, Serial No. TP-1001 and on the series first article Type No. QD 000 P40 BA, Serial No. TP-1006. Certain parameters have been retested using further series items (called samples) or are tested at each item.

| Test                        | Requirement                                                                                                                                                                                      | Details                                                                  | Units tested                                |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|---------------------------------------------|
| Dimensions                  | Compliant with the geometry according to the CAD model.                                                                                                                                          | IT IS CAD File (*)                                                       | First article, Samples                      |
| Material thickness of shell | Compliant with the requirements according to the standards                                                                                                                                       | 2mm +/- 0.2mm in flat and specific areas of head section                 | First article, Samples, TP-1314 ff.         |
| Material thickness at ERP   | Compliant with the requirements according to the standards                                                                                                                                       | 6mm +/- 0.2mm at ERP                                                     | First article, A3 items                     |
| Material parameters         | Dielectric parameters for required frequencies                                                                                                                                                   | 300 MHz – 6 GHz;<br>Relative permittivity < 5;<br>Loss tangent < 0.05    | Material samples                            |
| Material resistivity        | The material has been tested to be compatible with the liquids defined in the standards if handled and cleaned according to the instructions. Observe technical Note for material compatibility. | DEGMRE based simulating liquids                                          | Pre-series, First article, Material samples |
| Sagging                     | Compliant with the requirements according to the standards. Sagging of the flat section when filled with tissue simulating liquid                                                                | < 1% typical < 0.6% if filled with 155mm of HSL900 and without DUT below | Prototypes, Sample testing                  |

#### Standards

- (1) CENELEC EN 50361
- (2) IEEE Std 1528-2003
- (3) IEC 62209 Part 1
- (4) FCC OET Bulletin 65, Supplement C, Edition 01-01

(\*) The IT IS CAD file is derived from [2] and is also within the tolerance requirements of the shapes of the other documents.

#### Conformity

Based on the sample tests above, we certify that this item is in compliance with the uncertainty requirements of SAR measurements specified in standards [1] to [4].

Date 07.07.2005

Signature / Stamp

**s p e a g**

Schmid & Partner Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland  
Phone: +41 1 245 9700 / Fax: +41 1 245 9773  
info@speag.com, http://www.speag.com

Doc No: SE1 - QD 000 P40 C - 3

Page 1 (1)

## 10. System Validation from Original Equipment Supplier

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
S Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client: **SGS-TW (Auden)**

Certificate No: **D750V3-1015\_Aug16**

### CALIBRATION CERTIFICATE

Object: **D750V3 - SN: 1015**

Calibration procedure(s): **QA CAL-05.v9**  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **August 30, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (MATE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104775         | 06-Apr-16 (No. 217-02288/02288)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 100245         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Reference 20 dB Attenuator  | SN: 5068 (20K)     | 06-Apr-16 (No. 217-02292)         | Apr-17                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 06-Apr-16 (No. 217-02295)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 7349           | 15-Jun-16 (No. EX3-7349_Jun16)    | Jun-17                 |
| DAE4                        | SN: 601            | 30-Oct-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: GB37460704     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: US37292783     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: MY41092817     | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06     | SN: 100372         | 15-Jun-16 (in house check Jun-16) | In house check: Oct-16 |
| Network Analyzer HP 8753E   | SN: US37390585     | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

|                |                            |                                        |                                                                                                  |
|----------------|----------------------------|----------------------------------------|--------------------------------------------------------------------------------------------------|
| Calibrated by: | Name: <b>Michael Weber</b> | Function: <b>Laboratory Technician</b> | Signature:  |
| Approved by:   | Name: <b>Katja Polovic</b> | Function: <b>Technical Manager</b>     | Signature:   |

Issued: August 30, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: **D750V3-1015\_Aug16**

Page 1 of 8

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zugheuerstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

### Glossary:

TSL tissue simulating liquid  
ConvF sensitivity in TSL / NORM x,y,z  
N/A not applicable or not measured

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.6.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Rat Phantom    |             |
| Distance Dipole Center - TSL | 15 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 750 MHz $\pm$ 1 MHz    |             |

### Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 41.9           | 0.89 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 42.4 $\pm$ 6 % | 0.91 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | —              | —                    |

### SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.11 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 8.32 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.36 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 5.45 W/kg $\pm$ 16.5 % (k=2) |

### Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 55.5           | 0.96 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 54.9 $\pm$ 6 % | 0.99 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | —              | —                    |

### SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 2.25 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 8.77 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 1.47 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 5.76 W/kg $\pm$ 16.5 % (k=2) |

#### Appendix (Additional assessments outside the scope of SCS 0108)

##### Antenna Parameters with Head TSL

|                                      |                              |
|--------------------------------------|------------------------------|
| Impedance, transformed to feed point | 53.1 $\Omega$ - 0.2 $\Omega$ |
| Return Loss                          | -30.5 dB                     |

##### Antenna Parameters with Body TSL

|                                      |                              |
|--------------------------------------|------------------------------|
| Impedance, transformed to feed point | 49.0 $\Omega$ - 2.8 $\Omega$ |
| Return Loss                          | -30.6 dB                     |

##### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.037 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of this dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

##### Additional EUT Data

|                 |                |
|-----------------|----------------|
| Manufactured by | SPEAG          |
| Manufactured on | March 22, 2010 |

## DASY5 Validation Report for Head TSL

Date: 30.08.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1015**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.91 \text{ S/m}$ ;  $\epsilon_r = 42.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.07, 10.07, 10.07); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 58.26 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.16 W/kg

SAR(1 g) = 2.11 W/kg; SAR(10 g) = 1.38 W/kg

Maximum value of SAR (measured) = 2.81 W/kg



0 dB = 2.81 W/kg = 4.49 dBW/kg

## DASY5 Validation Report for Body TSL

Date: 30.08.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1015**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.99$  S/m;  $\epsilon_r = 54.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.99, 9.99, 9.99); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.47 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.39 W/kg


**SAR(1 g) = 2.25 W/kg; SAR(10 g) = 1.47 W/kg**

Maximum value of SAR (measured) = 2.97 W/kg



0 dB = 2.97 W/kg = 4.73 dBW/kg

Impedance Measurement Plot for Body TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。  
 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **SGS-TW (Auden)**

Certificate No: D835V2-4d063\_Aug16

## CALIBRATION CERTIFICATE

Object **D835V2 - SN:4d063**

Calibration procedure(s) **QA-CAL-05.V9**  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date **August 25, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the stated laboratory facility, environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103241         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103240         | 06-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 06-Apr-16 (No. 217-02292)         | Apr-17                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 06-Apr-16 (No. 217-02295)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 7349           | 16-Jun-16 (No. EX3-7349_Jun16)    | Jun-17                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-801_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: 0637480704     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8461A       | SN: US57292783     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8461A       | SN: NY41000317     | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator F&S SMT-06     | SN: 100972         | 16-Jun-16 (In house check Jun-16) | In house check: Oct-16 |
| Network Analyzer HP-8753E   | SN: US57393585     | 16-Oct-15 (In house check Oct-15) | In house check: Oct-16 |

|                |               |                       |           |
|----------------|---------------|-----------------------|-----------|
|                | Name          | Function              | Signature |
| Calibrated by: | Michael Weber | Laboratory Technician |           |
| Approved by:   | Kolja Pokorny | Technical Manager     |           |

Issued: August 29, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D835V2-4d063\_Aug16

Page 1 of 8

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

### Glossary:

TSL tissue simulating liquid  
ConvF sensitivity in TSL / NORM x,y,z  
N/A not applicable or not measured

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1:

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 15 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 835 MHz $\pm$ 1 MHz    |             |

## Head TSL parameters

The following parameters and calculations were applied:

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 41.5           | 0.90 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 42.1 $\pm$ 6 % | 0.93 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | —              | —                    |

## SAR result with Head TSL

| SAR averaged over 1 cm <sup>2</sup> (1 g) of Head TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 2.40 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 9.40 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>2</sup> (10 g) of Head TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 1.54 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 6.05 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied:

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 55.2           | 0.97 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 54.7 $\pm$ 6 % | 1.01 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | —              | —                    |

## SAR result with Body TSL

| SAR averaged over 1 cm <sup>2</sup> (1 g) of Body TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 2.47 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 9.57 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>2</sup> (10 g) of Body TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 1.61 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 6.28 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $51.2 \Omega - 2.6 j\Omega$ |
| Return Loss                          | -30.3 dB                    |

### Antenna Parameters with Body TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $47.3 \Omega - 5.5 j\Omega$ |
| Return Loss                          | -24.0 dB                    |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.392 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | November 27, 2006 |

## DASY5 Validation Report for Head TSL

Date: 25.08.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d063**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.93 \text{ S/m}$ ;  $\epsilon_r = 42$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.72, 9.72, 9.72); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 100I
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 61.75 V/m; Power Drift = 0.03 dB


Peak SAR (extrapolated) = 3.65 W/kg

**SAR(1 g) = 2.4 W/kg; SAR(10 g) = 1.54 W/kg**

Maximum value of SAR (measured) = 3.24 W/kg



## Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 25.08.2016

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d063

Communication System: UTD 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 1.01 \text{ S/m}$ ;  $\epsilon_r = 54.7$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.73, 9.73, 9.73); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49A.A; Serial: 1001
- DASY52 52.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/ $P_{in}=250 \text{ mW}$ , $d=15\text{mm}$ /Zoom Scan (7x7x7)/Cube 0:

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 59.83 V/m; Power Drift = -0.00 dB


Peak SAR (extrapolated) = 3.63 W/kg

SAR(1 g) = 2.47 W/kg; SAR(10 g) = 1.61 W/kg

Maximum value of SAR (measured) = 3.25 W/kg



### Impedance Measurement Plot for Body TSL



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client: SGS-TW (Auden)

Certificate No: D1750V2-1008\_Aug16

## CALIBRATION CERTIFICATE

Object: D1750V2 - SN:1008

Calibration procedure(s): QA CAL-05.v9  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: August 31, 2016

The calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (MTE critical for calibration):

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 06-Apr-16 (No. 217-02292)         | Apr-17                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 06-Apr-16 (No. 217-02295)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 7349           | 15-Jun-16 (No. EX3-7349_Jun16)    | Jun-17                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: GB37480704     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8461A       | SN: US37292783     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: MY41042317     | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| RF generator R&S SMT-06     | SN: 100972         | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E   | SN: US37390586     | 16-Oct-11 (in house check Oct-15) | In house check: Oct-16 |

|                |                      |                                 |            |
|----------------|----------------------|---------------------------------|------------|
| Calibrated by: | Name: Johannes Kurka | Function: Laboratory Technician | Signature: |
| Approved by:   | Name: Kaija Pekovic  | Function: Technical Manager     | Signature: |

Issued: August 31, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D1750V2-1008\_Aug16

Page 1 of 8

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
S Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

## Glossary:

TSL tissue simulating liquid  
ConvF sensitivity in TSL / NORM x,y,z  
N/A not applicable or not measured

## Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 885664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Additional Documentation:

- DASY4/5 System Handbook

## Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 1750 MHz $\pm$ 1 MHz   |             |

### Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 40.1           | 1.37 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.3 $\pm$ 6 % | 1.37 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | —              | —                    |

### SAR result with Head TSL

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 9.28 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 37.2 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 4.90 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 19.6 W/kg $\pm$ 16.5 % (k=2) |

### Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 53.4           | 1.49 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 53.1 $\pm$ 6 % | 1.49 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | —              | —                    |

### SAR result with Body TSL

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 9.34 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 37.3 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 4.96 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 19.9 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.0 $\Omega$ - 0.2 j $\Omega$ |
| Return Loss                          | -40.1 dB                       |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 46.7 $\Omega$ - 0.5 j $\Omega$ |
| Return Loss                          | -28.5 dB                       |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.221 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |              |
|-----------------|--------------|
| Manufactured by | SPEAG        |
| Manufactured on | May 27, 2003 |

## DASY5 Validation Report for Head TSL

Date: 24.08.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN:1008**

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.37$  S/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.46, 8.46, 8.46); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 105.8 V/m; Power Drift = 0.03 dB


Peak SAR (extrapolated) = 17.2 W/kg

**SAR(1 g) = 9.28 W/kg; SAR(10 g) = 4.9 W/kg**

Maximum value of SAR (measured) = 14.3 W/kg



Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 31.08.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN:1008**

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 53.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.25, 8.25, 8.25); Calibrated: 15.06.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 100.8 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 16.4 W/kg

SAR(1 g) = 9.34 W/kg; SAR(10 g) = 4.98 W/kg

Maximum value of SAR (measured) = 13.9 W/kg



### Impedance Measurement Plot for Body TSL



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **SGS-TW (Auden)**

Certificate No: **D1900V2-5d027\_Apr16**

## CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d027**

Calibration procedure(s) **QA CAL-05.v9  
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date **April 25, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/C0289)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)         | Apr-17                 |
| Type-N mismatch combination | SN: 3047 2 / 06327 | 05-Apr-16 (No. 217-02295)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)    | Dec-16                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: GB37480704     | 07-Oct-15 (No. 217-02222)         | in house check: Oct-16 |
| Power sensor HP 8481A       | SN: US37292783     | 07-Oct-15 (No. 217-02222)         | in house check: Oct-16 |
| Power sensor HP 8481A       | SN: MY41092317     | 07-Oct-15 (No. 217-02223)         | in house check: Oct-16 |
| RF generator R&S SMT-06     | SN: 100872         | 15-Jun-15 (in house check Jun-15) | in house check: Oct-16 |
| Network Analyzer HP 8753E   | SN: US37390685     | 16-Oct-01 (in house check Oct-15) | in house check: Oct-16 |

|                |               |                       |           |
|----------------|---------------|-----------------------|-----------|
|                | Name          | Function              | Signature |
| Calibrated by: | Michael Weber | Laboratory Technician |           |
| Approved by:   | Kolja Pokovic | Technical Manager     |           |

Issued: April 25, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: **D1900V2-5d027\_Apr16**

Page 1 of 8

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

## Glossary:

TSL tissue simulating liquid  
ConvF sensitivity in TSL / NORM x,y,z  
N/A not applicable or not measured

## Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Additional Documentation:

- DASY4/5 System Handbook

## Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 1900 MHz $\pm$ 1 MHz   |             |

### Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 40.0           | 1.40 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.0 $\pm$ 6 % | 1.37 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 9.55 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 36.7 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.03 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 20.3 W/kg $\pm$ 16.5 % (k=2) |

### Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 53.3           | 1.52 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 52.9 $\pm$ 6 % | 1.49 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 9.83 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 39.7 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.21 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 21.0 W/kg $\pm$ 16.5 % (k=2) |

**Appendix (Additional assessments outside the scope of SCS 0108)****Antenna Parameters with Head TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.8 $\Omega$ + 4.4 j $\Omega$ |
| Return Loss                          | - 27.0 dB                      |

**Antenna Parameters with Body TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 46.5 $\Omega$ + 5.6 j $\Omega$ |
| Return Loss                          | - 23.3 dB                      |

**General Antenna Parameters and Design**

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.196 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

**Additional EUT Data**

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | December 17, 2002 |

## DASY5 Validation Report for Head TSL

Date: 25.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d027**

Communication System: UID 0 - C/W; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.37$  S/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.2, 8.2, 8.2); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.9 V/m; Power Drift = 0.02 dB


Peak SAR (extrapolated) = 17.2 W/kg

**SAR(1 g) = 9.55 W/kg; SAR(10 g) = 5.03 W/kg**

Maximum value of SAR (measured) = 14.3 W/kg



Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 25.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d027**

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.03, 8.03, 8.03); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.2 V/m; Power Drift = 0.02 dB


Peak SAR (extrapolated) = 17.2 W/kg

**SAR(1 g) = 9.83 W/kg; SAR(10 g) = 5.21 W/kg**

Maximum value of SAR (measured) = 14.7 W/kg



Impedance Measurement Plot for Body TSL



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



Schweizerischer Kalibrierdienst  
Service suisse d'étalonnage  
Servizio svizzero di taratura  
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client: **SGS-TW (Auden)**

Certificate No.: **D2450V2-727\_Apr16**

## CALIBRATION CERTIFICATE

Object: **D2450V2 - SN:727**

Calibration procedure(s): **QA CAL-05.V9**  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **April 19, 2016**

This calibration certificate documents the traceability to national standards, which realise the physical units of measurement (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $\approx 70\%$ .

Calibration Equipment used (M&T: critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Reference 20 dB Attenuator  | SN: 5038 (20k)     | 06-Apr-16 (No. 217-02292)         | Apr-17                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 06-Apr-16 (No. 217-02295)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)    | Dec-16                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: 0837480704     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: US37292793     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: MY41082317     | 07-Oct-15 (No. 217-02223)         | In house check: Oct-16 |
| P/F generator R&S SMT-06    | SN: 100972         | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E   | SN: US37390585     | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

|                |                                |                                    |                |
|----------------|--------------------------------|------------------------------------|----------------|
| Calibrated by: | Name:<br><b>Michael Weber</b>  | Function:<br>Laboratory Technician | Signature:<br> |
| Approved by:   | Name:<br><b>Kolja Pokorski</b> | Technical Manager                  |                |

Issued: April 20, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D2450V2-727\_Apr16

Page 1 of 8

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

## Glossary:

TSL tissue simulating liquid  
ConvF sensitivity in TSL / NORM x,y,z  
N/A not applicable or not measured

## Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 8 GHz"

## Additional Documentation:

- DASY4/5 System Handbook

## Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 2450 MHz $\pm$ 1 MHz   |             |

### Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 39.2           | 1.80 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.0 $\pm$ 6 % | 1.83 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 12.8 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 51.0 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.93 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 23.7 W/kg $\pm$ 16.5 % (k=2) |

### Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 52.7           | 1.95 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 52.7 $\pm$ 6 % | 1.98 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 12.5 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 49.6 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.86 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 23.3 W/kg $\pm$ 16.5 % (k=2) |

**Appendix (Additional assessments outside the scope of SCS 0108)****Antenna Parameters with Head TSL**

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $55.3 \Omega + 2.0 j\Omega$ |
| Return Loss                          | - 25.4 dB                   |

**Antenna Parameters with Body TSL**

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $52.1 \Omega + 4.8 j\Omega$ |
| Return Loss                          | - 25.9 dB                   |

**General Antenna Parameters and Design**

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.148 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

**Additional EUT Data**

|                 |                  |
|-----------------|------------------|
| Manufactured by | SPEAG            |
| Manufactured on | January 09, 2003 |

## DASY5 Validation Report for Head TSL

Date: 19.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 727**

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.83$  S/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvR(7.76, 7.76, 7.76); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 112.1 V/m; Power Drift = 0.05 dB


Peak SAR (extrapolated) = 25.7 W/kg

SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.93 W/kg

Maximum value of SAR (measured) = 20.8 W/kg



## Impedance Measurement Plot for Head TSL



**- End of 1<sup>st</sup> part of report -**