Application Document for FCC Part 15, Subpart C (Intentional Radiator) Class II Permissive change

Model Number: AR5BMB-44

Document Number: FCC 19-0274-0

FCC ID: ANO20040600BTL

August 17, 2004

EMC Advisory R&D Engineer

Toshiya Murota

Signature

IBM Japan, Ltd. EMC Engineering

LAB-S59

1623-14, Shimotsuruma,

Yamato-shi Kanagawa-ken 242-8502, Japan

Phone: +81-46-215-6574

Fax: +81-46-273-7420

E-Mail: murota@jp.ibm.com

EMC Engineering Manager / NVLAP signatory

Akihisa Sakurai

Signature

IBM Japan, Ltd. EMC Engineering

LAB-S59

1623-14, Shimotsuruma,

Yamato-shi Kanagawa-ken 242-8502, Japan

Phone: +81-46-215-2613

Fax: +81-46-273-7420

E-Mail: akihisa@jp.ibm.com

System Solution and Technology Manager
Hirohide Komiyama

Signature:

IBM Japan, Ltd.

Portable Systems

LAB-R75

1623-14, Shimotsuruma,

Yamato-shi Kanagawa-ken 242-8502, Japan

Phone: +81-46-215-2725

Portable Systems Director

Masaki Kobayashi

Signature:

JBM Japan, Ltd.

Portable Systems

AB-R70

1623-14, Shimotsuruma,

Yamato-shi Kanagawa-ken 242-8502, Japan

Phone: +81-46-215-3889

Yellow Sheet: No. EMB73

Outline of Submission

Document Number: FCC 19-0274-0

1. Objective

This is a certification compliance test report for **Class II permissive change** of the following LMA transmitter device pursuant to FCC Part 15 subpart C (Intentional Radiator).

• FCC ID : ANO20040600BTL

Model Number : AR5BMB-44

• Advertising Name : IBM 11a/b/g Wireless LAN Mini PCI Adapter II

• The last grant date : July/26/2004

There is no hardware nor electrical modification made to the applying modular transmitter itself, but the following new antenna systems (host PC devices) is to be added in this Class II change application.

- IBM ThinkPad **G40** Series
- IBM ThinkPad X30 Series
- IBM ThinkPad X40 Series

2. Product Description

The applying modular transmitter device is an OEM mini-PCI wireless LAN card supplied by Atheros Communications, Inc. The modular device complies with the following transmission modes.

- IEEE802.11a (5180MHz ~ 5320MHz band OFDM)
- IEEE802.11a (5745MHz ~ 5825MHz band OFDM)
- IEEE802.11b (2412MHz ~ 2462MHz band Direct Sequence Spread Spectrum)
- IEEE802.11g (2412MHz ~ 2462MHz band OFDM)

The 5180MHz-5320MHz band OFDM mode is subjected to the FCC 15 subpart E (U-NII device), and is to be certified with the separate application as **composite** device.

3. Installation of the applying transmitter

- ThinkPad X30, X40 Series: pre-installed by IBM. Also user installable option cards are provided.
- ThinkPad **G40** Series: pre-installed by IBM only due to the intricate location of mini-PCI card slot (Refer to the separate exhibit "Antenna_Info.pdf".)

The unique electrical connector (so called "Electronic Handshake" BIOS Lock) is employed for both applying modular device and host units to satisfy the FCC Part 15.203 or RSS-210 §5.5, and the FCC Part 15.407(d) or RSS 6.2.2 q1(i). This mechanism enables user to install the applying LMA transmitter to the specified hosts (IBM ThinkPad X30 and X40 Series).

The detail explanation of the unique coupling between the LMA transmitter and antenna systems is shown in the separate exhibit "Confidential_e-Handshake.pdf", however IBM would like to hold it in confidence to maintain the secure "unique operability" with the applying device and IBM antenna systems.

The Electronic Handshake BIOS Lock function is also effective for the user's maintenance in replacing a broken card with a spare part for X30 or X40 Series. As for G40 Series, IBM Service centers or dealers replace broken cards.

Document Number: FCC 19-0274-0

4. Co-located Transmitters

The applying LMA transmitter collocates with the following Bluetooth modules and transmits RF frequency simultaneously.

- FCC ID: ANO20020100MTN (IBM Integrated Bluetooth III with 56 Modem)

- FCC ID: PI4BT-IBM-PCII (Bluetooth PC Card II)

- FCC ID: PI4BT-ULTRA (Bluetooth UltraPort Module from IBM)

As for the RF safety evaluation, refer to the separate exhibit "RF_Exposure.pdf".

5. Related Submittal(s)/Grant(s)/Notes

During the applying modular device stops RF transmission, the host unit with full peripheral devices including the applying modular device is classified as an unintentional radiator, Digital Device under the FCC Part 15 Subpart B or the Industry Canada Class B Emission Compliance (ICES-003), and subject to DoC.

6. Submittal documents

•	Product Labeling	Yes	
•	LAM Qualification	omitted	(identical with the original filing)
•	Internal Photos	omitted	(ditto)
•	External Photos	omitted	(ditto)
•	Block Diagrams	omitted	(ditto)
•	Schematic Diagrams	omitted	(ditto)
•	Parts List	omitted	(ditto)
•	Circuitry Descriptions of LMA transmitter	omitted	(ditto)
•	Electronic Handshake BIOS Lock logic	Yes	
•	The new antenna system Info.	Yes	
•	Test Report with the new antenna systems	Yes	
•	Test Setup Photos	Yes	
•	RF Exposure evaluation for the new antennas	Yes	
•	IBM Web site concerning the grant condition	Yes	
•	Users Manual	Yes	