

Test by:

# **RF Exposure Report**

### For

Applicant Name:	Katmai Technology Limited
Address:	Flat 1201, Floor 12, HARVEST BUILDING 29-37, WING KUT ST CENTRAL, HONGKONG
EUT Name:	ELECTRIC FIREPLACE
Brand Name:	N/A
Model Number:	INF88W-3D
Series Model Number:	INF98W-3D, INF95W-3D, INF-50H, INF-60H, INF-72H, INF-88H, INF-95H, INF-98H

### **Issued By**

#### **Company Name:** BTF Testing Lab (Shenzhen) Co., Ltd. F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Address: China


Report Number: BTF240819R00103 Test Standards: 47 CFR Part 2 Subpart J Section 2.1091 FCC ID: 2A95UINF88W3D **Test Conclusion:** Pass Date of sample receipt: 2024-08-19 Test Date: 2024-08-20 to 2024-09-03 Date of Issue: 2024-09-04

Shenz Ssxx.guo/ Tester Prepared by: hris wu Chris Liu/Project engineer Ryan.CJ / EMC Manager

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.




Revision History				
Version	Issue Date	Revisions Content		
R_V0	2024-09-04	Original		
and the second second	10 A			
Note:	Once the revision has	Once the revision has been made, then previous versions reports are invalid.		





### **Table of Contents**

1.	Introd		4
	1.1	Identification of Testing Laboratory	4
	1.2	Identification of the Responsible Testing Location	4
	1.3	Laboratory Condition	
	1.4	Announcement	4
2.		uct Information	
	2.1	Application Information	5
	2.2	Manufacturer Information	5
	2.3	Factory Information	5
	2.4	General Description of Equipment under Test (EUT)	5
3.		JIREMENT	
	3.1	Assessment Result	6





### 1. Introduction

### 1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.		
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China		
Phone Number:	+86-0755-23146130		
Fax Number:	+86-0755-23146130		

### **1.2 Identification of the Responsible Testing Location**

Test Location:	BTF Testing Lab (Shenzhen) Co., Ltd.			
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China			
Description:	All measurement facilities used to collect the measurement data are located at F101,201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China			
FCC Registration Number:	518915			
Designation Number:	CN1330			

### **1.3 Laboratory Condition**

Ambient Temperature:	20°C to 25°C
Ambient Relative Humidity:	45% to 55%
Ambient Pressure:	100 kPa to 102 kPa

### **1.4 Announcement**

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



### 2. Product Information

### 2.1 Application Information

Company Name:	Katmai Technology Limited		
Address:	Flat 1201, Floor 12, HARVEST BUILDING 29-37, WING KUT ST CENTRAL,HONGKONG		

### 2.2 Manufacturer Information

Company Name:	Huizhou Zihanxuan Household Electrical Co., Ltd.
Address:	Yinglong Industrial park, Tiantou Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong

### 2.3 Factory Information

Company Name:	Huizhou Zihanxuan Household Electrical Co., Ltd.
Address:	Yinglong Industrial park, Tiantou Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong

### 2.4 General Description of Equipment under Test (EUT)

EUT Name:	ELECTRIC FIREPLACE			
Test Model Number:	INF88W-3D			
Series Model Number:	INF98W-3D, INF95W-3D, INF-50H, INF-60H, INF-72H, INF-88H, INF-98 INF-98H			
Description of Model name differentiation:	Only the model name is different, everything else is the same			
Hardware version	N/A			
Software version	N/A			
Power Supply:	AC 120V 60Hz			
Power Adaptor:	N/A			



## 3. Test Requirement

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b), Limits for Maximum Permissible Exposure (MPE),

Frequency range	Electric field	Magnetic field strength	Power density	Averaging time
(MHz)	strength(V/m)	(A/m)	(mW/cm <sup>2</sup> )	(minutes)
	(A) Limits f	or Occupational/Controlled	Exposures	
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300-1500	-	-	f/300	6
1500-100,000	-	-	5	6
	(B) Limits for G	General Population/Uncontr	olled Exposure	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30
Nata f - frage and in N				

Note: f = frequency in MHz

#### **EVALUATION METHOD**

Transmission formula: Pd = (Pout\*G)/(4\*pi\*r<sup>2</sup>)

Where

Pd = power density in mW/cm<sup>2</sup>, Pout = output power to antenna in mW, G = gain of antenna in linear scale; Pi = 3.1416, R = distance between observation point and center of the radiator in cm

### 3.1 Assessment Result

⊠ Passed

Not Applicable

Frequency (MHz)	Туре	Conducted Power (dBm)	Maximum Tune- up (dBm)	Power Density (mW/cm2)	Limit (mW/cm2)	Result
2480	BLE	-2.19	-2.00	0.0002	1.0000	Pass
2480	WIFI	12.73	13.00	0.0071	1.0000	Pass

Note: The exposure evaluation safety distance is 20cm.



Test Report Number: BTF240819R00103



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

www.btf-lab.com

### --END OF REPORT--