


FCC Test Report

FCC ID : I88WAX650S
Equipment : 802.11ax (WiFi 6) Dual-Radio Unified Pro
Access Point
Model No. : WAX650S
Brand Name : ZYXEL
Applicant : Zyxel Communications Corporation
Address : No.2 Industry East RD. IX, Hsinchu Science
Park, Hsinchu 30075, Taiwan, R.O.C
Standard : 47 CFR FCC Part 15.247
Received Date : Aug. 01, 2019
Tested Date : Aug. 15 ~ Sep. 16, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	Test Equipment List and Calibration Data.....	9
1.5	Test Standards	10
1.6	Deviation from Test Standard and Measurement Procedure.....	10
1.7	Measurement Uncertainty	10
2	TEST CONFIGURATION.....	11
2.1	Testing Condition	11
2.2	The Worst Test Modes and Channel Details	11
3	TRANSMITTER TEST RESULTS	12
3.1	Conducted Emissions.....	12
3.2	6dB and Occupied Bandwidth.....	17
3.3	RF Output Power.....	20
3.4	Power Spectral Density	22
3.5	Emissions in Restricted Frequency Bands.....	25
3.6	Emissions in non-restricted Frequency Bands.....	37
4	TEST LABORATORY INFORMATION	39

Release Record

Report No.	Version	Description	Issued Date
FR980101AE	Rev. 01	Initial issue	Nov. 05, 2019

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 2.962MHz 42.61(Margin -3.39dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 4960.00 MHz 52.52(Margin -1.48dB) - AV	Pass
15.247(b)(3)	Maximum Output Power	Power [dBm]: 5.58	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	LE	2402-2480	0-39 [40]	1 Mbps
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.				

1.1.2 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remarks
1	Dipole	UFL	4.7	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from adapter 30~57Vdc from POE
-------------------	---

Note: The above power supply is not bundled in market.

1.1.4 Radio Details


Radio	Function
1	Wi-Fi 2.4GHz, 4T4R
2	Wi-Fi 5GHz, 4T4R
3	Wi-Fi 2.4GHz & 5GHz, RX only
4	Bluetooth LE only

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.6 Test Tool and Duty Cycle

Test Tool	BTool, v1.41.11	
Duty Cycle and Duty Factor	Duty Cycle (%)	Duty Factor (dB)
	100.00%	0.00




1.1.7 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/1Mbps	default	default	default


1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Notebook	DELL	Latitude E6440	DoC	---
2	POE Switch	ZYXEL	XS1930-12HP	---	Provided by applicant.
3	Adapter	APD	WA-30P12R	---	Provided by applicant.

1.3 Test Setup Chart



Test Setup Diagram (POE mode)



Kept in control area

No.	Signal cable / Length (m)
1	RJ45, 1m non-shielded with load
2	RJ45, 10m non-shielded.
3	RJ45, 1m non-shielded.

1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Sep. 16, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Jan. 08, 2019	Jan. 07, 2020
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 05, 2018	Nov. 04, 2019
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 23, 2018	Oct. 22, 2019
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Tested Date	Aug. 15 ~ Aug. 26, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Jan. 07, 2019	Jan. 06, 2020
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 17, 2019	Apr. 16, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Jan. 07, 2019	Jan. 06, 2020
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 09, 2018	Nov. 08, 2019
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 08, 2018	Oct. 07, 2019
Preamplifier	EMC	EMC02325	980187	Aug. 14, 2019	Aug. 13, 2020
Preamplifier	Agilent	83017A	MY53270014	Aug. 07, 2019	Aug. 06, 2020
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Oct. 01, 2018	Sep. 30, 2019
RF cable-8M	EMC	EMC104-SM-SM-8000	181107	Oct. 01, 2018	Sep. 30, 2019
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Oct. 01, 2018	Sep. 30, 2019
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Oct. 01, 2018	Sep. 30, 2019
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Oct. 01, 2018	Sep. 30, 2019
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Oct. 01, 2018	Sep. 30, 2019
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Sep. 10, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Apr. 17, 2019	Apr. 16, 2020
Power Meter	Anritsu	ML2495A	1241002	Oct. 09, 2018	Oct. 08, 2019
Power Sensor	Anritsu	MA2411B	1207366	Oct. 09, 2018	Oct. 08, 2019
DC POWER SOURCE	GW INSTEK	GPC-6030D	EM892433	Oct. 25, 2018	Oct. 24, 2019
AC POWER SOURCE	APC	AFC-500W	F312060012	Nov. 29, 2018	Nov. 28, 2019
Measurement Software	Sporton	SENSE-15247_FS	V5.10.2	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.130 Hz
Conducted power	± 0.808 dB
Power density	± 0.583 dB
Conducted emission	± 2.715 dB
AC conducted emission	± 2.92 dB
Radiated emission ≤ 1 GHz	± 3.96 dB
Radiated emission > 1 GHz	± 4.51 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	24°C / 62%	Alex Tsai
Radiated Emissions	03CH03-WS	24-25°C / 63-64%	Roger Lu Brad Wu
RF Conducted	TH01-WS	22°C / 65%	Roger Lu

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- ISSED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions	BT LE	2402	1Mbps	1, 2
Radiated Emissions ≤ 1GHz	BT LE	2402	1Mbps	1, 2
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	1
Maximum Output Power	BT LE	2402, 2440, 2480	1Mbps	1
6dB bandwidth				
Power spectral density				
NOTE: 1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The Z-plane results were found as the worst case and were shown in this report. 2. The EUT had been tested by following test configurations. 1) Configuration 1: Adapter mode 2) Configuration 2: POE mode				

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions


Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Line	Test Configuration	1



	Freq	Level	Limit	Over	Read	LISN	cable	Remark
	MHz	dBuV	Line	Limit	Level	factor	loss	
			dBuV	dB	dBuV	dB	dB	
1	0.163	31.16	55.30	-24.14	21.43	9.53	0.06	Average
2	0.163	45.52	65.30	-19.78	35.79	9.53	0.06	QP
3	0.192	31.29	53.93	-22.64	21.50	9.54	0.07	Average
4	0.192	45.20	63.93	-18.73	35.41	9.54	0.07	QP
5	0.240	29.14	52.08	-22.94	19.31	9.55	0.07	Average
6	0.240	41.37	62.08	-20.71	31.54	9.55	0.07	QP
7	0.307	23.98	50.06	-26.08	14.11	9.56	0.08	Average
8	0.307	36.00	60.06	-24.06	26.13	9.56	0.08	QP
9	3.156	25.27	46.00	-20.73	15.05	9.61	0.24	Average
10	3.156	32.13	56.00	-23.87	21.91	9.61	0.24	QP
11*	18.328	43.81	50.00	-6.19	32.99	9.66	0.59	Average
12	18.328	51.19	60.00	-8.81	40.37	9.66	0.59	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).


Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Neutral	Test Configuration	1



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.171	30.18	54.90	-24.72	20.43	9.57	0.06	Average
2	0.171	43.98	64.90	-20.92	34.23	9.57	0.06	QP
3	0.204	30.16	53.45	-23.29	20.37	9.58	0.07	Average
4	0.204	41.47	63.45	-21.98	31.68	9.58	0.07	QP
5	0.234	28.62	52.30	-23.68	18.82	9.59	0.07	Average
6	0.234	40.03	62.30	-22.27	30.23	9.59	0.07	QP
7	0.365	26.58	48.61	-22.03	16.77	9.61	0.08	Average
8	0.365	37.53	58.61	-21.08	27.72	9.61	0.08	QP
9	4.952	21.79	46.00	-24.21	11.53	9.67	0.32	Average
10	4.952	30.33	56.00	-25.67	20.07	9.67	0.32	QP
11*	18.426	43.70	50.00	-6.30	32.89	9.80	0.59	Average
12	18.426	50.54	60.00	-9.46	39.73	9.80	0.59	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).


Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Line	Test Configuration	2



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.159	43.06	55.52	-12.46	33.48	9.53	0.05	Average
2	0.159	48.58	65.52	-16.94	39.00	9.53	0.05	QP
3	0.989	42.39	46.00	-3.61	32.69	9.60	0.10	Average
4	0.989	43.15	56.00	-12.85	33.45	9.60	0.10	QP
5	1.480	40.61	46.00	-5.39	30.88	9.60	0.13	Average
6	1.480	41.01	56.00	-14.99	31.28	9.60	0.13	QP
7	2.474	39.75	46.00	-6.25	29.95	9.60	0.20	Average
8	2.474	40.90	56.00	-15.10	31.10	9.60	0.20	QP
9*	2.962	42.61	46.00	-3.39	32.77	9.61	0.23	Average
10	2.962	44.19	56.00	-11.81	34.35	9.61	0.23	QP
11	4.797	34.64	46.00	-11.36	24.71	9.62	0.31	Average
12	4.797	43.04	56.00	-12.96	33.11	9.62	0.31	QP
13	17.109	39.66	50.00	-10.34	29.42	9.66	0.58	Average
14	17.109	48.32	60.00	-11.68	38.08	9.66	0.58	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Neutral	Test Configuration	2



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.156	37.92	55.69	-17.77	28.30	9.57	0.05	Average
2	0.156	47.98	65.69	-17.71	38.36	9.57	0.05	QP
3*	0.989	42.21	46.00	-3.79	32.47	9.64	0.10	Average
4	0.989	45.28	56.00	-10.72	35.54	9.64	0.10	QP
5	1.480	38.86	46.00	-7.14	29.08	9.65	0.13	Average
6	1.480	39.04	56.00	-16.96	29.26	9.65	0.13	QP
7	2.962	40.78	46.00	-5.22	30.89	9.66	0.23	Average
8	2.962	41.23	56.00	-14.77	31.34	9.66	0.23	QP
9	4.848	34.88	46.00	-11.12	24.90	9.67	0.31	Average
10	4.848	43.72	56.00	-12.28	33.74	9.67	0.31	QP
11	16.573	38.97	50.00	-11.03	28.62	9.78	0.57	Average
12	16.573	47.39	60.00	-12.61	37.04	9.78	0.57	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup



3.2.4 Test Result of 6dB and Occupied Bandwidth

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	713.768k	1.075M	1M08F1D	695.652k	1.046M

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;

Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	702.899k	1.046M
2440MHz	Pass	500k	695.652k	1.071M
2480MHz	Pass	500k	713.768k	1.075M

Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

BT-LE(1Mbps)

EBW


2402MHz



BT-LE(1Mbps)

EBW


2440MHz



BT-LE(1Mbps)

EBW

2480MHz



3.3 RF Output Power

3.3.1 Limit of RF Output Power


Conducted power shall not exceed 1Watt.

Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.

3.3.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Summary of Peak Conducted Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	5.58	0.00361

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	4.70	5.58	30.00
2440MHz	Pass	4.70	5.33	30.00
2480MHz	Pass	4.70	5.14	30.00

Summary of Conducted (Average) Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	5.47	0.00352

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	4.70	5.47	-
2440MHz	Pass	4.70	5.21	-
2480MHz	Pass	4.70	5.01	-

Note: Average power is for reference only.

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Summary

Mode	PD (dBm/3kHz)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-6.19


Result

Mode	Result	Gain (dBi)	PD (dBm/3kHz)	PD Limit (dBm/3kHz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	4.70	-6.23	8.00
2440MHz	Pass	4.70	-6.36	8.00
2480MHz	Pass	4.70	-6.19	8.00

BT-LE(1Mbps)

PSD


2402MHz



BT-LE(1Mbps)

PSD


2440MHz



BT-LE(1Mbps)

PSD

2480MHz



3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	45.52	24.74	40.00	-15.26	33.45	-8.71	Peak	---	---
2	173.56	26.02	43.50	-17.48	35.50	-9.48	Peak	---	---
3	210.42	26.07	43.50	-17.43	38.10	-12.03	Peak	---	---
4	277.35	32.59	46.00	-13.41	41.53	-8.94	Peak	---	---
5	526.64	30.31	46.00	-15.69	32.89	-2.58	Peak	---	---
6	793.39	33.32	46.00	-12.68	30.67	2.65	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	43.58	36.83	40.00	-3.17	45.76	-8.93	Peak	---	---
2	145.43	30.44	43.50	-13.06	39.40	-8.96	Peak	---	---
3	171.62	33.69	43.50	-9.81	42.93	-9.24	Peak	---	---
4	283.17	28.51	46.00	-17.49	37.24	-8.73	Peak	---	---
5	526.64	35.90	46.00	-10.10	38.48	-2.58	Peak	---	---
6	869.05	35.42	46.00	-10.58	32.00	3.42	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	67.83	28.60	40.00	-11.40	38.91	-10.31	Peak	---	---
2	173.56	37.35	43.50	-6.15	46.83	-9.48	Peak	---	---
3	210.42	35.71	43.50	-7.79	47.74	-12.03	Peak	---	---
4	323.91	31.75	46.00	-14.25	39.18	-7.43	Peak	---	---
5	539.25	30.61	46.00	-15.39	33.16	-2.55	Peak	---	---
6	800.18	35.45	46.00	-10.55	32.76	2.69	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	37.76	33.50	40.00	-6.50	43.06	-9.56	Peak	---	---
2	66.86	33.31	40.00	-6.69	43.64	-10.33	Peak	---	---
3	136.70	33.96	43.50	-9.54	43.51	-9.55	Peak	---	---
4	170.65	35.81	43.50	-7.69	45.00	-9.19	Peak	---	---
5	215.27	33.05	43.50	-10.45	45.15	-12.10	Peak	---	---
6	540.22	34.97	46.00	-11.03	37.52	-2.55	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	42.30	54.00	-11.70	41.88	0.42	Average	115	315
2	2390.00	54.57	74.00	-19.43	54.15	0.42	Peak	115	315
3 *	2402.00	88.52			88.12	0.40	Average	115	315
4 *	2402.00	89.55			89.15	0.40	Peak	115	315
5	4804.00	41.93	54.00	-12.07	35.61	6.32	Average	251	98
6	4804.00	51.63	74.00	-22.37	45.31	6.32	Peak	251	98
7	12010.00	46.29	54.00	-7.71	29.82	16.47	Average	246	81
8	12010.00	59.49	74.00	-14.51	43.02	16.47	Peak	246	81

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	42.38	54.00	-11.62	41.96	0.42	Average	183	58
2	2390.00	54.62	74.00	-19.38	54.20	0.42	Peak	183	58
3 *	2402.00	102.70			102.30	0.40	Average	183	58
4 *	2402.00	103.76			103.36	0.40	Peak	183	58
5	4804.00	46.86	54.00	-7.14	40.54	6.32	Average	252	48
6	4804.00	55.03	74.00	-18.97	48.71	6.32	Peak	252	48
7	12010.00	46.33	54.00	-7.67	29.86	16.47	Average	241	53
8	12010.00	60.38	74.00	-13.62	43.91	16.47	Peak	241	53


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	42.44	54.00	-11.56	42.02	0.42	Average	112	313
2	2390.00	54.54	74.00	-19.46	54.12	0.42	Peak	112	313
3 *	2440.00	88.38			88.02	0.36	Average	112	313
4 *	2440.00	89.45			89.09	0.36	Peak	112	313
5	2483.50	42.42	54.00	-11.58	42.16	0.26	Average	112	313
6	2483.50	54.52	74.00	-19.48	54.26	0.26	Peak	112	313
7	4880.00	45.93	54.00	-8.07	39.50	6.43	Average	205	82
8	4880.00	53.97	74.00	-20.03	47.54	6.43	Peak	205	82
9	7320.00	42.41	54.00	-11.59	30.62	11.79	Average	192	16
10	7320.00	54.83	74.00	-19.17	43.04	11.79	Peak	192	16


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	42.56	54.00	-11.44	42.14	0.42	Average	190	53
2	2390.00	54.51	74.00	-19.49	54.09	0.42	Peak	190	53
3 *	2440.00	102.29			101.93	0.36	Average	190	53
4 *	2440.00	103.26			102.90	0.36	Peak	190	53
5	2483.50	42.68	54.00	-11.32	42.42	0.26	Average	190	53
6	2483.50	54.58	74.00	-19.42	54.32	0.26	Peak	190	53
7	4880.00	51.34	54.00	-2.66	44.91	6.43	Average	215	46
8	4880.00	57.72	74.00	-16.28	51.29	6.43	Peak	215	46
9	7320.00	43.97	54.00	-10.03	32.18	11.79	Average	216	192
10	7320.00	55.67	74.00	-18.33	43.88	11.79	Peak	216	192


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	1



		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	*	2480.00	88.63			88.36	0.27	Average	116	310
2	*	2480.00	89.69			89.42	0.27	Peak	116	310
3		2483.50	42.42	54.00	-11.58	42.16	0.26	Average	116	310
4		2483.50	54.41	74.00	-19.59	54.15	0.26	Peak	116	310
5		4960.00	42.08	54.00	-11.92	35.37	6.71	Average	221	45
6		4960.00	51.96	74.00	-22.04	45.25	6.71	Peak	221	45
7		7440.00	42.13	54.00	-11.87	30.31	11.82	Average	208	116
8		7440.00	54.16	74.00	-19.84	42.34	11.82	Peak	208	116


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	1



		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	*	2480.00	102.68			102.41	0.27	Average	187	53
2	*	2480.00	103.71			103.44	0.27	Peak	187	53
3		2483.50	44.34	54.00	-9.66	44.08	0.26	Average	187	53
4		2483.50	56.40	74.00	-17.60	56.14	0.26	Peak	187	53
5		4960.00	52.52	54.00	-1.48	45.81	6.71	Average	209	21
6		4960.00	58.57	74.00	-15.43	51.86	6.71	Peak	209	21
7		7440.00	42.62	54.00	-11.38	30.80	11.82	Average	199	261
8		7440.00	55.31	74.00	-18.69	43.49	11.82	Peak	199	261

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency

3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level


Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.6.3 Test Setup



3.6.4 Test Result of Emissions in non-restricted Frequency Bands



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan,
R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==