

## RF Exposure Requirements

---

Product Description: Cycling Speed & Cadence Sensor

Model No.: BK465, BK463, BK467, BK6, CY3

FCC ID: 2AF9HBK465

According to the KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, 16 where

-  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation

- The result is rounded to one decimal place for comparison

### Bluetooth(BLE)

| Conducted Power (dBm) | Max. Power (mW) | Distance (mm) | Frequency (GHz) | Result | Limit |
|-----------------------|-----------------|---------------|-----------------|--------|-------|
| -7.12                 | 0.19            | 5             | 2.402           | 0.06   | 3     |

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$ :  $0.19/5 \cdot \sqrt{2.402} = 0.06$

The exclusion thresholds is less than 3, therefore, the RF exposure evaluation is not required.