

RF Exposure Evaluation Report

Report No.: RWAZ202300129K

Applicant: Shenzhen Youmi Intelligent Technology Co., Ltd.

Address: 406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China

Product Name: Smart phone

Product Model: PG2311GBA

Multiple Models: N/A

Trade Mark: UMIDIGI

FCC ID: 2ATZ4-G6

Standards: 47 CFR §1.1310
KDB 447498 D01 General RF Exposure Guidance v06

Test Date: 2023/12/22~2024/02/22

Test Result: Complied

Report Date: 2024/02/27

Reviewed by:

Abel chen

Abel Chen
Project Engineer

Approved by:

Jacob Kong

Jacob Kong
Manager

Prepared by:

World Alliance Testing and Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★"

Announcement

1. This test report shall not be reproduced in full or partial, without the written approval of World Alliance Testing and Certification (Shenzhen) Co., Ltd
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.
5. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

Revision History

Version No.	Issued Date	Description
00	27, Feb, 2024	Original

Contents

1	General Information	4
1.1	Client Information	4
1.2	Product Description of EUT	4
1.3	Laboratory Location.....	4
2	RF Exposure Evaluation	5
2.1	Standard	5
2.2	Result.....	5

1 General Information

1.1 Client Information

Applicant:	Shenzhen Youmi Intelligent Technology Co., Ltd.
Address:	406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China
Manufacturer:	Shenzhen Youmi Intelligent Technology Co., Ltd.
Address:	406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China

1.2 Product Description of EUT

Sample Serial Number	2X-5 (assigned by WATC)
Sample Received Date	2023-12-05
Sample Status	Good Condition
Frequency Range	BT/BLE: 2402MHz - 2480MHz NFC: 13.56MHz
Maximum Conducted Output Power	Bluetooth: 6.36dBm. BLE: -4.25dBm NFC: 66.49dBuV/m@3m
Modulation Technology	Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK NFC: ASK
Antenna Gain [#]	BT/BLE: 1.1dBi NFC: 0.98dBi
Power Supply	DC 3.87V from battery or DC 5V from USB Port
Adapter Information	Adapter 1 Model: HF-0502000U Input: AC100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 2A Adapter 2 Model: HJ-0502000W2-US Input: AC100-240V, 50/60Hz, 0.3A Output: DC 5V, 2A
Modification	Sample No Modification by the test lab

1.3 Laboratory Location

World Alliance Testing and Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: qa@watc.com.cn

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.

2 RF Exposure Evaluation

2.1 Standard

According to §1.1310, radio frequency devices shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2.2 Result

Radio	Frequency (MHz)	Maximum Conducted Power including Tune-up Tolerance (dBm)	Min. test separation distance (mm)	Result (1-g SAR)	Exclusion Limit (1-g SAR)	Verdict
BT	2402-2480	6.4	5	1.4	3.0	Pass
BLE	2402-2480	-4.2	5	0.1	3.0	Pass

Note: The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

For NFC:

The power of EUT: E Field@3m is 66.49dBuV/m = -28.71dBm (0.0013mW)

Note: $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$ for $d = 3$ m.

SAR test exclusion threshold for NFC(13.56MHz) separation distance < 50 mm

$$= [474 * (1 + \log(100/f(\text{MHz})))]/2$$

$$= 443\text{mW}$$

$$> 0.0013\text{mW}$$

Result: Complied, No need standalone SAR test.

---End of Report---