# WYZE

V2.0 2021.8.12 更新型号

V1.0 正

# QUICK START GUIDE

# **WELCOME TO WYZE**

Small and flexible, our Wyze Leak Sensors were designed with a modern home in mind. Place anywhere to help ensure that your house is protected against unwanted leaks. Included in the bundle is a leak sensor probe that can reach places that our leak sensor cannot. Best of all, it's smart enough to tell whether the body or the sensor probe is detecting the leak.

#### IN THE BOX

Wyze Leak Sensor × 3 CR2450 Battery × 3

Wyze Leak Sensor Probe × 1 Quick Start Guide × 1

#### **ACTIVATION**

To use the Wyze Leak Sensor, you will first need to set up your Wyze Sense Hub (sold separately). The Wyze Leak Sensor Probe can be connected to any Wyze Leak Sensor through the connection port.

# **SETUP**

**▶** Download the Wyze app and sign in or create an





open the Wyze app and tap the + sign on the top-left corner of the Home tab. Tap Add Device > Sensors > Wyze Leak Sensor. Follow the instructions in the Wyze app to complete installation and setup.

If you haven't already set up your Wyze Sense Hub. tap the Home Monitoring tab in the Wyze app. When your Home Monitoring license is activated, tap **Start** Setup. This will guide you through the installation

Not seeing this screen? Go to services.wyze.com to activate your subscription.

Remove the plastic battery tab. Then press and hold the reset button on the side until the status light on the top of the leak sensor starts flashing.

In the Wyze app, name your sensor when prompted.

35 If you want to attach the leak sensor probe to the sensor, just connect it via the connection port. The leak sensor will automatically recognize the sensor probe.

Place your leak sensor or the sensor probe in the location you want to use it in.

(2) l'utilisateur de l'appareil doit accepter tout brouillage

d'en compromettre le fonctionnement.

radioélectrique subi, même si le brouillage est susceptible

## V1.0 背

#### **SPECIFICATIONS:**

Battery: CR2450

Dimensions: 48 mm x 48 mm x 25 mm Battery Life: 1.5 years based on normal usage Mounting Method: Ground

Range: 500ft

Operation Temperature: 32°F - 104°F (0°C - 40°C) Operation Humidity: 85% at 86°F (30°C) Weather Resistance: IP67 (Indoor–use only)

## **FCC WARNING:**

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

#### **FCC RADIATION EXPOSURE STATEMENT:**

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20 cm between the radiator & your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

#### **ISED RADIATION EXPOSURE STATEMENT:**

This equipment complies with ISED RF radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. This equipment should be installed and operated with minumum distance 20 cm between the radiator & your body.

Cet appareil est conforme aux limites d'exposition de rayonnement RF ISED établies pour un environnement non contrôlé. Cet émetteur ne doit pas être co-implanté ou fonctionner en conjonction avec toute autre antenne ou transmetteur. Cet équipement doit être installé et utilisé avec une distance minimale de 20 cm entre le radiateur et

#### **ISED RSS WARNING:**

This device complies with ISED licence-exempt RSS standard (s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the

Le présent appareil est conforme aux CNR d'ISED applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et

# **NEED HELP?**

Contact our support teams https://wyze.com/support Join our Community: https://wyze.com/community

User Manual Version: 1.0



Scan the QR code to learn more

切刀 齿刀 开槽 半穿 粘合

Scale 1:1 Unit:mm

型号: WSWL1 规格: WSWL1-KSZP01 V2.0

物料编码:

样品 物料材质 ▶ 105g无光铜 产品名 ▶ 水浸传感器三只装说明书 印刷颜色 ▶ CMYK 审核 ▶ 样品数量 ▶ 特种工艺 ▶ 折页,过油 设计于 ▶ 于树媛 成品尺寸 ▶ 70\*68mm 批准▶