

FCC Test Report

(Class II Permissive Change)

Product Name	Intel® Dual Band Wireless-AC 8265
Model No.	8265D2W
FCC ID.	PD98265D2

Applicant	Intel Mobile Communications
Address	100 Center Point Circle, Suite 200 Columbia, South Carolina 29210 USA

Date of Receipt	Sep. 07, 2016
Issued Date	Sep. 23, 2016
Report No.	1690163R-RFUSP23V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

Test Report

Issued Date: Sep. 23, 2016

Report No.: 1690163R-RFUSP23V00



Product Name	Intel® Dual Band Wireless-AC 8265
Applicant	Intel Mobile Communications
Address	100 Center Point Circle, Suite 200 Columbia, South Carolina 29210 USA
Manufacturer	Intel Mobile Communications
Model No.	8265D2W
FCC ID.	PD98265D2
EUT Rated Voltage	DC 3.3V (via Mini-PCI Express slot)
EUT Test Voltage	AC 120V/60Hz
Trade Name	Intel
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2015 ANSI C63.4: 2014, ANSI C63.10: 2013 KDB 558074 D01 DTS Meas Guidance v03r05
Test Result	Complied

Documented By :

Leven Huang

(Senior Adm. Specialist / Leven Huang)

Tested By :

Eason chen

(Engineer / Eason Chen)

Approved By :

Vincent Lin

(Director / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION.....	4
1.1. EUT Description	4
1.2. Operational Description.....	6
1.3. Tested System Details.....	7
1.4. Configuration of Tested System.....	7
1.5. EUT Exercise Software	7
1.6. Test Facility.....	8
2. LIST OF TEST ITEM AND EQUIPMENT.....	9
3. PEAK POWER OUTPUT.....	10
3.1. Test Setup.....	10
3.2. Limit	10
3.3. Test Procedure.....	10
3.4. Uncertainty.....	10
3.5. Test Result of Peak Power Output.....	11
4. RADIATED EMISSION	14
4.1. Test Setup.....	14
4.2. Limits.....	15
4.3. Test Procedure.....	16
4.4. Uncertainty.....	16
4.5. Test Result of Radiated Emission.....	17
5. BAND EDGE	29
5.1. Test Setup.....	29
5.2. Limit	30
5.3. Test Procedure.....	30
5.4. Uncertainty.....	30
5.5. Test Result of Band Edge.....	31
6. EMI REDUCTION METHOD DURING COMPLIANCE TESTING.....	43
Attachment 1: EUT Test Photographs	
Attachment 2: EUT Detailed Photographs	

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Intel® Dual Band Wireless-AC 8265
Trade Name	Intel
Model No.	8265D2W
FCC ID.	PD98265D2
Frequency Range	2402 – 2480MHz
Channel Number	79
Type of Modulation	FHSS: GFSK(1Mbps) / π /4DQPSK(2Mbps) / 8DPSK(3Mbps)
Antenna Type	Dipole Antenna
Channel Control	Auto
Antenna Gain	Refer to the table “Antenna List”

Antenna List:

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	WIESON Technologies co., ltd	GY121HT0321-003-H (External) (WIFI)	Dipole Antenna	2.89dBi for 2.4GHz

Note: The antenna of EUT is conform to FCC 15.203

Center Frequency of Each Channel: (For V3.0+HS, V2.1+EDR)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 00:	2402 MHz	Channel 20:	2422 MHz	Channel 40:	2442 MHz	Channel 60:	2462 MHz
Channel 01:	2403 MHz	Channel 21:	2423 MHz	Channel 41:	2443 MHz	Channel 61:	2463 MHz
Channel 02:	2404 MHz	Channel 22:	2424 MHz	Channel 42:	2444 MHz	Channel 62:	2464 MHz
Channel 03:	2405 MHz	Channel 23:	2425 MHz	Channel 43:	2445 MHz	Channel 63:	2465 MHz
Channel 04:	2406 MHz	Channel 24:	2426 MHz	Channel 44:	2446 MHz	Channel 64:	2466 MHz
Channel 05:	2407 MHz	Channel 25:	2427 MHz	Channel 45:	2447 MHz	Channel 65:	2467 MHz
Channel 06:	2408 MHz	Channel 26:	2428 MHz	Channel 46:	2448 MHz	Channel 66:	2468 MHz
Channel 07:	2409 MHz	Channel 27:	2429 MHz	Channel 47:	2449 MHz	Channel 67:	2469 MHz
Channel 08:	2410 MHz	Channel 28:	2430 MHz	Channel 48:	2450 MHz	Channel 68:	2470 MHz
Channel 09:	2411 MHz	Channel 29:	2431 MHz	Channel 49:	2451 MHz	Channel 69:	2471 MHz
Channel 10:	2412 MHz	Channel 30:	2432 MHz	Channel 50:	2452 MHz	Channel 70:	2472 MHz
Channel 11:	2413 MHz	Channel 31:	2433 MHz	Channel 51:	2453 MHz	Channel 71:	2473 MHz
Channel 12:	2414 MHz	Channel 32:	2434 MHz	Channel 52:	2454 MHz	Channel 72:	2474 MHz
Channel 13:	2415 MHz	Channel 33:	2435 MHz	Channel 53:	2455 MHz	Channel 73:	2475 MHz
Channel 14:	2416 MHz	Channel 34:	2436 MHz	Channel 54:	2456 MHz	Channel 74:	2476 MHz
Channel 15:	2417 MHz	Channel 35:	2437 MHz	Channel 55:	2457 MHz	Channel 75:	2477 MHz
Channel 16:	2418 MHz	Channel 36:	2438 MHz	Channel 56:	2458 MHz	Channel 76:	2478 MHz
Channel 17:	2419 MHz	Channel 37:	2439 MHz	Channel 57:	2459 MHz	Channel 77:	2479 MHz
Channel 18:	2420 MHz	Channel 38:	2440 MHz	Channel 58:	2460 MHz	Channel 78:	2480 MHz
Channel 19:	2421 MHz	Channel 39:	2441 MHz	Channel 59:	2461 MHz		

Note:

1. The EUT is an Intel® Dual Band Wireless-AC 8265 with a built-in WLAN 、Bluetooth transceiver, this report for Bluetooth.
2. These tests were conducted on a sample for the purpose of demonstrating compliance of Bluetooth transmitter with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
4. This is to request a Class II permissive change for FCC ID: PD98265D2, originally granted on 06/28/2016.

The major change filed under this application is:

Change #1: Addition an new antenna, antenna type is different with the original application.

(Antenna type: Dipole antenna)

Test Mode	Mode 1: Transmit - 1Mbps (GFSK) Mode 2: Transmit - 2Mbps (4DQPSK) Mode 3: Transmit - 3Mbps (8DPSK)
-----------	--


1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Notebook PC	DELL	N/A	N/A	Non-Shielded, 1.8m
2 Test Fixture	Intel	N/A	N/A	N/A

Signal Cable Type	Signal cable Description
A Test Fixture Line	Non-Shielded, 1.0m

1.4. Configuration of Tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown on 1.4
- (2) Execute “DRTU (Ver 1.8.7-02915)” program on the EUT.
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Start the continuous transmission.
- (5) Verify that the EUT works properly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	30-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from QuieTek Corporation's Web Site : <http://www.quietek.com/chinese/about/certificates.aspx?bval=5>
The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>

Site Description: File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Registration Number: 92195

Site Name: Quietek Corporation
Site Address: No.5-22, Ruishukeng,
Linkou Dist. New Taipei City 24451,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com

FCC Accreditation Number: TW1014

2. List of Test Item and Equipment


	Equipment	Manufacturer	Model No.	Serial No.	Cali. Data	Due. Data
X	Power Meter	Anritsu	ML2495A	6K00003357	2016/6/23	2017/6/22
X	Spectrum Analyzer	R&S	FSP40	100170	2016/1/5	2017/1/3
	Loop Antenna	TESEQ	HLA6121	37133	2016/3/18	2017/3/17
X	Bi-Log Antenna	Schaffner Chase	CBL6112B	2707	2016/6/11	2017/6/10
X	Horn Antenna	ETS-Lindgren	3117	00203761	2015/10/15	2016/10/13
	Horn Antenna	Schwarzbeck	BBHA9170	209	2016/4/14	2017/4/13
X	Pre-Amplifier	QuieTek	QTK-LK-E-I-A	N/A	2016/6/16	2017/6/15
X	Pre-Amplifier	EMCI	EMC012630SE	980210	2016/1/26	2017/1/24
	Pre-Amplifier	NARDA WE	DBL-1840N506	013	2016/8/6	2017/8/4
	Filter	MicroTRON	BRM50701	019	2015/10/20	2016/10/18
	Filter	Microwave Circuits	N0257881	36681	2015/12/7	2016/12/5
X	EMI Test Receiver	R&S	ESCS 30	838251/001	2016/7/21	2017/7/20
X	Coaxial Cable	QTK(Arnist)	RG 214	LC003-RG	2016/6/16	2017/6/15
X	Coaxial signal switch	Anritsu	MP59B	6201415889	2016/6/16	2017/6/15

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “X” are used to measure the final test results.

3. Peak Power Output

3.1. Test Setup



3.2. Limit

The maximum peak power shall be less 1 Watt.

3.3. Test Procedure

The EUT was setup to ANSI C63.4, 2014; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

3.4. Uncertainty

± 1.27 dB

3.5. Test Result of Peak Power Output

Product : Intel® Dual Band Wireless-AC 8265
 Test Item : Peak Power Output
 Test Site : No.3 OATS
 Test date : 2016.09.13
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402.00	10.29	1 Watt= 30 dBm	Pass
Channel 39	2441.00	11.82	1 Watt= 30 dBm	Pass
Channel 78	2480.00	10.86	1 Watt= 30 dBm	Pass

Product : Intel® Dual Band Wireless-AC 8265
 Test Item : Peak Power Output
 Test Site : No.3 OATS
 Test date : 2016.09.13
 Test Mode : Mode 2: Transmit - 2Mbps (4DQPSK)

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402.00	10.08	1 Watt= 30 dBm	Pass
Channel 39	2441.00	11.59	1 Watt= 30 dBm	Pass
Channel 78	2480.00	10.49	1 Watt= 30 dBm	Pass


Product : Intel® Dual Band Wireless-AC 8265
Test Item : Peak Power Output
Test Site : No.3 OATS
Test date : 2016.09.13
Test Mode : Mode 3: Transmit - 3Mbps (8DPSK)

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402.00	9.89	1 Watt= 30 dBm	Pass
Channel 39	2441.00	11.25	1 Watt= 30 dBm	Pass
Channel 78	2480.00	10.04	1 Watt= 30 dBm	Pass


4. Radiated Emission

4.1. Test Setup

Below 1GHz



Above 1GHz



4.2. Limits

➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	uV/m @3m	dBμV/m@3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

- Remarks:
1. RF Voltage (dBμV) = 20 log RF Voltage (uV)
 2. In the Above Table, the tighter limit applies at the band edges.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

4.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The measurement frequency range from 9kHz - 10th Harmonic of fundamental was investigated.

4.4. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

4.5. Test Result of Radiated Emission

Product : Intel® Dual Band Wireless-AC 8265
 Test Item : Harmonic Radiated Emission
 Test Site : No.3 OATS
 Test date : 2016.09.13
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)(2402MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
Horizontal					
Peak Detector:					
4804.000	2.511	42.920	45.430	-28.570	74.000
7206.000	9.511	38.620	48.131	-25.869	74.000
9608.000	10.394	38.170	48.564	-25.436	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4804.000	2.923	42.910	45.832	-28.168	74.000
7206.000	9.988	39.170	49.159	-24.841	74.000
9608.000	10.847	38.210	49.057	-24.943	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Harmonic Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.13
Test Mode : Mode 1: Transmit - 1Mbps (GFSK)(2441MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBμV	dBμV/m	dB	dBμV/m
Horizontal					
Peak Detector:					
4882.000	2.025	42.750	44.775	-29.225	74.000
7323.000	9.762	38.510	48.271	-25.729	74.000
9764.000	9.682	37.870	47.551	-26.449	74.000
Average					
Detector:					
--					
Vertical					
Peak Detector:					
4882.000	2.488	46.450	48.938	-25.062	74.000
7323.000	10.375	38.240	48.614	-25.386	74.000
9764.000	10.315	37.680	47.995	-26.005	74.000
Average					
Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Harmonic Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.13
Test Mode : Mode 1: Transmit - 1Mbps (GFSK)(2480MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
Horizontal					
Peak Detector:					
4960.000	2.582	41.730	44.312	-29.688	74.000
7440.000	10.555	37.960	48.515	-25.485	74.000
9920.000	10.206	38.520	48.726	-25.274	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4960.000	3.398	44.620	48.019	-25.981	74.000
7440.000	11.214	38.510	49.724	-24.276	74.000
9920.000	11.245	38.450	49.695	-24.305	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Harmonic Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.13
Test Mode : Mode 2: Transmit - 2Mbps (4DQPSK) (2402MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level	dB	dBμV/m
Horizontal					
Peak Detector:					
4804.000	2.511	42.510	45.020	-28.980	74.000
7206.000	9.511	38.930	48.441	-25.559	74.000
9608.000	10.394	38.540	48.934	-25.066	74.000
Average					
Detector:					
--					
Vertical					
Peak Detector:					
4804.000	2.923	44.510	47.432	-26.568	74.000
7206.000	9.988	38.940	48.929	-25.071	74.000
9608.000	10.847	38.210	49.057	-24.943	74.000
Average					
Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Harmonic Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.13
Test Mode : Mode 2: Transmit - 2Mbps (4DQPSK) (2441MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBμV	dBμV/m	dB	dBμV/m
Horizontal					
Peak Detector:					
4882.000	2.025	42.060	44.085	-29.915	74.000
7323.000	9.762	38.930	48.691	-25.309	74.000
9764.000	9.682	37.820	47.501	-26.499	74.000
Average					
Detector:					
--					
Vertical					
Peak Detector:					
4882.000	2.488	45.860	48.348	-25.652	74.000
7323.000	10.375	38.170	48.544	-25.456	74.000
9764.000	10.315	38.590	48.905	-25.095	74.000
Average					
Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Harmonic Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.13
Test Mode : Mode 2: Transmit - 2Mbps (4DQPSK) (2480MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
Horizontal					
Peak Detector:					
4960.000	2.582	41.520	44.102	-29.898	74.000
7440.000	10.555	38.540	49.095	-24.905	74.000
9920.000	10.206	38.120	48.326	-25.674	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4960.000	3.398	43.790	47.189	-26.811	74.000
7440.000	11.214	38.560	49.774	-24.226	74.000
9920.000	11.245	38.460	49.705	-24.295	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Harmonic Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.13
Test Mode : Mode 3: Transmit - 3Mbps (8DPSK)(2402MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
Horizontal					
Peak Detector:					
4804.000	2.511	42.580	45.090	-28.910	74.000
7206.000	9.511	39.630	49.141	-24.859	74.000
9608.000	10.394	38.460	48.854	-25.146	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4804.000	2.923	45.310	48.232	-25.768	74.000
7206.000	9.988	38.720	48.709	-25.291	74.000
9608.000	10.847	38.920	49.767	-24.233	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Harmonic Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.13
Test Mode : Mode 3: Transmit - 3Mbps (8DPSK) (2441MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
Horizontal					
Peak Detector:					
4882.000	2.025	42.810	44.835	-29.165	74.000
7323.000	9.762	38.920	48.681	-25.319	74.000
9764.000	9.682	38.590	48.271	-25.729	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4882.000	2.488	45.760	48.248	-25.752	74.000
7323.000	10.375	38.490	48.864	-25.136	74.000
9764.000	10.315	39.260	49.575	-24.425	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Harmonic Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.13
Test Mode : Mode 3: Transmit - 3Mbps (8DPSK) (2480MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
Horizontal					
Peak Detector:					
4960.000	2.582	41.980	44.562	-29.438	74.000
7440.000	10.555	38.460	49.015	-24.985	74.000
9920.000	10.206	37.620	47.826	-26.174	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4960.000	3.398	44.710	48.109	-25.891	74.000
7440.000	11.214	38.460	49.674	-24.326	74.000
9920.000	11.245	37.920	49.165	-24.835	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : General Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.12
Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2441MHz)

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
Horizontal					
299.660	-4.751	28.924	24.173	-21.827	46.000
406.360	0.628	26.472	27.101	-18.899	46.000
598.420	3.524	25.591	29.115	-16.885	46.000
712.880	3.792	28.016	31.808	-14.192	46.000
823.460	7.241	23.880	31.121	-14.879	46.000
967.020	7.299	24.886	32.185	-21.815	54.000
Vertical					
117.300	-3.740	31.859	28.119	-15.381	43.500
377.260	0.647	26.958	27.605	-18.395	46.000
544.100	1.503	29.348	30.851	-15.149	46.000
615.880	1.473	26.060	27.533	-18.467	46.000
823.460	3.081	29.895	32.976	-13.024	46.000
965.080	3.832	34.480	38.312	-15.688	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : General Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.12
Test Mode : Mode 2: Transmit - 2Mbps (4DQPSK) (2441MHz)

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
Horizontal					
99.840	-9.873	33.013	23.140	-20.360	43.500
365.620	0.382	28.491	28.873	-17.127	46.000
460.680	4.030	27.005	31.035	-14.965	46.000
592.600	3.437	29.382	32.819	-13.181	46.000
740.040	3.710	27.337	31.047	-14.953	46.000
889.420	6.654	26.431	33.085	-12.915	46.000
Vertical					
99.840	-6.063	36.255	30.192	-13.308	43.500
377.260	0.647	27.503	28.150	-17.850	46.000
544.100	1.503	28.803	30.306	-15.694	46.000
691.540	2.092	29.098	31.190	-14.810	46.000
736.160	-0.866	30.769	29.903	-16.097	46.000
866.140	-0.330	32.343	32.013	-13.987	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : General Radiated Emission
Test Site : No.3 OATS
Test date : 2016.09.12
Test Mode : Mode 3: Transmit - 3Mbps (8DPSK) (2441MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
Horizontal					
99.840	-9.873	32.038	22.165	-21.335	43.500
352.040	-1.282	29.452	28.170	-17.830	46.000
460.680	4.030	27.636	31.666	-14.334	46.000
592.600	3.437	26.425	29.862	-16.138	46.000
767.200	5.099	28.782	33.882	-12.118	46.000
908.820	6.330	25.133	31.463	-14.537	46.000
Vertical					
99.840	-6.063	36.982	30.919	-12.581	43.500
363.680	0.079	26.068	26.147	-19.853	46.000
538.280	1.996	28.095	30.091	-15.909	46.000
687.660	2.292	32.516	34.808	-11.192	46.000
809.880	3.026	31.995	35.021	-10.979	46.000
963.140	3.581	36.277	39.858	-14.142	54.000

Note:


1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

5. Band Edge

5.1. Test Setup

RF Radiated Measurement:

Above 1GHz



5.2. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.3. Test Procedure

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.

The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz, respectively.

5.4. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

5.5. Test Result of Band Edge

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2402MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2388.986	6.470	38.640	45.110	74.000	54.000	Pass
00 (Peak)	2390.000	6.474	35.972	42.447	74.000	54.000	Pass
00 (Peak)	2400.000	6.528	55.115	61.643	--	--	--
00 (Peak)	2402.029	6.540	90.188	96.728	--	--	--
00 (Average)	2390.000	6.474	24.140	30.615	74.000	54.000	Pass
00 (Average)	2400.000	6.528	35.932	42.460	--	--	--
00 (Average)	2402.029	6.540	76.064	82.604	--	--	--

Figure Channel 00:

Horizontal (Peak)





Figure Channel 00:

Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2402MHz)

RF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2390.000	5.880	41.627	47.508	74.000	54.000	Pass
00 (Peak)	2400.000	5.879	65.918	71.797	--	--	--
00 (Peak)	2402.029	5.884	100.027	105.911	--	--	--
00 (Average)	2390.000	5.880	25.684	31.565	74.000	54.000	Pass
00 (Average)	2400.000	5.879	43.214	49.093	--	--	--
00 (Average)	2402.029	5.884	83.119	89.003	--	--	--

Figure Channel 00: Vertical (Peak)





Figure Channel 00: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. " * ", means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2480MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78 (Peak)	2480.022	7.086	90.742	97.827	--	--	--
78 (Peak)	2483.500	7.110	41.832	48.942	74.000	54.000	Pass
78 (Average)	2480.022	7.086	76.401	83.486	--	--	--
78 (Average)	2483.500	7.110	27.437	34.547	74.000	54.000	Pass

Figure Channel 78: Horizontal (Peak)





Figure Channel 78: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. " * ", means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2480MHz)

RF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78 (Peak)	2480.022	6.342	102.046	108.388	--	--	--
78 (Peak)	2483.500	6.363	52.890	59.253	74.000	54.000	Pass
78 (Peak)	2483.935	6.366	54.085	60.451	74.000	54.000	Pass
78 (Average)	2480.022	6.342	85.321	91.663	--	--	--
78 (Average)	2483.500	6.363	34.851	41.214	74.000	54.000	Pass

Figure Channel 78: Vertical (Peak)





Figure Channel 78: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. " * ", means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 2: Transmit - 2Mbps (4DQPSK) (2402MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2390.000	6.474	37.270	43.745	74.000	54.000	Pass
00 (Peak)	2400.000	6.528	68.735	75.263	--	--	--
00 (Peak)	2402.174	6.541	88.928	95.469	--	--	--
00 (Average)	2390.000	6.474	24.705	31.180	74.000	54.000	Pass
00 (Average)	2400.000	6.528	45.514	52.042	--	--	--
00 (Average)	2402.029	6.540	72.534	79.074	--	--	--

Figure Channel 00: Horizontal (Peak)





Figure Channel 00: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 2: Transmit - 2Mbps (4DQPSK) (2402MHz)

RF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2390.000	5.880	42.038	47.919	74.000	54.000	Pass
00 (Peak)	2400.000	5.879	78.463	84.342	--	--	--
00 (Peak)	2402.174	5.884	98.738	104.622	--	--	--
00 (Average)	2390.000	5.880	28.523	34.404	74.000	54.000	Pass
00 (Average)	2400.000	5.879	53.651	59.530	--	--	--
00 (Average)	2402.029	5.884	80.747	86.631	--	--	--

Figure Channel 00: Vertical (Peak)





Figure Channel 00: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. " * ", means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 2: Transmit - 2Mbps (4DQPSK) (2480MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78 (Peak)	2479.877	7.085	89.415	96.499	--	--	--
78 (Peak)	2483.500	7.110	42.927	50.037	74.000	54.000	Pass
78 (Average)	2480.022	7.086	73.484	80.569	--	--	--
78 (Average)	2483.500	7.110	30.086	37.196	74.000	54.000	Pass

Figure Channel 78: Horizontal (Peak)





Figure Channel 78: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 2: Transmit - 2Mbps (4DQPSK) (2480MHz)

RF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78 (Peak)	2479.877	6.341	100.689	107.030	--	--	--
78 (Peak)	2483.500	6.363	52.936	59.299	74.000	54.000	Pass
78 (Average)	2480.022	6.342	83.002	89.344	--	--	--
78 (Average)	2483.500	6.363	38.119	44.482	74.000	54.000	Pass

Figure Channel 78:

Vertical (Peak)





Figure Channel 78:

Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. " * ", means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 3: Transmit - 3Mbps (8DPSK) (2402MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2390.000	6.474	38.450	44.925	74.000	54.000	Pass
00 (Peak)	2400.000	6.528	68.217	74.745	--	--	--
00 (Peak)	2402.029	6.540	88.994	95.534	--	--	--
00 (Average)	2390.000	6.474	24.806	31.281	74.000	54.000	Pass
00 (Average)	2400.000	6.528	45.290	51.818	--	--	--
00 (Average)	2402.174	6.541	72.552	79.093	--	--	--

Figure Channel 00:

Horizontal (Peak)





Figure Channel 00:

Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 3: Transmit - 3Mbps (8DPSK) (2402MHz)

RF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2387.971	5.890	45.563	51.452	74.000	54.000	Pass
00 (Peak)	2390.000	5.880	44.046	49.927	74.000	54.000	Pass
00 (Peak)	2400.000	5.879	78.192	84.071	--	--	--
00 (Peak)	2402.029	5.884	98.803	104.687	--	--	--
00 (Average)	2390.000	5.880	28.885	34.766	74.000	54.000	Pass
00 (Average)	2400.000	5.879	53.669	59.548	--	--	--
00 (Average)	2402.029	5.884	82.117	88.001	--	--	--

Figure Channel 00:

Vertical (Peak)





Figure Channel 00:

Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 3: Transmit - 3Mbps (8DPSK) (2480MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78 (Peak)	2480.022	7.086	88.915	96.000	--	--	--
78 (Peak)	2483.500	7.110	44.643	51.753	74.000	54.000	Pass
78 (Average)	2479.877	7.085	73.732	80.816	--	--	--
78 (Average)	2483.500	7.110	29.133	36.243	74.000	54.000	Pass

Figure Channel 78: Horizontal (Peak)





Figure Channel 78: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. " * ", means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Intel® Dual Band Wireless-AC 8265
Test Item : Band Edge
Test Site : No.3 OATS
Test date : 2016.09.10
Test Mode : Mode 3: Transmit - 3Mbps (8DPSK) (2480MHz)

RF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78 (Peak)	2479.877	6.341	100.193	106.534	--	--	--
78 (Peak)	2483.500	6.363	54.664	61.027	74.000	54.000	Pass
78 (Peak)	2484.370	6.368	55.689	62.058	74.000	54.000	Pass
78 (Average)	2479.877	6.341	82.165	88.506	--	--	--
78 (Average)	2483.500	6.363	36.796	43.159	74.000	54.000	Pass

Figure Channel 78: Vertical (Peak)





Figure Channel 78: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. " * ", means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

6. EMI Reduction Method During Compliance Testing

No modification was made during testing.