

TEST REPORT

Report No.: SHATBL2404001W04

Applicant : Star Systems International Limited

Product Name : Tarvos Pro

Brand Name : SSI

Model Name : HRD31000

FCC ID : 2AA7KTARVOSPRO31000

Test Standard : 47 CFR 2.1091

Date of Test : Jan. 10,2024~Mar. 29,2024

Report Prepared by : Chris Xu
(Chris Xu)

Report Approved by : Ghost Li.
(Ghost Li)

Authorized Signatory : Terry Yang
(Terry Yang)



TABLE OF CONTENTS

REVISION HISTORY	3
DECLARATION OF REPORT	4
1. GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Factory	5
1.4 General Information of EUT	6
1.5 Equipment Specification	7
1.6 Laboratory Information	7
1.7 Applicable Standards	7
2. FCC 47CFR 2.1091 REQUIREMENT	8

REVISION HISTORY

Rev.	Issue Date	Revisions	Revised by
A0	2024.03.29	Initial Release	N/A

DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR 2.1091. And it is applicable only to the tested sample identified in the report.
2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.
3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.
4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.
5. In this report, '☐' indicates that EUT does not support content after '☐' , and '☒' indicates that it supports content after '☒'

1. GENERAL DESCRIPTION

1.1 Applicant

Name : Star Systems International Limited
Address : Unit 7, 8/F, Vanta Industrial Centre, 21-33 Tai Lin Pai Road, Kwai Chung, NT, Hong Kong

1.2 Manufacturer

Name : Star Systems International Limited
Address : Unit 7, 8/F, Vanta Industrial Centre, 21-33 Tai Lin Pai Road, Kwai Chung, NT, Hong Kong

1.3 Factory

Name : SumoSys Inc
Address : Unit 3B-C, Philexcel Business Park Annex, Clark Freeport Zone, Pampanga 2023 Philippines

1.4 General Information of EUT

General Information	
Equipment Name	Tarvos Pro
Brand Name	SSI
Model Name	HRD31000
Series Model	HRD310XY(X,Y=0-9, A-Z, a-z, blank)
Model Difference	Different in Antenna option, and names are different between models, everything else is the same.
Adapter	Model: MIT-09G-56D Brand: MsTronic Input: 90-264 V Output: 56 V Manufacturer: MSTRONIC Co., Ltd.
Battery	Model: BR-1225A/BN Brand: Panasonic Battery Rated Voltage: 3 V Charge Limit Voltage: N/A Capacity: 48 mAh Manufacturer: Panasonic
Frequency Range	902.75MHz~ 927.25MHz
Modulation Type	FHSS
Temperature Range	-40C to +70C
Hardware Version	R1
Software Version	1.1.1.32641
Connecting I/O Port(s)	Refer to the remark below.

Remark:

The above information of EUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.5 Equipment Specification

Table for Filed Antenna
Antenna 1(External Antenna)

Ant.	Brand	Model Name	Antenna Name	Connector	Gain (dBi)	Antenna Cable loss (dB)	Antenna combination(dB)
1	SSI	Tarvos Pro (HRD31000)	Avior	N/A	15	12	3
2	SSI	Tarvos Pro (HRD31000)	Avalon	N/A	13	12	1
3	SSI	Tarvos Pro (HRD31000)	Cheetah	N/A	12	12	0
4	SSI	Tarvos Pro (HRD31000)	Kuma	N/A	10	12	-2
5	SSI	Tarvos Pro (HRD31000)	Bobcat	N/A	8	12	-4

Antenna 2(Internal Antenna)

Ant.	Brand	Model Name	Antenna Name	Connector	Gain (dBi)	Antenna Cable loss (dB)	Antenna combination(dB)
1	SSI	Tarvos Pro (HRD31000)	Avalon	N/A	13	0	13

1.6 Laboratory Information

Company Name	:	Shanghai ATBL Technology Co., Ltd.
Address	:	Building 8,No.160 Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone	:	+86(0)21-51298625

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

47 CFR Part 2.1091

FCC KDB 447498 D01 Interim General RF Exposure Guidance v06

2. FCC 47CFR 2.1091 REQUIREMENT

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

*Note:

1. f= Frequency in MHz * Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

CALCULATION

A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated.

Antenna 1(External Antenna):

EUT Antenna Gain=3dBi (Numeric 1.99), $\pi=3.14$, R=45cm

FCC Rules	Frequency	Output Power	Output Power	Power Density	Power Density Limit	Result
	MHz	dBm	mW	mW/cm ²	mW/cm ²	Pass/Fail
§ 2.1091	902.75	29.36	862.979	0.05	0.6	Pass

Antenna 2(Internal Antenna):

EUT Antenna Gain=13dBi (Numeric 19.95), $\pi=3.14$, R=45cm

FCC Rules	Frequency	Output Power	Output Power	Power Density	Power Density Limit	Result
	MHz	dBm	mW	mW/cm ²	mW/cm ²	Pass/Fail
§ 2.1091	902.75	29.00	794.328	0.199	0.6	Pass

Note:

1. only worst case was recorded in the test report.
- 2.The calculated distance is 45 cm.
- 3.The EUT internal antenna, external antenna,Simultaneous transmission is not supported.

*****END OF THE REPORT*****