

# 1. RF Exposure Requirements

---

## 1.1 General Information

### Client Information

Applicant:	Rollease Acmeda Inc
Address of applicant:	750 East Main Street, 7th Floor Stamford, CT 06902, United States of America
Manufacturer:	Rollease Acmeda Inc
Address of manufacturer:	750 East Main Street, 7th Floor Stamford, CT 06902, United States of America

### General Description of EUT:

Product Name:	Pulse PRO, Wireless Link PRO, Pulse PRO
Trade Name:	/
Model No.:	MT02-5401-050001
Adding Model(s):	MT02-5401-067002, MT02-5401-050003
Rated Voltage:	DC5V
	MODEL:GPE006E-050100-Z
Power Adaptor :	INPUT:100-240V~50/60Hz 0.2A
	OUTPUT:DC5.0V,1.0A 5.0W Max
FCC ID:	2AGGZ003B9ACA59
Equipment Type:	Mobile device

### Technical Characteristics of EUT:

Frequency Range:	433.92 MHz
Max. Field Strength:	433.92MHz: 91.82dBuV/m(3m)
Data Rate:	/
Modulation:	ASK
Antenna Type:	Chip Antenna
Antenna Gain:	0.79dBi

## 1.2 RF Exposure Exemption

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

**Option A:** FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

**Option B:** FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula.  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

**Option C:** FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$
300-1,500	$0.0128 R^2 f$
1,500-100,000	$19.2 R^2$

**For Multiple RF sources:** FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

### 1.3 Calculated Result

Radio Access Technology	Prediction Frequency (MHz)	Max. Field Strength (dBuV/m)	Antenna Gain (dBi)	Output Power (dBm)	Tune-Up Power (dBm)	ERP (dBm)
SRD	433.92	91.82	0.79	-4.23	-4.00	-5.36

Radio Access Technology	Prediction Frequency (MHz)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	Tune-Up Time-Averaged Power (dBm)	ERP (dBm)
Wi-Fi	2412	26.62	3.4	100	27.00	28.25
BT BLE	2402	6.80	3.4	100	7.00	8.25

Frequency (MHz)	Option	Min. Distance (cm)	Max. Power (dBm)	Max. Power (mW)	Exposure Limit (mW)	Ratio	Result Pass/Fail
433.92	C	20.00	-5.36	0.29	222.17	0.01	Pass
2412	C	20.00	28.25	668.34	768.00	0.87	Pass
2402	C	20.00	8.25	6.68	768.00	0.01	Pass

Note: 1.  $EIRP = E - 104.8 + 20 \log D$ ; Output Power =  $EIRP - \text{Antenna Gain}$ ;

$ERP = EIRP - 2.15 \text{ dB}$

2. Option A, B and C refers as clause 1.2.

3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power.

For option C, ERP converts to Max. Power;

4. For option B,  $P_{th}$  (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure Limit (mW).

5. Ratio = Tune-Up ERP (mW) / Exposure Limit (mW)

**Mode for Simultaneous Multi-band Transmission:**

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result
					Pass/Fail
SRD + Wi-Fi	0.01	0.87	0.88	1	Pass
SRD + BT BLE	0.01	0.01	0.02	1	Pass

*Note 1: For Wi-Fi & Bluetooth Internet of Things Module (FCC ID: 2AC7Z-ESP32WROVERE; the issue date: 01/31/2022)*

*Wi-Fi(2.4G) Maximum peak output power (dBm):26.62; Antenna Gain (dBi):3.4*

*BT BLE Maximum peak output power (dBm):6.80; Antenna Gain (dBi):3.4*

*Note 2: BT and Wi-Fi can't transmit at the same time.*

Result: Pass