



MEASUREMENT REPORT

FCC PART 22H, 24E, 27

FCC ID: HLEHT730BTNFL

APPLICANT: Unitech Electronics Co., Ltd.

Application Type: Certification

Product: Handheld Data Terminal

Model No.: HT730

Brand Name: unitech

FCC Classification: PCS Licensed Transmitter held to ear (PCE)

FCC Rule Part(s): Part2, Part22 Subpart H, Part24 Subpart E, Part27

Test Procedure(s): ANSI/TIA-603-E-2016

Received Date: January 6, 2021

Test Date: February 3 ~ March 3, 2021

Tested By : Peter Syu
(Peter Syu)

Reviewed By : Paddy Chen
(Paddy Chen)

Approved By : Chenz Ker
(Chenz Ker)



The test results only relate to the tested sample.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2101TW2601-U8	1.0	Original Report	2021-03-17	

CONTENTS

Description	Page
§2.1033 General Information	5
1. INTRODUCTION	6
1.1. Scope	6
1.2. MRT Test Location	6
2. PRODUCT INFORMATION	7
2.1. Feature of Equipment under Test.....	7
2.2. Equipment Description	8
2.3. Device Capabilities	8
2.4. Test Configuration	8
2.5. EMI Suppression Device(s)/Modifications.....	8
3. DESCRIPTION OF TEST	9
3.1. Evaluation Procedure	9
3.2. Cellular – Base Frequency Blocks	9
3.3. Cellular – Mobile Frequency Blocks.....	9
3.4. PCS – Base Frequency Blocks.....	10
3.5. PCS – Mobile Frequency Blocks	10
3.6. Occupied Bandwidth.....	11
3.7. Spurious and Harmonic Emissions at Antenna Terminal	11
3.8. Power and Radiated Spurious Emissions	12
3.9. Peak-Average Ratio	13
3.10. Frequency Stability / Temperature Variation	13
4. TEST EQUIPMENT CALIBRATION DATE.....	14
5. SAMPLE CALCULATIONS	15
6. MEASUREMENT UNCERTAINTY.....	16
7. TEST RESULT	17
7.1. Summary.....	17
7.2. Occupied Bandwidth.....	19
7.2.1. Test Limit	19
7.2.2. Test Procedure used.....	19
7.2.3. Test Setting.....	19
7.2.4. Test Setup	19
7.2.5. Test Result.....	20
7.3. Conducted Spurious Emissions	37

7.3.1. Test Limit	37
7.3.2. Test Procedure Used	37
7.3.3. Test Setting	37
7.3.4. Test Setup	37
7.3.5. Test Result	38
7.4. Band Edge at Antenna Terminal	112
7.4.1. Test Limit	112
7.4.2. Test Procedure Used	112
7.4.3. Test Setting	112
7.4.4. Test Setup	113
7.4.5. Test Result	114
7.5. Power and Radiated Spurious Emissions	169
7.5.1 Test Limit	169
7.5.2 Test Procedure Used	169
7.5.3 Test Setting	170
7.5.4 Test Setup	172
7.5.5 Test Result	173
7.6. Peak-Average Ratio	215
7.6.1 Test Limit	215
7.6.2 Test Procedure	215
7.6.3 Test Setup	215
7.6.4 Test Result	216
7.7. Frequency Stability Under Temperature & Voltage Variations	233
7.7.1 Test Limit	233
7.7.2 Test Procedure	233
7.7.3 Test Setup	233
7.7.4 Test Result	234

§2.1033 General Information

Applicant	Unitech Electronics Co., Ltd.
Applicant Address	5F, No. 136, Lane 235, Pao-Chiao Rd., Hsin-Tien Dist., New Taipei City, Taiwan
Manufacturer	Unitech Electronics Co., Ltd.
Manufacturer Address	5F, No. 136, Lane 235, Pao-Chiao Rd., Hsin-Tien Dist., New Taipei City, Taiwan
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT FCC Registration No.	153292
FCC Rule Part(s)	Part 22H, Part 24E, Part27
Test Device Serial No.	#1 <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Fuxing Rd., Taoyuan, Taiwan (R.O.C)

- MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
- MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
- MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Feature of Equipment under Test

Product Name	Handheld Data Terminal
Model No.	HT730
Brand Name	unitech
Supports Radios Spec.	WPAN: Bluetooth Dual Mode: V5.1 NFC 13.56MHz WLAN: 2.4G: 802.11b/g/n-20/n-40 5G: 802.11a/n-20/ac-20/n-40/ac-40/ac-80, Band 1,2,3,4 WWAN: 3G: Band 2, 5 4G: Band 2,4,5,7,17,41 GNSS: GPS, GLONASS, Galileo, BeiDou
4G Operation Band (s)	Band 2, 4, 5, 7, 17, 41
Frequency Range	Band2: 1850MHz–1910MHz Band4: 1710MHz–1755MHz Band5: 824MHz–849MHz Band7: 2500MHz–2570MHz Band17: 704MHz–716MHz Band41: 2555MHz-2655MHz
Power Adapter	Brand: TEN PAO Model No: S018BYU1200150 Input: AC 100-240V ~ 50-60Hz 600mA Output: DC 5V/9V/12V, 3A/2A/1.5A

Note: There are two types of keyboard on this product, the only difference is the number of buttons. This report only evaluated the product with more buttons.

2.2. Equipment Description

Antenna Type	FPCB
Antenna M/N	SAA31559A
Antenna Gain	Band 2: -1.05dBi, Band 4: -1.02dBi, Band 5: -1.46dBi, Band 7: -1.29dBi Band 17: -4.03dBi, Band 41: -1.04dBi
Type of Modulation	QPSK, 16QAM

Note: The test report has showed the worst test mode.

2.3. Device Capabilities

This device contains the following capabilities:

LTE Band 2, 4, 5, 7, 17, 41

2.4. Test Configuration

The **Handheld Data Terminal** was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01v03r01. See section 3.0 of this report for a description of the radiated and antenna port conducted emissions tests.

2.5. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

3. DESCRIPTION OF TEST


3.1. Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168) were used in the measurement of the **Handheld Data Terminal**

Deviation from measurement procedure.....None


3.2. Cellular – Base Frequency Blocks

\$22.905




3.3. Cellular – Mobile Frequency Blocks

\$22.905




3.4. PCS – Base Frequency Blocks

§24.229



3.5. PCS – Mobile Frequency Blocks

§24.229



3.6. Occupied Bandwidth

§2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The spectrum analyzers' "occupied bandwidth" measurement function was used to record the occupied bandwidth in accordance with KDB 971168.

3.7. Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

3.8. Power and Radiated Spurious Emissions

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurement and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 80cm high PVC support structure is placed on top of the turntable.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d [\text{dBm}] = P_g [\text{dBm}] - \text{cable loss} [\text{dB}] + \text{antenna gain} [\text{dBd/dBi}]$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g [\text{dBm}] - \text{cable loss} [\text{dB}]$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10 \cdot \log_{10}(\text{Power} [\text{Watts}])$ specified in 22.917(a).

3.9. Peak-Average Ratio

§24.232(d)

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

For pulsed signals, the spectrum analyzer is set to use an internal “RF Burst” trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the “on time” of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power. For continuous signals, the trigger is set to “free run” in the CCDF measurement mode.

3.10. Frequency Stability / Temperature Variation

§2.1055 §22.355 §22.863 §22.905 §24.229 §24.235

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

4. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2021/3/26
Cable	Rosnol	N1C50-RG400-B 1C50-500CM	MRTTWE00013	1 year	2021/6/21
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2021/3/25

Radiated Emissions – AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2021/10/5
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2021/3/25
Active Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2021/4/27
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2021/4/24
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2021/4/24
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2021/4/24
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2021/4/24
Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2021/6/16
Cable	Rosnol	K1K50-UP0264- K1K50-4M	MRTTWE00012	1 year	2021/6/21

Conducted Test Equipment – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2021/10/14
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2021/7/14
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2021/3/26
Wideband Radio Communication Taster	R&S	CMW 500	MRTTWA00084	1 year	2021/9/8

Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software
EMI	V3	EMI Test Software

5. SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EGPRS Emission Designator

Emission Designator = 250KG7W

GSM BW = 250 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA / CDMA Emission Designator

Emission Designator = 1M25F9W

WCDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

LTE Emission Designator

Emission Designator = QPSK 5M00G7D / 16QAM 5M00W7D

LTE BW = 1.4/3/5/10/15/20 MHz

QPSK G = Phase Modulation /

16QAM W= in a combination of two or more of the following modes: amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission

Example: Spurious emission at 1688.10 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -65.0dBm. The gain of the substituted antenna is 6.5dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -65.0dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 4.5 dB at 1688.1MHz. So 2 dB is added to the signal generator reading of -25dBm yielding -23dBm. The fundamental EIRP was 24.0dBm so this harmonic was 24.0dBm - (-23) = 47dBc.

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

Radiated Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 3.92dB (Below 30M)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 4.25dB (30M~1G)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 4.40dB (1G~18G)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 4.45dB (18G~40G)
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 78.4\text{Hz}$
Conducted Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 2.65\text{ dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 3.3%
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 0.82^\circ\text{C}/ \pm 3\%$
DC Voltage
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 0.3\%$

7. TEST RESULT

7.1. Summary

Company Name: Unitech Electronics Co., Ltd.
FCC Classification: PCS Licensed Transmitter (PCB)
Mode(s): LTE Band 2, 4, 5, 7, 17, 41

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
Transmitter Mode(TX)					
2.1049	Occupied bandwidth	N/A	Conducted	Pass	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(c) 27.52(h)	Conducted Spurious Emissions	$> 43 + 10\log_{10} (P[\text{Watts}])$ at for all out-of-band emissions (Band 2,4,5,12,13,17)		Pass	Section 7.3
2.1051 27.53(m)		$> 55 + 10\log_{10} (P[\text{Watts}])$ at for all out-of-band emissions (Band 7.41)			
2.1051 22.917(a) 24.238(a) 27.53(c) 27.52(h)	Band Edge	$> 43 + 10\log_{10} (P[\text{Watts}])$ at for all out-of-band emissions		Pass	Section 7.4
27.53(m)		27.53(m)(4)			
2.1046	Conducted Output Power	N/A		Pass	Section 7.5
22.913(a)	Radiated Output Power	$< 7 \text{ Watts max. ERP}$ (Band 5)	Radiated	Pass	Section 7.5
24.232(c) 27.50(d)(h)		$< 2 \text{ Watts max. EIRP}$ (Band 2, 7,41)		Pass	
27.50(b)		$< 3 \text{ Watts max. ERP}$ (Band 12,13,17)		Pass	
27.50(d)		$< 1 \text{ Watts max. EIRP}$ (Band 4)		Pass	

2.1053 22.917(a) 24.238(a) 27.53(c) 27.53(h)	Radiated Spurious Emissions	> 43 + \log_{10} (P[Watts]) for all out-of-band emissions (Band 2,4,5,12,13,17)	Radiated	Pass	Section 7.5
2.1053 27.53(m)		> 55 + $10\log_{10}$ (P[Watts]) for all out-of-band emissions (Band 7)			
24.232(d) 27.50(B)	Peak-Average Ratio	<13dB	Conducted	Pass	Section 7.6
2.1055 22.355	Frequency Stability	< 2.5 ppm		Pass	Section 7.7
2.1055 24.235 27.54		Within Authorized Band			

Notes:

- 1) Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- 2) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

7.2. Occupied Bandwidth

7.2.1. Test Limit

N/A


7.2.2. Test Procedure used

KDB 971168 D01v03r01 – Section 4.2 & ANSI/TIA-603-E-2016

7.2.3. Test Setting

1. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
2. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW. (RBW = approximately 1% of the emission bandwidth).
3. Set the detection mode to peak, and the trace mode to max hold.
4. Use the 99 % power bandwidth function of the spectrum analyzer (if available) and report the measured bandwidth.


7.2.4. Test Setup




7.2.5. Test Result

Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 2	CH18900 (1880MHz)	QPSK	1.4	6	0	1.080	1.222	Pass
			3	15	0	2.686	2.978	Pass
			5	25	0	4.494	4.936	Pass
			10	50	0	8.951	9.724	Pass
			15	75	0	13.359	14.410	Pass
			20	100	0	17.843	19.050	Pass
		16QAM	1.4	6	0	1.082	1.228	Pass
			3	15	0	2.690	2.965	Pass
			5	25	0	4.488	4.889	Pass
			10	50	0	8.965	9.717	Pass
			15	75	0	13.388	14.330	Pass
			20	100	0	17.870	19.210	Pass


LTE Band 2 QPSK 1.4MHz CH18900 6RB#0




LTE Band 2 QPSK 3MHz CH18900 15RB#0




LTE Band 2 QPSK 5MHz CH18900 25RB#0




LTE Band 2 QPSK 10MHz CH18900 50RB#0




LTE Band 2 QPSK 15MHz CH18900 75RB#0




LTE Band 2 QPSK 20MHz CH18900 100RB#0




LTE Band 2 16QAM 1.4MHz CH18900 6RB#0




LTE Band 2 16QAM 3MHz CH18900 15RB#0




LTE Band 2 16QAM 5MHz CH18900 25RB#0




LTE Band 2 16QAM 10MHz CH18900 50RB#0



LTE Band 2 16QAM 15MHz CH18900 75RB#0




LTE Band 2 16QAM 20MHz CH18900 100RB#0




Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 4	CH20175 (1732.5MHz)	QPSK	1.4	6	0	1.082	1.218	Pass
			3	15	0	2.686	2.986	Pass
			5	25	0	4.475	4.882	Pass
			10	50	0	8.944	9.769	Pass
			15	75	0	13.352	14.360	Pass
			20	100	0	17.846	19.130	Pass
		16QAM	1.4	6	0	1.087	1.229	Pass
			3	15	0	2.689	2.963	Pass
			5	25	0	4.461	4.789	Pass
			10	50	0	8.951	9.671	Pass
			15	75	0	13.367	14.350	Pass
			20	100	0	17.843	19.980	Pass


LTE Band 4 QPSK 1.4MHz CH20175 6RB#0




LTE Band 4 QPSK 3MHz CH20175 15RB#0




LTE Band 4 QPSK 5MHz CH20175 25RB#0




LTE Band 4 QPSK 10MHz CH20175 50RB#0




LTE Band 4 QPSK 15MHz CH20175 75RB#0




LTE Band 4 QPSK 20MHz CH20175 100RB#0




LTE Band 4 16QAM 1.4MHz CH20175 6RB#0




LTE Band 4 16QAM 3MHz CH20175 15RB#0




LTE Band 4 16QAM 5MHz CH20175 25RB#0




LTE Band 4 16QAM 10MHz CH20175 50RB#0



LTE Band 4 16QAM 15MHz CH20175 75RB#0




LTE Band 4 16QAM 20MHz CH20175 100RB#0




Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 5	CH20525 (836.5MHz)	QPSK	1.4	6	0	1.077	1.211	Pass
			3	15	0	2.682	2.982	Pass
			5	25	0	4.490	4.870	Pass
			10	50	0	8.957	9.701	Pass
		16QAM	1.4	6	0	1.082	1.217	Pass
			3	15	0	2.689	2.954	Pass
			5	25	0	4.484	4.890	Pass
			10	50	0	8.953	9.746	Pass


LTE Band 5 QPSK 1.4MHz CH20525 6RB#0




LTE Band 5 QPSK 3MHz CH20525 15RB#0




LTE Band 5 QPSK 5MHz CH20525 25RB#0




LTE Band 5 QPSK 10MHz CH20525 50RB#0




LTE Band 5 16QAM 1.4MHz CH20525 6RB#0




LTE Band 5 16QAM 3MHz CH20525 15RB#0



LTE Band 5 16QAM 5MHz CH20525 25RB#0




LTE Band 5 16QAM 10MHz CH20525 50RB#0




Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 7	CH21100 (2535MHz)	QPSK	5	25	0	4.492	4.932	Pass
			10	50	0	8.946	9.674	Pass
			15	75	0	13.360	14.210	Pass
			20	100	0	17.876	19.210	Pass
		16QAM	5	25	0	4.489	4.921	Pass
			10	50	0	8.964	9.701	Pass
			15	75	0	13.375	14.390	Pass
			20	100	0	17.850	19.150	Pass


LTE Band 7 QPSK 5MHz CH21100 25RB#0




LTE Band 7 QPSK 10MHz CH21100 50RB#0




LTE Band 7 QPSK 15MHz CH21100 75RB#0




LTE Band 7 QPSK 20MHz CH21100 100RB#0




LTE Band 7 16QAM 5MHz CH21100 25RB#0




LTE Band 7 16QAM 10MHz CH21100 50RB#0



LTE Band 7 16QAM 15MHz CH21100 75RB#0




LTE Band 7 16QAM 20MHz CH21100 100RB#0




Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 17	CH23790 (710MHz)	QPSK	5	25	0	4.466	4.876	Pass
			10	50	0	8.962	9.513	Pass
		16QAM	5	25	0	4.481	4.906	Pass
			10	50	0	8.967	9.647	Pass


LTE Band 17 QPSK 5MHz CH23790 25RB#0




LTE Band 17 QPSK 10MHz CH23790 50RB#0



LTE Band 17 16QAM 5MHz CH23790 25RB#0




LTE Band 17 16QAM 10MHz CH23790 50RB#0




Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 41	CH40740 (2605MHz)	QPSK	5	25	0	4.483	5.058	Pass
			10	50	0	8.946	9.670	Pass
			15	75	0	13.380	14.310	Pass
			20	100	0	17.850	19.150	Pass
		16QAM	5	25	0	4.462	4.887	Pass
			10	50	0	8.947	9.598	Pass
			15	75	0	13.378	14.380	Pass
			20	100	0	17.875	19.030	Pass


LTE Band 41 QPSK 5MHz CH40740 25RB#0




LTE Band 41 QPSK 10MHz CH40740 50RB#0




LTE Band 41 QPSK 15MHz CH40740 75RB#0




LTE Band 41 QPSK 20MHz CH40740 100RB#0




LTE Band 41 16QAM 5MHz CH40740 25RB#0




LTE Band 41 16QAM 10MHz CH40740 50RB#0



LTE Band 41 16QAM 15MHz CH40740 75RB#0



LTE Band 41 16QAM 20MHz CH40740 100RB#0



7.3. Conducted Spurious Emissions

7.3.1. Test Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log_{10}(P)$ dB for Band 2,4,5,12,13,17/ $55 + 10\log_{10}(P)$ dB for Band7.


7.3.2. Test Procedure Used

KDB 971168 D01v03r01 – Section 6.0 & ANSI/TIA-603-E-2016

7.3.3. Test Setting

Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz is at or below 1GHz and 1MHz is above 1GHz, If any, up to 10th harmonic.

7.3.4. Test Setup




7.3.5. Test Result


Test Mode	Modulation	Channel/ Frequency (MHz)	Bandwidth (MHz)	RB Size	RB Offset	Test Result
LTE Band 2 (Low Channel)	QPSK	CH18607 / 1850.7MHz	1.4	1	2	Pass
		CH18615 / 1851.5MHz	3	1	7	Pass
		CH18625 / 1852.5MHz	5	1	12	Pass
		CH18650 / 1855MHz	10	1	25	Pass
		CH18675 / 1857.5MHz	15	1	36	Pass
		CH18700 / 1860MHz	20	1	49	Pass
	16QAM	CH18607 / 1850.7MHz	1.4	1	2	Pass
		CH18615 / 1851.5MHz	3	1	7	Pass
		CH18625 / 1852.5MHz	5	1	12	Pass
		CH18650 / 1855MHz	10	1	25	Pass
		CH18675 / 1857.5MHz	15	1	36	Pass
		CH18700 / 1860MHz	20	1	49	Pass
LTE Band 2 (Middle Channel)	QPSK	CH18900 / 1880MHz	1.4	1	2	Pass
			3	1	7	Pass
			5	1	12	Pass
			10	1	25	Pass
			15	1	36	Pass
			20	1	49	Pass
	16QAM		1.4	1	2	Pass
			3	1	7	Pass
			5	1	12	Pass
			10	1	25	Pass
			15	1	36	Pass
			20	1	49	Pass

Test Mode	Modulation	Channel/ Frequency (MHz)	Bandwidth (MHz)	RB Size	RB Offset	Test Result
LTE Band 2 (High Channel)	QPSK	CH19193 / 1909.3MHz	1.4	1	2	Pass
		CH19185 / 1908.5MHz	3	1	7	Pass
		CH19175 / 1907.5MHz	5	1	12	Pass
		CH19150 / 1905MHz	10	1	25	Pass
		CH19125 / 1902.5MHz	15	1	36	Pass
		CH19100 / 1900MHz	20	1	49	Pass
	16QAM	CH19193 / 1909.3MHz	1.4	1	2	Pass
		CH19185 / 1908.5MHz	3	1	7	Pass
		CH19175 / 1907.5MHz	5	1	12	Pass
		CH19150 / 1905MHz	10	1	25	Pass
		CH19125 / 1902.5MHz	15	1	36	Pass
		CH19100 / 1900MHz	20	1	49	Pass


LTE Band 2 QPSK 1.4MHz CH18607 1RB#2_30MHz-1GHz




LTE Band 2 QPSK 1.4MHz CH18607 1RB#2_1GHz-20GHz




LTE Band 2 QPSK 3MHz CH18615 1RB#7_30MHz-1GHz



LTE Band 2 QPSK 3MHz CH18615 1RB#7_1GHz-20GHz



LTE Band 2 QPSK 5MHz CH18625 1RB#12_30MHz-1GHz



LTE Band 2 QPSK 5MHz CH18625 1RB#12_1GHz-20GHz

