

Prüfbericht-Nr.: Test report no.:	CN244E0L 005	Auftrags-Nr.: Order no.:	168449632	Seite 1 von 37 Page 1 of 37
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2023-10-26	
Auftraggeber: Client:	SZ DJI Osmo Technology Co.,Ltd. 4F, Jingkou Community Comprehensive Service Building, No. 83 Bishui Road North, Guangming Street, Guangming District, Shenzhen, China			
Prüfgegenstand: Test item:	DJI SDR Transmission			
Bezeichnung / Typ-Nr.: Identification / Type no.:	TX5 (Trademark: DJI)			
Auftrags-Inhalt: Order content:	FCC approval			
Prüfgrundlage: Test specification:	FCC 47 CFR § 2.1093 IEEE Std 1528-2013 IC RSS-102 Issue 5: March 2015 IEC/62209-1528: 2020 Published RF exposure KDB procedures			
Wareneingangsdatum: Date of sample receipt:	2023-12-29	Please refer to Photo Document		
Prüfmuster-Nr.: Test sample no.:	A003634023-002			
Prüfzeitraum: Testing period:	2024-01-29 –2024-02-04			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	<u>X Bell Hu</u>		genehmigt von: authorized by:	<u>X Jonathan Li</u>
Datum: Date: 2024-05-21	Signed by: Bell Hu		Ausstellungsdatum: Issue date: 2024-05-21	Signed by: Jonathan Li
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert
Sonstiges / Other:	FCC ID: 2ANDR-TX53209			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				

Prüfbericht - Nr.: CN244E0L 005

Test Report No.

Seite 2 von 37

Page 2 of 37

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system.</i> <i>Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. <i>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Table of Contents

1.	GENERAL INFORMATION.....	5
1.1.	STATEMENT OF COMPLIANCE	5
1.2.	EQUIPMENT UNDER TEST (EUT) INFORMATION.....	6
1.2.1.	<i>General Information</i>	<i>6</i>
2.	TEST SITES	7
2.1.	TEST FACILITIES	7
2.2.	AMBIENT CONDITION.....	7
2.3.	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	8
3.	MEASUREMENT UNCERTAINTY.....	9
4.	TEST SPECIFICATION, METHODS AND PROCEDURES.....	11
5.	SAR MEASUREMENT SYSTEM.....	12
5.1.	DEFINITION OF SPECIFIC ABSORPTION RATE (SAR).....	12
5.2.	SPEAG DASY SYSTEM	12
5.2.1.	<i>Robot.....</i>	<i>13</i>
5.2.2.	<i>Probes.....</i>	<i>14</i>
5.2.3.	<i>Data Acquisition Electronics (DAE)</i>	<i>14</i>
5.2.4.	<i>Phantoms.....</i>	<i>15</i>
5.2.5.	<i>Device Holder</i>	<i>16</i>
5.2.6.	<i>System Validation Dipoles</i>	<i>16</i>
5.2.7.	<i>Tissue Simulating Liquids</i>	<i>17</i>
5.2.8.	<i>SAR System Verification.....</i>	<i>20</i>
6.	SAR MEASUREMENT PROCEDURE	21
6.1.	AREA & ZOOM SCAN PROCEDURE	21
6.2.	VOLUME SCAN PROCEDURE.....	21
6.3.	POWER DRIFT MONITORING	22
6.4.	SPATIAL PEAK SAR EVALUATION	22
6.5.	SAR AVERAGED METHODS.....	22
7.	SAR MEASUREMENT EVALUATION	23
7.1.	EUT CONFIGURATION AND SETTING	23
7.2.	EUT TESTING POSITION.....	24
7.2.1.	<i>Extremity Exposure Conditions.....</i>	<i>24</i>
7.3.	TISSUE VERIFICATION	25
7.4.	SYSTEM VALIDATION.....	25
7.5.	SYSTEM VERIFICATION.....	25
7.6.	MAXIMUM CONDUCTED POWER	26
7.7.	SIMULTANEOUS TRANSMISSION POSSIBILITIES.....	29
7.8.	SAR TESTING RESULTS.....	30
7.8.1.	<i>SAR Test Reduction Considerations</i>	<i>30</i>

Prüfbericht - Nr.: CN244E0L 005
Test Report No.

Seite 4 von 37

Page 4 of 37

7.8.2.	SAR Results for Extremity Exposure Condition (Separation Distance is 0 cm Gap)	31
7.8.3.	SAR Measurement Variability	34
7.8.4.	<SAR Summation Analysis>	35

APPENDIXES	37
-------------------------	-----------

Appendix A: SAR Plots of System Verification
Appendix B: SAR Plots of SAR Measurement
Appendix C: Calibration Certificate for probe and Dipole
Appendix D: Photographs of setup and antenna Location Diagram

1. General Information

1.1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows:

Mode	Highest Reported Extremity SAR _{10g} (0 cm Gap) (W/kg)	Limit Extremity SAR _{10g} (W/kg)
WLAN 2.4G	1.77	4.0
WLAN 5.1G	2.53	
SDR 2.4G	0.45	
SDR 5.6G	0.79	
SDR 5.8G	1.80	
Highest Simultaneous Transmission SAR (MIMO)	Extremity SAR _{10g} (0 cm Gap) (W/kg)	
WLAN 2.4G+SDR 5G	2.71	
WLAN 5G+SDR 2.4G	2.60	
WLAN 5G+SDR 5G	3.14	

Note:

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/kg as averaged over any 1 gram of tissue; 10-gram SAR for Product Specific 10g SAR, limit: 4.0W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992/ IC RSS-102 Issue 5:2015, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Prüfbericht - Nr.: CN244E0L 005

Test Report No.

Seite 6 von 37

Page 6 of 37

1.2. Equipment Under Test (EUT) Information**1.2.1. General Information**

General Information of EUT	Value
Kind of Equipment	DJI SDR Transmission
Type Designation	TX5
Trademark	DJI
FCC ID	2ANDR-TX53209
Testing Voltage	DC 7.4V
Extreme Temperature Range	-10°C to +45°C
Radiofrequency operating mode	1) 2.4GHz SDR: operating within 2400-2483.5MHz, supports 1.4MHz/3MHz/10MHz/20MHz/40MHz Bandwidth 2) 2.4GHz Wi-Fi: operating within 2400-2483.5MHz, supports 20MHz/40MHz Bandwidth and IEEE 802.11 b/g/n20/n40/ax20/ax40 3) 5.2GHz Wi-Fi: operating within 5150-5250MHz, supports 20MHz/40MHz/80MHz Bandwidth and IEEE 802.11 a/n20/n40/ac20/ac40/ac80/ax20/ax40/ax80 4) 5.6GHz SDR: operating within 5470-5725MHz, supports 20MHz/40MHz Bandwidth (Transmitting only) 5) 5.8GHz SDR: operating within 5725-5850MHz, supports 1.4MHz/3MHz/10MHz/20MHz/40MHz Bandwidth

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

2. Test Sites

2.1. Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

No. 362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China

A2LA Cert. No.: 5162.01

FCC Registration No.: 694916

IC Registration No.: 25069

2.2. Ambient Condition

Ambient Temperature	21.8°C - 22.7°C
Relative Humidity	42% - 57%

2.3. List of Test and Measurement Instruments

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D2450V2	1014	May. 19, 2021	3 years
System Validation Dipole	SPEAG	D5GHzV2	1280	May. 17, 2021	3 years
Dosimetric E-Field Probe	SPEAG	EX3DV4	7506	Jun. 29, 2023	1 year
Data Acquisition Electronics	SPEAG	DAE4	1557	Jul. 6, 2023	1 year
Signal Analyzer	R&S	FSV 7	103665	Jul. 25, 2023	1 year
Vector Network Analyzer	R&S	ZNB 8	107040	Jul. 25, 2023	1 year
Dielectric assessment Kit	SPEAG	DAK-3.5	1269	Jun. 26, 2023	1 year
Signal Generator	R&S	SMB 100A	180840	Jul. 25, 2023	1 year
EPM Series Power Meter	Keysight	N1914A	MY58240005	Nov. 14, 2023	1 year
Power Sensor	Keysight	N8481H	MY58250002	Nov. 14, 2023	1 year
Power Sensor	Keysight	N8481H	MY58250006	Nov. 14, 2023	1 year
DC Power Supply	Topward	3303D	809332	Nov. 14, 2023	1 year
Coaxial Directional Coupler	Keysight	773D	MY52180552	Nov. 14, 2023	1 year
Coaxial Directional Coupler	shhuaxiang	DTO-0.4/3.9-10	18052101	Nov. 14, 2023	1 year
Coaxial attenuator	Keysight	8491A	MY52463219	Nov. 14, 2023	1 year
Coaxial attenuator	Keysight	8491A	MY52463210	Nov. 14, 2023	1 year
Coaxial attenuator	Keysight	8491A	MY52463222	Nov. 14, 2023	1 year
Digital Thermometer	LKM	DTM3000	3116	Nov. 14, 2023	1 year
Power Amplifier Mini circuit	mini-circuits	ZHL-42W	SN002101809	N/A	N/A
Power Amplifier Mini circuit	mini-circuits	ZVE-8G	SN070501814	N/A	N/A

3. Measurement Uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)	Vi Veff
Measurement System Errors								
Probe Calibration	±13.3%	Normal (k=2)	2	1	1	± 6.65 %	± 6.65 %	∞
Probe Calibration Drift	±1.7%	Rectangular	√3	1	1	±1.0%	±1.0%	∞
Probe Linearity	±4.7%	Rectangular	√3	1	1	±2.7%	±2.7%	∞
Broadband Signal	±3.0%	Rectangular	√3	1	1	±1.7%	±1.7%	∞
Probe Isotropy	±7.6%	Rectangular	√3	1	1	±4.4%	±4.4%	∞
Other Probe + Electronic	±0.7%	Normal	1	1	1	±0.7%	±0.7%	∞
RF Ambient	±1.8%	Normal	1	1	1	±1.8%	±1.8%	∞
Probe Positioning	±0.006mm	Normal	1	0.14	0.14	±0.10%	±0.10%	∞
Data Processing	±1.2%	Normal	1	1	1	±1.2%	±1.2%	∞
Phantom and Device Errors								
Conductivity (meas.) ^{DAK}	±2.5%	Normal	1	0.78	0.71	±2.0%	±1.8%	100
Conductivity (temp.) ^{BB}	±3.3%	Rectangular	√3	0.78	0.71	±1.5%	±1.4%	∞
Phantom Permittivity	±14.0%	Rectangular	√3	0	0	±0%	±0%	∞
Distance DUT – TSL	±2.0%	Normal	1	2	2	±4.0%	±4.0%	∞
Device Positioning	±2.4%/±2.8%	Normal	1	1	1	±2.8%	±2.8%	30
Device Holder	±3.4%/±3.5%	Normal	1	1	1	±3.5%	±3.5%	30
DUT Modulation ^m	±2.4%	Rectangular	√3	1	1	±1.4%	±1.4%	∞
Time-average SAR	±1.7%	Rectangular	√3	1	1	±1.0%	±1.0%	∞
DUT drift	±2.5%	Normal	1	1	1	±2.5%	±2.5%	30
Val Antenna Unc. ^{val}	±0.0%	Normal	1	1	1	±0%	±0%	
Unc. Input Power ^{val}	±0.0%	Normal	1	1	1	±0%	±0%	
Correction to the SAR results								
C(ε,σ)	±1.9%	Normal	1	1	0.84	±1.9%	±1.6%	
SAR scaling ^p	±0.0%	Rectangular	√3	1	1	±0%	±0%	
Combined Standard Uncertainty (K = 1)						±12.54%	±12.44%	
Expanded Uncertainty (K = 2)						±25.1%	±24.9%	

Uncertainty budget for frequency range 300 MHz to 3 GHz

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)	Vi Veff
Measurement System Errors								
Probe Calibration	±13.1%	Normal (k=2)	2	1	1	± 6.55 %	± 6.55 %	∞
Probe Calibration Drift	±1.7%	Rectangular	√3	1	1	±1.0%	±1.0%	∞
Probe Linearity	±4.7%	Rectangular	√3	1	1	±2.7%	±2.7%	∞
Broadband Signal	±2.6%	Rectangular	√3	1	1	±1.5%	±1.5%	∞
Probe Isotropy	±7.6%	Rectangular	√3	1	1	±4.4%	±4.4%	∞
Other Probe + Electronic	±1.2%	Normal	1	1	1	±1.2%	±1.2%	∞
RF Ambient	±1.8%	Normal	1	1	1	±1.8%	±1.8%	∞
Probe Positioning	±0.005mm	Normal	1	0.29	0.29	±0.15%	±0.15%	∞
Data Processing	±2.3%	Normal	1	1	1	±2.3%	±2.3%	∞
Phantom and Device Errors								
Conductivity (meas.) ^{DAK}	±2.5%	Normal	1	0.78	0.71	±2.0%	±1.8%	60
Conductivity (temp.) ^{BB}	±3.3%	Rectangular	√3	0.78	0.71	±1.5%	±1.4%	∞
Phantom Permittivity	±14.0%	Rectangular	√3	0.25	0.25	±2%	±2%	∞
Distance DUT – TSL	±2.0%	Normal	1	2	2	±4.0%	±4.0%	∞
Device Positioning	±2.4%/±2.8%	Normal	1	1	1	±2.8%	±2.8%	30
Device Holder	±3.4%/±3.5%	Normal	1	1	1	±3.5%	±3.5%	30
DUT Modulation ^m	±2.4%	Rectangular	√3	1	1	±1.4%	±1.4%	∞
Time-average SAR	±1.7%	Rectangular	√3	1	1	±1.0%	±1.0%	∞
DUT drift	±2.5%	Normal	1	1	1	±2.5%	±2.5%	30
Val Antenna Unc. ^{val}	±0.0%	Normal	1	1	1	±0%	±0%	
Unc. Input Power ^{val}	±0.0%	Normal	1	1	1	±0%	±0%	
Correction to the SAR results								
Deviation to Target	±1.9%	Normal	1	1	0.84	±1.9%	±1.6%	
SAR scaling ^p	±0.0%	Rectangular	√3	1	1	±0%	±0%	
Combined Standard Uncertainty (K = 1)						±12.8%	±12.7%	
Expanded Uncertainty (K = 2)						±25.6%	±25.4%	

Uncertainty budget for frequency range 3 GHz to 6 GHz

4. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE STD 1528- 2013, the following FCC Published RF exposure KDB procedures & manufacturer KDB inquiries:

- KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- KDB 865664 D02 RF Exposure Reporting v01r02
- KDB 248227 D01 802 11 Wi-Fi SAR v02r02
- KDB 447498 D01 General RF Exposure Guidance v06
- KDB 447498 D04 Interim General RF Exposure Guidance v01
- IC RSS-102 Issue 5: March 2015
- IC RSS-102 Issue 5: Amendment 1 (February 2, 2021)
- IEC/IEEE 62209-1528:2020 Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)

In addition to the above, the following information was used:

- [TCB workshop](#) April, 2019; Page 19, Tissue Simulating Liquids(TSL)

5. SAR Measurement System

5.1. Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


SAR measurement can be related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

5.2. SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.




DASY System Setup

5.2.1.Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



5.2.2. Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

5.2.3. Data Acquisition Electronics (DAE)

Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	$< 5\mu$ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

5.2.4. Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEC/IEEE 62209-1528. It enables the dosimetric evaluation of left and right hand phone usage as well as body-mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	The ELI phantom is used for compliance testing of handheld and body-mounted wireless devices in the frequency range of 4 MHz to 10 GHz. ELI is fully compatible with the IEC/IEEE 62209-1528 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all of SPEAG's dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

5.2.5. Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-1528 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

5.2.6. System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W ($f < 1\text{GHz}$), > 40 W ($f > 1\text{GHz}$)	

5.2.7. Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
For Body				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

The following table gives the recipes for tissue simulating liquids.

Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

Simulating Head Liquid (HBBL600-6000MHz), Manufactured by SPEAG:


Water (% by weight)	Esters, Emulsifiers, Inhibitors (% by weight)	Sodium salt (% by weight)
50 - 65%	10 - 30%	8 - 25%

Simulating Body Liquid (MBBL600-6000MHz), Manufactured by SPEAG:

Water (% by weight)	Esters, Emulsifiers, Inhibitors (% by weight)	Sodium salt (% by weight)
60 - 80%	20 - 40%	0 - 1.5%

5.2.8.SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

6. SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

6.1. Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ($\Delta x, \Delta y$)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

6.2. Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

6.3. Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

6.4. Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

6.5. SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

7. SAR Measurement Evaluation

7.1. EUT Configuration and Setting

This equipment SDR technology SAR test reference 248227 D01 802 11 Wi-Fi SAR


<Considerations Related to SDR for Setup and Testing>

This device has installed SDR engineering testing software which can provide continuous transmitting RF signal. During SDR SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

7.2. EUT Testing Position

7.2.1. Extremity Exposure Conditions

This device is fixed to a bracket when used, Our body is far away from it when we use it, only our hands are close to it, The 10-g extremity SAR test exclusions may be applied, We evaluated all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge.



Based on the antenna location shown on appendix D of this report, the SAR testing required for extremity mode is listed as below.

Antenna	Front Face	Rear Face	Left Side	Right Side	Top Side	Bottom Side
Antenna 0	✓	✓	✓		✓	
Antenna 1	✓	✓	✓	✓	✓	
Antenna 2	✓	✓		✓	✓	
Antenna 3	✓	✓	✓	✓	✓	

7.3. Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Jan. 29, 2024	H2450	2450	1.845	39.408	1.80	39.20	2.50	0.53
		2437.5	1.830	39.460	1.79	39.22	2.29	0.61
Feb. 02, 2024	H2450	2450	1.845	39.401	1.80	39.20	2.50	0.51
		2437	1.830	39.455	1.79	39.22	2.35	0.60
Feb. 04, 2024	H5G	5250	4.742	36.257	4.71	35.90	0.68	0.99
		5210	4.699	36.237	4.67	35.99	0.62	0.69
Jan. 30, 2024	H5G	5600	5.041	34.826	5.07	35.50	-0.57	-1.90
		5550	4.983	34.910	5.02	35.55	-0.64	-1.80
Jan. 31, 2024	H5G	5800	5.239	34.553	5.27	35.30	-0.59	-2.12
		5786.5	5.222	34.572	5.26	35.31	-0.63	-2.09

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within ± 2 °C.

7.4. System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Jan. 29, 2024	7506	Head	2450	1.845	39.408	Pass	Pass	Pass	OFDM	N/A	Pass
Feb. 02, 2024	7506	Head	2450	1.845	39.401	Pass	Pass	Pass	OFDM	N/A	Pass
Feb. 04, 2024	7506	Head	5250	4.742	36.257	Pass	Pass	Pass	OFDM	N/A	Pass
Jan. 30, 2024	7506	Head	5600	5.041	34.826	Pass	Pass	Pass	OFDM	N/A	Pass
Jan. 31, 2024	7506	Head	5800	5.239	34.553	Pass	Pass	Pass	OFDM	N/A	Pass

7.5. System Verification

The measuring result for system verification is tabulated as below.

Test Date	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Jan. 29, 2024	2450	23.60	6.04	24.16	2.37	1014	7506	1557
Feb. 02, 2024	2450	23.60	6.01	24.04	1.86	1014	7506	1557
Feb. 04, 2024	5250	22.50	2.34	23.40	4.00	1280	7506	1557
Jan. 30, 2024	5600	23.60	2.45	24.50	3.81	1280	7506	1557
Jan. 31, 2024	5800	22.50	2.37	23.70	5.33	1280	7506	1557

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

7.6. Maximum Conducted Power

All combinations have been tested, the Worst average power (Unit: dBm) is shown as below.

<WLAN 2.4G>

Mode	802.11b		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	19.98	20.64	20.43
Tune-up	21.0		
Mode	802.11g		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	19.91	20.24	19.93
Tune-up	20.5		
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	20.39	20.82	20.64
Tune-up	21.0		
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	3 (2422)	6 (2437)	9 (2452)
Average Power	19.91	19.97	20.02
Tune-up	20.5		

<WLAN 5.1G>

Mode	802.11a		
Channel / Frequency (MHz)	36 (5180)	40 (5200)	48 (5240)
Average Power	12.66	12.83	12.88
Tune-up	13.0		
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	36 (5180)	40 (5200)	48 (5240)
Average Power	13.2	13.03	13.16
Tune-up	13.5		
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	38 (5190)	46 (5230)	
Average Power	18.12	18.1	
Tune-up	18.5		
Mode	802.11ac (VHT80)		
Channel / Frequency (MHz)	42 (5210)		
Average Power	18.42		
Tune-up	18.5		
Mode	802.11ax (80)		
Channel / Frequency (MHz)	42 (5210)		
Average Power	18.4		
Tune-up	18.5		

<SDR-2.4G>

Mode	1.4MHz Bandwidth											
Channel / Frequency (MHz)	Low (2403.5)		Mid (2435.5)		High (2469.5)							
Average Power	14.59		14.95		14.94							
Tune-up	15.5											
Mode	1.4MHz Bandwidth (CA Mode)											
Channel / Frequency (MHz)	Low (2405.12)		Mid (2437.12)		High (2471.12)							
Average Power	14.83		14.69		14.89							
Tune-up	15.0											
Mode	3MHz Bandwidth											
Channel / Frequency (MHz)	Low (2405.5)		Mid (2435.5)		High (2469.5)							
Average Power	14.88		14.73		15.15							
Tune-up	15.0											
Mode	3MHz Bandwidth (CA Mode)											
Channel / Frequency (MHz)	Low (2408.2)		Mid (2438.2)		High (2471.2)							
Average Power	14.97		14.72		14.93							
Tune-up	15.5											
Mode	10MHz Bandwidth											
Channel / Frequency (MHz)	2407.5		2437.5		2467.5							
Average Power	24.65		24.90		24.83							
Tune-up	25.5											
Mode	20MHz Bandwidth											
Channel / Frequency (MHz)	2412.5		2437.5		2460.5		2462.5					
Average Power	24.05		25.6		22.86		22.13					
Tune-up	26.0				23.0							
Mode	40MHz Bandwidth											
Channel / Frequency (MHz)	2422.5		2425.5		2426.5		2437.5		2448.5		2452.5	
Average Power	20.83		21.69		/		24.4		21.58		20.73	
Tune-up	22.0				25.0				22.0			

<SDR-5.6G>

Mode	20MHz Bandwidth		
Channel / Frequency (MHz)	Low (5500)	Mid (5580)	High (5700)
Average Power	20.85	20.65	21.1
Tune-up	21.5		
Mode	40MHz Bandwidth		
Channel / Frequency (MHz)	Low (5510)	Mid (5550)	High (5670)
Average Power	21.41	21.45	21.46
Tune-up	22.0		

<SDR-5.8G>

Mode	1.4MHz Bandwidth		
Channel / Frequency (MHz)	Low (5728.5)	Mid (5786.5)	High (5846.5)
Average Power	14.69	15.42	15.66
Tune-up	16.0		
Mode	1.4MHz Bandwidth (CA Mode)		
Channel / Frequency (MHz)	Low (5730.12)	Mid (5788.12)	High (5848.12)
Average Power	15.07	15.34	15.49
Tune-up	16.0		
Mode	3MHz Bandwidth		
Channel / Frequency (MHz)	Low (5727.5)	Mid (5784.5)	High (5844.5)
Average Power	15.54	15.56	15.72
Tune-up	16.0		
Mode	3MHz Bandwidth (CA Mode)		
Channel / Frequency (MHz)	Low (5730.2)	Mid (5787.2)	High (5847.2)
Average Power	15.00	15.41	15.40
Tune-up	16.0		
Mode	10MHz Bandwidth		
Channel / Frequency (MHz)	Low (5730.5)	Mid (5786.5)	High (5844.5)
Average Power	25.9	25.49	26.03
Tune-up	26.5		
Mode	20MHz Bandwidth		
Channel / Frequency (MHz)	Low (5735.5)	Mid (5786.5)	High (5839.5)
Average Power	25.81	25.93	25.43
Tune-up	26.5		
Mode	40MHz Bandwidth		
Channel / Frequency (MHz)	Low (5745.5)	Mid (5786.5)	High (5829.5)
Average Power	25.88	25.24	25.69
Tune-up	26.0		

7.7. Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Extremity Exposure Condition
1	WLAN 2.4G+SDR 5G	Yes
2	WLAN 5G+SDR 2.4G	Yes
3	WLAN 5G+SDR 5G	Yes

7.8. SAR Testing Results

7.8.1. SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.
- (2) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

7.8.2.SAR Results for Extremity Exposure Condition (Separation Distance is 0 cm Gap)

Plot No.	Band	Mode	Test Position	Channel	Frequency	Antenna	Degree	Max. Duty Cycle	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-10g (W/kg)	Scaled SAR-10g (W/kg)
	802.11b	-	Front Face	6	2437	0	0	1	21.0	20.64	1.09	-0.11	0.835	0.91
	802.11b	-	Rear Face	6	2437	0	0	1	21.0	20.64	1.09	0.11	0.097	0.11
	802.11b	-	Left Side	6	2437	0	0	1	21.0	20.64	1.09	-0.04	0.437	0.47
	802.11b	-	Top Side	6	2437	0	0	1	21.0	20.64	1.09	0.06	0.095	0.10
	802.11b	-	Front Face	6	2437	0	90	1	21.0	20.64	1.09	0.13	0.609	0.66
	802.11b	-	Rear Face	6	2437	0	90	1	21.0	20.64	1.09	0.09	0.087	0.09
	802.11b	-	Left Side	6	2437	0	90	1	21.0	20.64	1.09	0.04	0.588	0.64
	802.11b	-	Top Side	6	2437	0	90	1	21.0	20.64	1.09	0.13	0.085	0.09
	802.11b	-	Front Face	6	2437	3	0	1	21.0	20.64	1.09	0.07	0.638	0.69
	802.11b	-	Rear Face	6	2437	3	0	1	21.0	20.64	1.09	0.05	0.217	0.24
	802.11b	-	Left Side	6	2437	3	0	1	21.0	20.64	1.09	-0.06	0.408	0.44
	802.11b	-	Top Side	6	2437	3	0	1	21.0	20.64	1.09	0.11	0.58	0.63
	802.11b	-	Front Face	6	2437	3	90	1	21.0	20.64	1.09	0.04	0.801	0.87
	802.11b	-	Rear Face	6	2437	3	90	1	21.0	20.64	1.09	0.02	0.144	0.16
	802.11b	-	Left Side	6	2437	3	90	1	21.0	20.64	1.09	0.03	0.058	0.06
	802.11b	-	Right Side	6	2437	3	90	1	21.0	20.64	1.09	0.17	0.04	0.04
1	802.11b	-	Top Side	6	2437	3	90	1	21.0	20.64	1.09	0.05	1.63	1.77
	802.11ac	VHT80	Front Face	42	5210	0	0	1	18.5	18.42	1.02	0.06	0.603	0.61
	802.11ac	VHT80	Rear Face	42	5210	0	0	1	18.5	18.42	1.02	0.12	0.204	0.21
	802.11ac	VHT80	Left Side	42	5210	0	0	1	18.5	18.42	1.02	0.11	0.391	0.40
	802.11ac	VHT80	Top Side	42	5210	0	0	1	18.5	18.42	1.02	0.07	1.96	2.00
	802.11ac	VHT80	Front Face	42	5210	0	90	1	18.5	18.42	1.02	-0.03	0.511	0.52
	802.11ac	VHT80	Rear Face	42	5210	0	90	1	18.5	18.42	1.02	0.11	0.124	0.13
2	802.11ac	VHT80	Left Side	42	5210	0	90	1	18.5	18.42	1.02	-0.03	2.48	2.53
	802.11ac	VHT80	Top Side	42	5210	0	90	1	18.5	18.42	1.02	0.06	1.83	1.86
	802.11ac	VHT80	Front Face	42	5210	3	0	1	18.5	18.42	1.02	0.09	0.558	0.57
	802.11ac	VHT80	Rear Face	42	5210	3	0	1	18.5	18.42	1.02	0.03	0.178	0.18
	802.11ac	VHT80	Left Side	42	5210	3	0	1	18.5	18.42	1.02	0.06	1.58	1.61
	802.11ac	VHT80	Top Side	42	5210	3	0	1	18.5	18.42	1.02	0.13	0.572	0.58
	802.11ac	VHT80	Front Face	42	5210	3	90	1	18.5	18.42	1.02	-0.04	0.474	0.48
	802.11ac	VHT80	Rear Face	42	5210	3	90	1	18.5	18.42	1.02	-0.05	0.096	0.10
	802.11ac	VHT80	Left Side	42	5210	3	90	1	18.5	18.42	1.02	0.09	1.62	1.65
	802.11ac	VHT80	Right Side	42	5210	3	90	1	18.5	18.42	1.02	0.14	0.198	0.20
	802.11ac	VHT80	Top Side	42	5210	3	90	1	18.5	18.42	1.02	-0.06	2.26	2.30
	802.11ax	VHT80	Left Side	42	5210	0+3	0	1	18.5	18.40	1.02	0.03	1.1	1.13
	802.11ax	VHT80	Left Side	42	5210	0+3	90	1	18.5	18.40	1.02	0.02	1.07	1.09
	802.11ax	VHT80	Top Side	42	5210	0+3	0	1	18.5	18.40	1.02	-0.18	1.39	1.42
	802.11ax	VHT80	Top Side	42	5210	0+3	90	1	18.5	18.40	1.02	0.06	1.28	1.31
	802.11ac	VHT80	Left Side	42	5210	0	90	1	18.5	18.42	1.02	-0.08	2.43	2.48
	SDR 2.4G	20M	Front Face	Mid	2437.5	0	0	10%	25.5	24.9	1.15	-0.04	0.916	0.11
	SDR 2.4G	20M	Rear Face	Mid	2437.5	0	0	10%	25.5	24.9	1.15	0.08	0.108	0.01
	SDR 2.4G	20M	Left Side	Mid	2437.5	0	0	10%	25.5	24.9	1.15	0.07	0.858	0.10
	SDR 2.4G	20M	Top Side	Mid	2437.5	0	0	10%	25.5	24.9	1.15	0.02	0.101	0.01
	SDR 2.4G	20M	Front Face	Mid	2437.5	0	90	10%	25.5	24.9	1.15	-0.08	0.869	0.10
	SDR 2.4G	20M	Rear Face	Mid	2437.5	0	90	10%	25.5	24.9	1.15	-0.07	0.118	0.01
	SDR 2.4G	20M	Left Side	Mid	2437.5	0	90	10%	25.5	24.9	1.15	-0.07	3.67	0.42
	SDR 2.4G	20M	Top Side	Mid	2437.5	0	90	10%	25.5	24.9	1.15	0.01	0.134	0.02
3	SDR 2.4G	20M	Front Face	Mid	2437.5	1	0	10%	25.5	24.9	1.15	0.08	3.93	0.45
	SDR 2.4G	20M	Rear Face	Mid	2437.5	1	0	10%	25.5	24.9	1.15	-0.04	0.209	0.02
	SDR 2.4G	20M	Right Side	Mid	2437.5	1	0	10%	25.5	24.9	1.15	0.08	0.852	0.10
	SDR 2.4G	20M	Top Side	Mid	2437.5	1	0	10%	25.5	24.9	1.15	-0.02	1.01	0.12
	SDR 2.4G	20M	Front Face	Mid	2437.5	1	90	10%	25.5	24.9	1.15	0.09	2.65	0.30
	SDR 2.4G	20M	Rear Face	Mid	2437.5	1	90	10%	25.5	24.9	1.15	-0.19	0.105	0.01
	SDR 2.4G	20M	Left Side	Mid	2437.5	1	90	10%	25.5	24.9	1.15	0.15	0.17	0.02
	SDR 2.4G	20M	Right Side	Mid	2437.5	1	90	10%	25.5	24.9	1.15	0.05	0.066	0.01
	SDR 2.4G	20M	Top Side	Mid	2437.5	1	90	10%	25.5	24.9	1.15	-0.01	2.41	0.28
	SDR 2.4G	20M	Front Face	Mid	2437.5	2	0	10%	25.5	24.9	1.15	0.04	0.71	0.08
	SDR 2.4G	20M	Rear Face	Mid	2437.5	2	0	10%	25.5	24.9	1.15	0.14	0.215	0.02
	SDR 2.4G	20M	Right Side	Mid	2437.5	2	0	10%	25.5	24.9	1.15	0.06	0.46	0.05
	SDR 2.4G	20M	Top Side	Mid	2437.5	2	0	10%	25.5	24.9	1.15	0.07	0.18	0.02
	SDR 2.4G	20M	Front Face	Mid	2437.5	2	90	10%	25.5	24.9	1.15	0.16	0.529	0.06
	SDR 2.4G	20M	Rear Face	Mid	2437.5	2	90	10%	25.5	24.9	1.15	0.03	0.027	0.00

	SDR 2.4G	20M	Right Side	Mid	2437.5	2	90	10%	25.5	24.9	1.15	-0.07	3.05	0.35
	SDR 2.4G	20M	Top Side	Mid	2437.5	2	90	10%	25.5	24.9	1.15	-0.01	0.022	0.00
	SDR 2.4G	20M	Front Face	Mid	2437.5	3	0	10%	25.5	24.9	1.15	0.08	1.59	0.18
	SDR 2.4G	20M	Rear Face	Mid	2437.5	3	0	10%	25.5	24.9	1.15	0.16	0.471	0.05
	SDR 2.4G	20M	Left Side	Mid	2437.5	3	0	10%	25.5	24.9	1.15	0.06	0.974	0.11
	SDR 2.4G	20M	Top Side	Mid	2437.5	3	0	10%	25.5	24.9	1.15	0.09	1.34	0.15
	SDR 2.4G	20M	Front Face	Mid	2437.5	3	90	10%	25.5	24.9	1.15	0.18	1.59	0.18
	SDR 2.4G	20M	Rear Face	Mid	2437.5	3	90	10%	25.5	24.9	1.15	0.06	0.293	0.03
	SDR 2.4G	20M	Left Side	Mid	2437.5	3	90	10%	25.5	24.9	1.15	0.17	0.165	0.02
	SDR 2.4G	20M	Right Side	Mid	2437.5	3	90	10%	25.5	24.9	1.15	0.01	0.088	0.01
	SDR 2.4G	20M	Top Side	Mid	2437.5	3	90	10%	25.5	24.9	1.15	-0.14	3.81	0.44
	SDR 2.4G	20M	Front Face	Mid	2437.5	1	0	10%	25.5	24.9	1.15	0.01	3.85	0.44
	SDR 5.6G	40M	Front Face	Mid	5550	0	0	10%	22.0	21.45	1.14	0.14	1.03	0.12
	SDR 5.6G	40M	Rear Face	Mid	5550	0	0	10%	22.0	21.45	1.14	-0.18	0.373	0.04
	SDR 5.6G	40M	Left Side	Mid	5550	0	0	10%	22.0	21.45	1.14	-0.17	1.41	0.16
	SDR 5.6G	40M	Top Side	Mid	5550	0	0	10%	22.0	21.45	1.14	0.06	0.446	0.05
	SDR 5.6G	40M	Front Face	Mid	5550	0	90	10%	22.0	21.45	1.14	0.07	1.27	0.14
	SDR 5.6G	40M	Rear Face	Mid	5550	0	90	10%	22.0	21.45	1.14	0.02	0.31	0.04
	SDR 5.6G	40M	Left Side	Mid	5550	0	90	10%	22.0	21.45	1.14	0.14	4.77	0.54
	SDR 5.6G	40M	Top Side	Mid	5550	0	90	10%	22.0	21.45	1.14	0.19	0.173	0.02
	SDR 5.6G	40M	Front Face	Mid	5550	1	0	10%	22.0	21.45	1.14	0.06	2.25	0.26
	SDR 5.6G	40M	Rear Face	Mid	5550	1	0	10%	22.0	21.45	1.14	-0.03	0.228	0.03
	SDR 5.6G	40M	Right Side	Mid	5550	1	0	10%	22.0	21.45	1.14	0.02	0.815	0.09
	SDR 5.6G	40M	Top Side	Mid	5550	1	0	10%	22.0	21.45	1.14	0.04	1.36	0.15
	SDR 5.6G	40M	Front Face	Mid	5550	1	90	10%	22.0	21.45	1.14	0.05	1.35	0.15
	SDR 5.6G	40M	Rear Face	Mid	5550	1	90	10%	22.0	21.45	1.14	0.01	0.176	0.02
	SDR 5.6G	40M	Left Side	Mid	5550	1	90	10%	22.0	21.45	1.14	0.08	0.24	0.03
	SDR 5.6G	40M	Right Side	Mid	5550	1	90	10%	22.0	21.45	1.14	0.08	0.271	0.03
	SDR 5.6G	40M	Top Side	Mid	5550	1	90	10%	22.0	21.45	1.14	0.06	2.82	0.32
	SDR 5.6G	40M	Front Face	Mid	5550	2	0	10%	22.0	21.45	1.14	-0.1	1.27	0.14
	SDR 5.6G	40M	Rear Face	Mid	5550	2	0	10%	22.0	21.45	1.14	0.05	0.155	0.02
	SDR 5.6G	40M	Right Side	Mid	5550	2	0	10%	22.0	21.45	1.14	0.13	1.48	0.17
	SDR 5.6G	40M	Top Side	Mid	5550	2	0	10%	22.0	21.45	1.14	-0.02	0.542	0.06
	SDR 5.6G	40M	Front Face	Mid	5550	2	90	10%	22.0	21.45	1.14	0.04	1.18	0.13
	SDR 5.6G	40M	Rear Face	Mid	5550	2	90	10%	22.0	21.45	1.14	0.03	0.414	0.05
4	SDR 5.6G	40M	Right Side	Mid	5550	2	90	10%	22.0	21.45	1.14	-0.15	6.99	0.79
	SDR 5.6G	40M	Top Side	Mid	5550	2	90	10%	22.0	21.45	1.14	0.07	0.129	0.01
	SDR 5.6G	40M	Front Face	Mid	5550	3	0	10%	22.0	21.45	1.14	0.18	0.714	0.08
	SDR 5.6G	40M	Rear Face	Mid	5550	3	0	10%	22.0	21.45	1.14	0.09	0.341	0.04
	SDR 5.6G	40M	Left Side	Mid	5550	3	0	10%	22.0	21.45	1.14	0.05	0.666	0.08
	SDR 5.6G	40M	Top Side	Mid	5550	3	0	10%	22.0	21.45	1.14	-0.04	1.16	0.13
	SDR 5.6G	40M	Front Face	Mid	5550	3	90	10%	22.0	21.45	1.14	0.04	0.905	0.10
	SDR 5.6G	40M	Rear Face	Mid	5550	3	90	10%	22.0	21.45	1.14	-0.02	0.239	0.03
	SDR 5.6G	40M	Left Side	Mid	5550	3	90	10%	22.0	21.45	1.14	0.07	0.169	0.02
	SDR 5.6G	40M	Right Side	Mid	5550	3	90	10%	22.0	21.45	1.14	0.02	0.523	0.06
	SDR 5.6G	40M	Top Side	Mid	5550	3	90	10%	22.0	21.45	1.14	-0.12	2.21	0.25
	SDR 5.6G	40M	Right Side	Mid	5550	2	90	10%	22.0	21.45	1.14	0.02	6.74	0.76
	SDR 5.8G	20M	Front Face	Mid	5786.5	0	0	10%	26.5	25.93	1.14	0.06	2.22	0.25
	SDR 5.8G	20M	Rear Face	Mid	5786.5	0	0	10%	26.5	25.93	1.14	0.13	0.677	0.08
	SDR 5.8G	20M	Left Side	Mid	5786.5	0	0	10%	26.5	25.93	1.14	0.18	3.19	0.36
	SDR 5.8G	20M	Top Side	Mid	5786.5	0	0	10%	26.5	25.93	1.14	0.18	1.29	0.15
	SDR 5.8G	20M	Front Face	Mid	5786.5	0	90	10%	26.5	25.93	1.14	0.04	3.09	0.35
	SDR 5.8G	20M	Rear Face	Mid	5786.5	0	90	10%	26.5	25.93	1.14	-0.09	0.754	0.09
5	SDR 5.8G	20M	Left Side	Mid	5786.5	0	90	10%	26.5	25.93	1.14	-0.19	15.8	1.80
	SDR 5.8G	20M	Top Side	Mid	5786.5	0	90	10%	26.5	25.93	1.14	0.08	0.468	0.05
	SDR 5.8G	20M	Front Face	Mid	5786.5	1	0	10%	26.5	25.93	1.14	0.09	4.8	0.55
	SDR 5.8G	20M	Rear Face	Mid	5786.5	1	0	10%	26.5	25.93	1.14	0.13	0.549	0.06
	SDR 5.8G	20M	Right Side	Mid	5786.5	1	0	10%	26.5	25.93	1.14	0.15	1.34	0.15
	SDR 5.8G	20M	Top Side	Mid	5786.5	1	0	10%	26.5	25.93	1.14	0.05	3.62	0.41
	SDR 5.8G	20M	Front Face	Mid	5786.5	1	90	10%	26.5	25.93	1.14	0.18	2.83	0.32
	SDR 5.8G	20M	Rear Face	Mid	5786.5	1	90	10%	26.5	25.93	1.14	0.06	0.561	0.06
	SDR 5.8G	20M	Left Side	Mid	5786.5	1	90	10%	26.5	25.93	1.14	0.13	0.243	0.03
	SDR 5.8G	20M	Right Side	Mid	5786.5	1	90	10%	26.5	25.93	1.14	-0.12	0.219	0.02
	SDR 5.8G	20M	Top Side	Mid	5786.5	1	90	10%	26.5	25.93	1.14	0.03	5.79	0.66
	SDR 5.8G	20M	Front Face	Mid	5786.5	2	0	10%	26.5	25.93	1.14	0.05	3.18	0.36
	SDR 5.8G	20M	Rear Face	Mid	5786.5	2	0	10%	26.5	25.93	1.14	0.03	1.13	0.13
	SDR 5.8G	20M	Right Side	Mid	5786.5	2	0	10%	26.5	25.93	1.14	0.12	4.36	0.50

Prüfbericht - Nr.: CN244E0L 005
Test Report No.

Seite 33 von 37

Page 33 of 37

	SDR 5.8G	20M	Top Side	Mid	5786.5	2	0	10%	26.5	25.93	1.14	-0.02	1.6	0.18
	SDR 5.8G	20M	Front Face	Mid	5786.5	2	90	10%	26.5	25.93	1.14	0.04	3.36	0.38
	SDR 5.8G	20M	Rear Face	Mid	5786.5	2	90	10%	26.5	25.93	1.14	0.1	0.837	0.10
	SDR 5.8G	20M	Right Side	Mid	5786.5	2	90	10%	26.5	25.93	1.14	-0.09	15.3	1.74
	SDR 5.8G	20M	Top Side	Mid	5786.5	2	90	10%	26.5	25.93	1.14	0.02	0.377	0.04
	SDR 5.8G	20M	Front Face	Mid	5786.5	3	0	10%	26.5	25.93	1.14	0.15	2.06	0.23
	SDR 5.8G	20M	Rear Face	Mid	5786.5	3	0	10%	26.5	25.93	1.14	0.05	0.997	0.11
	SDR 5.8G	20M	Left Side	Mid	5786.5	3	0	10%	26.5	25.93	1.14	0.12	1.53	0.17
	SDR 5.8G	20M	Top Side	Mid	5786.5	3	0	10%	26.5	25.93	1.14	-0.02	3.63	0.41
	SDR 5.8G	20M	Front Face	Mid	5786.5	3	90	10%	26.5	25.93	1.14	0.04	1.57	0.18
	SDR 5.8G	20M	Rear Face	Mid	5786.5	3	90	10%	26.5	25.93	1.14	0.17	0.577	0.07
	SDR 5.8G	20M	Left Side	Mid	5786.5	3	90	10%	26.5	25.93	1.14	0.03	0.156	0.02
	SDR 5.8G	20M	Right Side	Mid	5786.5	3	90	10%	26.5	25.93	1.14	-0.08	0.951	0.11
	SDR 5.8G	20M	Top Side	Mid	5786.5	3	90	10%	26.5	25.93	1.14	0.08	5.88	0.67
	SDR 5.8G	20M	Left Side	Mid	5786.5	0	90	10%	26.5	25.93	1.14	0.05	15.5	1.77

Note: This device is for properly worn on the limbs when in normal use, and the SAR limit of 4 W/kg averaged over ten gram of tissue applied.

Max normal duty cycle is 10% for 2.4GHz, 5.6GHz and 5.8GHz SDR bands.

1) 2.4GHz SDR

Ton (ms)	T(Total) ms	Duty cycle (%)
0.5021*2	10.13	10%

2) 5.6GHz SDR

Ton (ms)	T(Total) ms	Duty cycle (%)
0.5021*2	10.13	10%

2) 5.8GHz SDR

Ton (ms)	T(Total) ms	Duty cycle (%)
0.5021*2	10.13	10%

7.8.3.SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Band	Mode	Test Position	Ch.	Antenna.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
802.11ac	VHT80	Left Side	42	Ant0_Degree90	2.48	2.43	1.02	N/A	N/A	N/A	N/A
SDR 2.4G	20M	Front Face	Mid(2437.5MHz)	Ant1_Degree0	3.93	3.85	1.02	N/A	N/A	N/A	N/A
SDR 5.6G	40M	Right Side	Mid(5550MHz)	Ant2_Degree90	6.99	6.74	1.04	N/A	N/A	N/A	N/A
SDR 5.8G	20M	Left Side	High(5839.5MHz)	Ant0_Degree90	15.8	15.5	1.02	N/A	N/A	N/A	N/A

7.8.4.<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{10g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{10g} 4.0 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{10g} is greater than the SAR limit (SAR_{10g} 4.0 W/kg), SAR test exclusion is determined by the SPLSR.

This device [0,1] [0,3] [2,1] [2,3] dual transmission.

The maximum summed SAR value is as below.

Position	WLAN 2.4G			WLAN 5G		
	Antenna 0	Antenna 3	MIMO	Antenna 0	Antenna 3	MIMO
Front Face	0.91	0.87	1.78	0.61	0.57	1.18
Rear Face	0.11	0.24	0.35	0.21	0.18	0.39
Left Side	0.64	0.44	1.08	2.53	1.65	1.13
Right Side		0.04	0.04		0.20	0.20
Top Side	0.10	1.77	1.87	2.00	2.30	1.42
Bottom Side						

Position	SDR 2.4G							
	Antenna 0	Antenna 1	Antenna 2	Antenna 3	Antenna 0+1	Antenna 0+3	Antenna 2+1	Antenna 2+3
Front Face	0.11	0.45	0.08	0.18	0.56	0.29	0.53	0.26
Rear Face	0.01	0.02	0.02	0.05	0.03	0.06	0.04	0.07
Left Side	0.42	0.02		0.11	0.44	0.53	0.02	0.11
Right Side		0.10	0.35	0.01	0.10	0.01	0.45	0.36
Top Side	0.02	0.28	0.02	0.44	0.30	0.46	0.30	0.46
Bottom Side								

Position	SDR 5.6G							
	Antenna 0	Antenna 1	Antenna 2	Antenna 3	Antenna 0+1	Antenna 0+3	Antenna 2+1	Antenna 2+3
Front Face	0.14	0.26	0.14	0.10	0.40	0.24	0.40	0.24
Rear Face	0.04	0.03	0.05	0.04	0.07	0.08	0.08	0.09
Left Side	0.54	0.03		0.08	0.57	0.62	0.03	0.08
Right Side		0.09	0.79	0.06	0.09	0.06	0.88	0.85
Top Side	0.05	0.32	0.06	0.25	0.37	0.30	0.38	0.31
Bottom Side								

Position	SDR 5.8G							
	Antenna 0	Antenna 1	Antenna 2	Antenna 3	Antenna 0+1	Antenna 0+3	Antenna 2+1	Antenna 2+3
Front Face	0.35	0.55	0.38	0.23	0.90	0.58	0.93	0.61
Rear Face	0.09	0.06	0.13	0.11	0.15	0.20	0.19	0.24
Left Side	1.80	0.03		0.17	1.83	1.97	0.03	0.17
Right Side		0.15	1.74	0.11	0.15	0.11	1.89	1.85
Top Side	0.15	0.66	0.18	0.67	0.81	0.82	0.84	0.85
Bottom Side								

Prüfbericht - Nr.: CN244E0L 005

Test Report No.

Seite 36 von 37

Page 36 of 37

Position	WLAN 2.4G +SDR 5G	WLAN 5G +SDR 2.4G	WLAN 5G +SDR 5G
Front Face	2.71	1.71	2.11
Rear Face	0.54	0.43	0.58
Left Side	1.11	2.55	2.56
Right Side	1.93	0.65	2.09
Top Side	2.71	2.60	3.14
Bottom Side			

Note: Simultaneous mode supported in the configuration WLAN (Ant 0,3) + SDR (Ant 1,2)

Test Engineer: Warren Xiong, Carl Liu

Appendixes

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

Appendix B: SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

Appendix C: Calibration Certificate for probe and Dipole

Appendix D: Photographs setup and Antenna location Diagram