

FCC - TEST REPORT

Report Number : **60.790.19.014.01R01** Date of Issue : June 28, 2019

Model : **CX FLEX SINGLE-POWER+**

Product Type : **Merchandise Theft Deterrent System**

Applicant : Mobile Technologies Inc.

Address : 1050 NE 67th Ave, Hillsboro, OR 97124

Production Facility : HONG KONG ANDROIDS TECHNOLOGY CO.LTD

Address : Yitao Technology Industrial Park, Baihua Yuan Rd., The Second
Industrial Area, Guangming Sub-district Office, Guangming New
District, Shenzhen, China

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including Appendices : 18

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval

1 Table of Contents

1 Table of Contents.....	2
2 Description of Equipment Under Test	3
3 Summary of Test Standards	4
4 Details about the Test Laboratory	5
4.1 Test Equipment Site List	6
4.2 Measurement System Uncertainty	7
5 Summary of Test Results.....	8
6 General Remarks.....	9
7 Test Setups.....	10
7.1 Radiated test setups 9kHz-30MHz.....	10
7.2 Radiated test setups Below 1GHz.....	10
7.3 Radiated test setups Above 1GHz	10
7.4 AC Power Line Conducted Emission test setups	11
7.5 Conducted RF test setups.....	11
8 Emission Test Results	12
8.1 Spurious Radiated Emission	12
8.2 Conducted Emission at AC Power Line.....	15
8.3 6dB & 99% Bandwidth	17
9 Appendix A - General Product Information	18

2 Description of Equipment Under Test

Description of the Equipment Under Test

Product: Merchandise Theft Deterrent System

Model no.: CX FLEX SINGLE-POWER+

FCC ID: 2AA2X-15000204

Rating: EUT rating: DC 5V,3A or 9V,3A or 12V,3A or 15V,3A or 20V,2.25A
Assist AC/DC adapter:100-240V ~50/60Hz, 1.2A Max. Input
DC 5V,3A or 9V,3A or 12V,3A or 15V,3A or 20V,2.25A output

Frequency: 125kHz (Tx and Rx)

Modulation: AM

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	REMARK
AC/DC adapter	ADAPTER TECH.	ADP045T-A200	Provided by applicant
User Card	MTI	/	Provided by applicant

Auxiliary Software Used during Test:

DESCRIPTION	SOFTWARE NAME	VERSION	REMARK
/	/	/	/

3 Summary of Test Standards

Test Standards
FCC Part 15 Subpart C 10-1-17 Edition Federal Communications Commission, PART 15 — Radio Frequency Devices, Subpart C — Unintentional Radiators

All the tests were performed using the procedures from ANSI C63.4(2014) and ANSI C63.10 (2013).

4 Details about the Test Laboratory

Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13 Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2,
Shenzhen 518052, P.R.China
FCC Registration Number: 514049

Emission Tests	
Test Item	Test Site
FCC Part 15 Subpart C	
FCC Title 47 Part 15.205, 15.209 Spurious Radiated Emission	Site 1
FCC Title 47 Part 15.207 Conduct Emission	Site 1
FCC Title 47 Part 15.215 20dB Bandwidth	Site 1

4.1 Test Equipment Site List

Radiated emission Test – Site 1

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2019-7-6
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100398	2019-7-6
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2019-6-28
Horn Antenna	Rohde & Schwarz	HF907	102294	2019-6-28
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2019-7-6
Signal Generator	Rohde & Schwarz	SMY01	839369/005	2019-7-6
Attenuator	Agilent	8491A	MY39264334	2019-7-6
3m Semi-anechoic chamber	TDK	9X6X6	----	2020-7-7
Test software	Rohde & Schwarz	EMC32	Version 9.15.00	N/A

Conducted Emission Test - Site 1

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	2019-7-6
LISN	Rohde & Schwarz	ENV4200	100249	2019-7-6
LISN	Rohde & Schwarz	ENV432	101318	2019-7-6
LISN	Rohde & Schwarz	ENV216	100326	2019-7-6
ISN	Rohde & Schwarz	ENY81	100177	2019-7-6
ISN	Rohde & Schwarz	ENY81-CA6	101664	2019-7-6
High Voltage Probe	Rohde & Schwarz	TK9420(VT94 20)	9420-584	2019-6-30
RF Current Probe	Rohde & Schwarz	EZ-17	100816	2019-6-30
Attenuator	Shanghai Huaxiang	TS2-26-3	080928189	2019-7-6
Test software	Rohde & Schwarz	EMC32	Version9.15.00	N/A

20dB Bandwidth– Site 1

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	101030	2019-7-6

4.2 Measurement System Uncertainty

Measurement System Uncertainty Emissions

System Measurement Uncertainty	
Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 9kHz-30MHz	4.46dB
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.91dB; Vertical: 4.89dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-18000MHz	Horizontal: 4.80dB; Vertical: 4.79dB;
Uncertainty for Conducted Emission at AC Power Line 150kHz-30MHz	3.21dB
Uncertainty for frequency test	0.6×10^{-7}

5 Summary of Test Results

Emission Tests				
FCC Part 15 Subpart C				
Test Condition	Pages	Test Result		
		Pass	Fail	N/A
FCC Title 47 Part 15.205, 15.209 Spurious Radiated Emission	12-14	☒	☐	☐
FCC Title 47 Part 15.207 Conduct Emission	15-16	☒	☐	☐
FCC Title 47 Part 15.215 20dB Bandwidth	17	☒	☐	☐

6 General Remarks

Remarks

This submittal(s) (test report) is intended for **FCC ID: 2AA2X-15000204**, complies with Section 15.205, 15.207, 15.209, 15.215 of the FCC Part 15, Subpart C rules.

The TX and RX frequency range is 125kHz.

SUMMARY:

- All tests according to the regulations cited on page 8 were

■ - Performed

□ - **Not** Performed

- The Equipment Under Test

■ - **Fulfills** the general approval requirements.


□ - **Does not** fulfill the general approval requirements.

Sample Received Date: May 20, 2019

Testing Start Date: June 3, 2019

Testing End Date: June 26, 2019

Reviewed by:



Hosea CHAN
EMC Project Engineer


Prepared by:




Eric LI
EMC Senior Project Engineer

7 Test Setups


7.1 Radiated test setups 9kHz-30MHz




7.2 Radiated test setups Below 1GHz




7.3 Radiated test setups Above 1GHz



7.4 AC Power Line Conducted Emission test setups



7.5 Conducted RF test setups



8 Emission Test Results

8.1 Spurious Radiated Emission

EUT: CX FLEX SINGLE-POWER+
Op Condition: Operated, TX Mode
Test Specification: FCC15.205, 15.209
Comment: 120V AC
Remark: 9kHz to 30MHz

Test Result

☒ Passed☐ Not Passed


Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector PK/QP/AV
0.125	46.38	105.67	-59.29	Peak
0.250	32.28	99.65	-67.37	Peak

Spurious Radiated Emission

EUT: CX FLEX SINGLE-POWER+
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.205, 15.209
 Comment: 120V AC
 Remark: 30MHz to 1GHz, Antenna: Horizontal

Test Result

☒ Passed

☐ Not Passed



Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Corr. (dB)
42.428125	24.85	40.00	-15.15	16.7
63.707500	24.38	40.00	-15.62	14.5
84.926250	23.16	40.00	-16.84	13.0
106.205625	23.64	43.50	-19.86	15.6
148.764375	27.77	43.50	-15.73	13.3
293.900625	25.89	46.00	-20.11	19.8
360.891250	28.18	46.00	-17.82	21.5

Spurious Radiated Emission

EUT: CX FLEX SINGLE-POWER+
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.205, 15.209
 Comment: 120V AC
 Remark: 30MHz to 1GHz, Antenna: Vertical

Test Result

☒ Passed


☐ Not Passed


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Corr. (dB)
42.428125	34.17	40.00	-5.83	16.7
63.707500	24.34	40.00	-15.66	14.5
106.145000	22.44	43.50	-21.06	15.6
148.764375	29.91	43.50	-13.59	13.3
376.896250	24.89	46.00	-21.11	21.8
596.419375	31.35	46.00	-14.65	26.1

8.2 Conducted Emission at AC Power Line

EUT: CX FLEX SINGLE-POWER+
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.207
 Comment: 120V AC
 Remark: L Line

Test Result

☒ Passed☐ Not Passed

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Corr. (dB)
0.186000	47.44	---	64.21	-16.77	10.2
0.562000	37.50	---	56.00	-18.50	10.3
1.282000	40.10	---	56.00	-15.90	10.3
2.294000	38.81	---	56.00	-17.19	10.3
3.746000	38.16	---	56.00	-17.84	10.4
10.230000	43.62	---	60.00	-16.38	10.6


Conducted Emission at AC Power Line

EUT: CX FLEX SINGLE-POWER+
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.207
 Comment: 120V AC
 Remark: N Line

Test Result

☒ Passed

☐ Not Passed





Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Corr. (dB)
0.198000	46.08	---	63.69	-17.62	10.2
0.554000	38.54	---	56.00	-17.46	10.3
1.342000	40.99	---	56.00	-15.01	10.3
2.446000	39.75	---	56.00	-16.25	10.3
3.586000	39.05	---	56.00	-16.95	10.4
10.274000	43.54	---	60.00	-16.46	10.7

8.3 6dB & 99% Bandwidth

EUT: CX FLEX SINGLE-POWER+
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.215, 20dB Bandwidth
 Comment: 120V AC

Test Result

☒ Passed☐ Not Passed

Bandwidth	Measured Value
20dB bandwidth	6.2 kHz
99% bandwidth	20.3 kHz

9 Appendix A - General Product Information

Radiofrequency radiation exposure evaluation

This exposure evaluation is intended for **FCC ID: 2AA2X-15000204**.

According to KDB 447498 D01v06 section 4.3.1, For frequencies below 100 MHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

Step b)

$\{[\text{Power allowed at numeric threshold for 50mm in step a)}] + [(\text{test separation distance} - 50\text{mm}) \cdot (f(\text{MHz})/150)]\}$ mW

Step c) 1)

For test separation distances $> 50\text{mm}$ and $< 200\text{mm}$, the power threshold at the corresponding test separation distance at 100MHz in step b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$

Step c) 2)

For test separation distances $\leq 50\text{mm}$, the power threshold determined by the equation in c) 1) for 50mm and 100MHz is multiplied by $\frac{1}{2}$.

>> The fundamental frequency of the EUT is 125kHz, the test separation distance is $\leq 50\text{mm}$.
(Manufacturer specified the separation distance is: 20mm)

Step a)

>> Numeric threshold, mW / 50mm $\cdot \sqrt{0.1\text{GHz}} \leq 3.0$
Numeric threshold $\leq 474.3\text{mW}$

Step b)

>> Numeric threshold $\leq 474.3\text{mW} + (50\text{mm} - 50\text{mm} \cdot 100\text{MHz}/150)$
Numeric threshold $\leq 474.3\text{mW}$

Step c) 1) & c) 2)

>> Numeric threshold $\leq 474.3\text{mW} \cdot [1 + \log 100/100\text{MHz}] \cdot \frac{1}{2}$
Numeric threshold $\leq 237.15\text{mW}$

>> The transmitter strength of EUT measured is: 46.38 dB μ V/m

The power calculated is 0.000000867mW

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.