

FCC ID: N6C-LLW4250

To whom it may concern,

We, UL Japan, Inc, hereby declare that Low Latency Wireless Device, model: LLW-4250 (FCC ID: N6C-LLW4250) of Silex Technology, Inc. is exempt from RF exposure SAR evaluation because the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula according to the Code of Federal Regulation title 47 section 1.1307(b)(3)(i)(B). This method is used at separation distances d (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive) for single RF sources. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d / 20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$$

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

When the minimum separation distance is shorter than 0.5 cm, 0.5 cm is applied.

The SAR evaluation exemption threshold is calculated as below.

[WLAN 2.4 GHz band part]

P_{th} (mW)	3060
f (GHz)	2.462
$ERP_{20 \text{ cm}}$ (mW)	3060
d (cm)	20.0

Conducted Power (dBm)	21.00
(mW)	125.89
Antenna Gain (dBi)	1.50
EIRP (dBm)	22.50
(dBm)	20.36
ERP (mW)	108.64

The Maximum time-averaged power or ERP whichever greater is 125.9 mW.
(Rounded up to two decimals place)


[WLAN 5 GHz band part]

P_{th} (mW)	3060
f (GHz)	5.825
$ERP_{20\text{ cm}}$ (mW)	3060
d (cm)	20.0

Conducted Power	(dBm)	19.00
	(mW)	79.43
Antenna Gain	(dBi)	1.70
EIRP	(dBm)	20.70
ERP	(dBm)	18.56
	(mW)	71.78

The Maximum time-averaged power or ERP whichever greater is 79.5 mW.
(Rounded up to two decimals place)

Thank you for your attention to this matter.



Satofumi Matsuyama
Engineer