

## RF Exposure Evaluation Report

**Report Reference No.**..... : **MTEB24120249-H**

**FCC ID**..... : **2A2RN-ACEVCJTSEN**

Compiled by

( position+printed name+signature)..: File administrators Alisa Luo



Supervised by

( position+printed name+signature)..: Test Engineer Sunny Deng



Approved by

( position+printed name+signature)..: Manager Yvette Zhou



Date of issue..... : **Dec.19,2024**

**Representative Laboratory Name.** : **Shenzhen Most Technology Service Co., Ltd.**

Address..... : No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,  
Nanshan, Shenzhen, Guangdong, China.

**Applicant's name**..... : **Xiamen Joint Tech. Co., Ltd**

Address..... : Building #1, No.268 HouXiang Rd, Xinyang, Industrial Park,  
Haicang District, XIAMEN, Fujian, China.

**Test specification/ Standard**..... : **47 CFR Part 1.1307; 47 CFR Part 1.1310**

**KDB447498D01 General RF Exposure Guidance v06**

TRF Originator..... : Shenzhen Most Technology Service Co., Ltd.

**Shenzhen Most Technology Service Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description**..... : Electric Vehicle AC Charger

Trade Mark..... : JTSE

Model/Type reference..... : JTSE-13448W2

Listed Models ..... : JTSE-134XXWYY  
(XX stands for Electric current 32,48; YY stands for 1,2;)

Modulation Type..... : ASK

Operation Frequency..... : 13.56MHz, 315MHz

Hardware Version..... : V1.4

Software Version..... : V1.0.9.1

Rating..... : AC 240V/60Hz

Result..... : **PASS**

TEST REPORT

Equipment under Test : Electric Vehicle AC Charger

Model /Type : JTSE-13448W2

Listed Models JTSE-134XXWYY  
(XX stands for Electric current 32,48;YY stands for 1,2;)

Remark Difference in input voltage and current.

Applicant : Xiamen Joint Tech. Co., Ltd

Address : Building #1,No.268 HouXiang Rd,Xinyang,Industrial Park,Haicang District,XIAMEN,Fujian,China.

Manufacturer : Xiamen Joint Tech. Co., Ltd

Address : Building #1,No.268 HouXiang Rd,Xinyang,Industrial Park,Haicang District,XIAMEN,Fujian,China.

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2024-12-19	Initial Issue	Alisa Luo

## **2. SAR Evaluation**

### **2.1 RF Exposure Compliance Requirement**

#### **2.1.1 Standard Requirement**

According to KDB447498D01 General RF Exposure Guidance v06

##### **4.3.1. Standalone SAR test exclusion considerations**

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### **2.1.2 Limits**

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C): 33

- 1) For test separation distances  $> 50$  mm and  $< 200$  mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances  $\leq 50$  mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz.

When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any SAR test results below 100 MHz to be acceptable.<sup>34</sup>

**2.1.3 EUT RF Exposure**

For 13.56MHz wireless:  
 Field strength=78.1dBuV/m  
 EIRP =78.1dBuV/m-95.2+6= -11.1dBm

Channel	EIRP	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
13.56 MHz	-11.1dBm	± 1	-10.1	0.098	0.000019	0.9789	Pass

Note: 1) Refer to report MTEB24050211-R for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (EIRP)/(4 * \pi * R^2) = (0.098)/(4 * 3.1416 * 20^2) = 0.000019$

For 315MHz wireless:  
 Field strength=70.53dBuV/m  
 EIRP =70.53dBuV/m-95.2= -24.67dBm

Channel	EIRP	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
315 MHz	-24.67dBm	± 1	-23.67	0.004	0.0000008	0.9789	Pass

Note: 1) Refer to report MTEB24050211-R for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (EIRP)/(4 * \pi * R^2) = (0.004)/(4 * 3.1416 * 20^2) = 0.0000008$

Contains FCCID: XMR2023FCS960K

## 5. Radio Frequency Radiation Exposure Evaluation

### 5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
Bluetooth	2402.0	0.73	6.00	6.730	4.710	0.001	1.000
2.4GHz WLAN	2412.0	0.73	20.00	20.730	118.304	0.024	1.000
5.2GHz WLAN	5180.0	1.14	19.00	20.140	103.276	0.021	1.000
5.3GHz WLAN	5260.0	1.00	19.00	20.000	100.000	0.020	1.000
5.5GHz WLAN	5500.0	0.60	19.00	19.600	91.201	0.018	1.000
5.8GHz WLAN	5745.0	0.95	19.00	19.950	98.855	0.020	1.000

**Note:**

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. According to the EUT characteristic, WLAN 2.4GHz and WLAN 5GHz cannot transmit simultaneously.
4. According to the EUT characteristic, WLAN and Bluetooth cannot transmit simultaneously.

### Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

Simultaneous TX (NFC+2.4G+315MHz)

Mode	Power Density(mW/m <sup>2</sup> )		Conclusion
	Results	Limit	
Simultaneous TX	0.024	1.0	PASS

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Results (NFC+2.4G+315MHz) = 0.000019/0.9789+0.024/1+0.0000008/0.9789=0.024

.....THE END OF REPORT.....