

## SPECIFICATION FOR APPROVAL

CUSTOMER:

CUST P/N:

FINE P/N:

Watch transmitter **7.8UH 0.08\*24P\*11TS**

DESC:

DATE:

**2024/05/30**

Version:

**A.0**

PREPARED BY	CHECKED BY	APPROVED BY	CUSTOMER APPROVE
黄燕铭	宁元安	黄锦华	

Shenzhen Songdao Technology Co., Ltd.

Factory Address: 8th Floor, Building 2, Sanjia High - tech Industrial Park, No. 123, Junfa 3rd Road, Dongkeng Town, Dongguan City.

TEL: 13728755750

E-mail: 506388681@qq.com


## Version Change History

[illegible]

# SPECIFICATION

DESC	Apple wireless charging transmitter coil <b>15*21.5-7.8UH</b>	Rev: A.0	CUST:	<b>XXX</b>
			CUST P/N:	

## 一、 DIMENSION:(mm)



A 24.5±0.5

B 23.7±0.5

C 21.5±0.5

D 14.5±0.3

E 7.7±0.05

F 3±2

H 35±2

### Note:


1.Cross the outgoing wires.

2.Wrap high-temperature tape Ts with a width of [mm (ref)] around the wire outlet.

3. Magnetic sheet: diameter 24.5±0.5mm, Inner hole diameter 7.7mm, Thickness 2.6±0.2mm

4.Use N52 magnets sized 7.5\*2.2mm with adhesive backing.

## 二、 SCHEMATIC DIAGRAM:



## 三、 Winding Specification:

NO.	TERMINAL		WIRE	Turns	Winding Direction
1	S	F	0.08*24P	11Ts	CCW

## 四、 ELECTRICAL CHARACTERISTICS:

TEMPERATURE:25±10°C, RELATIVE HUMIDITY:65±20%

NO.	ITEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS
1	IND.	S-F	3.7uH ±20% Single coil	100KHz/0.25V	LCZ METER 1062B
2	IND.	S-F	7.8 uH ±20% Single coil	100KHz/0.25V	LCZ METER 1062B
3	DCR	S-F	≤125mΩ	100KHz/0.25V	LCZ METER 502B
4	Q	S-F	≥35	100KHz/0.25V	LCZ METER 502B

Adapt to the environment

Parameter

Value

Operating temperature

-20℃ — +70℃

Storage temperature

-20℃ — +70℃

PREPARED BY/DATE	CHECKED BY/DATE
黄燕铭 2024/05/30	黄锦华 2024/05/30