

FCC TEST REPORT

FCC ID: YMX-EC7610A1

On Behalf of

XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD.

Massage Chair

Model No.: EC-7610A, OG8900/Master Drive Duo, CZ-720

Prepared for	:	XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD.
Address	:	(5/F)NO.168, QIANPU ROAD, SIMING DISTRICT, XIAMEN, Fujian CHINA

Prepared By	:	Shenzhen Alpha Product Testing Co., Ltd.
Address	:	Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

Test Result	:	Pass
Version Number	:	VO
Date of Report	:	July 18, 2024
Date of Test	:	April 23, 2024 ~July 18, 2024
Date of Receipt	:	April 23, 2024
Report Number	:	A2402103G1-C01-R01

TABLE OF CONTENTS

De	escription	Page
1.	Test Result Summary	5
2.	EUT Description	6
	2.1. Description of Device (EUT)	6
	2.2. Accessories of Device (EUT)	7
	2.3. Tested Supporting System Details	7
	2.4. Block Diagram of Connection between EUT and Simulators	7
	2.5. Description of Test Modes	7
	2.6. Test Conditions	7
	2.7. Test Facility	8
	2.8. Measurement Uncertainty	8
3.	Test Results and Measurement Data	9
	3.1. RF Exposure Test	9
	3.1.1. Test Specification	9
	3.1.2. Test Instruments	10
	3.1.3. Test data	10
4.	Photos of test setup	11

TEST REPORT DECLARATION

Applicant	:	XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD.			
Address	:	(5/F)NO.168, QIAN	5/F)NO.168, QIANPU ROAD,SIMING DISTRICT,XIAMEN,Fujian CHINA		
Manufacturer	:	XIAMEN HEALTHC	XIAMEN HEALTHCARE ELECTRONIC CO.,LTD.		
Address	:	65-66#, 62-63# BUILDING, SIMING ZONE, TONGAN INDUSTRIAL DISTRICT, XIAMEN CITY, FUJIAN PROVINCE, P.R.CHINA			
EUT Description	:	Massage Chair			
		(A) Model No.	:	EC-7610A, OG8900/Master Drive Duo, CZ-720	
		(B) Trademark	:	N/A	

Measurement Standard Used:

FCC CFR Title 47 Part 15 Subpart C

FCC KDB 680106 D01 Wireless Transfer v04

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness test. Also, this report shows that the EUT is technically compliant with the KDB 680106 D01 requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....:

Yannis Wen **Project Engineer**

yannis wen Tanepo

Jack Xu **Project Manager**

Date of issue.....

Approved by (name + signature).....:

July 18, 2024

Revision History

Revision	Issue Date	Revisions	Revised By
V0	July 18, 2024	Initial released Issue	Yannis Wen

1. Test Result Summary

Requirement	CFR 47 Section	Result
RF EXPOSURE	§1.1307(b)(1) & KDB680106	PASS

Note:

1. PASS: Test item meets the requirement.

2. Fail: Test item does not meet the requirement.

3. N/A: Test case does not apply to the test object.

4. The test result judgment is decided by the limit of test standard.

2. EUT Description

2.1. Description of Device (EUT)						
EUT Name	:	Massage Chair				
Model No.	:	EC-7610A, OG8900/Master Drive Duo, CZ-720				
DIFF	:	There is no difference except the name of the model. All tests are made with the EC-7610A model.				
Power supply	:	110-120V~ 60Hz				
EUT information	:	Wireless Output: 5W				
Operation frequency	:	110~205KHz				
Modulation	:	MSK				
Antenna Type	:	Coil Antenna, Maximum Gain is 0dBi (This value is supplied by applicant).				
Software version	:	V1.0				
Hardware version	:	V1.0				
Connector cable loss	:	Max. coaxial cable loss:0.5dB (Cable loss value is provided by applicant.)				
Intend use environment	:	Residential, commercial and light industrial environment				

2.2. Accessories of Device (EUT)

Accessories1	:	/	
Manufacturer	:	/	
Model	:	/	
Ratings	:	/	

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification
1	Wireless load				

2.4. Block Diagram of Connection between EUT and Simulators



2.5. Description of Test Modes

Channel	Frequency (KHz)
1	129

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35 ℃	24 ℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission Registration Number: 293961

July 15, 2019 Certificated by IC Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for H-Field	2.39dB
Uncertainty for E-Field	2.45dB
Uncertainty for conducted RF Power	0.65dB
Uncertainty for temperature	0.2 °C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

3. Test Results and Measurement Data

3.1. RF Exposure Test

3.1.1. Test Specification

Test Requirement:	FCC Rules and Regulations KDB680106					
Test Method:	§1.1307(b)(1) & KDB680106					
Limits:	According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1093 RF exposure is calculated. According KDB 680106 D01 Wireless Transfer v04					
Test Setup:	B + Field & B-Field Probe					
Test Mode:	Wireless charging load has been charge at no load, middle load and full load. All test modes were pre-tested, but we only recorded the worse case in this report.					
Test Procedure:	 The RF exposure test was performed in shielded chamber The measurement probe was placed at test distance(8cm) which is between the edge of the charger and the geometric centre of probe. The measurement probe used to search of highest strength. The highest emission level was recorded and compared with limit as soon as measurement of each points (A,B,C) were completed. The EUT were measured according to the dictates of KDB 680106 D01 Wireless Transfer v04. 					
Test Result:	PASS					

3.1.2. Test Instruments

Item	Equipment	Manufacturer	Model No.	Firmware version	Serial No.	Last Cal.	Cal. Due day
1	Exposure Level Tester	narda	ELT-400	N/A	N-0231	2023.08.22	2024.08.21
2	Magnetic field probe 100cm2	narda	ELT probe 100cm2	N/A	M0675	2023.08.22	2024.08.21
3	Isotropic Electric Field Probe	narda	EP-601	N/A	511WX60706	2023.08.16	2024.08.15

3.1.3. Test data

For Full load mode:

E-Field Strength at 8cm for position A,B,C from the edges surrounding the EUT (V/m)

U			0	<u> </u>	· · · /		
Frequency	Test	Test	Test	Test	Test	Limit	Limits
Range	Position	Position	Position	Position	Position	(50%)	Test
(MHz)	А	В	С	D	E	(V/m)	(V/m)
0.110-0.146	1.570	1.309	1.547	/	/	307	614

H-Filed Strength at 8cm for position A,B,C from the edges surrounding the EUT (A/m)

Frequency	Test Position	Measurement(uT)	Result(A/m)	Limit (50%)	Limits Test
Range				(A/m)	(A/m)
	А	0.874	0.699		
0.110-0.146	В	0.853	0.682	0.815	1.63
	С	0.854	0.683		

For Null load mode:

E-Field Strength 8cm for position A,B,C from the edges surrounding the EUT (V/m)

Frequency	Test	Test	Test	Test	Test	Limit	Limits
Range	Position	Position	Position	Position	Position	(50%)	Test
(MHz)	А	В	С	D	E	(V/m)	(V/m)
0.110-0.146	1.200	0.997	1.045	/	/	307	614

H-Filed Strength at 8cm for position A,B,C from the edges surrounding the EUT (A/m)

Frequency	Test Position	Measurement(uT)	Result(A/m)	Limit (50%)	Limits Test
Range				(A/m)	(A/m)
	А	0.820	0.656		
0.110-0.146	В	0.813	0.650	0.815	1.63
	С	0.829	0.663		

Note: $A / m = \frac{\mu T}{1.25}$

4. Photos of test setup

For Full load mode(8cm)



А

For Full load mode(8cm)



For Full load mode(8cm)



С

For Full load mode(8m)



For Full load mode(8cm)



В



For Full load mode(8cm)

С

-----END OF REPORT------