

Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

RF Exposure evaluation							
Report Reference No	GRCTR250302031-02						
FCC ID :	2BF7U-YY28351						
Compiled by		1 1111					
(position+printed name+signature):	Testing Engineer Jimmy Wang	for Mey					
Supervised by		1 11 show					
(position+printed name+signature):	Project Engineer Kelley Zhang	(Colley 20)					
Approved by							
(position+printed name+signature):	Manager Sam Wang	Son. Way					
Date of issue	Apr. 14, 2025						
Testing Laboratory Name	Shenzhen GUOREN Certification	n Technology Service Co., Ltd.					
Address:	101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China						
Applicant's name	y Co., Ltd						
Address:	Shop 802 on the first floor, No. 283 Xitou New Village, HechengStreet, Gaoming District, Foshan City						
Test specification:							
Standard:	47CFR §2.1091 KDB447498 D01						
Shenzhen GUOREN Certification Tee	chnology Service Co., Ltd. All rig	ghts reserved.					
This publication may be reproduced in Shenzhen GUOREN Certification Tech source of the material. Shenzhen GUO responsibility for and will not assume lia reproduced material due to its placeme	whole or in part for non-commercia nology Service Co., Ltd. is acknow REN Certification Technology Serv ability for damages resulting from the ent and context.	I purposes as long as the ledged as copyright owner and rice Co., Ltd. takes no ne reader's interpretation of the					
Test item description:	Bluetooth controller						
Trade Mark	1						
Manufacturer	Foshan Yiyi Lighting Technology	Co., Ltd					
Model/Type reference:	YY2835						
Listed Models	1						
Hardware Version	V1.0						
Software Version	V1.0						
Frequency	From 2412 - 2462MHz						
Ratings	DC 5V From External Circuit						
Result:	PASS						

TEST REPORT

Test Result:		PASS
Address	:	Shop 802 on the first floor, No. 283 Xitou New Village, HechengStreet, Gaoming District, Foshan City
Manufacturer	:	Foshan Yiyi Lighting Technology Co., Ltd
Address	:	Shop 802 on the first floor, No. 283 Xitou New Village, HechengStreet, Gaoming District, Foshan City
Applicant	:	Foshan Yiyi Lighting Technology Co., Ltd
Listed Models	:	/
Model /Type	:	YY2835
Equipment under Test	:	Bluetooth controller

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY	4
1.1. General Remarks	4
1.2. Product Description	4 4
1.4. Short description of the Equipment under Test (EUT)	
1.5. EUT configuration	5 5
	ə
2. TEST ENVIRONMENT	6
2.1. Address of the test laboratory	6
2.2. Test Facility	6
2.4. Statement of the measurement uncertainty	
3. METHOD OF MEASUREMENT	8
3.1. Applicable Standard	
3.2. Limit	8
3.3. MPE Calculation Method	8 9
3.5. Manufacturing Tolerance	9
4. EVALUATION RESULT	9

5. CONCLUSION

1. <u>SUMMARY</u>

1.1. General Remarks

Date of receipt of test sample	÷	Mar. 19, 2025
		M. 40.0005
Testing commenced on	:	Mar. 19, 2025
Testing concluded on	:	Apr. 14, 2025

1.2. Product Description

Product Name:	Bluetooth controller				
Model/Type reference:	YY2835				
Listed Models:	1				
Power supply:	DC 5V From External Circuit				
Tooting comple ID:	GRCTR250302031-1# (Engineer sample),				
resting sample ID.	GRCTR250302031-2# (Normal sample)				
Bluetooth					
Supported type:	Bluetooth low Energy				
Modulation:	GFSK				
Operation frequency:	2402MHz to 2480MHz				
Channel number:	40				
Channel separation:	2 MHz				
Antenna type:	PCB antenna				
Antenna gain*(Supplied by the customer):	0.43 dBi				
Remark:*When the information provided by the customer was used to calculate test results, if the information provided by the customer is not accurate, shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility.					

1.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	0	230V / 50 Hz	Ο	120V / 60Hz
		0	12 V DC	Ο	24 V DC
		\bullet	Other (specified in blank bel	ow)	

DC 5V From External Circuit

1.4. Short description of the Equipment under Test (EUT)

This is a Bluetooth controller.

For more details, refer to the user's manual of the EUT.

1.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

• - supplied by the manufacturer

 \bigcirc - supplied by the lab

Ο	Adapter	M/N:	TPA-83A050200CU01
		Manufacturer:	Tianyin

1.6. Modifications

No modifications were implemented to meet testing criteria.

2. <u>TEST ENVIRONMENT</u>

2.1. Address of the test laboratory

Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

2.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 920798 Designation Number: CN1304

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6202.01

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

ISED#: 27264 CAB identifier: CN0115

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

CNAS-Lab Code: L15631

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories for the Competence of Testing and Calibration Laboratories.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

2.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C		
Humidity:	30-60 %		
Atmospheric pressure:	950-1050mbar		

2.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen GUOREN Certification Technology Service Co., Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GUOREN Certification Technology Service Co., Ltd.:

Test Items	Measurement Uncertainty	Notes		
Max output power	0.54 dB	(1)		
(1) This was actively as a set of the second se				

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. <u>Method of measurement</u>

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2. Limit

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)
	Limits for Oco	cupational/Control	lled Exposure	
$\begin{array}{r} 0.3 - 3.0 \\ 3.0 - 30 \\ 30 - 300 \\ 300 - 1500 \\ 1500 - \\ 100,000 \end{array}$	614 1842/f 61.4 / /	1.63 4.89/f 0.163 / /	(100) * (900/f ²)* 1.0 f/300 5	6 6 6 6

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)
	Limits for Oco	cupational/Control	led Exposure	
$\begin{array}{r} 0.3 - 3.0 \\ 3.0 - 30 \\ 30 - 300 \\ 300 - 1500 \\ 1500 - \\ 100,000 \end{array}$	614 824/f 27.5 / /	1.63 2.19/f 0.073 / /	(100) * (180/f ²)* 0.2 f/1500 1.0	30 30 30 30 30 30

F=frequency in MHz

*=Plane-wave equivalent power density

3.3. MPE Calculation Method

Predication of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

S=PG/4πR²

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

3.4. Antenna Information

Antenna No.	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
BLE	/	PCB ANT	0.43 dBi for 2400-2500MHz	

EUT can only use antennas certificated as follows provided by manufacturer;

3.5. Manufacturing Tolerance

BLE(Peak)									
Channel	GFSK								
	Channel 00	Channel 19	Channel 39						
Target (dBm)	-2.0	-2.0	-2.0						
Tolerance ± (dB)	1.0	1.0	1.0						

4. Evaluation Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, r=20cm, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

	Output power		Antenna	Antenna	MDE	MPE
Modulation Type	dBm	mW	Gain	Gain	(mW/cm ²)	Limits
			(dBi)	(linear)		(mW/cm ²)
BLE	-1.0	0.7943	0.43	1.1041	0.00017	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;

2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

5. <u>Conclusion</u>

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

.....End of Report.....