

FCC PART 15.407 TEST REPORT

For

TP-Link Technologies Co., Ltd.

Building 24 (floors 1,3,4,5) and 28 (floors1-4),Central Science and Technology
Park,Nanshan,Shenzhen,China

FCC ID: TE7X20PROV1

Report Type: Original Report	Product Type: X20 Pro FDD-LTE Smartphone
Report Number: RSZ190626009-00D	
Report Date: 2019-07-17	
Reviewed By: Engineer	Jacob Kong 
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	10
SUPPORT EQUIPMENT LIST AND DETAILS	10
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS.....	12
TEST EQUIPMENT LIST	13
FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION	15
APPLICABLE STANDARD	15
TEST RESULT	15
FCC §15.203 – ANTENNA REQUIREMENT.....	16
APPLICABLE STANDARD	16
ANTENNA CONNECTOR CONSTRUCTION	16
FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP.....	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
TEST RESULTS SUMMARY	18
TEST DATA	18
§15.205 & §15.209 & §15.407(B) (1), (4), (6), (7) – UNDESIRABLE EMISSION	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	22
TEST PROCEDURE	22
CORRECTED AMPLITUDE & MARGIN CALCULATION	23
TEST RESULTS SUMMARY	23
TEST DATA	23
FCC §15.407(a) (1) – 26 dB & 6dB EMISSION BANDWIDTH.....	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST DATA	35
FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER	59
APPLICABLE STANDARD	59

TEST PROCEDURE59

TEST DATA60

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY62

APPLICABLE STANDARD62

TEST PROCEDURE62

TEST DATA63

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	X20 Pro FDD-LTE Smartphone
Tested Model	TP9131C
Multiple Model [#]	TP9131CXYZZ
Frequency Range	5G WI-FI: 5150-5250 MHz; 5725-5850 MHz
Transmit Power (Average Conducted)	5150-5250 MHz: 13.44dBm (802.11a), 12.26dBm(802.11n20), 11.90 dBm(802.11n40), 10.96dBm (802.11ac20), 10.40dBm(802.11 ac40), 9.37 dBm(802.11 ac80) 5725-5850 MHz 14.06dBm (802.11a), 12.80dBm(802.11n20), 12.65 dBm(802.11n40), 11.68dBm (802.11ac20), 11.76dBm(802.11 ac40), 11.04dBm(802.11 ac80)
Modulation Technique	WIFI: OFDM
Antenna Specification	FPC Antenna: 0.7dBi
Voltage Range	DC 3.85V from battery or DC 5.0V from adapter
Date of Test	2019-07-02~2019-07-13
Sample serial number	DE9131C931200001
Received date	2019-06-26
Sample/EUT Status	Good condition
Adapter information	Model: A8A-050200U-US1 Input: AC 100-240V, 50/60Hz, 0.35A Output: DC 5V, 2A

Notes: This series products model: TP9131CXYZZ and TP9131C are identical schematics, Model TP9131C was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.

Objective

This type approval report is prepared on behalf of *TP-Link Technologies Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS&DSS, Part 22H /24E / 27 PCE and Part 15B JBP submissions with FCC ID: TE7X20PROV1.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

The device support 802.11a/n20/n40/ac20/ac40/ac80 modes.

For 5150-5250MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 5725-5850MHz Band, 8 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785
151	5755	159	5795
153	5765	161	5805
155	5775	165	5825

EUT Exercise Software

Wi-Fi test in the engineer mode.


The device was tested with the worst case was performed as below:

Mode	Data rate	Power level
802.11a	1 Mbps	16
802.11n20	6 Mbps	15
802.11n40	MCS0	15
802.11ac20	MCS0	14.5
802.11ac40	MCS0	14.5
802.11ac80	MCS0	14.5

Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.


Duty cycle

802.11a mode




Date: 5.JUL.2019 11:46:29

802.11n20 mode




Date: 5.JUL.2019 11:43:56

802.11n40 mode




Date: 5.JUL.2019 11:44:32

802.11ac20 Mode




Date: 5.JUL.2019 11:43:03

802.11ac40 Mode



Date: 5.JUL.2019 11:42:14

802.11ac80 Mode



Date: 5.JUL.2019 11:41:14

Band	Duty Cycle (%)	T(ms)	1/T(kHz)	VBW Setting	10log(1/x)
802.11a	100	-	-	10Hz	-
802.11n20	100	-	-	10Hz	-
802.11n40	100	-	-	10Hz	-
802.11ac20	100	-	-	10Hz	-
802.11ac40	100	-	-	10Hz	-
802.11ac80	100	-	-	10Hz	-

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielding Un-detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§ 1.1307 , §2.1093	RF Exposure (SAR)	Compliance*
§15.203	Antenna Requirement	Compliance
§15.407(b)(6)& §15.207(a)	Conducted Emissions	Compliance
§15.205& §15.209 &§15.407(b) (1), (4),(7)	Undesirable Emission& Restricted Bands	Compliance
§15.407(b) (1),(4)	Out Of Band Emission	Not Applicable
§15.407(a) (1), (5),(e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliance
§15.407(a)(1),(3)	Conducted Transmitter Output Power	Compliance
§15.407 (a)(1),(3)	Power Spectral Density	Compliance

Note: * Please refer to SAR report released by BACL, report number: RSZ190626009-20.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2019-01-25	2020-01-25
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2019-03-02	2020-03-02
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Un-known	Conducted Emission Cable	78652	UF A210B-1-0720-504504	2018-11-12	2019-11-12
Radiated Emission Test					
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40-N	102259	2019-06-22	2020-06-22
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
Sonoma Instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2018-07-11	2019-07-11
Ducommun technologies	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	RG-214	1	2019-05-21	2019-11-19
Ducommun technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Heatsink Required	Amplifier	QLW-18405536-J0	15964001002	2018-11-12	2019-11-12
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2016-10-14	2019-10-14

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2019-03-02	2020-03-01
Agilent	USB wideband power meter	U2021XA	MY54250003	2019-06-23	2020-06-23
Ducommun technologies	RF Cable	RG-214	3	Each Time	
WEINSCHTEL	3dB Attenuator	6231	666	Each Time	

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ190626009-20.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 0.7dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2019-07-02.

EUT operation mode: Transmitting (worst case is 802.11a mode 5745MHz)

AC 120V/60 Hz, Line:

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.209500	53.6	19.8	63.2	9.6	QP
0.225500	52.0	19.8	62.6	10.6	QP
12.530830	46.8	20.0	60.0	13.2	QP
13.535710	45.6	20.0	60.0	14.4	QP
14.723630	46.8	20.0	60.0	13.2	QP
15.751710	44.4	20.1	60.0	15.6	QP
0.209500	47.7	19.8	53.2	5.5	Ave.
0.225500	45.5	19.8	52.6	7.1	Ave.
12.530830	34.8	20.0	50.0	15.2	Ave.
13.535710	33.8	20.0	50.0	16.2	Ave.
14.723630	32.6	20.0	50.0	17.4	Ave.
15.751710	29.7	20.1	50.0	20.3	Ave.

AC120V, 60 Hz, Neutral:

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.221500	52.5	19.8	62.8	10.3	QP
0.987090	42.1	19.8	56.0	13.9	QP
1.597910	42.1	19.8	56.0	13.9	QP
1.838310	43.4	19.8	56.0	12.6	QP
1.932930	43.8	19.9	56.0	12.2	QP
2.287350	41.5	19.8	56.0	14.5	QP
0.221500	46.7	19.8	52.8	6.0	Ave.
0.987090	35.0	19.8	46.0	11.0	Ave.
1.597910	31.7	19.8	46.0	14.3	Ave.
1.838310	32.3	19.8	46.0	13.7	Ave.
1.932930	32.1	19.9	46.0	13.9	Ave.
2.287350	30.9	19.8	46.0	15.1	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

§15.205 & §15.209 & §15.407(B) (1), (4), (6), (7) – UNDESIRABLE EMISSION**Applicable Standard**

FCC §15.407 (b) (1), (4), (6), (7); §15.209; §15.205;

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.


(4) For transmitters operating in the 5.725-5.85 GHz band:


(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

EUT Setup

Below 1 GHz:



Above 1 GHz:

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure**Radiated Spurious Emission**

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to ANSI C63.10-2013,9.4: For field strength measurements made at other than the distance at which the applicable limit is specified, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance). In some cases, a different distance correction factor may be required;

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$ is the field strength of the emission at the distance specified by the limit, in dB μ V/m
 E_{Meas} is the field strength of the emission at the measurement distance, in dB μ V/m
 d_{Meas} is the measurement distance, in m
 $d_{\text{SpecLimit}}$ is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1/3) = -9.5$ dB

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart E, section 15.205, 15.209 and 15.407 rules.

Test Data


Environmental Conditions

Temperature:	25~24 °C
Relative Humidity:	52~58 %
ATM Pressure:	100.9~101.0 kPa

The testing was performed by Leo Huang and Curry Xiang from 2019-07-02 to 2019-07-04.

EUT operation mode: Transmitting

30 MHz – 1 GHz: (worst case is 802.11a mode 5745 MHz)



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
30.374220	17.53	126.0	V	178.0	-7.9	40.00	22.47
40.915625	16.40	105.0	V	172.0	-14.4	40.00	23.60
45.116750	15.44	132.0	V	233.0	-17.3	40.00	25.56
682.898500	20.38	276.0	H	100.0	-2.0	46.00	25.62
839.171125	28.88	209.0	H	188.0	5.9	46.00	17.12
897.577250	27.62	396.0	H	59.0	4.3	46.00	18.38

30 MHz ~ 40 GHz:**5150-5250 MHz:**

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBµV/m)	FCC Part 15.407/205/209	
	Reading (dBµV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBµV/m)	Margin (dB)
802.11a									
5180 MHz									
5149.11	34.88	PK	317	1.4	H	38.36	73.24	83.5	10.26
5149.11	16.84	Ave.	317	1.4	H	38.36	55.20	63.5	8.30
5378.05	31.22	PK	91	2.0	H	39.09	70.31	83.5	13.19
5378.05	16.71	Ave.	91	2.0	H	39.09	55.80	63.5	7.70
10360.00	42.71	PK	246	2.3	H	17.42	60.13	77.7	17.57
5200 MHz									
10400.00	41.72	PK	203	2.1	H	17.52	59.24	77.7	18.46
5240 MHz									
5137.46	30.71	PK	143	1.5	H	38.36	69.07	83.5	14.43
5137.46	16.54	Ave.	143	1.5	H	38.36	54.90	63.5	8.60
5379.91	31.43	PK	139	1.0	H	39.09	70.52	83.5	12.98
5379.91	16.67	Ave.	139	1.0	H	39.09	55.76	63.5	7.74
10480.00	42.21	PK	150	1.0	H	17.25	59.46	77.7	18.24
802.11n20									
5180 MHz									
5137.46	31.22	PK	35	1.5	H	38.36	69.58	83.5	13.92
5137.46	16.61	Ave.	35	1.5	H	38.36	54.97	63.5	8.53
5423.78	31.47	PK	37	1.1	H	39.19	70.66	83.5	12.84
5423.78	16.69	Ave.	37	1.1	H	39.19	55.88	63.5	7.62
10360.00	42.20	PK	7	1.0	H	17.42	59.62	77.7	18.08
5200 MHz									
10400.00	42.59	PK	301	1.6	H	17.52	60.11	77.7	17.59
5240 MHz									
5121.02	30.67	PK	264	1.7	H	38.36	69.03	83.5	14.47
5121.02	15.74	Ave.	264	1.7	H	38.36	54.10	63.5	9.40
5454.51	31.24	PK	347	2.3	H	39.37	70.61	83.5	12.89
5454.51	16.53	Ave.	347	2.3	H	39.37	55.90	63.5	7.60
10480.00	41.98	PK	144	1.2	H	17.25	59.23	77.7	18.47

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11n40									
5190 MHz									
5149.56	36.82	PK	280	2.4	H	38.36	75.18	83.5	8.32
5149.56	18.83	Ave.	280	2.4	H	38.36	57.19	63.5	6.31
5434.13	30.74	PK	290	1.2	H	39.29	70.03	83.5	13.47
5434.13	15.93	Ave.	290	1.2	H	39.29	55.22	63.5	8.28
10380.00	41.63	PK	264	1.2	H	17.42	59.05	77.7	18.65
5230 MHz									
5148.81	31.70	PK	305	1.9	H	38.36	70.06	83.5	13.44
5148.81	16.24	Ave.	305	1.9	H	38.36	54.60	63.5	8.90
5417.77	31.49	PK	170	2.1	H	39.19	70.68	83.5	12.82
5417.77	16.13	Ave.	170	2.1	H	39.19	55.32	63.5	8.18
10460.00	41.74	PK	13	2.4	H	17.15	58.89	77.7	18.81
802.11ac20									
5180 MHz									
5144.18	31.39	PK	305	2.5	H	38.36	69.75	83.5	13.75
5144.18	16.58	Ave.	305	2.5	H	38.36	54.94	63.5	8.56
5428.88	30.12	PK	302	1.5	H	39.19	69.31	83.5	14.19
5428.88	15.84	Ave.	302	1.5	H	39.19	55.03	63.5	8.47
10360.00	42.14	PK	290	2.4	H	17.42	59.56	77.7	18.14
5200 MHz									
10400.00	41.11	PK	94	2.4	H	17.52	58.63	77.7	19.07
5240 MHz									
5146.49	30.59	PK	128	1.4	H	38.36	68.95	83.5	14.55
5146.49	15.94	Ave.	128	1.4	H	38.36	54.30	63.5	9.20
5397.20	30.61	PK	360	1.1	H	39.19	69.80	83.5	13.70
5397.20	16.10	Ave.	360	1.1	H	39.19	55.29	63.5	8.21
10480.00	41.76	PK	313	1.6	H	17.25	59.01	77.7	18.69
802.11ac40									
5190 MHz									
5139.20	30.36	PK	157	1.2	H	38.36	68.72	83.5	14.78
5139.20	15.72	Ave.	157	1.2	H	38.36	54.08	63.5	9.42
5405.64	31.11	PK	122	1.2	H	39.19	70.30	83.5	13.20
5405.64	16.25	Ave.	122	1.2	H	39.19	55.44	63.5	8.06
10380.00	43.01	PK	39	1.7	H	17.42	60.43	77.7	17.27
5230 MHz									
5133.52	31.18	PK	126	1.2	H	38.36	69.54	83.5	13.96
5133.52	16.56	Ave.	126	1.2	H	38.36	54.92	63.5	8.58
5458.01	30.33	PK	193	1.7	H	39.37	69.70	83.5	13.80
5458.01	15.94	Ave.	193	1.7	H	39.37	55.31	63.5	8.19
10460.00	41.83	PK	163	1.5	H	17.15	58.98	77.7	18.72

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11ac80									
5210 MHz									
5120.73	30.61	PK	188	1.3	H	38.36	68.97	83.5	14.53
5120.73	16.02	Ave.	188	1.3	H	38.36	54.38	63.5	9.12
5426.97	30.86	PK	92	1.3	H	39.19	70.05	83.5	13.45
5426.97	16.35	Ave.	92	1.3	H	39.19	55.54	63.5	7.96
10420.00	42.31	PK	298	2.1	H	17.52	59.83	77.7	17.87

5725-5850 MHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBµV/m)	FCC Part 15.407/205/209	
	Reading (dBµV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
802.11a									
5745 MHz									
5696.99	31.52	PK	356	1.6	H	39.49	71.01	112.47	41.46
5719.43	35.11	PK	356	1.6	H	39.49	74.60	120.14	45.54
5724.64	41.20	PK	266	2.2	H	39.49	80.69	130.88	50.19
11490.00	41.80	PK	87	1.1	H	17.47	59.27	83.5	24.23
11490.00	26.97	Ave.	87	1.1	H	17.47	44.44	63.5	19.06
5785 MHz									
11570.00	42.25	PK	229	1.9	H	17.51	59.76	83.5	23.74
11570.00	27.92	Ave.	229	1.9	H	17.51	45.43	63.5	18.07
5825 MHz									
5853.14	33.97	PK	309	2.3	H	39.87	73.84	120.54	46.70
5861.93	32.87	PK	309	2.3	H	39.87	72.74	118.36	45.62
5886.61	33.64	PK	172	2.2	H	39.87	73.51	106.11	32.60
11650.00	41.71	PK	260	2.1	H	16.18	57.89	83.5	25.61
11650.00	27.87	Ave.	260	2.1	H	16.18	44.05	63.5	19.45
802.11n20									
5745 MHz									
5688.96	31.20	PK	183	1.2	H	39.49	70.69	129.49	58.80
5718.71	38.14	PK	183	1.2	H	39.49	77.63	120.01	42.38
5723.53	43.92	PK	155	2.5	H	39.49	83.41	101.34	17.93
11490.00	40.56	PK	120	2.1	H	17.47	58.03	83.5	25.47
11490.00	27.01	Ave.	120	2.1	H	17.47	44.48	63.5	19.02
5785 MHz									
11570.00	41.44	PK	48	2.2	H	17.51	58.95	83.5	24.55
11570.00	27.92	Ave.	48	2.2	H	17.51	45.43	63.5	18.07
5825 MHz									
5850.97	34.30	PK	235	1.3	H	39.87	74.17	129.49	55.32
5856.02	32.72	PK	235	1.3	H	39.87	72.59	120.01	47.42
5893.05	32.41	PK	49	2.4	H	39.87	72.28	101.34	29.06
11650.00	41.68	PK	330	1.5	H	16.18	57.86	83.5	25.64
11650.00	27.65	Ave.	330	1.5	H	16.18	43.83	63.5	19.67

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
802.11n40									
5755 MHz									
5650.94	31.82	PK	113	1.2	H	39.49	71.31	78.4	7.09
5749.08	37.77	PK	113	1.2	H	39.49	77.26	128.44	51.18
5722.69	39.84	PK	148	1.0	H	39.49	79.33	126.43	47.10
11510.00	42.16	PK	104	1.5	H	17.47	59.63	83.5	23.87
11510.00	28.04	Ave.	104	1.5	H	17.47	45.51	63.5	17.99
5795 MHz									
5852.44	33.29	PK	328	2.1	H	39.87	73.16	126.14	52.98
5871.74	32.82	PK	328	2.1	H	39.87	72.69	115.61	42.92
5907.81	32.21	PK	289	1.1	H	39.87	72.08	90.42	18.34
11590.00	41.47	PK	293	1.9	H	17.51	58.98	83.5	24.52
11590.00	27.63	Ave.	293	1.9	H	17.51	45.14	63.5	18.36
802.11ac20									
5745 MHz									
5697.28	31.06	PK	349	1.9	H	39.49	70.55	112.69	42.14
5718.65	31.92	PK	349	1.9	H	39.49	71.41	119.92	48.51
5724.84	36.47	PK	243	2.3	H	39.49	75.96	131.34	55.38
11490.00	40.88	PK	294	1.0	H	17.47	58.35	83.5	25.15
11490.00	26.97	Ave.	294	1.0	H	17.47	44.44	63.5	19.06
5785 MHz									
11570.00	41.16	PK	69	2.1	H	17.51	58.67	83.5	24.83
11570.00	27.28	Ave.	69	2.1	H	17.51	44.79	63.5	18.71
5825 MHz									
5851.80	32.16	PK	112	2.4	H	39.87	72.03	127.6	55.57
5859.76	32.52	PK	112	2.4	H	39.87	72.39	118.97	46.58
5889.21	33.01	PK	58	1.8	H	39.87	72.88	104.18	31.30
11650.00	41.64	PK	47	2.2	H	16.18	57.82	83.5	25.68
11650.00	27.43	Ave.	47	2.2	H	16.18	43.61	63.5	19.89

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
802.11ac40									
5755 MHz									
5675.94	31.42	PK	153	1.7	H	39.49	70.91	96.9	25.99
5711.27	33.52	PK	153	1.7	H	39.49	73.01	117.86	44.85
5723.31	35.36	PK	169	2.5	H	39.49	74.85	127.85	53.00
11510.00	41.89	PK	105	1.6	H	17.47	59.36	83.5	24.14
11510.00	28.06	Ave.	105	1.6	H	17.47	45.53	63.5	17.97
5795 MHz									
5854.55	32.47	PK	148	2.3	H	39.87	72.34	121.33	48.99
5871.77	33.40	PK	148	2.3	H	39.87	73.27	115.6	42.33
5898.69	33.09	PK	141	1.3	H	39.87	72.96	97.17	24.21
11590.00	42.10	PK	325	1.6	H	17.51	59.61	83.5	23.89
11590.00	28.45	Ave.	325	1.6	H	17.51	45.96	63.5	17.54
802.11ac80									
5775 MHz									
5695.76	31.54	PK	84	1.2	H	39.49	71.03	111.56	40.53
5719.72	34.52	PK	84	1.2	H	39.49	74.01	120.22	46.21
5723.49	36.26	PK	164	1.4	H	39.49	75.75	128.26	52.51
11550.00	42.33	PK	187	1.5	H	17.51	59.84	83.5	23.66
11550.00	28.41	Ave.	187	1.5	H	17.51	45.92	63.5	17.58

Note:


Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) + Cable Loss – Amplifier Factor


Margin = Limit- Corr. Amplitude

All other spurious emissions are 20 dB below the limit or are on the system noise floor level.

Peak
Pre-scan with 802.11a 5180MHz
Horizontal




Date: 4.JUL.2019 00:46:16




Date: 4.JUL.2019 03:08:00

Vertical




Date: 4.JUL.2019 00:53:14




Date: 4.JUL.2019 03:19:36

Average Horizontal




Date: 4.JUL.2019 00:49:03




Date: 4.JUL.2019 03:13:58

Vertical



Date: 4.JUL.2019 00:56:58



Date: 4.JUL.2019 03:24:45

FCC §15.407(a) (1) – 26 dB & 6dB EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure


1. Emission Bandwidth (EBW)

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	52~56 %
ATM Pressure:	100.9~101.0 kPa

The testing was performed by James Fu from 2019-07-05 to 2019-07-09.


EUT operation mode: Transmitting

Test Result: Pass; please refer to the following tables and plots.

5150 MHz - 5250 MHz:


Frequency (MHz)	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Remark
802.11a			No transmitted signal in the 99% bandwidth extends into the U-NII-2A band
5180	20.423	16.731	
5200	20.769	16.731	
5240	21.051	16.731	
802.11n20			
5180	20.603	17.756	
5200	20.897	17.821	
5240	21.282	17.756	
802.11n40			
5190	41.759	36.282	
5230	41.590	36.410	
802.11ac20			
5180	20.667	17.692	
5200	20.449	17.692	
5240	20.513	17.692	
802.11ac40			
5190	41.359	36.282	
5230	41.590	36.282	
802.11ac80			
5210	81.795	75.641	

802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz




Date: 5.JUL.2019 10:56:50

802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz




Date: 5.JUL.2019 11:06:35

802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz




Date: 5.JUL.2019 11:07:36


802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz



Date: 5.JUL.2019 11:10:08


802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz

Date: 5.JUL.2019 11:12:47

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz


Date: 5.JUL.2019 11:14:32

802.11n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5190 MHz




Date: 5.JUL.2019 11:35:14

802.11n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5230 MHz




Date: 5.JUL.2019 11:36:35

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz




Date: 5.JUL.2019 11:22:33

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz




Date: 5.JUL.2019 11:23:43

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz




Date: 5.JUL.2019 11:25:36


802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5190 MHz



Date: 5.JUL.2019 11:28:42

802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5230 MHz

Date: 5.JUL.2019 11:30:42


802.11ac80 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5210 MHz

Date: 5.JUL.2019 11:39:00

5725 MHz – 5850 MHz:


Frequency (MHz)	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Remark
802.11a				No transmitted signal in the 99% bandwidth extends into the U-NII-2C band
5745	16.384	16.795	0.5	
5785	16.321	16.731	0.5	
5825	16.321	16.731	0.5	
802.11n20				
5745	17.628	17.756	0.5	
5785	17.603	17.756	0.5	
5825	17.667	17.756	0.5	
802.11n40				
5755	36.410	36.282	0.5	
5795	36.359	36.282	0.5	
802.11ac20				
5745	17.628	17.692	0.5	
5785	17.603	17.692	0.5	
5825	17.603	17.692	0.5	
802.11ac40				
5755	36.359	36.282	0.5	
5795	36.231	36.282	0.5	
802.11ac80				
5775	76.667	75.385	0.5	

802.11a mode, 6dB Emission Bandwidth, 5745 MHz




Date: 5.JUL.2019 14:12:14

802.11a mode, 6dB Emission Bandwidth, 5785 MHz




Date: 5.JUL.2019 14:13:26

802.11a mode, 6dB Emission Bandwidth, 5825 MHz



Date: 5.JUL.2019 15:09:38

802.11n20 mode, 6dB Emission Bandwidth, 5745 MHz



Date: 5.JUL.2019 14:02:47

Ref 28 dBm * Att 20 dB * RBW 100 kHz Delta 1 [T1] -1.43 dB
 * VBW 300 kHz SWT 20 ms 17.602564103 MHz

Offset 3.3 dB Marker 1 [T1] -1.54 dBm
 5.776230769 GHz

1 PK MAXH

D1 -0.3 dBm
 D2 -6.37 dBm

Center 5.785 GHz 4 MHz/ Span 40 MHz

Ref 28 dBm * Att 20 dB * RBW 100 kHz Delta 1 [T1] -1.87 dB
 * VBW 300 kHz 17.666666667 MHz
 SWT 20 ms

Offset 3.5 dB Marker 1 [T1] -4.99 dBm
 5.816230769 GHz

1 PK MAXH


D1 -0.7 dBm
 D2 -5.77 dBm

3DB

Center 5.825 GHz 4 MHz/ Span 40 MHz


Page 47 of 78

802.11n40 mode, 6dB Emission Bandwidth, 5755 MHz





Date: 5.JUL.2019 14:09:38


802.11n40 mode, 6dB Emission Bandwidth, 5795 MHz



Date: 6.JUL.2019 16:18:03




802.11ac20 mode, 6dB Emission Bandwidth, 5825 MHz




Date: 5.JUL.2019 13:59:52

802.11ac40 mode, 6dB Emission Bandwidth, 5755 MHz




Date: 5.JUL.2019 13:52:41

802.11ac40 mode, 6dB Emission Bandwidth, 5795 MHz




Date: 5.JUL.2019 13:55:14

802.11ac80 mode, 6dB Emission Bandwidth, 5775 MHz




Date: 9.JUL.2019 16:20:24

802.11a mode, 99% Occupied Bandwidth, 5745 MHz




Date: 5.JUL.2019 16:03:00

802.11a mode, 99% Occupied Bandwidth, 5785 MHz




Date: 5.JUL.2019 16:03:59

802.11a mode, 99% Occupied Bandwidth, 5825 MHz




Date: 5.JUL.2019 16:05:05

802.11n20 mode, 99% Occupied Bandwidth, 5745 MHz




Date: 5.JUL.2019 16:11:55

802.11n20 mode, 99% Occupied Bandwidth, 5785 MHz




Date: 5.JUL.2019 16:11:15

802.11n20 mode, 99% Occupied Bandwidth, 5825 MHz




Date: 5.JUL.2019 16:07:35

802.11n40 mode, 99% Occupied Bandwidth, 5755 MHz




Date: 5.JUL.2019 16:17:43

802.11n40 mode, 99% Occupied Bandwidth, 5795 MHz




Date: 5.JUL.2019 16:17:20

802.11ac20 mode, 99% Occupied Bandwidth, 5745 MHz




Date: 5.JUL.2019 16:13:30

802.11ac20 mode, 99% Occupied Bandwidth, 5785 MHz




Date: 5.JUL.2019 16:14:25

802.11ac20 mode, 99% Occupied Bandwidth, 5825 MHz




Date: 5.JUL.2019 16:14:56

802.11ac40 mode, 99% Occupied Bandwidth, 5755 MHz




Date: 5.JUL.2019 16:15:45

802.11ac40 mode, 99% Occupied Bandwidth, 5795 MHz



Date: 5.JUL.2019 16:16:39

802.11ac80 mode, 99% Occupied Bandwidth, 5775 MHz



Date: 5.JUL.2019 16:26:38

FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER**Applicable Standard**


For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by James Fu on 2019-07-12.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the following tables.

5150 MHz – 5250 MHz

Frequency (MHz)	Conducted Average Output Power (dBm)	Limit (dBm)
802.11a		
5180	13.14	24
5200	13.40	
5240	13.44	
802.11n20		
5180	11.80	24
5200	12.15	
5240	12.26	
802.11n40		
5190	11.65	24
5230	11.90	
802.11ac20		
5180	10.46	24
5200	10.66	
5240	10.96	
802.11ac40		
5190	10.34	24
5230	10.40	
802.11ac80		
5210	9.37	24

5725 MHz – 5825 MHz:

Frequency (MHz)	Conducted Average Output Power (dBm)	Limit (dBm)
802.11a		
5745	14.06	30
5785	13.16	
5825	12.53	
802.11n20		
5745	12.80	30
5785	12.15	
5825	11.37	
802.11n40		
5755	12.65	30
5795	11.90	
802.11ac20		
5745	11.68	30
5785	10.91	
5825	10.47	
802.11ac40		
5755	11.76	30
5795	11.21	
802.11ac80		
5775	11.04	30

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY

Applicable Standard

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.1.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500 \text{ kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by James Fu on 2019-07-12.

EUT operation mode: Transmitting


Test Result: Pass

Please refer to the following tables and plots.

5150 MHz – 5250 MHz


Frequency (MHz)	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)
802.11a		
5180	3.16	11
5200	3.43	
5240	3.43	
802.11n20		
5180	1.86	11
5200	2.19	
5240	2.09	
802.11n40		
5190	-1.10	11
5230	-1.16	
802. 11ac20		
5180	0.53	11
5200	0.42	
5240	0.43	
802. 11ac40		
5190	-2.86	11
5230	-2.84	
802. 11ac80		
5210	-6.86	11

802.11a mode, Power Spectral Density, 5180 MHz




Date: 12.JUL.2019 20:34:49

802.11a mode, Power Spectral Density, 5200 MHz




Date: 12.JUL.2019 20:35:13

802.11a mode, Power Spectral Density, 5240 MHz




Date: 12.JUL.2019 20:35:43

802.11n20 mode, Power Spectral Density, 5180 MHz




Date: 12.JUL.2019 20:32:52

802.11n20 mode, Power Spectral Density, 5200 MHz




Date: 12.JUL.2019 20:33:18

802.11n20 mode, Power Spectral Density, 5240 MHz




Date: 12.JUL.2019 20:33:47

802.11n40 mode, Power Spectral Density, 5190 MHz




Date: 12.JUL.2019 20:27:40

802.11n40 mode, Power Spectral Density, 5230 MHz




Date: 12.JUL.2019 20:28:53

802.11ac20 mode, Power Spectral Density, 5180 MHz




Date: 12.JUL.2019 20:31:11

802.11ac20 mode, Power Spectral Density, 5200 MHz




Date: 12.JUL.2019 20:31:51

802. 11ac20 mode, Power Spectral Density, 5240 MHz




Date: 12.JUL.2019 20:32:17

802. 11ac40 mode, Power Spectral Density, 5190 MHz




Date: 12.JUL.2019 20:21:17

802. 11ac40 mode, Power Spectral Density, 5230 MHz



Date: 12.JUL.2019 20:20:46

802. 11ac80 mode, Power Spectral Density, 5210 MHz




Date: 12.JUL.2019 20:29:57

5725 MHz – 5825 MHz:


Frequency (MHz)	Power Spectral Density (dBm/500kHz)	Limit (dBm/500kHz)
802.11a		
5745	1.26	30
5785	1.05	
5825	0.18	
802.11n20		
5745	0.16	30
5785	-0.09	
5825	-1.04	
802.11n40		
5755	-2.96	30
5795	-3.62	
802.11ac20		
5745	-0.95	30
5785	-1.32	
5825	-2.31	
802.11ac40		
5755	-4.04	30
5795	-4.68	
802.11ac80		
5775	-7.86	30

802.11a mode, Power Spectral Density, 5745 MHz




Date: 12.JUL.2019 21:02:54

802.11a mode, Power Spectral Density, 5785 MHz




Date: 12.JUL.2019 21:03:17

802.11a mode, Power Spectral Density, 5825 MHz




Date: 12.JUL.2019 21:03:35

802.11n20 mode, Power Spectral Density, 5745 MHz




Date: 12.JUL.2019 21:00:13

802.11n20 mode, Power Spectral Density, 5785 MHz




Date: 12.JUL.2019 21:00:35

802.11n20 mode, Power Spectral Density, 5825 MHz




Date: 12.JUL.2019 21:00:58

802.11n40 mode, Power Spectral Density, 5755 MHz




Date: 12.JUL.2019 20:59:15

802.11n40 mode, Power Spectral Density, 5795 MHz




Date: 12.JUL.2019 20:59:32

802.11ac20 mode, Power Spectral Density, 5745 MHz




Date: 12.JUL.2019 21:01:31

802.11ac20 mode, Power Spectral Density, 5785 MHz




Date: 12.JUL.2019 21:01:58

802. 11ac20 mode, Power Spectral Density, 5825 MHz




Date: 12.JUL.2019 21:02:19

802. 11ac40 mode, Power Spectral Density, 5755 MHz




Date: 12.JUL.2019 20:58:18

802. 11ac40 mode, Power Spectral Density, 5795 MHz



Date: 12.JUL.2019 20:58:46

802. 11ac80 mode, Power Spectral Density, 5775 MHz



Date: 12.JUL.2019 20:57:44

***** END OF REPORT *****