

## RF Exposure Report

FCC ID: 2A2YH-M3101

Applicant: Suzhou Mojawa Intelligent Electronic Co., Ltd

Address: Room F1-A-1028, Building A2, No. 8, Qicun Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone , Jiangsu Province, PRC

Manufacturer: Suzhou Mojawa Intelligent Electronic Co., Ltd

Address: Room F1-A-1028, Building A2, No. 8, Qicun Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone , Jiangsu Province, PRC

Product(s): HaptiFit TERRA

Brand:  MOJAWA

Test Model(s): M3101

Series Model(s): N/A

Test Date: Dec. 09, 2023 ~ Dec. 26, 2023

Issued Date: Jan. 11, 2024

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.


Address: No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China

Test Firm Registration No.: 915896

Standards: FCC Part 2(Section 2.1093)  
KDB 447498 D01 General RF Exposure Guidance v06  
IEEE C95.1


The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Nature Lee

Reviewed by :



Dragon Long

Approved by :



Scott He

"This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. Our report includes all the tests requested by you and the results thereof based upon the information that you provided to us. The report would be invalid without specific stamp of test institute and the signatures of tester and approver."

**Table of contents**

Release control record .....	3
1 General Information .....	4
1.1 General Description of EUT .....	4
2 RF exposure limit .....	5
3 Calculation .....	5
4 Calculation SAR test exclusion thresholds.....	6
Appendix – Information on the Testing Laboratories.....	7

Test Report No.: 23082202-SE-US-01

**Release control record**


Issue No.	Reason for change	Date Issued
23082202-SE-US-01	Original Release	Jan. 11, 2024

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)  
Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-83078199](#)  
Web.: [www.hwa-hsing.com](#)  
E-Mail: [customerservice.dg@hwa-hsing.com](#)

Release  
Ver. 1.4

**1 General Information****1.1 General Description of EUT**

Product	HaptiFit TERRA
Brand	 MOJAWA
Sample No.	HS2312110010
Test Model(s)	M3101
Series Model(s)	N/A
Status of EUT	Engineering Prototype
Power Supply Rating	DC 5V from USB or DC 3.8V from battery
Modulation Type	GFSK, $\pi/4$ DQPSK, 8DPSK for FHSS, GFSK for DTS
Transfer Rate	1/2/3Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	79
Output Power (Average)	BLE: -0.945dBm EDR: -0.964dBm
Antenna Type and Antenna Gain	Chip Antenna; 2.39dBi Gain
Antenna Connector	N/A
Accessory Device	Type-C Cable: Unshielded, 20cm USB Cable: Unshielded, 20cm

## Note:

1. Please refer to the EUT photo document (Reference No.: 23082202-01&02) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
3. Description of available battery to the EUT. This product can be selected from different manufacturers of batteries. See the following table for battery details.

No.	Manufacturer	Product Name	Model No.	Rated voltage	Rated Current or Power
1	Guangdong Mic-power New Energy Co., Ltd.	Rechargeable Li-ion Polymer Battery	M581221	3.8V	200mAh, 0.76Wh
2	Hunan Yideng New Energy Co., Ltd.	Rechargeable Li-ion Polymer Battery	581129	3.8V	200mAh, 0.76Wh

## 2 RF exposure limit

The corresponding SAR Exclusion Threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, 16 where

- ☐  $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- ☐ Power and distance are rounded to the nearest mW and mm before calculation
- ☐ The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, the distance of 5 mm is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:

- a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · (f(MHz)/150)] mW, at 100MHz to 1500 MHz
- b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at  $> 1500$  MHz and  $\leq 6$  GHz

- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.

- a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$  for test separation distances  $> 50$  mm and  $< 200$  mm.
- b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$  for test separation distances  $\leq 50$  mm.
- c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

## 3 Calculation

The antenna of this product, under normal use condition, is at less than 5mm away from the body of the user.

**4 Calculation SAR test exclusion thresholds**

The measured of Maximum RF Conduted Power

Mode	Frequency (MHz)	Maximum RF Power (dBm)
BT GFSK	2402-2480	-0.964
BT 8DPSK	2402-2480	-1.955
BLE	2402-2480	-0.945

The tuned Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT GFSK	2402-2480	-1	±2	-3	1
BT 8DPSK	2402-2480	-2	±2	-4	0
BLE	2402-2480	-1	±2	-3	1

SAR Test Exclusion Thresholds

Frequency (MHz)	Maximum source-based time averaged conducted output power(dBm)	Minimum separation distance (mm)	Result of Eq. 1	Limit for 1-g SAR	Limit for 10-g extremity SAR	Verdict
2402-2480	1	5	0.3965	3.0	7.5	Exempt from SAR

**Conclusion:** Therefore this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.

Test Report No.: 23082202-SE-US-01

**Appendix – Information on the Testing Laboratories**

We, [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Contact Tel: [0769-83078199](#)

Email: [Customerservice.dg@hwa-hsing.com](mailto:Customerservice.dg@hwa-hsing.com)

Web Site: [www.hwa-hsing.com](http://www.hwa-hsing.com)

--- END ---