



**中认信通**  
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



## TEST REPORT

**Applicant:** UNNECTO HOLDING LIMITED

**Address:** 13/F HARBOUR COMMERCIAL BUILDING 122-124 CONNAUGHT  
ROAD CENTRAL SHEUNG WAN HONG KONG

**FCC ID:** 2ADR3EA227

**Product Name:** WIRELESS EARBUDS

**Standard(s):** 47 CFR Part 15, Subpart C(15.247)  
ANSI C63.10-2013  
KDB 558074 D01 15.247 Meas Guidance v05r02

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

**Report Number:** CR240104515-00A

**Date Of Issue:** 2024/2/7

**Reviewed By:** Calvin Chen

Title: RF Engineer

**Approved By:** Sun Zhong

Title: Manager

**Test Laboratory:** China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,  
Guangdong, China  
Tel: +86-769-82016888

## Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

## Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

## CONTENTS

<b>DOCUMENT REVISION HISTORY .....</b>	<b>5</b>
<b>1. GENERAL INFORMATION .....</b>	<b>6</b>
<b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....</b>	<b>6</b>
<b>1.2 DESCRIPTION OF TEST CONFIGURATION.....</b>	<b>7</b>
1.2.1 EUT Operation Condition:.....	7
1.2.2 Support Equipment List and Details .....	7
1.2.3 Support Cable List and Details .....	7
1.2.4 Block Diagram of Test Setup.....	7
<b>1.3 MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>3. REQUIREMENTS AND TEST PROCEDURES .....</b>	<b>10</b>
<b>3.1 AC LINE CONDUCTED EMISSIONS.....</b>	<b>10</b>
3.1.1 Applicable Standard.....	10
3.1.2 EUT Setup.....	11
3.1.3 EMI Test Receiver Setup .....	11
3.1.4 Test Procedure .....	12
3.1.5 Corrected Amplitude & Margin Calculation.....	12
<b>3.2 RADIATION SPURIOUS EMISSIONS.....</b>	<b>13</b>
3.2.1 Applicable Standard.....	13
3.2.2 EUT Setup.....	13
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup .....	14
3.2.4 Test Procedure .....	15
3.2.5 Corrected Amplitude & Margin Calculation.....	15
<b>3.3 MINIMUM 6 DB BANDWIDTH.....</b>	<b>16</b>
3.3.1 Applicable Standard.....	16
3.3.2 EUT Setup.....	16
3.3.3 Test Procedure .....	16
<b>3.4 MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>17</b>
3.4.1 Applicable Standard.....	17
3.4.2 EUT Setup.....	17
3.4.3 Test Procedure .....	17
<b>3.5 MAXIMUM POWER SPECTRAL DENSITY.....</b>	<b>18</b>
3.5.1 Applicable Standard.....	18
3.5.2 EUT Setup.....	18
3.5.3 Test Procedure .....	18
<b>3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>19</b>
3.6.1 Applicable Standard.....	19
3.6.2 EUT Setup.....	19
3.6.3 Test Procedure .....	19
<b>3.7 DUTY CYCLE .....</b>	<b>20</b>
3.7.1 EUT Setup.....	20
3.7.2 Test Procedure .....	20

<b>3.8 ANTENNA REQUIREMENT.....</b>	<b>20</b>
3.8.1 Applicable Standard.....	20
3.8.2 Judgment.....	20
<b>4. Test DATA AND RESULTS.....</b>	<b>21</b>
<b>4.1 AC LINE CONDUCTED EMISSIONS.....</b>	<b>21</b>
<b>4.2 RADIATION SPURIOUS EMISSIONS.....</b>	<b>22</b>
<b>4.3 RF CONDUCTED TEST .....</b>	<b>48</b>
<b>5. RF EXPOSURE EVALUATION .....</b>	<b>49</b>
<b>5.1 APPLICABLE STANDARD.....</b>	<b>49</b>
<b>5.2 MEASUREMENT RESULT .....</b>	<b>49</b>
<b>6. EUT PHOTOGRAPHS .....</b>	<b>50</b>
<b>7. TEST SETUP PHOTOGRAPHS .....</b>	<b>51</b>

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR240104515-00A	Original Report	2024/2/7

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>	WIRELESS EARBUDS
<b>EUT Model:</b>	EA227
<b>Operation Frequency:</b>	2402-2480 MHz
<b>Maximum Peak Output Power (Conducted):</b>	-10.13dBm
<b>Modulation Type:</b>	GFSK
<b>Rated Input Voltage:</b>	DC 3.7V from battery
<b>Serial Number:</b>	2GUK-1 (for RF Conducted Test) 2GUK-2 (for Radiated Spurious Emissions Test)
<b>EUT Received Date:</b>	2024/1/22
<b>EUT Received Status:</b>	Good

Note: The device have two earbuds, there are electrically identical, only right unit was tested.

### Operation Frequency Detail:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2402
Middle	2440
Highest	2480

### Antenna Information Detail▲:

Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain (dBi)
Chip	50	2.4~2.4835GHz	1.7

The Method of §15.203 Compliance:

- ☒ Antenna was permanently attached to the unit.  
☐ Antenna use a unique type of connector to attach to the EUT.  
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### Accessory Information:

No.

## 1.2 Description of Test Configuration

### 1.2.1 EUT Operation Condition:

For BLE:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:	No		
EUT Exercise Software:	FCC Assist_1.5.exe		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
1Mbps	default	default	default
2Mbps	default	default	default


### 1.2.2 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

### 1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
/	/	/	/	/	/

### 1.2.4 Block Diagram of Test Setup



### 1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9k~30MHz:4.12dB 30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)



## 2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Not Applicable
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliant
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.203	Antenna Requirement	Compliant
§15.247 (i) & §1.1310	RF Exposure Evaluation	Compliant

### 3. REQUIREMENTS AND TEST PROCEDURES

#### 3.1 AC Line Conducted Emissions

##### 3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000  $\mu$ V within the frequency band 535-1705 kHz, as measured using a 50  $\mu$ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

### 3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

### 3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### 3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

### 3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

## 3.2 Radiation Spurious Emissions


### 3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


### 3.2.2 EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



**Above 1GHz:**

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

**3.2.3 EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz -1000 MHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

### 3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

All emissions under the average limit and under the noise floor have not recorded in the report.

### 3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


### 3.3 Minimum 6 dB Bandwidth

#### 3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### 3.3.2 EUT Setup



#### 3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times \text{RBW}$ .
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.




### 3.4 Maximum Conducted Output Power

#### 3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

#### 3.4.2 EUT Setup



#### 3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.1

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the  $RBW \geq DTS$  bandwidth.
- Set  $VBW \geq [3 \times RBW]$ .
- Set  $span \geq [3 \times RBW]$ .
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.


### 3.5 Maximum power spectral density

#### 3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

#### 3.5.2 EUT Setup



#### 3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set the VBW  $\geq [3 \times \text{RBW}]$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


### 3.6 100 kHz Bandwidth of Frequency Band Edge

#### 3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 3.6.2 EUT Setup



#### 3.6.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW  $\geq [3 \times \text{RBW}]$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

### 3.7 Duty Cycle

#### 3.7.1 EUT Setup



#### 3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.
- 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)

### 3.8 Antenna Requirement

#### 3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

#### 3.8.2 Judgment

**Compliant.** Please refer to the Antenna Information detail in Section 1.

## 4. Test DATA AND RESULTS

---

### 4.1 AC Line Conducted Emissions

**Not Applicable**, the device was powered by battery when operating.

## 4.2 Radiation Spurious Emissions

Serial Number:	2GUK-2	Test Date:	2024/1/26
Test Site:	966-1, 966-2	Test Mode:	Transmitting
Tester:	Vic Du, Mack Huang	Test Result:	Pass

### Environmental Conditions:

Temperature: (°C)	23.5~26.4	Relative Humidity: (%)	39~59	ATM Pressure: (kPa)	102.2
----------------------	-----------	---------------------------	-------	---------------------------	-------

### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Below 1GHz					
Sunol Sciences	Antenna	JB6	A082520-5	2023/12/1	2026/11/30
BACL	Loop Antenna	1313-1A	3110611	2023/12/4	2026/12/3
Daruikang	Coaxial Cable	BNC-JJ-RG58	C-0300-01	2024/1/11	2025/1/10
Daruikang	Coaxial Cable	BNC-JJ-RG58	C-0500-01	2024/1/11	2025/1/10
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A
Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	9912-5985	2023/12/6	2026/12/5
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2024/1/15	2025/1/14
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2024/1/15	2025/1/14
A.H	Preamplifier	PAM-0118P	628	2024/1/15	2025/1/14
Audix	Test Software	E3	191218 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2023/9/15	2024/9/14
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

Please refer to the below table and plots.


Provides BLE 1MHz Middle channel test results at 30MHz-1GHz (highest power for Conducted Output Power).

After pre-scan in the X, Y and Z axes of orientation, the worst case is below: Z.

Radiation Spurious Emissions from 1 to 25GHz provides test results and test plots(Only the test plot with the smallest harmonic margin is provided) for sideband and harmonics of the Z-axis.

1) 9KHz -30MHz:


Project No.: CR240104515-RF  
Tester: Vic Du  
Polarization: Parallel  
Note: Transmitting BLE



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.009	39.27	35.60	74.87	128.42	53.55	Peak
2	0.010	37.34	34.70	72.04	127.79	55.75	Peak
3	0.012	38.46	33.39	71.85	125.93	54.08	Peak
4	0.014	38.79	32.39	71.18	124.59	53.41	Peak
5	0.015	39.77	32.01	71.78	124.12	52.34	Peak
6	0.024	29.63	27.56	57.19	119.99	62.80	Peak




Project No.: CR240104515-RF  
Tester: Vic Du  
Polarization: Parallel  
Note: Transmitting BLE




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.159	34.61	11.90	46.51	103.58	57.07	Peak
2	0.213	35.31	9.40	44.71	101.04	56.33	Peak
3	0.502	37.53	0.94	38.47	73.58	35.11	Peak
4	0.661	33.99	-0.91	33.08	71.14	38.06	Peak
5	0.796	34.59	-2.47	32.12	69.50	37.38	Peak
6	29.061	35.60	-7.26	28.34	69.54	41.20	Peak

Project No.: CR240104515-RF  
Tester: Vic Du  
Polarization: Perpendicular  
Note: Transmitting BLE




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.009	37.67	35.33	73.00	128.23	55.23	Peak
2	0.010	38.20	34.56	72.76	127.69	54.93	Peak
3	0.011	39.75	33.88	73.63	126.69	53.06	Peak
4	0.013	37.94	32.77	70.71	125.07	54.36	Peak
5	0.015	38.65	31.91	70.56	124.00	53.44	Peak
6	0.024	31.51	27.59	59.10	120.02	60.92	Peak

Project No.: CR240104515-RF  
Tester: Vic Du  
Polarization: Perpendicular  
Note: Transmitting BLE




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.153	34.50	12.17	46.67	103.90	57.23	Peak
2	0.213	35.71	9.40	45.11	101.04	55.93	Peak
3	0.343	35.11	4.41	39.52	96.90	57.38	Peak
4	0.654	35.66	-0.83	34.83	71.24	36.41	Peak
5	1.037	37.34	-4.34	33.00	67.15	34.15	Peak
6	28.452	34.94	-7.36	27.58	69.54	41.96	Peak

Project No.: CR240104515-RF  
Tester: Vic Du  
Polarization: Ground-parallel  
Note: Transmitting BLE



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.009	37.55	35.73	73.28	128.52	55.24	Peak
2	0.009	37.75	35.26	73.01	128.18	55.17	Peak
3	0.011	36.48	33.76	70.24	126.49	56.25	Peak
4	0.014	36.49	32.57	69.06	124.81	55.75	Peak
5	0.016	37.81	31.57	69.38	123.61	54.23	Peak
6	0.017	34.73	31.14	65.87	123.14	57.27	Peak


Project No.: CR240104515-RF  
Tester: Vic Du  
Polarization: Ground-parallel  
Note: Transmitting BLE



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.155	34.63	12.09	46.72	103.81	57.09	Peak
2	0.183	35.65	10.76	46.41	102.33	55.92	Peak
3	0.546	39.01	0.42	39.43	72.83	33.40	Peak
4	0.686	38.82	-1.20	37.62	70.81	33.19	Peak
5	1.043	42.56	-4.36	38.20	67.10	28.90	Peak
6	26.418	35.51	-7.54	27.97	69.54	41.57	Peak

## 2)30MHz-1GHz:


Project No.: CR240104515-RF  
Tester: Vic Du  
Polarization: horizontal  
Note: Transmitting BLE



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	28.43	-4.18	24.25	40.00	15.75	Peak
2	71.080	28.33	-17.19	11.14	40.00	28.86	Peak
3	120.277	27.49	-11.18	16.31	43.50	27.19	Peak
4	157.007	28.12	-11.87	16.25	43.50	27.25	Peak
5	774.158	27.83	-1.94	25.89	46.00	20.11	Peak
6	912.862	28.65	0.43	29.08	46.00	16.92	Peak

Project No.: CR240104515-RF  
Tester: Vic Du  
Polarization: vertical  
Note: Transmitting BLE

Date: 2024-01-26



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	26.96	-3.87	23.09	40.00	16.91	Peak
2	75.977	29.19	-17.08	12.11	40.00	27.89	Peak
3	120.699	28.51	-11.13	17.38	43.50	26.12	Peak
4	152.664	28.00	-12.17	15.83	43.50	27.67	Peak
5	716.682	28.48	-2.76	25.72	46.00	20.28	Peak
6	938.833	27.51	0.82	28.33	46.00	17.67	Peak

**3) 1-25GHz:****BLE 1Mbps:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2402 MHz							
4804.000	50.82	PK	H	-5.70	45.12	74.00	28.88
4804.000	38.14	AV	H	-5.70	32.44	54.00	21.56
4804.000	49.22	PK	V	-5.70	43.52	74.00	30.48
4804.000	37.35	AV	V	-5.70	31.65	54.00	22.35
7206.000	47.42	PK	H	-0.32	47.10	74.00	26.90
7206.000	35.10	AV	H	-0.32	34.78	54.00	19.22
7206.000	46.58	PK	V	-0.32	46.26	74.00	27.74
7206.000	34.09	AV	V	-0.32	33.77	54.00	20.23
Middle Channel: 2440 MHz							
4880.000	50.20	PK	H	-5.50	44.70	74.00	29.30
4880.000	37.89	AV	H	-5.50	32.39	54.00	21.61
4880.000	49.68	PK	V	-5.50	44.18	74.00	29.82
4880.000	36.77	AV	V	-5.50	31.27	54.00	22.73
7320.000	47.21	PK	H	0.47	47.68	74.00	26.32
7320.000	35.20	AV	H	0.47	35.67	54.00	18.33
7320.000	47.10	PK	V	0.47	47.57	74.00	26.43
7320.000	35.36	AV	V	0.47	35.83	54.00	18.17
High Channel: 2480 MHz							
4960.000	49.79	PK	H	-5.11	44.68	74.00	29.32
4960.000	37.12	AV	H	-5.11	32.01	54.00	21.99
4960.000	49.02	PK	V	-5.11	43.91	74.00	30.09
4960.000	37.33	AV	V	-5.11	32.22	54.00	21.78
7440.000	47.68	PK	H	0.63	48.31	74.00	25.69
7440.000	35.16	AV	H	0.63	35.79	54.00	18.21
7440.000	46.96	PK	V	0.63	47.59	74.00	26.41
7440.000	34.34	AV	V	0.63	34.97	54.00	19.03




**BLE 2Mbps:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2402 MHz							
4804.000	49.27	PK	H	-5.70	43.57	74.00	30.43
4804.000	37.10	AV	H	-5.70	31.40	54.00	22.60
4804.000	48.58	PK	V	-5.70	42.88	74.00	31.12
4804.000	36.33	AV	V	-5.70	30.63	54.00	23.37
7206.000	47.42	PK	H	-0.32	47.10	74.00	26.90
7206.000	35.09	AV	H	-0.32	34.77	54.00	19.23
7206.000	47.13	PK	V	-0.32	46.81	74.00	27.19
7206.000	35.22	AV	V	-0.32	34.90	54.00	19.10
Middle Channel: 2440 MHz							
4880.000	48.74	PK	H	-5.50	43.24	74.00	30.76
4880.000	36.29	AV	H	-5.50	30.79	54.00	23.21
4880.000	48.11	PK	V	-5.50	42.61	74.00	31.39
4880.000	36.43	AV	V	-5.50	30.93	54.00	23.07
7320.000	47.56	PK	H	0.47	48.03	74.00	25.97
7320.000	35.02	AV	H	0.47	35.49	54.00	18.51
7320.000	46.74	PK	V	0.47	47.21	74.00	26.79
7320.000	34.55	AV	V	0.47	35.02	54.00	18.98
High Channel: 2480 MHz							
4960.000	49.67	PK	H	-5.11	44.56	74.00	29.44
4960.000	37.24	AV	H	-5.11	32.13	54.00	21.87
4960.000	48.79	PK	V	-5.11	43.68	74.00	30.32
4960.000	36.23	AV	V	-5.11	31.12	54.00	22.88
7440.000	47.10	PK	H	0.63	47.73	74.00	26.27
7440.000	35.01	AV	H	0.63	35.64	54.00	18.36
7440.000	47.66	PK	V	0.63	48.29	74.00	25.71
7440.000	35.19	AV	V	0.63	35.82	54.00	18.18

**Listed with the worst harmonic margin test plot (BLE 1M bps Middle Channel)**


Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: horizontal  
Note: BLE Middle Channel

Date: 2024-01-26




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4880.000	50.20	-5.50	44.70	74.00	29.30	Peak
2	4880.000	37.89	-5.50	32.39	54.00	21.61	Average

Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: vertical  
Note: BLE Middle Channel




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4880.000	49.68	-5.50	44.18	74.00	29.82	Peak
2	4880.000	36.77	-5.50	31.27	54.00	22.73	Average

Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: horizontal  
Note: BLE Middle Channel




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	7320.000	47.21	0.47	47.68	74.00	26.32	Peak
2	7320.000	35.20	0.47	35.67	54.00	18.33	Average
3	17736.000	44.40	15.86	60.26	74.00	13.74	Peak
4	17736.000	31.92	15.86	47.78	54.00	6.22	Average

Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: vertical  
Note: BLE Middle Channel




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	7320.000	47.10	0.47	47.57	74.00	26.43	Peak
2	7320.000	35.36	0.47	35.83	54.00	18.17	Average
3	17726.400	44.02	15.80	59.82	74.00	14.18	Peak
4	17726.400	31.85	15.80	47.65	54.00	6.35	Average

Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: Horizontal  
Note: BLE Middle Channel




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	21721.200	51.53	4.97	56.50	74.00	17.50	Peak
2	21721.200	39.15	4.97	44.12	54.00	9.88	Average

Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: Vertical  
Note: BLE Middle Channel



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	23391.400	51.44	5.40	56.84	74.00	17.16	Peak
2	23391.400	38.96	5.40	44.36	54.00	9.64	Average


Edge:  
BLE 1M 2402 Edge 2310-2404MHz Horizontal:





BLE 1M 2402 Edge 2310-2404MHz Vertical:


Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: Vertical  
Note: BLE 1M 2402 Edge



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2375.875	28.91	31.44	60.35	74.00	13.65	Peak
2	2375.875	16.21	31.44	47.65	54.00	6.35	Average

BLE 1M 2480 Edge 2478-2550MHz Horizontal:


Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: Horizontal  
Note: BLE 1M 2480 Edge



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2528.645	28.37	31.63	60.00	74.00	14.00	Peak
2	2528.645	15.72	31.63	47.35	54.00	6.65	Average

## BLE 1M 2480 Edge 2478-2550MHz Vertical:


Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: Vertical  
Note: BLE 1M 2480 Edge



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2519.472	28.37	31.59	59.96	74.00	14.04	Peak
2	2519.472	14.76	31.59	46.35	54.00	7.65	Average

## BLE 2M 2402 Edge 2310-2404MHz Horizontal:


Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: Horizontal  
Note: BLE 2M 2402 Edge



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	2382.625	27.58	31.45	59.03	74.00	14.97	Peak
2	2382.625	14.02	31.45	45.47	54.00	8.53	Average

BLE 2M 2402 Edge 2310-2404MHz Vertical:

Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: Vertical  
Note: BLE 2M 2402 Edge




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	2349.104	28.11	31.40	59.51	74.00	14.49	Peak
2	2349.104	14.57	31.40	45.97	54.00	8.03	Average

## BLE 2M 2480 Edge 2478-2550MHz Horizontal:

Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: Horizontal  
Note: BLE 2M 2480 Edge


Date: 2024-01-26



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2494.906	28.64	31.51	60.15	74.00	13.85	Peak
2	2494.906	14.89	31.51	46.40	54.00	7.60	Average

BLE 2M 2480 Edge 2478-2550MHz Vertical:

Project No.: CR240104515-RF  
Tester: Mack Huang  
Polarization: Vertical  
Note: BLE 2M 2480 Edge



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2544.859	28.20	31.70	59.90	74.00	14.10	Peak
2	2544.859	14.33	31.70	46.03	54.00	7.97	Average

### **4.3 RF Conducted Test**

Please refer to Appendix 00A.



## 5. RF EXPOSURE EVALUATION

### 5.1 Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### 5.2 Measurement Result

FCC ID: 2ADR3EA227

For BT:

The max conducted power including tune-up tolerance is -8.0dBm (0.16 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$   
 $= 0.16/5 \cdot (\sqrt{2.480}) = 0.1 < 3.0$

For BLE:

The max conducted power including tune-up tolerance is -10.0dBm (0.1 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$   
 $= 0.1/5 \cdot (\sqrt{2.480}) = 0 < 3.0$

Note: 1. The max conducted power including tune-up tolerance was provided by manufacturer.  
2. BT can't transmit simultaneously with BLE.

**Result: Compliant. The stand-alone SAR evaluation is not necessary.**

## **6. EUT PHOTOGRAPHS**

---

Please refer to the attachment CR240104515-EXP EUT EXTERNAL PHOTOGRAPHS and CR240104515-INP EUT INTERNAL PHOTOGRAPHS

## **7. TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment CR240104515-00A-TSP TEST SETUP PHOTOGRAPHS.

**===== END OF REPORT =====**