



TEST REPORT

Product Name: DLP Portable Projector
FCC ID: 2A6W6-B0004
Trademark: CASIRIS
Model Number: SHP-K7A, SHP-K7B, SHP-K7C, SHP-K7D, SHP-K7E
Prepared For: HANGZHOU ZHONGKEJIGUANG TECHNOLOGY CO., LTD
Address: Room107, Building 2, No.600, 21 Street, ETDA Hangzhou, Zhejiang, China
Manufacturer: HANGZHOU ZHONGKEJIGUANG TECHNOLOGY CO., LTD
Address: Room107, Building 2, No.600, 21 Street, ETDA Hangzhou, Zhejiang, China
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: Nov. 19, 2024
Sample tested Date: Nov. 19, 2024 to Nov. 25, 2024
Issue Date: Nov. 25, 2024
Report No.: CTB24111911501RF04
Test Standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407
Test Results: PASS
Remark: This is WIFI-5GHz band radio test report.

Compiled by:

Reviewed by:

Approved by:

Zhou kui

Arron Liu

Zhou KuiArron LiuBin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration	Page
1. VERSION.....	3
2. TEST SUMMARY	4
3. MEASUREMENT UNCERTAINTY	5
4. PRODUCT INFORMATION AND TEST SETUP	6
4.1 Product Information	6
4.2 Test Setup Configuration.....	7
4.3 Support Equipment.....	7
4.5 Test Mode	9
4.6 Test Environment	9
5. TEST FACILITY AND TEST INSTRUMENT USED	10
5.1 Test Facility	10
5.2 Test Instrument Used	10
6. AC POWER LINE CONDUCTED EMISSION.....	13
6.1 Block Diagram Of Test Setup	13
6.2 Limit.....	13
6.3 Test procedure	13
6.4 Test Result	15
7. RADIATED SPURIOUS EMISSIONS.....	17
7.1 Block Diagram Of Test Setup	17
7.2 Limit.....	17
7.3 Test procedure	18
7.4 Test Result	19
8. BAND EDGE	25
8.1 Block Diagram Of Test Setup	25
8.2 Limit.....	25
8.3 Test procedure	25
8.4 Test Result	26
9. CONDUCTED OUTPUT POWER.....	42
9.1 Block Diagram Of Test Setup	42
9.2 Limit.....	42
9.3 Test procedure	43
9.4 Test Result	44
10. EMISSION BANDWIDTH& OCCUPIED BANDWIDTH.....	66
10.1 Block Diagram Of Test Setup	66
10.2 Limits.....	66
10.3 Test Procedure.....	66
10.4 Test Results	68
11. POWER SPECTRAL DENSITY.....	90
11.1 Block Diagram Of Test Setup	90
11.2 Limit.....	90
11.3 Test procedure	90
11.4 Test Result	92
12. FREQUENCY STABILITY	114
12.1 Block Diagram Of Test Setup	114
12.2 Limit.....	114
12.3 Test procedure	114
12.4 Test Result	115
13. OPERATION IN THE ABSENCE OF INFORMATION TO THE TRANSMIT.....	139
13.1 Requirement.....	139
13.2 Test Results	139
14. ANTENNA REQUIREMENT	140
15. EUT TEST SETUP PHOTOGRAPHS.....	141

(Note: N/A means not applicable)

1. VERSION

Report No.	Issue Date	Description	Approved
CTB24111911501RF04	Nov. 25, 2024	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
AC Power Line Conducted Emission	47 CFR Part 15 Subpart E Section 15.407 (b)(6)	ANSI C63.10-2013	PASS
Radiated Spurious emissions	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033	PASS
Band edge	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033	PASS
Conducted Peak Output Power	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033	PASS
Emission Bandwidth & Occupied Bandwidth	47 CFR Part 15 Subpart E Section 15.407 (a)(e)	KDB789033	PASS
Power Spectral Density	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033	PASS
Frequency stability	47 CFR Part 15 Subpart E Section 15.407 (g)	KDB789033	PASS
Operation in the absence of information to the transmit	47 CFR Part 15 Subpart E Section 15.407 (b)	47 CFR Part 15 Subpart E	PASS
Antenna Requirement	47 CFR Part 15 Subpart E Section 15.203	/	PASS

Remark:

Test according to ANSI C63.10-2013.

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Item	Uncertainty
Occupancy bandwidth	$U=\pm 54.3\text{Hz}$
Adjacent channel power	$U=\pm 1.3\text{dB}$
Conducted Adjacent channel power	$U=\pm 1.38\text{dB}$
Conducted output power Above 1G	$U=\pm 1.0\text{dB}$
Conducted output power below 1G	$U=\pm 0.9\text{dB}$
Power Spectral Density , Conduction	$U=\pm 1.0\text{dB}$
Conduction spurious emissions	$U=\pm 2.8\text{dB}$
Out of band emission	$U=\pm 54\text{Hz}$
3m camber Radiated spurious emission(9KHz-30MHz)	$U=\pm 4.8\text{dB}$
3m camber Radiated spurious emission(30MHz-1GHz)	$U=\pm 4.3\text{dB}$
3m chamber Radiated spurious emission(1GHz-18GHz)	$U=\pm 4.5\text{dB}$
3m chamber Radiated spurious emission(18GHz-40GHz)	$U=\pm 3.4\text{dB}$
humidity uncertainty	$U=\pm 5.3\%$
Temperature uncertainty	$U=\pm 0.59^{\circ}\text{C}$
Supply voltages	$U=\pm 3\%$
Time	$U=\pm 5\%$
Conducted emission(150K-30MHz)	3.2dB

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model(s):	SHP-K7A, SHP-K7B, SHP-K7C, SHP-K7D, SHP-K7E
Model Description:	All the model are the same circuit and RF module, only the model names are different. Test sample model: SHP-K7A
Wi-Fi Specification:	IEEE 802.11a/n/ac
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	IEEE 802.11a/n/ac(20M): 5150MHz ~5250MHz/ 4 channel IEEE 802.11n/ac(40M): 5150MHz ~5250MHz/ 2 channel IEEE 802.11ac(80M): 5150MHz ~5250MHz/ 1 channel IEEE 802.11a/n/ac(20M): 5250MHz ~5350 MHz/ 4 channel IEEE 802.11n/ac(40M): 5250MHz ~5350 MHz/ 2 channel IEEE 802.11ac(80M): 5250MHz ~5350 MHz/ 1 channel IEEE 802.11a/n/ac(20M): 5470MHz ~5725 MHz/ 11 channel IEEE 802.11n/ac(40M): 5470MHz ~5725 MHz/ 5 channel IEEE 802.11ac(80M): 5470MHz ~5725 MHz/ 3 channel IEEE 802.11a/n/ac(20M): 5725MHz ~5850MHz/ 5 channel IEEE 802.11n/ac(40M): 5725MHz ~5850MHz/ 2 channel IEEE 802.11ac(80M): 5725MHz ~5850MHz/ 1 channel
Max. RF output power:	WiFi (5G): 17.374dBm
Type of Modulation:	WiFi (5G): OFDM
Antenna installation:	WiFi (5G): FPC antenna
Antenna Gain:	WiFi (5.2G): ANT1: 0.71dBi, ANT2: 0.67dBi WiFi (5.3G): ANT1: 0.69dBi, ANT2: 0.64dBi WiFi (5.6G): ANT1: 0.91dBi, ANT2: 0.87dBi WiFi (5.8G): ANT1: 0.72dBi, ANT2: 0.68dBi
Ratings:	ADAPTER: INPUT: 100-240V~, 50/60Hz 1.0A OUTPUT: 5.0V === 3.0A or 9.0V === 3.0A or 12.0V === 3.0A or 15.0V === 3.0A or 20.0V === 2.25A DC 7.2V by battery

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Quick Charger	JUEDING	PD045E-D1C0AVU	/	EUT

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

For 802.11a/n/ac(20M) Operation in the 5150MHz ~5250 MHz band			
Channel	Frequency	Channel	Frequency
36	5180MHz	44	5220MHz
40	5200MHz	48	5240MHz
For 802.11a/n/ac(20M) Operation in the 5250MHz ~5350 MHz band			
Channel	Frequency	Channel	Frequency
52	5260MHz	60	5300MHz
56	5280MHz	64	5320MHz
For 802.11a/n/ac(20M) Operation in the 5470MHz ~5725 MHz band			
Channel	Frequency	Channel	Frequency
100	5500MHz	124	5620 MHz
104	5520MHz	128	5640 MHz
108	5540MHz	132	5660 MHz
112	5560MHz	136	5680MHz
116	5580MHz	140	5700MHz
120	5600 MHz		
For 802.11a/n/ac(20M) Operation in the 5725MHz ~5850 MHz band			
Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz	NA	NA

For 802.11n/ac(40M) Operation in the 5150MHz ~5250 MHz band			
Channel	Frequency	Channel	Frequency
38	5190MHz	46	5230MHz
For 802.11n/ac(40M) Operation in the 5250MHz ~5350 MHz band			
Channel	Frequency	Channel	Frequency
54	5270MHz	62	5310MHz
For 802.11n/ac(40M) Operation in the 5470MHz ~5725 MHz band			
Channel	Frequency	Channel	Frequency
102	5510MHz	126	5630MHz
110	5550MHz	134	5670MHz
118	5590MHz		
For 802.11n/ac(40M) Operation in the 5725MHz ~5850 MHz band			
Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz

For 802.11ac(80M)		Operation in the 5150MHz ~5250 MHz band	
Channel	Frequency	Channel	Frequency
42	5210MHz	NA	NA
For 802.11ac(80M)		Operation in the 5250MHz ~5350 MHz band	
Channel	Frequency	Channel	Frequency
58	5290MHz	NA	NA
For 802.11ac(80M)		Operation in the 5470MHz ~5725 MHz band	
Channel	Frequency	Channel	Frequency
106	5530MHz	138	5690MHz
122	5610 MHz		
For 802.11ac(80M)		Operation in the 5725MHz ~5850 MHz band	
Channel	Frequency	NA	NA
155	5775MHz	NA	NA

NOTE: Dutycycle>98%.

Test mode	Rate
802.11a	54M
802.11n	500M
802.11ac	500M

4.5 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11a/n/ac(20M)	5150MHz ~5250 MHz	Channel 36	Channel 40	Channel 48
		5180MHz	5200MHz	5240MHz
802.11n/ac(40M)		Channel 38	N/A	Channel 46
		5190MHz	N/A	5230MHz
802.11ac(80M)		N/A	Channel 42	N/A
		N/A	5210MHz	N/A
802.11a/n/ac(20M)	5250MHz ~5350 MHz	Channel 52	Channel 56	Channel 64
		5260MHz	5280MHz	5320MHz
802.11n/ac(40M)		Channel 54	N/A	Channel 62
		5270MHz	N/A	5310MHz
802.11ac(80M)		N/A	Channel 58	N/A
		N/A	5290MHz	N/A
802.11a/n/ac(20M)	5470MHz ~5725 MHz	Channel 100	Channel 116	Channel 140
		5500MHz	5580MHz	5700MHz
802.11n/ac(40M)		Channel 102	N/A	Channel 134
		5510MHz	N/A	5670MHz
802.11ac(80M)		N/A	Channel 106	N/A
		N/A	5530MHz	N/A
802.11a/n/ac(20M)	5725MHz ~5850 MHz	Channel 149	Channel 157	Channel 165
		5745MHz	5785MHz	5825MHz
802.11n/ac(40M)		Channel 151	N/A	Channel 159
		5755MHz	N/A	5795MHz
802.11ac(80M)		N/A	Channel 155	N/A
		N/A	5775MHz	N/A

4.6 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(DC):NV	7.2V
Normal Temperature(°C):NT	23
Low Temperature(°C):LT	0
High Temperature(°C):HT	40

5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at 1&2F., Building A, No. 26, Xinhua Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

5.2 Test Instrument Used

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2025/6/28
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2025/6/28
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2025/6/28
4	Communication test set	R&S	CMW500	108058	V3.5.80	2025/6/28
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2025/6/28
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2025/6/28
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2025/6/28
9	2.4 GHz Filter	Shenxiang	MSF2400-24 83.5MS-1154	20181015001	/	2025/6/30
10	5 GHz Filter	Shenxiang	MSF5150-58 50MS-1155	20181015001	/	2025/6/30
11	Filter	Xingbo	XBLBQ-DZA 120	190821-1-1	/	2025/6/30
12	BT&WI-FI Automatic test software	Microwave	MTS8310	Ver. 2.0.0.0	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2025/6/28
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	/	2025/6/28
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/	/
16	966 chamber	C.R.T.	966	/	/	2027/6/21
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7 (104489/003)	2025/6/28
18	Amplifier	HP	8447E	2945A02747	/	2025/6/28
19	Amplifier	Agilent	8449B	3008A01838	/	2025/6/28
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2025/6/28
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2025/6/28

22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/28
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/
25	40G Horn antenna	A/H/System	SAS-574	588	/	2025/6/28
26	Amplifier	AEROFLEX	Aeroflex	097	/	2025/6/28
27	Power Metter	KEYSIGHT	N1912AP	N/A	A.05.00	2025/6/28


Continuous disturbance						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2027/6/21
2	AMN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/6/30
3	Pulse limiter	ROHDE&SCHWARZ	ESH3Z2	357881052	/	2025/6/28
4	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2025/6/30
5	Coaxial cable	ZDECL	Z302S	18091904	/	2025/6/30
6	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/30
7	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2025/10/25
8	EZ-EMC	Frad	EMC-con3A1.1	/	/	/
9	Current Probe	FCC	F-52B	199453	/	2025/5/27
10	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/6/28
11	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28

Radiated emission(No.2 Chamber)						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2026/11/14
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2026/7/07
3	Broadband Antenna	Schwarzbeck	VULB 9168	1471	/	2025/7/06
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/30
5	Preamplifier	Schwarzbeck	BBV 9743 B	00500	/	2025/5/23
6	EMI TEST RECEIVER	R&S	ESCI7	100861	/	2025/10/25
7	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
8	EMI test software	Farad	EZ-EMC	/	Ver. FARAD-3A1+	/
9	Coaxial cable	Rosenberg	8m	/	/	2025/10/25
10	Coaxial cable	Times	2m	/	/	2025/10/25

11	Coaxial cable	Times	2m	/	/	2025/10/25
12	Coaxial cable	Times	1m	/	/	2025/10/25
13	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/29
14	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/6/28
15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28

6. AC POWER LINE CONDUCTED EMISSION

6.1 Block Diagram Of Test Setup



6.2 Limit

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 1}
0.5 - 5	56	46
5 - 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

* Decreasing linearly with the logarithm of the frequency

6.3 Test procedure


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50 Ω /50 μ H + 5 Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane.

This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


6.4 Test Result

L:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1500	48.90	10.89	59.79	66.00	-6.21	QP
2		0.1500	29.26	10.89	40.15	56.00	-15.85	AVG
3		0.2232	43.54	10.69	54.23	62.70	-8.47	QP
4		0.2232	24.15	10.69	34.84	52.70	-17.86	AVG
5		0.4778	31.76	10.52	42.28	56.38	-14.10	QP
6		0.4778	20.64	10.52	31.16	46.38	-15.22	AVG
7		0.6820	32.56	10.70	43.26	56.00	-12.74	QP
8		0.6820	21.14	10.70	31.84	46.00	-14.16	AVG
9		3.4540	24.59	11.90	36.49	56.00	-19.51	QP
10		3.4540	11.81	11.90	23.71	46.00	-22.29	AVG
11		11.3900	12.81	13.27	26.08	60.00	-33.92	QP
12		11.3900	2.39	13.27	15.66	50.00	-34.34	AVG

N:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1620	46.82	10.85	57.67	65.36	-7.69	QP
2		0.1620	31.15	10.85	42.00	55.36	-13.36	AVG
3		0.2242	43.22	10.69	53.91	62.66	-8.75	QP
4		0.2242	28.11	10.69	38.80	52.66	-13.86	AVG
5		0.3618	31.59	10.60	42.19	58.69	-16.50	QP
6		0.3618	17.22	10.60	27.82	48.69	-20.87	AVG
7		0.7056	25.58	10.72	36.30	56.00	-19.70	QP
8		0.7056	15.44	10.72	26.16	46.00	-19.84	AVG
9		1.5540	19.06	11.30	30.36	56.00	-25.64	QP
10		1.5540	8.07	11.30	19.37	46.00	-26.63	AVG
11		3.4660	21.47	11.90	33.37	56.00	-22.63	QP
12		3.4660	8.75	11.90	20.65	46.00	-25.35	AVG

Remark:

1. Factor = Cable loss + LISN factor, Margin = Limit – Level
2. All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported.
3. All the test modes completed for test. Only the worst result of was reported.

7. RADIATED SPURIOUS EMISSIONS

7.1 Block Diagram Of Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1GHz

7.2 Limit

Spurious Emissions:

Frequency	Field strength (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	$20\log 2400/F \text{ (kHz)} + 80$	Quasi-peak	3
0.490MHz-1.705MHz	$20\log 24000/F \text{ (kHz)} + 40$	Quasi-peak	3
1.705MHz-30MHz	$20\log 30 + 40$	Quasi-peak	3
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-960MHz	46.0	Quasi-peak	3
960MHz-1GHz	54.0	Quasi-peak	3
Above 1GHz	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

If radiated measurements are performed, field strength is then converted to EIRP as follows:

$$(i) \text{ EIRP} = ((E \cdot d)^2) / 30$$

where:

- E is the field strength in V/m;
 - d is the measurement distance in meters;
 - EIRP is the equivalent isotropically radiated power in watts.
- (ii) Working in dB units, the above equation is equivalent to:

$$\text{EIRP[dBm]} = E[\text{dB}\mu\text{V/m}] + 20 \log(d[\text{meters}]) - 104.77$$
- (iii) Or, if d is 3 meters:

$$\text{EIRP[dBm]} = E[\text{dB}\mu\text{V/m}] - 95.2$$

7.3 Test procedure

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel
- j. Repeat above procedures until all frequencies measured was complete.

Receiver set:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average


7.4 Test Result

30MHz-1GHzTest Results:

Modulation : 802.11a (the worst data)


Test Channel : 5780MHz

Antenna polarity: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	59.6493	36.85	-14.64	22.21	40.00	-17.79	QP
2	94.0979	46.79	-18.27	28.52	43.50	-14.98	QP
3	196.5098	44.66	-17.03	27.63	43.50	-15.87	QP
4	297.2241	45.36	-13.92	31.44	46.00	-14.56	QP
5	435.5898	38.46	-11.30	27.16	46.00	-18.84	QP
6 *	726.8052	38.53	-4.69	33.84	46.00	-12.16	QP

Antenna polarity: V



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	59.6493	50.99	-14.64	36.35	40.00	-3.65	QP
2	83.2298	48.33	-18.41	29.92	40.00	-10.08	QP
3	182.5592	43.36	-16.17	27.19	43.50	-16.31	QP
4	360.4476	42.61	-12.96	29.65	46.00	-16.35	QP
5	601.4265	39.84	-6.46	33.38	46.00	-12.62	QP
6	721.7259	43.96	-4.83	39.13	46.00	-6.87	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

1.The margin of 9K-30MH measurement exceeds 20dB, so the test chart is not included. Test Mode: 802.11a20 (the worst)

Radiated Spurious Emission (Above 1GHz):

Modulation : 802.11(a) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5180MHz									
10360	39.10	16.39	55.49	74	-18.51	PK	1.40	214	H
10360	27.70	16.39	44.09	54	-9.91	AV	1.51	1	H
10360	41.15	16.39	57.54	74	-16.46	PK	1.32	35	V
10360	26.71	16.39	43.10	54	-10.90	AV	1.17	98	V
Channel:5240MHz									
10480	39.59	16.11	55.70	74	-18.30	PK	1.63	235	H
10480	27.24	16.11	43.35	54	-10.65	AV	1.30	308	H
10480	39.33	16.11	55.44	74	-18.56	PK	1.50	197	V
10480	25.89	16.11	42.00	54	-12.00	AV	1.42	224	V
Channel:5260MHz									
10520	41.45	16.39	57.84	74	-16.16	PK	1.45	272	H
10520	25.15	16.39	41.54	54	-12.46	AV	1.06	218	H
10520	39.91	16.39	56.30	74	-17.70	PK	1.32	262	V
10520	26.70	16.39	43.09	54	-10.91	AV	1.12	33	V
Channel:5320MHz									
10640	40.00	16.39	56.39	74	-17.61	PK	1.14	159	H
10640	27.31	16.39	43.70	54	-10.30	AV	1.57	169	H
10640	39.77	16.39	56.16	74	-17.84	PK	1.15	211	V
10640	26.97	16.39	43.36	54	-10.64	AV	1.27	145	V
Channel:5500MHz									
11000	40.32	16.39	56.71	74	-17.29	PK	1.32	218	H
11000	25.66	16.39	42.05	54	-11.95	AV	1.46	350	H
11000	40.53	16.39	56.92	74	-17.08	PK	1.08	308	V
11000	27.19	16.39	43.58	54	-10.42	AV	1.31	14	V
Channel:5700MHz									
11400	39.14	16.39	55.53	74	-18.47	PK	1.41	348	H
11400	26.75	16.39	43.14	54	-10.86	AV	1.58	274	H
11400	41.20	16.39	57.59	74	-16.41	PK	1.19	339	V
11400	25.99	16.39	42.38	54	-11.62	AV	1.57	240	V

Channel:5745MHz									
11490	40.98	17.46	58.44	74	-15.56	PK	1.59	121	H
11490	27.28	17.46	44.74	54	-9.26	AV	1.65	136	H
11490	40.37	17.46	57.83	74	-16.17	PK	1.79	82	V
11490	27.28	17.46	44.74	54	-9.26	AV	1.04	139	V
Channel:5825MHz									
11650	41.90	17.57	59.47	74	-14.53	PK	1.75	134	H
11650	25.43	17.57	43.00	54	-11.00	AV	1.38	126	H
11650	39.10	17.57	56.67	74	-17.33	PK	1.58	103	V
11650	27.30	17.57	44.87	54	-9.13	AV	1.32	150	V

Modulation : 802.11(n40) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5190MHz									
10380	39.56	16.34	55.90	74	-18.10	PK	1.03	254	H
10380	27.61	16.34	43.95	54	-10.05	AV	1.87	344	H
10380	41.02	16.34	57.36	74	-16.64	PK	1.65	19	V
10380	27.98	16.34	44.32	54	-9.68	AV	1.46	62	V
Channel:5230MHz									
10460	39.72	16.15	55.87	74	-18.13	PK	1.52	245	H
10460	26.59	16.15	42.74	54	-11.26	AV	1.30	97	H
10460	41.87	16.15	58.02	74	-15.98	PK	1.80	115	V
10460	26.66	16.15	42.81	54	-11.19	AV	1.90	360	V

Channel:5270MHz									
10540	41.90	16.34	58.24	74	-15.76	PK	1.30	241	H
10540	25.98	16.34	42.32	54	-11.68	AV	1.59	125	H
10540	41.91	16.34	58.25	74	-15.75	PK	1.46	40	V
10540	26.00	16.34	42.34	54	-11.66	AV	1.16	4	V
Channel:5310MHz									
10620	39.12	16.34	55.46	74	-18.54	PK	1.27	296	H
10620	25.09	16.34	41.43	54	-12.57	AV	1.12	83	H
10620	39.84	16.34	56.18	74	-17.82	PK	1.55	231	V

10620	25.85	16.34	42.19	54	-11.81	AV	1.86	134	V
Channel:5510MHz									
11020	40.21	16.34	56.55	74	-17.45	PK	1.45	309	H
11020	26.89	16.34	43.23	54	-10.77	AV	1.30	132	H
11020	39.15	16.34	55.49	74	-18.51	PK	1.69	155	V
11020	25.66	16.34	42.00	54	-12.00	AV	1.12	68	V
Channel:5670MHz									
11340	39.31	16.34	55.65	74	-18.35	PK	1.83	121	H
11340	25.97	16.34	42.31	54	-11.69	AV	1.30	152	H
11340	41.02	16.34	57.36	74	-16.64	PK	1.15	212	V
11340	25.44	16.34	41.78	54	-12.22	AV	1.78	341	V

Channel:5755MHz									
11510	40.72	17.49	58.21	74	-15.79	PK	1.88	331	H
11510	25.53	17.49	43.02	54	-10.98	AV	1.11	99	H
11510	39.56	17.49	57.05	74	-16.95	PK	1.55	353	V
11510	26.38	17.49	43.87	54	-10.13	AV	1.61	44	V
Channel:5795MHz									
11590	39.41	17.52	56.93	74	-16.73	PK	1.01	41	H
11590	26.63	17.52	44.15	54	-17.07	AV	1.41	261	H
11590	41.97	17.52	59.49	74	-14.51	PK	1.62	38	V
11590	26.97	17.52	44.49	54	-9.51	AV	1.80	272	V

Modulation : 802.11(VH80) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5210MHz									
10420	41.02	16.25	57.27	74	-16.73	PK	1.76	93	H
10420	26.93	16.25	43.18	54	-10.82	AV	1.63	167	H
10420	41.93	16.25	58.18	74	-15.82	PK	1.22	201	V
10420	27.22	16.25	43.47	54	-10.53	AV	1.01	75	V
Channel:5290MHz									
10580	40.34	16.25	56.59	74	-17.41	PK	1.26	9	H
10580	27.76	16.25	44.01	54	-9.99	AV	1.62	303	H


10580	40.25	16.25	56.50	74	-17.50	PK	1.09	268	V
10580	26.59	16.25	42.84	54	-11.16	AV	1.33	99	V
Channel:5530MHz									
11060	40.75	17.50	58.25	74	-15.75	PK	1.43	218	H
11060	25.58	17.50	43.08	54	-10.92	AV	1.72	173	H
11060	41.97	17.50	59.47	74	-14.53	PK	1.40	213	V
11060	27.79	17.50	45.29	54	-8.71	AV	1.47	28	V
Channel:5775MHz									
11550	39.18	17.50	56.68	74	-17.32	PK	1.10	119	H
11550	25.14	17.50	42.64	54	-11.36	AV	1.69	332	H
11550	41.52	17.50	59.02	74	-14.98	PK	1.04	88	V
11550	27.06	17.50	44.56	54	-9.44	AV	1.17	341	V

Remark:

- 1.Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits
- 2.The EUT was tested in the low, high channel and the worst case position data was reported.
- 3.Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. BAND EDGE

8.1 Block Diagram Of Test Setup



8.2 Limit

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

8.3 Test procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.


8.4 Test Result

Test Graph

5150-5250MHz:


ANT 1






ANT 2


802.11a-5180




802.11a-5240




802.11ac(VH20)-5180



802.11ac(VH20)-5240




802.11ac(VH40)-5190





802.11ac(VH40)-5230






5250-5350MHz:
ANT1







802.11n(HT40)-5270



802.11n(HT40)-5310



802.11ac(VH80)-5290




/



/

ANT2







802.11n(HT40)-5270




802.11n(HT40)-5310



802.11ac(VH80)-5290




/




/

5470-5725MHz:
ANT1






802.11n(HT40)-5510




802.11n(HT40)-5670



802.11ac(VH80)-5530





/




/

ANT2







802.11n(HT40)-5510



802.11n(HT40)-5670



802.11ac(VH80)-5530





/



/

5725-5850MHz
ANT1







802.11(n40)-5755




802.11(n40)-5795



802.11ac(VH80)-5775





/




/

ANT2







802.11(n40)-5755



802.11(n40)-5795



802.11ac(VH80)-5775




/



/

9. CONDUCTED OUTPUT POWER

9.1 Block Diagram Of Test Setup



9.2 Limit

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p.

at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

(5) The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution

bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

(h) Transmit Power Control (TPC) and Dynamic Frequency Selection (DFS).

(1) Transmit power control (TPC). U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p. of less than 500 mW.

9.3 Test procedure

According to KDB789033 D02v02r01 sectionE, the following is the measurement procedure.

(i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW $\geq$ 3 MHz.

(iv) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle $< 98\%$, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run."

(viii) Trace average at least 100 traces in power averaging (rms) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

9.4 Test Result

5150-5250MHz:

Test mode1	Test Channel (MHz)	Output Power dBm ANT1	Output Power dBm ANT2	Output Power dBm Total	Limit dBm
802.11a	5180	13.624	13.596	/	30
	5200	14.723	13.763	/	30
	5240	13.494	14.969	/	30
802.11ac20	5180	13.591	13.361	16.488	30
	5200	13.958	13.575	16.781	30
	5240	13.259	14.207	16.769	30
802.11ac40	5190	13.083	13.054	16.079	30
	5230	13.280	13.675	16.492	30
802.11ac80	5210	12.892	14.596	16.837	30
802.11n(HT20)	5180	14.044	13.329	16.711	30
	5200	13.888	13.987	16.948	30
	5240	14.105	13.762	16.947	30
802.11n(HT40)	5190	13.567	13.778	16.684	30
	5230	14.126	14.590	17.374	30

5250-5350MHz:

Test mode1	Test Channel (MHz)	Output Power dBm ANT1	Output Power dBm ANT2	Output Power dBm Total	Limit dBm
802.11a	5260	13.494	13.56	/	23.98
	5280	13.578	13.411	/	23.98
	5320	13.441	13.303	/	23.98
802.11ac20	5260	13.249	13.130	16.200	23.98
	5280	13.494	13.310	16.413	23.98
	5320	13.387	13.223	16.316	23.98
802.11ac40	5270	13.337	13.384	16.371	23.98
	5310	13.291	13.512	16.413	23.98
802.11ac80	5290	13.130	13.265	16.208	23.98
802.11n(HT20)	5260	13.518	13.151	16.349	23.98
	5280	13.542	13.357	16.461	23.98
	5320	13.439	13.235	16.348	23.98
802.11n(HT40)	5270	13.343	13.611	16.489	23.98
	5310	13.426	13.582	16.515	23.98


5470-5725MHz:


Test mode1	Test Channel (MHz)	Output Power dBm ANT1	Output Power dBm ANT2	Output Power dBm Total	Limit dBm
802.11a	5500	13.072	13.453	/	23.98
	5580	14.530	13.456	/	23.98
	5700	14.902	13.385	/	23.98
802.11ac20	5500	12.133	13.909	16.121	23.98
	5580	14.799	13.305	17.126	23.98
	5700	14.287	13.306	16.834	23.98
802.11ac40	5510	13.391	13.212	16.313	23.98
	5670	14.325	13.083	16.759	23.98
802.11ac80	5530	14.001	13.449	16.744	23.98
802.11n(HT20)	5500	13.594	13.237	16.429	23.98
	5580	13.687	14.437	17.088	23.98
	5700	13.938	13.544	16.756	23.98
802.11n(HT40)	5510	13.390	13.284	16.348	23.98
	5670	13.887	13.016	16.484	23.98

5725-5850MHz:


Test mode1	Test Channel (MHz)	Output Power dBm ANT1	Output Power dBm ANT2	Output Power dBm Total	Limit dBm
802.11a	5745	12.504	12.384	/	23.98
	5785	12.634	12.486	/	23.98
	5825	12.541	11.581	/	23.98
802.11ac20	5745	12.878	12.535	15.720	23.98
	5785	12.885	11.968	15.461	23.98
	5825	12.035	12.179	15.118	23.98
802.11ac40	5755	12.698	12.968	15.845	23.98
	5795	11.754	11.576	14.676	23.98
802.11ac80	5775	12.587	12.401	15.505	23.98
802.11n(HT20)	5745	12.274	12.225	15.260	23.98
	5785	12.969	11.778	15.424	23.98
	5825	12.790	11.296	15.117	23.98
802.11n(HT40)	5755	12.439	12.049	15.259	23.98
	5795	12.371	11.408	14.926	23.98

Test Graph:
5150-5250MHz-Power
ANT1







802.11ac(VH80)-5210




802.11n(HT20)-5180



802.11n(HT20)-5200




802.11n(HT20)-5240




802.11n(HT40)-5190



802.11n(HT40)-5230



ANT2







802.11ac(VH40)-5190




802.11ac(VH40)-5230



802.11ac(VH80)-5210




802.11n(HT20)-5180



802.11n(HT20)-5200





802.11n(HT20)-5240




802.11n(HT40)-5190




802.11n(HT40)-5230




5250-5350MHz-Power ANT1






802.11ac(VH80)-5290




802.11n(HT20)-5260



802.11n(HT20)-5280



802.11n(HT20)-5320



802.11n(HT40)-5270



802.11n(HT40)-5310