



FCC ID: 2AX7S-LN310A  
Report No.: T201104D06-SF

Page: 1 / 44  
Rev.: 00

## FCC TEST REPORT

FCC 47 CFR § 2.1093  
IEEE Std 1528-2013

for

Digital Paper System  
Model No.: EL310XX (X= 0~9 or A~Z)

Issued to:

**AlMobile Co., Ltd.**  
6F., No. 166, Sec.4, Chengde Rd., Shilin Dist.,  
Taipei City 11167 , Taiwan

Issued by

**Compliance Certification Services Inc.**  
**Wugu Lab.**  
No.11, Wugong 6th Rd., Wugu Dist.,  
New Taipei City, Taiwan. (R.O.C.)

Issued Date: 1/14/2021

### Statements of Conformity

Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

**Note:** This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T201104D06-SF

Page: 2 / 44  
Rev.: 00

### Revision History

| Rev. | Issue Date | Revisions     | Effect Page | Revised By |
|------|------------|---------------|-------------|------------|
| 00   | 1/14/2021  | Initial Issue | ALL         | Sky        |
|      |            |               |             |            |
|      |            |               |             |            |

## Table of Contents

|           |                                                               |           |
|-----------|---------------------------------------------------------------|-----------|
| <b>1</b>  | <b>CERTIFICATE OF COMPLIANCE (SAR EVALUATION)</b>             | <b>5</b>  |
| <b>2</b>  | <b>DESCRIPTION OF EQUIPMENT UNDER TEST</b>                    | <b>6</b>  |
| 2.1       | SUMMARY OF HIGHEST SAR VALUES                                 | 7         |
| <b>3</b>  | <b>REQUIREMENTS FOR COMPLIANCE TESTING DEFINED</b>            | <b>8</b>  |
| 3.1       | REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC        | 8         |
| <b>4</b>  | <b>DOSIMETRIC ASSESSMENT SYSTEM</b>                           | <b>9</b>  |
| 4.1       | MEASUREMENT SYSTEM DIAGRAM                                    | 10        |
| 4.2       | SYSTEM COMPONENTS                                             | 11        |
| <b>5</b>  | <b>EVALUATION PROCEDURES</b>                                  | <b>14</b> |
| <b>6</b>  | <b>SAR MEASUREMENT PROCEDURES</b>                             | <b>16</b> |
| 6.1       | NORMAL SAR TEST PROCEDURE                                     | 16        |
| <b>7</b>  | <b>MEASUREMENT UNCERTAINTY</b>                                | <b>18</b> |
| <b>8</b>  | <b>ANTENNA LOCATION</b>                                       | <b>19</b> |
| <b>9</b>  | <b>RF EXPOSURE CONDITIONS (TEST CONFIGURATIONS)</b>           | <b>20</b> |
| 9.1.      | STANDALONE SAR TEST EXCLUSION CONSIDERATIONS                  | 20        |
| 9.1.      | REQUIRED TEST CONFIGURATIONS                                  | 23        |
| <b>10</b> | <b>EXPOSURE LIMIT</b>                                         | <b>24</b> |
| <b>11</b> | <b>TISSUE DIELECTRIC PROPERTIES</b>                           | <b>25</b> |
| 11.1      | TEST LIQUID CONFIRMATION                                      | 25        |
| 11.2      | TYPICAL COMPOSITION OF INGREDIENTS FOR LIQUID TISSUE PHANTOMS | 26        |
| 11.3      | SIMULATING LIQUIDS PARAMETER CHECK RESULTS                    | 27        |
| <b>12</b> | <b>SYSTEM PERFORMANCE CHECK</b>                               | <b>28</b> |
| 12.1      | SYSTEM PERFORMANCE CHECK RESULTS                              | 29        |
| <b>13</b> | <b>RF OUTPUT POWER MEASUREMENT</b>                            | <b>30</b> |
| 13.1      | WI-FI 2.4GHZ (DTS BAND)                                       | 31        |
| 13.2      | WI-FI 5GHZ (U-NII BANDS)                                      | 32        |
| 13.3      | BLUETOOTH                                                     | 34        |
| <b>14</b> | <b>MEASURED AND REPORTED (SCALED) SAR RESULTS</b>             | <b>36</b> |
| 14.1.     | WI-FI (DTS BAND)                                              | 37        |
| 14.2.     | WI-FI (U-NII BAND)                                            | 37        |
| <b>15</b> | <b>SAR MEASUREMENT VARIABILITY</b>                            | <b>38</b> |
| <b>16</b> | <b>SIMULTANEOUS TRANSMISSION SAR ANALYSIS</b>                 | <b>39</b> |



Report No.: T201104D06-SF

Page: 4 / 44  
Rev.: 00

|           |                                                      |           |
|-----------|------------------------------------------------------|-----------|
| <b>17</b> | <b>EQUIPMENT LIST &amp; CALIBRATION STATUS .....</b> | <b>42</b> |
| <b>18</b> | <b>FACILITIES.....</b>                               | <b>43</b> |
| <b>19</b> | <b>REFERENCE .....</b>                               | <b>43</b> |
| <b>20</b> | <b>ATTACHMENTS .....</b>                             | <b>44</b> |

## 1 Certificate of Compliance (SAR Evaluation)

**Applicant** AIMobile Co., Ltd.  
6F., No. 166, Sec.4, Chengde Rd., Shilin Dist., Taipei City 11167 ,  
Taiwan

**Equipment Under Test:** Digital Paper System

**Trade Name:** Avalue

**Model No.:** EL310XX (X= 0~9 or A~Z)

**Date of Test:** Nov 17, 2020 to Nov 27, 2020

**Receive EUT Date:** Nov 13, 2020

**Device Category:** PORTABLE DEVICES

**Exposure Category:** GENERAL POPULATION/UNCONTROLLED EXPOSURE

| Applicable Standards |                                                                                                                                                                                                                                                                                                                                                                  |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FCC                  | <ul style="list-style-type: none"><li>● IEEE 1528 2013</li><li>● KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04</li><li>● KDB 865664 D02 RF Exposure Reporting v01r02</li><li>● KDB 616217 D04 SAR for laptop and tablets v01r02</li><li>● KDB 447498 D01 General RF Exposure Guidance v06</li><li>● KDB 248227 D01 SAR Meas for 802.11 v02r02</li></ul> |
| Limit                |                                                                                                                                                                                                                                                                                                                                                                  |
| 1.6 W/kg             |                                                                                                                                                                                                                                                                                                                                                                  |
| Test Result          |                                                                                                                                                                                                                                                                                                                                                                  |
| Pass                 |                                                                                                                                                                                                                                                                                                                                                                  |

The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Kevin Tsai  
Section Manager  
Compliance Certification Services Inc.

Tested by:



Stella Chang  
SAR Engineer  
Compliance Certification Services Inc.

## 2 Description of Equipment Under Test

|                       |                                                                                                                                                                  |                     |                         |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-------------------------|
| Product               | Digital Paper System                                                                                                                                             |                     |                         |
| Trade Name            | Avalue                                                                                                                                                           |                     |                         |
| Model No.             | EL310XX (X= 0~9 or A~Z)                                                                                                                                          |                     |                         |
| Model Discrepancy     | All the above models are identical except for the designation of model numbers. The suffix of (X= 0~9 or A~Z) on model number is just for marketing purpose only |                     |                         |
| Modulation Technique  | Bluetooth:GFSK for 1Mbps;π/4-DQPSK for 2Mbps;8DPSK for 3Mbps;LE                                                                                                  |                     |                         |
|                       | 802.11a: Orthogonal Frequency Division Multiplexing (OFDM)                                                                                                       |                     |                         |
|                       | 802.11b: Direct Sequence Spread Spectrum(DSSS)                                                                                                                   |                     |                         |
|                       | 802.11g: Orthogonal Frequency Division Multiplexing (OFDM)                                                                                                       |                     |                         |
|                       | 802.11n: Orthogonal Frequency Division Multiplexing (OFDM)                                                                                                       |                     |                         |
| Antenna Specification | 802.11ac: Orthogonal Frequency Division Multiplexing (OFDM)                                                                                                      |                     |                         |
|                       | Main Antenna                                                                                                                                                     |                     |                         |
|                       | Operating Mode                                                                                                                                                   | TX Freq Range (MHz) | Peak Antenna Gain (dBi) |
|                       | WLAN2.4GHz                                                                                                                                                       | 2412~2472           | 2.8                     |
|                       | WLAN5GHz                                                                                                                                                         | 5150~5850           | 3.42                    |
|                       | Brand name                                                                                                                                                       | YAGEO               |                         |
|                       | Type                                                                                                                                                             | PIFA                |                         |
|                       | Parts Number                                                                                                                                                     | ANTA0ZV1421124551   |                         |
|                       | Aux Antenna                                                                                                                                                      |                     |                         |
|                       | Operating Mode                                                                                                                                                   | TX Freq Range (MHz) | Peak Antenna Gain (dBi) |
|                       | WLAN2.4GHz                                                                                                                                                       | 2412~2472           | 2.94                    |
|                       | WLAN5GHz                                                                                                                                                         | 5150~5850           | 2.51                    |
|                       | Bluetooth                                                                                                                                                        | 2402~2480           | 2.94                    |
|                       | Brand name                                                                                                                                                       | YAGEO               |                         |
|                       | Type                                                                                                                                                             | PIFA                |                         |
| Parts Number          | ANTA0ZV1421124552                                                                                                                                                |                     |                         |

### Remark:

- 1.The sample selected for test was prototype that representative to production product and was provided by manufacturer
- 2.Disclaimer:Variant information between/among model numbers / trademarks is provided by the applicant, test results of this report are applicable to the sample EUT received of main test model name.
- 3.Disclaimer:Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received

## 2.1 Summary of Highest SAR Values

Results for highest reported SAR values for each frequency band and mode are as below:

| Technology/Band | Test configuration | Mode                | Highest Reported 1g-SAR (W/kg) |
|-----------------|--------------------|---------------------|--------------------------------|
| Wi-Fi 2.4 GHz   | Rear               | 802.11n (HT20)_MIMO | 0.794                          |
| U-NII           | Rear               | 802.11n (HT20)_MIMO | 1.162                          |

### Sum of the Highest SAR Values for Wi-Fi 5G\_MIMO & BT

| Test Position | Standalone SAR (W/kg) |         | Σ 1-g SAR (W/kg)    |
|---------------|-----------------------|---------|---------------------|
|               | U-NII<br>①            | BT<br>② | U-NII + BT<br>① + ② |
| Rear          | 1.162                 | 0.126   | 1.288               |

### **3 Requirements for Compliance Testing Defined**


#### **3.1 Requirements for Compliance Testing Defined by the FCC**

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/kg for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the FCC 47 CFR §2.1093 and IEEE Std 1528-2013.

## 4 Dosimetric Assessment System

These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than  $\pm 0.02$  mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EX3DV4-SN: 3665 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure and found to be better than  $\pm 0.25$  dB. The phantom used was the ELI Phantom as described in FCC supplement C, IEEE 1528 2013.

## 4.1 Measurement System Diagram



### The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7 or Windows XP.
- DASY5 software version: 52.10.3.1513.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.

## 4.2 System Components

| DASY5 Measurement Server                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <p>The DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE4 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.</p> <p>The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.</p>                                                                                                                                                                               |
|   | <p>The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.</p>                                                                         |
| Data Acquisition Electronics (DAE)                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|  | <p>The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.</p> <p>The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200MΩ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.</p> |

## EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements



|                       |                                                                                                                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction:</b>  | Symmetrical design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE)                                                |
| <b>Calibration:</b>   | Basic Broad Band Calibration in air: 10-3000 MHz.<br>Conversion Factors (CF) for HSL 900 and HSL 1800<br>CF-Calibration for other liquids and frequencies upon request.                                    |
| <b>Frequency:</b>     | 10 MHz to > 6 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 3 GHz)                                                                                                                                               |
| <b>Directivity:</b>   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in HSL (rotation normal to probe axis)                                                                                                    |
| <b>Dynamic Range:</b> | 10 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB<br>(noise: typically < 1 $\mu$ W/g)                                                                                                                    |
| <b>Dimensions:</b>    | Overall length: 330 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Distance from probe tip to dipole centers: 1 mm                                                                               |
| <b>Application:</b>   | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%. |

## SAM Phantom



|                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction:</b>    | The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 2013, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot. |
| <b>Shell Thickness:</b> | 2 $\pm$ 0.2 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Filling Volume:</b>  | Approx. 25 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Dimensions:</b>      | Height: 810mm; Length: 1000mm; Width: 500mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

## ELI Phantom



|                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction:</b>    | Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY5 and higher and is compatible with all SPEAG dosimetric probes and dipoles |
| <b>Shell Thickness:</b> | 2.0 $\pm$ 0.2 mm (sagging: <1%)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Filling Volume:</b>  | Approx. 25 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Dimensions:</b>      | Major ellipse axis: 600 mm<br>Minor axis: 400 mm 500mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## Device Holder for SAM Twin Phantom



**Construction:** In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).

## System Validation Kits for SAM Phantom



**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.


**Frequency:** 2450, 5300, 5600, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:** D2450V2: dipole length: 51.5 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm

## System Validation Kits for ELI phantom



**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 2450, 5300, 5600, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:** D2450V2: dipole length: 51.5 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm

## 5 Evaluation Procedures

### Data Evaluation

The DASY5 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

|                    |                           |                                  |
|--------------------|---------------------------|----------------------------------|
| Probe parameters:  | - Sensitivity             | $Norm_i, a_{i0}, a_{i1}, a_{i2}$ |
|                    | - Conversion factor       | $ConvF_i$                        |
|                    | - Diode compression point | $dcp_i$                          |
| Device parameters: | - Frequency               | $f$                              |
|                    | - Crest factor            | $cf$                             |
| Media parameters:  | - Conductivity            | $\sigma$                         |
|                    | - Density                 | $\rho$                           |

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

|      |         |                                   |                  |
|------|---------|-----------------------------------|------------------|
| with | $V_i$   | = Compensated signal of channel i | (i = x, y, z)    |
|      | $U_i$   | = Input signal of channel i       | (i = x, y, z)    |
|      | $cf$    | = Crest factor of exciting field  | (DASY parameter) |
|      | $dcp_i$ | = Diode compression point         | (DASY parameter) |

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes:

$$H_i = \sqrt{V_i} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$$

|      |          |                                   |               |
|------|----------|-----------------------------------|---------------|
| with | $V_i$    | = Compensated signal of channel i | (i = x, y, z) |
|      | $Norm_i$ | = Sensor sensitivity of channel i | (i = x, y, z) |

$\mu V/(V/m)^2$  for E0field Probes

|          |                                                 |
|----------|-------------------------------------------------|
| $ConvF$  | = Sensitivity enhancement in solution           |
| $a_{ij}$ | = Sensor sensitivity factors for H-field probes |
| $f$      | = Carrier frequency (GHz)                       |
| $E_i$    | = Electric field strength of channel i in V/m   |
| $H_i$    | = Magnetic field strength of channel i in A/m   |

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with

- $SAR$  = local specific absorption rate in W/kg
- $E_{tot}$  = total field strength in V/m
- $\sigma$  = conductivity in [mho/m] or [Siemens/m]
- $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{377} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with

- $P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>
- $E_{tot}$  = total electric field strength in V/m
- $H_{tot}$  = total magnetic field strength in A/m

## 6 SAR Measurement Procedures

### 6.1 Normal SAR Test Procedure

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, the grid resolution has to less than 15 mm by 15 mm at frequency  $\leq 2$  GHz; the grid resolution has to less than 12 mm by 12 mm at frequency between 2 GHz to 4 GHz; grid resolution has to less than 10 mm by 10 mm at frequency between 4 GHz to 6 GHz.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

|                                                                                                        | $\leq 3$ GHz                                                                                                                                                                                                                                                           | $> 3$ GHz                                              |
|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface | $5 \pm 1$ mm                                                                                                                                                                                                                                                           | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm     |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location              | $30^\circ \pm 1^\circ$                                                                                                                                                                                                                                                 | $20^\circ \pm 1^\circ$                                 |
| Maximum area scan spatial resolution: $\Delta x_{\text{zoom}}$ , $\Delta y_{\text{zoom}}$              | $\leq 2$ GHz: $\leq 15$ mm<br>$2 - 3$ GHz: $\leq 12$ mm                                                                                                                                                                                                                | $3 - 4$ GHz: $\leq 12$ mm<br>$4 - 6$ GHz: $\leq 10$ mm |
|                                                                                                        | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                        |

- Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures points in accordance with the frequency can be divided into three parts. (1)The zoom scan volume was set to 5x5x7 points at frequency  $\leq 2$ GHz. (2) The zoom scan volume was set to 7x7x7 points at frequency between 2GHz to 4GHz (3) The zoom scan volume was set to 7x7x12 points at frequency between 4GHz to 6GHz. The measures points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more then one maximum, the number of Zoom Scans has to be enlarged accordingly.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

|                                                                                        |                                           |                                                                                           | $\leq 3$ GHz                                                                  | $> 3$ GHz                                                                    |
|----------------------------------------------------------------------------------------|-------------------------------------------|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|------------------------------------------------------------------------------|
| Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$ |                                           |                                                                                           | $\leq 2$ GHz: $\leq 8$ mm<br>2 – 3 GHz: $\leq 5$ mm                           | 3 – 4 GHz: $\leq 5$ mm<br>4 – 6 GHz: $\leq 4$ mm                             |
| Maximum zoom scan spatial resolution, normal to phantom surface                        | Uniform grid: $\Delta z_{\text{Zoom}}(n)$ |                                                                                           | $\leq 5$ mm                                                                   | 3 – 4 GHz: $\leq 4$ mm<br>4 – 5 GHz: $\leq 3$ mm<br>5 – 6 GHz: $\leq 2$ mm   |
|                                                                                        | graded grid                               | $\Delta z_{\text{Zoom}}(1)$ :between 1 <sup>st</sup> two points loiest to phantom surface | $\leq 4$ mm                                                                   | 3 – 4 GHz: $\leq 3$ mm<br>4 – 5 GHz: $\leq 2.5$ mm<br>5 – 6 GHz: $\leq 2$ mm |
|                                                                                        |                                           | $\Delta z_{\text{Zoom}}(n>1)$ : between subsequent points                                 | $\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$                                  |                                                                              |
| Maximum zoom scan volume                                                               | x, y, z                                   | $\geq 30$ mm                                                                              | 3 – 4 GHz: $\geq 28$ mm<br>4 – 5 GHz: $\geq 25$ mm<br>5 – 6 GHz: $\geq 22$ mm |                                                                              |

- Power Drift Measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY5 software stop the measurements if this limit is exceeded.



- Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.

## **7 Measurement Uncertainty**

According to KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz section 2.8.2, SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is  $\geq 1.5$  W/kg for 1-g SAR, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

## 8 Antenna Location



## 9 RF Exposure Conditions (Test Configurations)

Please refer to chapter 8 for detailed information about antenna-to-antenna distance and antenna-to-edge distance.

### 9.1. Standalone SAR Test Exclusion Considerations

Since the *Dedicated Host Approach* is applied, the standalone SAR test exclusion procedure in KDB 447498 § 4.3.1 is applied in conjunction with KDB 616217 § 4.3 to determine the minimum test separation distance:

- o When the separation distance from the antenna to an adjacent edge is  $\leq 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.
- o When the separation distance from the antenna to an adjacent edge is  $> 5$  mm, the actual antenna-to-edge separation distance is applied to determine SAR test exclusion.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ , for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

- $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})}/x]$  W/kg for test separation distances  $\leq 50$  mm;  
where  $x = 7.5$  for 1-g SAR, and  $x = 18.75$  for 10-g SAR.
- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is  $> 50$  mm.

**SAR Test Exclusion Calculations for WLAN SISO****Antennas < 50mm to adjacent edges**

| Tx Interface  | Frequency (MHz) | Output Power |    | Separation Distances (mm) |        |        |        |        | Calculated Threshold Value |                 |                  |         |         |
|---------------|-----------------|--------------|----|---------------------------|--------|--------|--------|--------|----------------------------|-----------------|------------------|---------|---------|
|               |                 | dBm          | mW | Rear                      | Edge 1 | Edge 2 | Edge 3 | Edge 4 | Rear                       | Edge 1          | Edge 2           | Edge 3  | Edge 4  |
| Main Antenna  |                 |              |    |                           |        |        |        |        |                            |                 |                  |         |         |
| Wi-Fi 2.4 GHz | 2462            | 12.00        | 16 | 5                         | 31.1   | 5      | 119.1  | 228.8  | 5<br>-MEASURE-             | 0.8<br>-EXEMPT- | 5<br>-MEASURE-   | > 50 mm | > 50 mm |
| Wi-Fi 5.2 GHz | 5240            | 9.00         | 8  | 5                         | 31.1   | 5      | 119.1  | 228.8  | 3.7<br>-MEASURE-           | 0.6<br>-EXEMPT- | 3.7<br>-MEASURE- | > 50 mm | > 50 mm |
| Wi-Fi 5.3 GHz | 5320            | 9.00         | 8  | 5                         | 31.1   | 5      | 119.1  | 228.8  | 3.7<br>-MEASURE-           | 0.6<br>-EXEMPT- | 3.7<br>-MEASURE- | > 50 mm | > 50 mm |
| Wi-Fi 5.5 GHz | 5700            | 9.00         | 8  | 5                         | 31.1   | 5      | 119.1  | 228.8  | 3.8<br>-MEASURE-           | 0.6<br>-EXEMPT- | 3.8<br>-MEASURE- | > 50 mm | > 50 mm |
| Wi-Fi 5.8 GHz | 5825            | 8.00         | 6  | 5                         | 31.1   | 5      | 119.1  | 228.8  | 2.9<br>-EXEMPT-            | 0.5<br>-EXEMPT- | 2.9<br>-EXEMPT-  | > 50 mm | > 50 mm |

| Tx Interface  | Frequency (MHz) | Output Power |    | Separation Distances (mm) |        |        |        |        | Calculated Threshold Value |         |                  |                 |         |
|---------------|-----------------|--------------|----|---------------------------|--------|--------|--------|--------|----------------------------|---------|------------------|-----------------|---------|
|               |                 | dBm          | mW | Rear                      | Edge 1 | Edge 2 | Edge 3 | Edge 4 | Rear                       | Edge 1  | Edge 2           | Edge 3          | Edge 4  |
| Aux Antenna   |                 |              |    |                           |        |        |        |        |                            |         |                  |                 |         |
| Wi-Fi 2.4 GHz | 2462            | 12.00        | 16 | 5                         | 105.3  | 5      | 47.9   | 229.2  | 5<br>-MEASURE-             | > 50 mm | 5<br>-MEASURE-   | 0.5<br>-EXEMPT- | > 50 mm |
| Wi-Fi 5.2 GHz | 5240            | 9.00         | 8  | 5                         | 105.3  | 5      | 47.9   | 229.2  | 3.7<br>-MEASURE-           | > 50 mm | 3.7<br>-MEASURE- | 0.4<br>-EXEMPT- | > 50 mm |
| Wi-Fi 5.3 GHz | 5320            | 9.00         | 8  | 5                         | 105.3  | 5      | 47.9   | 229.2  | 3.7<br>-MEASURE-           | > 50 mm | 3.7<br>-MEASURE- | 0.4<br>-EXEMPT- | > 50 mm |
| Wi-Fi 5.5 GHz | 5700            | 9.00         | 8  | 5                         | 105.3  | 5      | 47.9   | 229.2  | 3.8<br>-MEASURE-           | > 50 mm | 3.8<br>-MEASURE- | 0.4<br>-EXEMPT- | > 50 mm |
| Wi-Fi 5.8 GHz | 5825            | 8.00         | 6  | 5                         | 105.3  | 5      | 47.9   | 229.2  | 2.9<br>-EXEMPT-            | > 50 mm | 2.9<br>-EXEMPT-  | 0.3<br>-EXEMPT- | > 50 mm |
| Bluetooth     | 2480            | 4.00         | 3  | 5                         | 105.3  | 5      | 47.9   | 229.2  | 0.9<br>-EXEMPT-            | > 50 mm | 0.9<br>-EXEMPT-  | 0.1<br>-EXEMPT- | > 50 mm |

**Note(s):**

According to KDB 447498, if the calculated threshold value is >3 then SAR testing is required.

**Antennas > 50mm to adjacent edges**

| Tx Interface  | Frequency (MHz) | Output Power |    | Separation Distances (mm) |        |        |        |        | Calculated Threshold Value |         |         |                      |                       |
|---------------|-----------------|--------------|----|---------------------------|--------|--------|--------|--------|----------------------------|---------|---------|----------------------|-----------------------|
|               |                 | dBm          | mW | Rear                      | Edge 1 | Edge 2 | Edge 3 | Edge 4 | Rear                       | Edge 1  | Edge 2  | Edge 3               | Edge 4                |
| Main Antenna  |                 |              |    |                           |        |        |        |        |                            |         |         |                      |                       |
| Wi-Fi 2.4 GHz | 2462            | 12.00        | 16 | 5                         | 31.1   | 5      | 119.1  | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | 786.6 mW<br>-EXEMPT- | 1883.6 mW<br>-EXEMPT- |
| Wi-Fi 5.2 GHz | 5240            | 9.00         | 8  | 5                         | 31.1   | 5      | 119.1  | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | 756.5 mW<br>-EXEMPT- | 1853.5 mW<br>-EXEMPT- |
| Wi-Fi 5.3 GHz | 5320            | 9.00         | 8  | 5                         | 31.1   | 5      | 119.1  | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | 756 mW<br>-EXEMPT-   | 1853 mW<br>-EXEMPT-   |
| Wi-Fi 5.5 GHz | 5700            | 9.00         | 8  | 5                         | 31.1   | 5      | 119.1  | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | 753.8 mW<br>-EXEMPT- | 1850.8 mW<br>-EXEMPT- |
| Wi-Fi 5.8 GHz | 5825            | 8.00         | 6  | 5                         | 31.1   | 5      | 119.1  | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | 753.2 mW<br>-EXEMPT- | 1850.2 mW<br>-EXEMPT- |

| Tx Interface  | Frequency (MHz) | Output Power |    | Separation Distances (mm) |        |        |        |        | Calculated Threshold Value |                      |         |         |                       |
|---------------|-----------------|--------------|----|---------------------------|--------|--------|--------|--------|----------------------------|----------------------|---------|---------|-----------------------|
|               |                 | dBm          | mW | Rear                      | Edge 1 | Edge 2 | Edge 3 | Edge 4 | Rear                       | Edge 1               | Edge 2  | Edge 3  | Edge 4                |
| Aux Antenna   |                 |              |    |                           |        |        |        |        |                            |                      |         |         |                       |
| Wi-Fi 2.4 GHz | 2462            | 12.00        | 16 | 5                         | 105.3  | 5      | 47.9   | 229.2  | < 50 mm                    | 648.6 mW<br>-EXEMPT- | < 50 mm | < 50 mm | 1887.6 mW<br>-EXEMPT- |
| Wi-Fi 5.2 GHz | 5240            | 9.00         | 8  | 5                         | 105.3  | 5      | 47.9   | 229.2  | < 50 mm                    | 618.5 mW<br>-EXEMPT- | < 50 mm | < 50 mm | 1857.5 mW<br>-EXEMPT- |
| Wi-Fi 5.3 GHz | 5320            | 9.00         | 8  | 5                         | 105.3  | 5      | 47.9   | 229.2  | < 50 mm                    | 618 mW<br>-EXEMPT-   | < 50 mm | < 50 mm | 1857 mW<br>-EXEMPT-   |
| Wi-Fi 5.5 GHz | 5700            | 9.00         | 8  | 5                         | 105.3  | 5      | 47.9   | 229.2  | < 50 mm                    | 615.8 mW<br>-EXEMPT- | < 50 mm | < 50 mm | 1854.8 mW<br>-EXEMPT- |
| Wi-Fi 5.8 GHz | 5825            | 8.00         | 6  | 5                         | 105.3  | 5      | 47.9   | 229.2  | < 50 mm                    | 615.2 mW<br>-EXEMPT- | < 50 mm | < 50 mm | 1854.2 mW<br>-EXEMPT- |
| Bluetooth     | 2480            | 4.00         | 3  | 5                         | 105.3  | 5      | 47.9   | 229.2  | < 50 mm                    | 648.3 mW<br>-EXEMPT- | < 50 mm | < 50 mm | 1887.3 mW<br>-EXEMPT- |

**Note(s):**

According to KDB 447498, if the calculated Power threshold is less than the output power then SAR testing is required.

**SAR Test Exclusion Calculations for WLAN MIMO****Antennas < 50mm to adjacent edges**

| Tx Interface  | Frequency (MHz) | Output Power |    | Separation Distances (mm) |        |        |        |        | Calculated Threshold Value |                 |                  |                 |         |
|---------------|-----------------|--------------|----|---------------------------|--------|--------|--------|--------|----------------------------|-----------------|------------------|-----------------|---------|
|               |                 | dBm          | mW | Rear                      | Edge 1 | Edge 2 | Edge 3 | Edge 4 | Rear                       | Edge 1          | Edge 2           | Edge 3          | Edge 4  |
| Wi-Fi 2.4 GHz | 2462            | 15.00        | 32 | 5                         | 31.1   | 5      | 47.9   | 228.8  | 10<br>-MEASURE-            | 1.6<br>-EXEMPT- | 10<br>-MEASURE-  | 1<br>-EXEMPT-   | > 50 mm |
| Wi-Fi 5.2 GHz | 5240            | 12.00        | 16 | 5                         | 31.1   | 5      | 47.9   | 228.8  | 7.3<br>-MEASURE-           | 1.2<br>-EXEMPT- | 7.3<br>-MEASURE- | 0.8<br>-EXEMPT- | > 50 mm |
| Wi-Fi 5.3 GHz | 5320            | 12.00        | 16 | 5                         | 31.1   | 5      | 47.9   | 228.8  | 7.4<br>-MEASURE-           | 1.2<br>-EXEMPT- | 7.4<br>-MEASURE- | 0.8<br>-EXEMPT- | > 50 mm |
| Wi-Fi 5.5 GHz | 5700            | 12.00        | 16 | 5                         | 31.1   | 5      | 47.9   | 228.8  | 7.6<br>-MEASURE-           | 1.2<br>-EXEMPT- | 7.6<br>-MEASURE- | 0.8<br>-EXEMPT- | > 50 mm |
| Wi-Fi 5.8 GHz | 5825            | 10.00        | 10 | 5                         | 31.1   | 5      | 47.9   | 228.8  | 4.8<br>-MEASURE-           | 0.8<br>-EXEMPT- | 4.8<br>-MEASURE- | 0.5<br>-EXEMPT- | > 50 mm |

**Note(s):**

According to KDB 447498, if the calculated threshold value is >3 then SAR testing is required.

**Antennas > 50mm to adjacent edges**

| Tx Interface  | Frequency (MHz) | Output Power |    | Separation Distances (mm) |        |        |        |        | Calculated Threshold Value |         |         |         |                       |
|---------------|-----------------|--------------|----|---------------------------|--------|--------|--------|--------|----------------------------|---------|---------|---------|-----------------------|
|               |                 | dBm          | mW | Rear                      | Edge 1 | Edge 2 | Edge 3 | Edge 4 | Rear                       | Edge 1  | Edge 2  | Edge 3  | Edge 4                |
| Wi-Fi 2.4 GHz | 2462            | 15.00        | 32 | 5                         | 31.1   | 5      | 47.9   | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | < 50 mm | 1883.6 mW<br>-EXEMPT- |
| Wi-Fi 5.2 GHz | 5240            | 12.00        | 16 | 5                         | 31.1   | 5      | 47.9   | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | < 50 mm | 1853.5 mW<br>-EXEMPT- |
| Wi-Fi 5.3 GHz | 5320            | 12.00        | 16 | 5                         | 31.1   | 5      | 47.9   | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | < 50 mm | 1853 mW<br>-EXEMPT-   |
| Wi-Fi 5.5 GHz | 5700            | 12.00        | 16 | 5                         | 31.1   | 5      | 47.9   | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | < 50 mm | 1850.8 mW<br>-EXEMPT- |
| Wi-Fi 5.8 GHz | 5825            | 10.00        | 10 | 5                         | 31.1   | 5      | 47.9   | 228.8  | < 50 mm                    | < 50 mm | < 50 mm | < 50 mm | 1850.2 mW<br>-EXEMPT- |

**Note(s):**

According to KDB 447498, if the calculated Power threshold is less than the output power then SAR testing is required.

## 9.1. REQUIRED TEST CONFIGURATIONS

The table below identifies the standalone test configurations required for this device according to the findings in Section 9.1:

| Main Antenna        |      |        |        |        |        |
|---------------------|------|--------|--------|--------|--------|
| Test Configurations | Rear | Edge 1 | Edge 2 | Edge 3 | Edge 4 |
| Wi-Fi 2.4 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.2 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.3 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.5 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.8 GHz       | No   | No     | No     | No     | No     |

| Aux Antenna         |      |        |        |        |        |
|---------------------|------|--------|--------|--------|--------|
| Test Configurations | Rear | Edge 1 | Edge 2 | Edge 3 | Edge 4 |
| Wi-Fi 2.4 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.2 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.3 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.5 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.8 GHz       | No   | No     | No     | No     | No     |
| Bluetooth           | No   | No     | No     | No     | No     |

| MIMO                |      |        |        |        |        |
|---------------------|------|--------|--------|--------|--------|
| Test Configurations | Rear | Edge 1 | Edge 2 | Edge 3 | Edge 4 |
| Wi-Fi 2.4 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.2 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.3 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.5 GHz       | Yes  | No     | Yes    | No     | No     |
| Wi-Fi 5.8 GHz       | Yes  | No     | Yes    | No     | No     |

### Note(s):

Yes = Testing is required.

No = Testing is not required.

## 10 Exposure Limit

### (A). Limits for Occupational/Controlled Exposure (W/kg)

| <u>Whole-Body</u> | <u>Partial-Body</u> | <u>Hands, Wrists, Feet and Ankles</u> |
|-------------------|---------------------|---------------------------------------|
| 0.4               | 8.0                 | 2.0                                   |

### (B). Limits for General Population/Uncontrolled Exposure (W/kg)

| <u>Whole-Body</u> | <u>Partial-Body</u> | <u>Hands, Wrists, Feet and Ankles</u> |
|-------------------|---------------------|---------------------------------------|
| 0.08              | 1.6                 | 4.0                                   |

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

#### Population/Uncontrolled Environments:

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

#### Occupational/Controlled Environments:

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

#### NOTE

**GENERAL POPULATION/UNCONTROLLED EXPOSURE  
PARTIAL BODY LIMIT  
1.6 W/kg**

## 11 Tissue Dielectric Properties

### 11.1 Test Liquid Confirmation

#### Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within  $\pm 5\%$  of the values given in the table below. 5% may not be easily achieved at certain frequencies.

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE 1528 2013 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head tissue parameters that have not been specified in IEEE 1528 2013 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE 1528 2013

| Target Frequency (MHz) | Head         |                |
|------------------------|--------------|----------------|
|                        | $\epsilon_r$ | $\sigma$ (S/m) |
| 150                    | 52.3         | 0.76           |
| 300                    | 45.3         | 0.87           |
| 450                    | 43.5         | 0.87           |
| 835                    | 41.5         | 0.90           |
| 900                    | 41.5         | 0.97           |
| 915                    | 41.5         | 0.98           |
| 1450                   | 40.5         | 1.20           |
| 1610                   | 40.3         | 1.29           |
| 1800 – 2000            | 40.0         | 1.40           |
| 2450                   | 39.2         | 1.80           |
| 3000                   | 38.5         | 2.40           |
| 5000                   | 36.2         | 4.45           |
| 5100                   | 36.1         | 4.55           |
| 5200                   | 36.0         | 4.66           |
| 5300                   | 35.9         | 4.76           |
| 5400                   | 35.8         | 4.86           |
| 5500                   | 35.6         | 4.96           |
| 5600                   | 35.5         | 5.07           |
| 5700                   | 35.4         | 5.17           |
| 5800                   | 35.3         | 5.27           |

#### IEEE Std 1528-2013

Refer to Table 3 within the IEEE Std 1528-2013

## 11.2 Typical Composition of Ingredients for Liquid Tissue Phantoms

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

| Ingredients<br>(% by weight) | Frequency (MHz) |       |       |      |       |       |       |      |      |      |
|------------------------------|-----------------|-------|-------|------|-------|-------|-------|------|------|------|
|                              | 450             |       | 835   |      | 915   |       | 1900  |      | 2450 |      |
| Tissue Type                  | Head            | Body  | Head  | Body | Head  | Body  | Head  | Body | Head | Body |
| Water                        | 38.56           | 51.16 | 41.45 | 52.4 | 41.05 | 56.0  | 54.9  | 40.4 | 62.7 | 73.2 |
| Salt (NaCl)                  | 3.95            | 1.49  | 1.45  | 1.4  | 1.35  | 0.76  | 0.18  | 0.5  | 0.5  | 0.04 |
| Sugar                        | 56.32           | 46.78 | 56.0  | 45.0 | 56.5  | 41.76 | 0.0   | 58.0 | 0.0  | 0.0  |
| HEC                          | 0.98            | 0.52  | 1.0   | 1.0  | 1.0   | 1.21  | 0.0   | 1.0  | 0.0  | 0.0  |
| Bactericide                  | 0.19            | 0.05  | 0.1   | 0.1  | 0.1   | 0.27  | 0.0   | 0.1  | 0.0  | 0.0  |
| Triton X-100                 | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 0.0   | 0.0  | 36.8 | 0.0  |
| DGBE                         | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 44.92 | 0.0  | 0.0  | 26.7 |
| Dielectric Constant          | 43.42           | 58.0  | 42.54 | 56.1 | 42.0  | 56.8  | 39.9  | 54.0 | 39.8 | 52.5 |
| Conductivity (S/m)           | 0.85            | 0.83  | 0.91  | 0.95 | 1.0   | 1.07  | 1.42  | 1.45 | 1.88 | 1.78 |

alt: 99% Pure Sodium Chloride

Sugar: 98% Pure Sucrose

Water: De-ionized, 16 MΩ<sup>+</sup> resistivity

HEC: Hydroxy thyl Cellulose

DGBE: 99% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra-pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether

### Simulating Liquids for 5 GHz, Manufactured by SPEAG

| Ingredients        | (% by weight) |
|--------------------|---------------|
| Water              | 78            |
| Mineral oil        | 11            |
| Emulsifiers        | 9             |
| Additives and Salt | 2             |

### 11.3 Simulating Liquids Parameter Check Results

| Date       | Tissue Type | Frequency (MHz) | Relative Permittivity ( $\epsilon_r$ ) |        |           | Conductivity ( $\sigma$ ) |        |           |
|------------|-------------|-----------------|----------------------------------------|--------|-----------|---------------------------|--------|-----------|
|            |             |                 | Measured                               | Target | Delta (%) | Measured                  | Target | Delta (%) |
| 2020/11/26 | Head        | 2400            | 39.89                                  | 39.30  | 1.50      | 1.71                      | 1.76   | -2.79     |
|            |             | 2450            | 39.62                                  | 39.20  | 1.07      | 1.76                      | 1.80   | -2.00     |
|            |             | 2500            | 39.43                                  | 39.13  | 0.77      | 1.83                      | 1.85   | -1.40     |
| 2020/11/17 | Head        | 5250            | 36.90                                  | 35.95  | 2.64      | 4.82                      | 4.71   | 2.31      |
|            |             | 5300            | 36.67                                  | 35.90  | 2.14      | 4.69                      | 4.76   | -1.51     |
|            |             | 5350            | 36.84                                  | 35.85  | 2.76      | 5.00                      | 4.81   | 4.01      |
| 2020/11/18 | Head        | 5250            | 35.94                                  | 35.95  | -0.03     | 4.71                      | 4.71   | 0.08      |
|            |             | 5300            | 35.93                                  | 35.90  | 0.08      | 4.85                      | 4.76   | 1.83      |
|            |             | 5350            | 35.83                                  | 35.85  | -0.06     | 4.86                      | 4.81   | 1.10      |
| 2020/11/19 | Head        | 5250            | 35.78                                  | 35.95  | -0.47     | 4.76                      | 4.71   | 1.08      |
|            |             | 5300            | 35.79                                  | 35.90  | -0.31     | 4.84                      | 4.76   | 1.64      |
|            |             | 5350            | 35.69                                  | 35.85  | -0.45     | 4.90                      | 4.81   | 1.91      |
| 2020/11/17 | Head        | 5500            | 36.58                                  | 35.65  | 2.61      | 4.92                      | 4.97   | -0.91     |
|            |             | 5600            | 36.11                                  | 35.50  | 1.72      | 5.05                      | 5.07   | -0.45     |
|            |             | 5700            | 35.69                                  | 35.40  | 0.82      | 5.15                      | 5.17   | -0.33     |
| 2020/11/18 | Head        | 5500            | 36.36                                  | 35.65  | 1.99      | 4.94                      | 4.97   | -0.60     |
|            |             | 5600            | 35.88                                  | 35.50  | 1.07      | 5.06                      | 5.07   | -0.16     |
|            |             | 5700            | 35.47                                  | 35.40  | 0.20      | 5.17                      | 5.17   | -0.02     |
| 2020/11/19 | Head        | 5500            | 35.44                                  | 35.65  | -0.59     | 5.08                      | 4.97   | 2.30      |
|            |             | 5600            | 35.07                                  | 35.50  | -1.21     | 5.13                      | 5.07   | 1.26      |
|            |             | 5700            | 34.65                                  | 35.40  | -2.12     | 5.38                      | 5.17   | 4.08      |
| 2020/11/27 | Head        | 5700            | 34.70                                  | 35.40  | -1.98     | 5.35                      | 5.17   | 3.46      |
|            |             | 5800            | 34.63                                  | 35.30  | -1.90     | 5.30                      | 5.27   | 0.53      |
|            |             | 5850            | 34.54                                  | 35.25  | -2.01     | 5.32                      | 5.32   | 0.02      |

## 12 System Performance Check

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

### System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the SAM twin phantom filled with Head simulating liquid of the following parameters.
- The DASY5 system with an E-field probe EX3DV4 SN: 3665 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration (dx=dy= 5 mm, dz= 5 mm).
- Distance between probe sensors and phantom surface was set to 3.0 mm.
- The dipole input power (forward power) was 250 mW $\pm$ 3% (below 2GHz) and 100 mW  $\pm$ 3%
- The results are normalized to 1 W input power.

### Reference SAR Values for System Performance Check

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

| System Dipole | Serial No. | Cal. Date  | Freq. (MHz) | Target SAR Values (W/kg) |      |
|---------------|------------|------------|-------------|--------------------------|------|
|               |            |            |             | 1g/10g                   | Head |
| D2450V2       | 727        | 2021/04/22 | 2450        | 1g                       | 52.6 |
|               |            |            |             | 10g                      | 24.7 |
| D5GHzV2       | 1023       | 2020/1/28  | 5300        | 1g                       | 82.8 |
|               |            |            |             | 10g                      | 23.4 |
| D5GHzV2       | 1023       | 2020/1/28  | 5600        | 1g                       | 83.1 |
|               |            |            |             | 10g                      | 23.5 |
| D5GHzV2       | 1023       | 2020/1/28  | 5800        | 1g                       | 81.4 |
|               |            |            |             | 10g                      | 22.7 |

**12.1 System Performance Check Results**

| Date       | Tissue Type | Dipole S/N        | Input Power (mW) | Measured 1g SAR (W/kg) | Targeted 1g SAR (W/kg) | Normalized 1g SAR (W/kg) | Delta 1g $\pm 10$ (%) | Measured 10g SAR (W/kg) | Targeted 10g SAR (W/kg) | Normalized 10g SAR (W/kg) | Delta 10g $\pm 10$ (%) | Plot No. |
|------------|-------------|-------------------|------------------|------------------------|------------------------|--------------------------|-----------------------|-------------------------|-------------------------|---------------------------|------------------------|----------|
| 2020/11/26 | Head        | D2450V2-727       | 250              | 13.10                  | 52.60                  | 52.4                     | -0.38                 | 6.13                    | 24.70                   | 24.52                     | -0.73                  | 1        |
| 2020/11/17 | Head        | D5GHzV2-1023-5300 | 100              | 8.44                   | 82.80                  | 84.4                     | 1.93                  | 2.41                    | 23.40                   | 24.1                      | 2.99                   | 2        |
| 2020/11/18 | Head        | D5GHzV2-1023-5300 | 100              | 8.67                   | 82.80                  | 86.7                     | 4.71                  | 2.46                    | 23.40                   | 24.6                      | 5.13                   | 3        |
| 2020/11/19 | Head        | D5GHzV2-1023-5300 | 100              | 8.21                   | 82.80                  | 82.1                     | -0.85                 | 2.35                    | 23.40                   | 23.5                      | 0.43                   | 4        |
| 2020/11/17 | Head        | D5GHzV2-1023-5600 | 100              | 8.77                   | 83.10                  | 87.7                     | 5.54                  | 2.46                    | 23.50                   | 24.6                      | 4.68                   | 5        |
| 2020/11/18 | Head        | D5GHzV2-1023-5600 | 100              | 8.57                   | 83.10                  | 85.7                     | 3.13                  | 2.42                    | 23.50                   | 24.2                      | 2.98                   | 6        |
| 2020/11/19 | Head        | D5GHzV2-1023-5600 | 100              | 8.98                   | 83.10                  | 89.8                     | 8.06                  | 2.52                    | 23.50                   | 25.2                      | 7.23                   | 7        |
| 2020/11/27 | Head        | D5GHzV2-1023-5800 | 100              | 8.06                   | 81.40                  | 80.6                     | -0.98                 | 2.29                    | 22.70                   | 22.9                      | 0.88                   | 8        |

### 13 RF Output Power Measurement

According to KDB248227 D01 802.11 Wi-Fi SAR v02r02 section 4, the default power measurement procedures are:

- 1) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- 2) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
  - a) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
  - b) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- 3) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.

**13.1 Wi-Fi 2.4GHz (DTS Band)****Measured Results**

| Band (GHz) | Mode           | Data Rate | Ch # | Freq. (MHz) | Meas. Avg Pwr (dBm) |              | Max Output Power (dBm) |         | SAR Test (Yes/No) |
|------------|----------------|-----------|------|-------------|---------------------|--------------|------------------------|---------|-------------------|
|            |                |           |      |             | Chain 0             | Chain 1      | Chain 0                | Chain 1 |                   |
| 2.4        | 802.11b        | 1 Mbps    | 1    | 2412        | 11.72               | 11.52        | 12                     | 12      | Yes               |
|            |                |           | 6    | 2437        | 11.69               | 11.63        |                        |         |                   |
|            |                |           | 11   | 2462        | 11.67               | 11.56        |                        |         |                   |
|            | 802.11g        | 6 Mbps    | 1    | 2412        | Not Required        | Not Required | 12                     | 12      | No                |
|            |                |           | 6    | 2437        |                     |              |                        |         |                   |
|            |                |           | 11   | 2462        |                     |              |                        |         |                   |
|            | 802.11n (HT20) | MCS0      | 1    | 2412        | Not Required        | Not Required | 12                     | 12      | No                |
|            |                |           | 6    | 2437        |                     |              |                        |         |                   |
|            |                |           | 11   | 2462        |                     |              |                        |         |                   |

**MIMO Measured Results**

| Band (GHz) | Mode           | Data Rate | Ch # | Freq. (MHz) | Meas. Avg Pwr (dBm) |         | Total Power (dBm) | Max Output Power (dBm) | SAR Test (Yes/No) |
|------------|----------------|-----------|------|-------------|---------------------|---------|-------------------|------------------------|-------------------|
|            |                |           |      |             | Chain 0             | Chain 1 |                   |                        |                   |
| 2.4        | 802.11n (HT20) | MCS0      | 1    | 2412        | 11.71               | 11.68   | 14.71             | 15                     | Yes               |
|            |                |           | 6    | 2437        | 11.68               | 11.57   | 14.64             |                        |                   |
|            |                |           | 11   | 2462        | 11.59               | 11.52   | 14.57             |                        |                   |

**Note(s):**

- SAR is not required for 802.11g/n modes when the adjusted SAR for 802.11b is < 1.2 W/kg.
- For "Not required", SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band. Additional output power measurements were not deemed necessary.

**13.2 Wi-Fi 5GHz (U-NII Bands)****Measured Results**

| Band (GHz)     | Mode             | Data Rate | Ch # | Freq. (MHz) | Meas. Avg Pwr (dBm) |              | Max Output Power (dBm) |         | SAR Test (Yes/No) |
|----------------|------------------|-----------|------|-------------|---------------------|--------------|------------------------|---------|-------------------|
|                |                  |           |      |             | Chain 0             | Chain 1      | Chain 0                | Chain 1 |                   |
| 5.2 (U-NII 1)  | 802.11a          | 6 Mbps    | 36   | 5180        | 8.63                | 8.59         | 9                      | 9       | No                |
|                |                  |           | 40   | 5200        | 8.59                | 8.54         |                        |         |                   |
|                |                  |           | 44   | 5220        | 8.56                | 8.51         |                        |         |                   |
|                |                  |           | 48   | 5240        | 8.64                | 8.67         |                        |         |                   |
|                | 802.11n (HT20)   | MCS0      | 36   | 5180        | Not Required        | Not Required | 9                      | 9       | No                |
|                |                  |           | 40   | 5200        |                     |              |                        |         |                   |
|                |                  |           | 44   | 5220        |                     |              |                        |         |                   |
|                |                  |           | 48   | 5240        |                     |              |                        |         |                   |
|                | 802.11n (HT40)   | MCS0      | 38   | 5190        |                     |              | 8                      | 8       | No                |
|                |                  |           | 46   | 5230        |                     |              | 8                      | 8       | No                |
|                | 802.11ac (VHT80) | MCS8      | 42   | 5210        |                     |              | 8                      | 8       | No                |
| 5.3 (U-NII 2A) | 802.11a          | 6 Mbps    | 52   | 5260        | 8.76                | 8.63         | 9                      | 9       | Yes               |
|                |                  |           | 56   | 5280        | 8.98                | 8.86         |                        |         |                   |
|                |                  |           | 60   | 5300        | 8.88                | 8.80         |                        |         |                   |
|                |                  |           | 64   | 5320        | 8.96                | 8.84         |                        |         |                   |
|                | 802.11n (HT20)   | MCS0      | 52   | 5260        | Not Required        | Not Required | 9                      | 9       | No                |
|                |                  |           | 56   | 5280        |                     |              |                        |         |                   |
|                |                  |           | 60   | 5300        |                     |              |                        |         |                   |
|                |                  |           | 64   | 5320        |                     |              |                        |         |                   |
|                | 802.11n (HT40)   | MCS0      | 54   | 5270        |                     |              | 8                      | 8       | No                |
|                |                  |           | 62   | 5310        |                     |              | 8                      | 8       | No                |
|                | 802.11ac (VHT80) | MCS8      | 58   | 5290        |                     |              | 8                      | 8       | No                |
| 5.5 (U-NII 2C) | 802.11a          | 6 Mbps    | 100  | 5500        | 8.65                | 8.53         | 9                      | 9       | Yes               |
|                |                  |           | 116  | 5580        | 8.50                | 8.58         |                        |         |                   |
|                |                  |           | 140  | 5700        | 8.86                | 8.59         |                        |         |                   |
|                | 802.11n (HT20)   | MCS0      | 100  | 5500        | Not Required        | Not Required | 9                      | 9       | No                |
|                |                  |           | 116  | 5580        |                     |              |                        |         |                   |
|                |                  |           | 140  | 5700        |                     |              |                        |         |                   |
|                | 802.11n (HT40)   | MCS0      | 102  | 5510        |                     |              | 8                      | 8       | No                |
|                |                  |           | 110  | 5550        |                     |              |                        |         |                   |
|                |                  |           | 134  | 5670        |                     |              |                        |         |                   |
|                | 802.11ac (VHT80) | MCS8      | 106  | 5530        |                     |              | 8                      | 8       | No                |
|                |                  |           | 122  | 5610        |                     |              |                        |         |                   |
| 5.8 (U-NII 3)  | 802.11a          | 6 Mbps    | 149  | 5745        | 7.68                | 7.52         | 8                      | 8       | Yes               |
|                |                  |           | 157  | 5785        | 7.71                | 7.56         |                        |         |                   |
|                |                  |           | 165  | 5825        | 7.72                | 7.61         |                        |         |                   |
|                | 802.11n (HT20)   | MCS0      | 149  | 5745        | Not Required        | Not Required | 7                      | 7       | No                |
|                |                  |           | 157  | 5785        |                     |              |                        |         |                   |
|                |                  |           | 165  | 5825        |                     |              |                        |         |                   |
|                | 802.11n (HT40)   | MCS0      | 151  | 5755        |                     |              | 7                      | 7       | No                |
|                |                  |           | 159  | 5795        |                     |              |                        |         |                   |
|                | 802.11ac (VHT80) | MCS8      | 155  | 5775        |                     |              | 7                      | 7       | No                |

**MIMO Measured Results**

| Band (GHz)        | Mode                | Data Rate | Ch # | Freq. (MHz) | Meas. Avg Pwr (dBm) |              | Total Power (dBm) | Max Output Power (dBm) | SAR Test (Yes/No) |
|-------------------|---------------------|-----------|------|-------------|---------------------|--------------|-------------------|------------------------|-------------------|
|                   |                     |           |      |             | Chain 0             | Chain 1      |                   |                        |                   |
| 5.2<br>(U-NII 1)  | 802.11n<br>(HT20)   | MCS0      | 36   | 5180        | 8.63                | 8.56         | 11.61             | 12                     | No                |
|                   |                     |           | 40   | 5200        | 8.72                | 8.68         | 11.71             |                        |                   |
|                   |                     |           | 44   | 5220        | 8.76                | 8.73         | 11.76             |                        |                   |
|                   |                     |           | 48   | 5240        | 8.79                | 8.70         | 11.76             |                        |                   |
|                   | 802.11n<br>(HT40)   | MCS0      | 38   | 5190        | Not Required        | Not Required | Not Required      | 11                     | No                |
|                   |                     |           | 46   | 5230        |                     |              |                   | 11                     | No                |
|                   | 802.11ac<br>(VHT80) | MCS8      | 42   | 5210        |                     |              |                   | 11                     | No                |
| 5.3<br>(U-NII 2A) | 802.11n<br>(HT20)   | MCS0      | 52   | 5260        | 8.96                | 8.90         | 11.94             | 12                     | Yes               |
|                   |                     |           | 56   | 5280        | 8.98                | 8.94         | 11.97             |                        |                   |
|                   |                     |           | 60   | 5300        | 8.85                | 8.75         | 11.81             |                        |                   |
|                   |                     |           | 64   | 5320        | 8.61                | 8.58         | 11.61             |                        |                   |
|                   | 802.11n<br>(HT40)   | MCS0      | 54   | 5270        | Not Required        | Not Required | Not Required      | 11                     | No                |
|                   |                     |           | 62   | 5310        |                     |              |                   | 11                     | No                |
|                   | 802.11ac<br>(VHT80) | MCS8      | 58   | 5290        |                     |              |                   | 11                     | No                |
| 5.5<br>(U-NII 2C) | 802.11n<br>(HT20)   | MCS0      | 100  | 5500        | 8.89                | 8.77         | 11.84             | 12                     | Yes               |
|                   |                     |           | 116  | 5580        | 8.70                | 8.90         | 11.81             |                        |                   |
|                   |                     |           | 140  | 5700        | 8.96                | 8.60         | 11.79             |                        |                   |
|                   | 802.11n<br>(HT40)   | MCS0      | 102  | 5510        | Not Required        | Not Required | Not Required      | 11                     | No                |
|                   |                     |           | 110  | 5550        |                     |              |                   | 11                     | No                |
|                   |                     |           | 134  | 5670        |                     |              |                   | 11                     | No                |
|                   | 802.11ac<br>(VHT80) | MCS8      | 106  | 5530        |                     |              |                   | 11                     | No                |
|                   |                     |           | 122  | 5610        |                     |              |                   | 11                     | No                |
| 5.8<br>(U-NII 3)  | 802.11n<br>(HT20)   | MCS0      | 149  | 5745        | Not Required        | Not Required | Not Required      | 10                     | No                |
|                   |                     |           | 157  | 5785        |                     |              |                   | 10                     | No                |
|                   |                     |           | 165  | 5825        |                     |              |                   | 10                     | No                |
|                   | 802.11n<br>(HT40)   | MCS0      | 151  | 5755        | Not Required        | Not Required | Not Required      | 10                     | No                |
|                   |                     |           | 159  | 5795        |                     |              |                   | 10                     | No                |
|                   | 802.11ac<br>(VHT80) | MCS8      | 155  | 5775        | 6.84                | 6.73         | 9.80              | 10                     | Yes               |

### 13.3 Bluetooth.

#### Average Power Measured Results


| Band (GHz) | Mode        | Ch # | Freq. (MHz) | Meas. Avg Pwr (dBm) | Max Output Power (dBm) | SAR Test (Yes/No) |
|------------|-------------|------|-------------|---------------------|------------------------|-------------------|
| 2.4        | GFSK        | 0    | 2402        | 3.93                | 4                      | No                |
|            |             | 39   | 2441        | 3.59                |                        |                   |
|            |             | 78   | 2480        | 3.56                |                        |                   |
|            | EDR, 8-DPSK | 0    | 2402        | 3.67                | 4                      | No                |
|            |             | 39   | 2441        | 3.72                |                        |                   |
|            |             | 78   | 2480        | 3.54                |                        |                   |
|            | LE, GFSK    | 0    | 2402        | 3.99                | 4                      | No                |
|            |             | 19   | 2440        | 3.73                |                        |                   |
|            |             | 39   | 2480        | 3.56                |                        |                   |

#### Duty Factor Measured Results

| Mode | Type  | T on (ms) | Period (ms) | Duty Cycle | Crest Factor (1/duty cycle) |
|------|-------|-----------|-------------|------------|-----------------------------|
| GFSK | DH5   | 2.88      | 3.75        | 76.80%     | 1.30                        |
| 8PSK | 3-DH5 | 2.88      | 3.75        | 76.80%     | 1.30                        |

## Duty Cycle plots

GFSK



## 14 Measured and Reported (Scaled) SAR Results

SAR Test Reduction criteria are as follows:

### KDB 447498 D01 General RF Exposure Guidance:

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- $\leq 0.8$  W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
- $\leq 0.6$  W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- $\leq 0.4$  W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz

### KDB 248227 D01 SAR meas for 802.11:

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the initial test position(s) by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The initial test position(s) is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the reported SAR for the initial test position is:

- $\leq 0.4$  W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to the required SAR procedures.
- $> 0.4$  W/kg, SAR is repeated using the same wireless mode test configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the reported SAR is  $\leq 0.8$  W/kg or all required test positions are tested.
  - o For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
  - o When it is unclear, all equivalent conditions must be tested.
- For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is  $> 0.8$  W/kg, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is  $\leq 1.2$  W/kg or all required test channels are considered.
  - o The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.
- When the specified maximum output power is the same for both UNII 1 and UNII 2A, begin SAR measurements in UNII 2A with the channel with the highest measured output power. If the reported SAR for UNII 2A is  $\leq 1.2$  W/kg, SAR is not required for UNII 1; otherwise treat the remaining bands separately and test them independently for SAR.
- When the specified maximum output power is different between UNII 1 and UNII 2A, begin SAR with the band that has the higher specified maximum output. If the highest reported SAR for the band with the highest specified power is  $\leq 1.2$  W/kg, testing for the band with the lower specified output power is not required; otherwise test the remaining bands independently for SAR.

To determine the initial test position, Area Scans were performed to determine the position with the *Maximum Value of SAR (measured)*. The position that produced the highest *Maximum Value of SAR* is considered the worst case position; thus used as the initial test position.

**14.1. Wi-Fi (DTS Band)**

| Mode           | Antenna             | Dist. (mm) | Test Position | Ch #. | Freq. (MHz) | Duty Cycle | Power (dBm)   |       | 1-g SAR (W/kg) |              | Plot No. |
|----------------|---------------------|------------|---------------|-------|-------------|------------|---------------|-------|----------------|--------------|----------|
|                |                     |            |               |       |             |            | Tune-up Limit | Meas. | Meas.          | Scaled       |          |
| 802.11b        | SISO Main 0         | 0          | Rear          | 1     | 2412        | 100.0%     | 12.0          | 11.72 | 0.592          | <b>0.631</b> | 1        |
|                |                     |            | Edge 2        | 1     | 2412        | 100.0%     | 12.0          | 11.72 | 0.404          | 0.431        |          |
| 802.11b        | SISO Aux 1          | 0          | Rear          | 6     | 2437        | 100.0%     | 12.0          | 11.63 | 0.524          | <b>0.571</b> | 2        |
|                |                     |            | Edge 2        | 6     | 2437        | 100.0%     | 12.0          | 11.63 | 0.197          | 0.215        |          |
| 802.11n (HT20) | MIMO (Main+Aux) 0+1 | 0          | Rear          | 1     | 2412        | 100.0%     | 15.0          | 14.71 | 0.742          | <b>0.794</b> | 3        |
|                |                     |            | Edge 2        | 1     | 2412        | 100.0%     | 15.0          | 14.71 | 0.577          | 0.618        |          |

**14.2. WI-FI (U-NII BAND)**

| Frequency Band | Mode            | Antenna             | Dist. (mm) | Test Position | Ch #. | Freq. (MHz) | Duty Cycle | Power (dBm)   |       | 1-g SAR (W/kg) |              | Plot No. |
|----------------|-----------------|---------------------|------------|---------------|-------|-------------|------------|---------------|-------|----------------|--------------|----------|
|                |                 |                     |            |               |       |             |            | Tune-up Limit | Meas. | Meas.          | Scaled       |          |
| 5.3 (U-NII 2A) | 802.11a         | SISO Main 0         | 0          | Rear          | 56    | 5280        | 100.0%     | 9.0           | 8.98  | 0.450          | <b>0.452</b> | 4        |
|                |                 |                     |            | Edge 2        | 56    | 5280        | 100.0%     | 9.0           | 8.98  | 0.357          | 0.359        |          |
|                | 802.11a         | SISO Aux 1          | 0          | Rear          | 56    | 5280        | 100.0%     | 9.0           | 8.86  | 0.735          | <b>0.759</b> | 5        |
|                |                 |                     |            | Edge 2        | 56    | 5280        | 100.0%     | 9.0           | 8.86  | 0.338          | 0.349        |          |
|                | 802.11n (HT20)  | MIMO (Main+Aux) 0+1 | 0          | Rear          | 52    | 5260        | 100.0%     | 12.0          | 11.94 | 0.790          | 0.801        |          |
|                |                 |                     |            | Rear          | 56    | 5280        | 100.0%     | 12.0          | 11.97 | 0.927          | <b>0.933</b> | 6        |
|                |                 |                     |            | Edge 2        | 56    | 5280        | 100.0%     | 12.0          | 11.97 | 0.497          | 0.500        |          |
| Frequency Band | Mode            | Antenna             | Dist. (mm) | Test Position | Ch #. | Freq. (MHz) | Duty Cycle | Power (dBm)   |       | 1-g SAR (W/kg) |              | Plot No. |
|                |                 |                     |            |               |       |             |            | Tune-up Limit | Meas. | Meas.          | Scaled       |          |
| 5.5 (U-NII 2C) | 802.11a         | SISO Main 0         | 0          | Rear          | 140   | 5700        | 100.0%     | 9.0           | 8.86  | 0.670          | <b>0.692</b> | 7        |
|                |                 |                     |            | Edge 2        | 140   | 5700        | 100.0%     | 9.0           | 8.86  | 0.459          | 0.474        |          |
|                | 802.11a         | SISO Aux 1          | 0          | Rear          | 116   | 5580        | 100.0%     | 9.0           | 8.58  | 0.706          | 0.778        |          |
|                |                 |                     |            | Rear          | 140   | 5700        | 100.0%     | 9.0           | 8.59  | 0.925          | <b>1.017</b> | 8        |
|                | 802.11n (HT20)  | MIMO (Main+Aux) 0+1 | 0          | Rear          | 100   | 5500        | 100.0%     | 12.0          | 11.84 | 1.120          | <b>1.162</b> | 9        |
|                |                 |                     |            | Rear          | 140   | 5700        | 100.0%     | 12.0          | 11.79 | 1.000          | 1.049        |          |
|                |                 |                     |            | Edge 2        | 100   | 5500        | 100.0%     | 12.0          | 11.84 | 0.421          | 0.437        |          |
| Frequency Band | Mode            | Antenna             | Dist. (mm) | Test Position | Ch #. | Freq. (MHz) | Duty Cycle | Power (dBm)   |       | 1-g SAR (W/kg) |              | Plot No. |
|                |                 |                     |            |               |       |             |            | Tune-up Limit | Meas. | Meas.          | Scaled       |          |
| 5.8 (U-NII 3)  | 802.11n (VHT80) | MIMO (Main+Aux) 0+1 | 0          | Rear          | 155   | 5775        | 100.0%     | 10.0          | 9.80  | 0.670          | <b>0.702</b> | 10       |
|                |                 |                     | 0          | Edge 2        | 155   | 5775        | 100.0%     | 10.0          | 9.80  | 0.425          | 0.445        |          |

## 15 SAR Measurement Variability

In accordance with published RF Exposure KDB 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.8$  or  $2$  W/kg (1-g or 10-g respectively); steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.8$  or  $2$  W/kg (1-g or 10-g respectively), repeat that measurement once.
- 3) Perform a second repeated measurement only if the **ratio of largest to smallest SAR** for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  or  $3.6$  W/kg ( $\sim 10\%$  from the 1-g or 10-g respective SAR limit).
- 4) Perform a third repeated measurement only if the original, first, or second repeated measurement is  $\geq 1.5$  or  $3.75$  W/kg (1-g or 10-g respectively) and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

| Mode           | Antenna             | Dist. (mm) | Test Position | Ch #. | Freq. (MHz) | Duty Cycle | Meas. SAR (W/kg) |          | Largest to Smallest SAR Ratio |
|----------------|---------------------|------------|---------------|-------|-------------|------------|------------------|----------|-------------------------------|
|                |                     |            |               |       |             |            | Original         | Repeated |                               |
| 802.11n (HT20) | MIMO (Main+Aux) 0+1 | 0          | Rear          | 56    | 5280        | 100        | 0.927            | 0.995    | 1.07                          |
| 802.11a        | SISO Aux 1          | 0          | Rear          | 140   | 5700        | 100        | 0.925            | 0.918    | 1.01                          |
| 802.11n (HT20) | MIMO (Main+Aux) 0+1 | 0          | Rear          | 100   | 5500        | 100        | 1.120            | 1.130    | 1.01                          |

### Note(s):

Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is  $< 1.20$ .

## 16 Simultaneous Transmission SAR Analysis

KDB 447498 D01 General RF Exposure Guidance explains how to calculate the SAR to Peak Location Ratio (SPLSR) between pairs of simultaneously transmitting antennas:

$$\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / R_i$$

Where:

**SAR<sub>1</sub>** is the highest measured or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

**SAR<sub>2</sub>** is the highest measured or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

**R<sub>i</sub>** is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured, for both antennas in the pair, it is determined by the actual x, y and z coordinates in the 1-g SAR for each SAR peak location, based on the extrapolated and interpolated result in the zoom scan measurement, using the formula of  $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$

In order for a pair of simultaneous transmitting antennas with the sum of 1-g SAR > 1.6 W/kg to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$(\text{SAR}_1 + \text{SAR}_2)^{1.5} / R_i \leq 0.04$$

### Simultaneous Transmission Condition

| RF Exposure Condition                                             | Item | Capable Transmit Configurations |              |
|-------------------------------------------------------------------|------|---------------------------------|--------------|
| Standalone                                                        | 1    | WLAN 2.4G_Main Ant              | + BT_Aux Ant |
|                                                                   | 2    | WLAN 5G_Main Ant                | + BT_Aux Ant |
|                                                                   | 3    | WLAN 2.4G_MIMO                  | + BT_Aux Ant |
|                                                                   | 4    | WLAN 5G_MIMO                    | + BT_Aux Ant |
| Notes:                                                            |      |                                 |              |
| 1. DTS Radio cannot transmit simultaneously with Bluetooth Radio. |      |                                 |              |
| 2. U-NII Radio can transmit simultaneously with Bluetooth Radio.  |      |                                 |              |

### Estimated SAR for Simultaneous Transmission SAR Analysis Considerations for SAR estimation

1. When standalone SAR test exclusion applies, standalone SAR must also be estimated to determine simultaneous transmission SAR test exclusion.
2. Dedicated Host Approach criteria for SAR test exclusion is likewise applied to SAR estimation, with certain distinctions between test exclusion and SAR estimation:
  - o When the separation distance from the antenna to an adjacent edge is  $\leq 5$  mm, a distance of 5 mm is applied for SAR estimation; this is the same between test exclusion and SAR estimation calculations.
  - o When the separation distance from the antenna to an adjacent edge is  $> 5$  mm but  $\leq 50$  mm, the actual antenna-to-edge separation distance is applied for SAR estimation.
  - o When the minimum test separation distance is  $> 50$  mm, the estimated SAR value is 0.4 W/kg
3. Please refer to [Estimated SAR Tables](#) to see which test positions are inherently compliant as they consist of only estimated SAR values for all applicable transmitters and consequently will always have sum of SAR values  $< 1.2$  W/kg. Simultaneous transmission SAR analysis was therefore not performed for these test positions.

### Estimated SAR for WLAN

| Tx Interface  | Output Power |    | Separation Distances (mm) |        |        |        |        | Estimated 1-g SAR Value (W/kg) |        |           |        |        |
|---------------|--------------|----|---------------------------|--------|--------|--------|--------|--------------------------------|--------|-----------|--------|--------|
|               | dBm          | mW | Rear                      | Edge 1 | Edge 2 | Edge 3 | Edge 4 | Rear                           | Edge 1 | Edge 2    | Edge 3 | Edge 4 |
| Main Antenna  |              |    |                           |        |        |        |        |                                |        |           |        |        |
| Wi-Fi 2.4 GHz | 12.00        | 16 | 5                         | 31.1   | 5      | 119.1  | 228.8  | -MEASURE-                      | 0.108  | -MEASURE- | 0.400  | 0.400  |
| Wi-Fi 5.2 GHz | 9.00         | 8  | 5                         | 31.1   | 5      | 119.1  | 228.8  | -MEASURE-                      | 0.079  | -MEASURE- | 0.400  | 0.400  |
| Wi-Fi 5.3 GHz | 9.00         | 8  | 5                         | 31.1   | 5      | 119.1  | 228.8  | -MEASURE-                      | 0.079  | -MEASURE- | 0.400  | 0.400  |
| Wi-Fi 5.5 GHz | 9.00         | 8  | 5                         | 31.1   | 5      | 119.1  | 228.8  | -MEASURE-                      | 0.082  | -MEASURE- | 0.400  | 0.400  |
| Wi-Fi 5.8 GHz | 8.00         | 6  | 5                         | 31.1   | 5      | 119.1  | 228.8  | 0.386                          | 0.062  | 0.386     | 0.400  | 0.400  |
| Aux Antenna   |              |    |                           |        |        |        |        |                                |        |           |        |        |
| Wi-Fi 2.4 GHz | 12.00        | 16 | 5                         | 105.3  | 5      | 47.9   | 229.2  | -MEASURE-                      | 0.400  | -MEASURE- | 0.070  | 0.400  |
| Wi-Fi 5.2 GHz | 9.00         | 8  | 5                         | 105.3  | 5      | 47.9   | 229.2  | -MEASURE-                      | 0.400  | -MEASURE- | 0.051  | 0.400  |
| Wi-Fi 5.3 GHz | 9.00         | 8  | 5                         | 105.3  | 5      | 47.9   | 229.2  | -MEASURE-                      | 0.400  | -MEASURE- | 0.051  | 0.400  |
| Wi-Fi 5.5 GHz | 9.00         | 8  | 5                         | 105.3  | 5      | 47.9   | 229.2  | -MEASURE-                      | 0.400  | -MEASURE- | 0.053  | 0.400  |
| Wi-Fi 5.8 GHz | 8.00         | 6  | 5                         | 105.3  | 5      | 47.9   | 229.2  | 0.386                          | 0.400  | 0.386     | 0.040  | 0.400  |
| Bluetooth     | 4.00         | 3  | 5                         | 105.3  | 5      | 47.9   | 229.2  | 0.126                          | 0.400  | 0.126     | 0.013  | 0.400  |
| MIMO          |              |    |                           |        |        |        |        |                                |        |           |        |        |
| Wi-Fi 2.4 GHz | 15.00        | 32 | 5                         | 31.1   | 5      | 47.9   | 228.8  | -MEASURE-                      | 0.216  | -MEASURE- | 0.139  | 0.400  |
| Wi-Fi 5.2 GHz | 12.00        | 16 | 5                         | 31.1   | 5      | 47.9   | 228.8  | -MEASURE-                      | 0.158  | -MEASURE- | 0.102  | 0.400  |
| Wi-Fi 5.3 GHz | 12.00        | 16 | 5                         | 31.1   | 5      | 47.9   | 228.8  | -MEASURE-                      | 0.159  | -MEASURE- | 0.103  | 0.400  |
| Wi-Fi 5.5 GHz | 12.00        | 16 | 5                         | 31.1   | 5      | 47.9   | 228.8  | -MEASURE-                      | 0.164  | -MEASURE- | 0.106  | 0.400  |
| Wi-Fi 5.8 GHz | 10.00        | 10 | 5                         | 31.1   | 5      | 47.9   | 228.8  | -MEASURE-                      | 0.104  | -MEASURE- | 0.067  | 0.400  |

### 16.1 Sum of the SAR for Wi-Fi 2.4G\_Main Ant & BT

| Test Position | Standalone SAR (W/kg) |         | $\sum$ 1-g SAR (W/kg) |
|---------------|-----------------------|---------|-----------------------|
|               | DTS<br>①              | BT<br>② | DTS + BT<br>① + ②     |
| Rear          | 0.631                 | 0.126   | 0.757                 |
| Edge 1        | 0.108                 | 0.400   | 0.508                 |
| Edge 2        | 0.431                 | 0.126   | 0.557                 |
| Edge 3        | 0.400                 | 0.013   | 0.413                 |
| Edge 4        | 0.400                 | 0.400   | 0.800                 |

### 16.2 Sum of the SAR for Wi-Fi 5G\_Main Ant & BT

| Test Position | Standalone SAR (W/kg) |         | $\sum$ 1-g SAR (W/kg) |
|---------------|-----------------------|---------|-----------------------|
|               | U-NII<br>①            | BT<br>② | U-NII + BT<br>① + ②   |
| Rear          | 0.692                 | 0.126   | 0.818                 |
| Edge 1        | 0.082                 | 0.400   | 0.482                 |
| Edge 2        | 0.474                 | 0.126   | 0.600                 |
| Edge 3        | 0.400                 | 0.013   | 0.413                 |
| Edge 4        | 0.400                 | 0.400   | 0.800                 |

### 16.3 Sum of the SAR for Wi-Fi 2.4G\_MIMO & BT

| Test Position | Standalone SAR (W/kg) |         | $\sum$ 1-g SAR (W/kg) |
|---------------|-----------------------|---------|-----------------------|
|               | DTS<br>①              | BT<br>② | DTS + BT<br>① + ②     |
| Rear          | 0.794                 | 0.126   | 0.920                 |
| Edge 1        | 0.216                 | 0.400   | 0.616                 |
| Edge 2        | 0.618                 | 0.126   | 0.744                 |
| Edge 3        | 0.139                 | 0.013   | 0.152                 |
| Edge 4        | 0.400                 | 0.400   | 0.800                 |

### 16.4 Sum of the SAR for Wi-Fi 5G\_MIMO & BT

| Test Position | Standalone SAR (W/kg) |         | $\sum$ 1-g SAR (W/kg) |
|---------------|-----------------------|---------|-----------------------|
|               | U-NII<br>①            | BT<br>② | U-NII + BT<br>① + ②   |
| Rear          | 1.162                 | 0.126   | 1.288                 |
| Edge 1        | 0.164                 | 0.400   | 0.564                 |
| Edge 2        | 0.500                 | 0.126   | 0.626                 |
| Edge 3        | 0.106                 | 0.013   | 0.119                 |
| Edge 4        | 0.400                 | 0.400   | 0.800                 |

### Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because either the sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

## 17 Equipment List & Calibration Status

| <b>Dielectric Property Measurements</b> |              |            |            |               |
|-----------------------------------------|--------------|------------|------------|---------------|
| Name of Equipment                       | Manufacturer | Type/Model | Serial No. | Cal. Due Date |
| Network Analyzer                        | Anritsu      | MS46322B   | 1740002    | 2021/1/1      |
| Dielectric Assessment Kit               | SPEAG        | DAK-3.5    | 1053       | 2021/1/27     |
| Thermometer                             | DER EE       | DE-3003    | P0006880   | 2020/12/19    |

| <b>System Check</b>          |              |            |            |               |
|------------------------------|--------------|------------|------------|---------------|
| Name of Equipment            | Manufacturer | Type/Model | Serial No. | Cal. Due Date |
| MXG Analog Signal Generator  | Agilent      | N5181A     | MY50141235 | 2021/5/3      |
| Power Meter                  | Agilent      | E4417A     | MY51410006 | 2021/3/8      |
| Power Sensor                 | Agilent      | E9301H     | MY51470001 | 2021/3/8      |
| Power Sensor                 | Agilent      | E9301H     | MY51470002 | 2021/3/8      |
| Dual Directional Coupler     | Agilent      | 772D       | MY46151242 | 2021/8/16     |
| Amplifier                    | EMCI         | ZVE-8G     | 980190     | N/A           |
| Dosimetric E-Field Probe     | SPEAG        | EX3DV4     | 3665       | 2021/8/19     |
| Data Acquisition Electronics | SPEAG        | DAE4       | 914        | 2021/6/22     |
| System Validation Dipole     | SPEAG        | D2450V2    | 727        | 2021/4/21     |
| System Validation Dipole     | SPEAG        | D5GHzV2    | 1023       | 2021/1/28     |
| Humidity/Temp meter          | TECPEL       | DTM-303A   | TP130074   | 2021/4/9      |
| Thermometer                  | DER EE       | DE-3003    | P0006880   | 2020/12/19    |

| <b>Software Version</b>   |  |
|---------------------------|--|
| DASY NEO52 D10.3 S14.6.13 |  |
| SEMCAD-X-PostPro          |  |

## 18 Facilities

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

## 19 Reference

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-2005: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 2006.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard Kuhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10

## 20 Attachments

| Exhibit | Content                          |
|---------|----------------------------------|
| 1       | System Performance Check Plots   |
| 2       | SAR Test Data Plots              |
| 3       | SAR Equipment calibration report |
| 4       | T201104D06-SF PHOTOS             |

**END OF REPORT**