

Appendix Test Data for BT(BDR/EDR) (Conducted Measurement)

Product Name: LED WIRELESS SPEAKERS

Trade Mark: 2BOOM, FISHER, CRAYOLA

Test Model: BT248

FCC ID: 2AIDL-BT248

Environmental Conditions

Temperature:	22.5
Relative Humidity:	56%
ATM Pressure:	100.0 kPa
Test Engineer:	Tony lu
Supervised by:	Max zhang
NOTE	N/A

1. Bandwidth

1.1 Test Result


1.1.1 OBW


Mode	TX Type	Frequency (MHz)	Packet Type	ANT	99% Occupied Bandwidth (MHz)		Verdict
					Result	Limit	
GFSK	SISO	2402	DH5	1	0.922	/	Pass
		2441	DH5	1	0.942	/	Pass
		2480	DH5	1	0.953	/	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	1.200	/	Pass
		2441	2DH5	1	1.213	/	Pass
		2480	2DH5	1	1.222	/	Pass
8DPSK	SISO	2402	3DH5	1	1.214	/	Pass
		2441	3DH5	1	1.217	/	Pass
		2480	3DH5	1	1.219	/	Pass


1.1.2 20dB BW


Mode	TX Type	Frequency (MHz)	Packet Type	ANT	20dB Bandwidth (MHz)		Verdict
					Result	Limit	
GFSK	SISO	2402	DH5	1	1.037	/	Pass
		2441	DH5	1	1.062	/	Pass
		2480	DH5	1	1.049	/	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	1.329	/	Pass
		2441	2DH5	1	1.336	/	Pass
		2480	2DH5	1	1.341	/	Pass
8DPSK	SISO	2402	3DH5	1	1.319	/	Pass
		2441	3DH5	1	1.320	/	Pass
		2480	3DH5	1	1.314	/	Pass


1.2 Test Graph
1.2.1 OBW
















1.2.2 20dB BW












2. Maximum Conducted Output Power


2.1 Test Result


2.1.1 Power


Mode	TX Type	Frequency (MHz)	Packet Type	Maximum Peak Conducted Output Power (dBm)		Verdict
				ANT1	Limit	
GFSK	SISO	2402	DH5	1.44	<=20.97	Pass
		2441	DH5	1.26	<=20.97	Pass
		2480	DH5	1.03	<=20.97	Pass
Pi/4DQPSK	SISO	2402	2DH5	2.06	<=20.97	Pass
		2441	2DH5	2.01	<=20.97	Pass
		2480	2DH5	1.79	<=20.97	Pass
8DPSK	SISO	2402	3DH5	2.25	<=20.97	Pass
		2441	3DH5	2.21	<=20.97	Pass
		2480	3DH5	2.03	<=20.97	Pass
Note1: Antenna Gain: Ant1: -0.48dBi;						


2.2 Test Graph
2.2.1 Power












3. Carrier Frequency Separation


3.1 Test Result

3.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	Packet Type	Channel Separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz)	Verdict
GFSK	SISO	HOPP	DH5	1.010	1.062	>=0.708	Pass
Pi/4DQPSK	SISO	HOPP	2DH5	0.986	1.341	>=0.894	Pass
8DPSK	SISO	HOPP	3DH5	1.003	1.320	>=0.88	Pass

3.2 Test Graph
3.2.1 Ant1





4. Number of Hopping Frequencies


4.1 Test Result


4.1.1 HoppNum

Mode	TX Type	Frequency (MHz)	Packet Type	Num of Hopping Frequencies		Verdict
				ANT1	Limit	
GFSK	SISO	HOPP	DH5	79	>=15	Pass
Pi/4DQPSK	SISO	HOPP	2DH5	79	>=15	Pass
8DPSK	SISO	HOPP	3DH5	79	>=15	Pass

4.2 Test Graph

4.2.1 HoppNum






5. Time of Occupancy (Dwell Time)


5.1 Test Result


5.1.1 Ant1


Ant1									
Mode	TX Type	Frequency (MHz)	Packet Type	Duration of Single Pulse (ms)	Observation Period (s)	Num of Pulse in Observation Period	Dwell Time (ms)	Limit (ms)	Verdict
GFSK	SISO	HOPP	DH1	0.380	31.600	317	120.460	<=400	Pass
			DH3	1.644	31.600	159	261.396	<=400	Pass
			DH5	2.890	31.600	97	280.330	<=400	Pass
Pi/4DQPSK	SISO	HOPP	2DH1	0.390	31.600	318	124.020	<=400	Pass
			2DH3	1.646	31.600	157	258.422	<=400	Pass
			2DH5	2.890	31.600	114	329.460	<=400	Pass
8DPSK	SISO	HOPP	3DH1	0.393	31.600	317	124.581	<=400	Pass
			3DH3	1.641	31.600	167	274.047	<=400	Pass
			3DH5	2.890	31.600	115	332.350	<=400	Pass


5.2 Test Graph
5.2.1 Ant1























6. Unwanted Emissions In Non-restricted Frequency Bands

6.1 Test Result

6.1.1 Ref


Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)
GFSK	SISO	2402	DH5	1	1.17
		2441	DH5	1	0.94
		2480	DH5	1	0.66
Pi/4DQPSK	SISO	2402	2DH5	1	1.09
		2441	2DH5	1	0.97
		2480	2DH5	1	0.65
8DPSK	SISO	2402	3DH5	1	1.05
		2441	3DH5	1	0.87
		2480	3DH5	1	0.40


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.


6.1.2 CSE


Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
GFSK	SISO	2402	DH5	1	1.17	-18.83	Pass
		2441	DH5	1	1.17	-18.83	Pass
		2480	DH5	1	1.17	-18.83	Pass
		HOPP	DH5	1	1.17	-18.83	Pass
					1.17	-18.83	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	1.09	-18.91	Pass
		2441	2DH5	1	1.09	-18.91	Pass
		2480	2DH5	1	1.09	-18.91	Pass
		HOPP	2DH5	1	1.09	-18.91	Pass
					1.09	-18.91	Pass
8DPSK	SISO	2402	3DH5	1	1.05	-18.95	Pass
		2441	3DH5	1	1.05	-18.95	Pass
		2480	3DH5	1	1.05	-18.95	Pass
		HOPP	3DH5	1	1.05	-18.95	Pass
					1.05	-18.95	Pass
Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.							


6.2 Test Graph
6.2.1 Ref











6.2.2 CSE

