

FCC RF EXPOSURE REPORT

FCC ID: ATL-TSBOOM

Project No. : 1605C238
Equipment : JUMBO LED Alarm Clock with wireless Shaker
Model : TimeShaker Boom, TSBOOMzzyy (zz=power
version, yy=color version)
Applicant : iLuv Creative Technology
Address : 2 Harbor Park Drive, Port Washington, NY
11050, USA

According: : FCC Guidelines for Human Exposure IEEE
C95.1

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Internal	N/A	0

GENERAL CONCLUSION:

Maximum measured transmitter power:

Field Strength (dBuV/m)	OutputPower (dBm)	Output Power (mW)	Limit (mW)
39.88	-55.42	0.0000	22

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 0.0000mW, less than 22mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold