



8DPSK Transmitting Band edge-left side




Date: 23.DEC.2021 09:44:15

8DPSK Hopping Band edge-left side




Date: 23.DEC.2021 09:54:38

8DPSK Transmitting Band edge-right side



Date: 23.DEC.2021 10:02:52

8DPSK Hopping Band edge-right side



Date: 23.DEC.2021 09:56:09

10. 20 DB Bandwidth

10.1 Block Diagram Of Test Setup



10.2 Limit

N/A

10.3 Test Procedure


1. Set RBW = 30kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission. .

10.4 Test Result


Temperature :	26°C	Relative Humidity :	54%
Test Voltage :	DC 3.85V	Remark	N/A

Modulation	Test Channel	Bandwidth(MHz)
GFSK	Low	0.870
GFSK	Middle	0.894
GFSK	High	0.894
$\pi/4$ DQPSK	Low	1.224
$\pi/4$ DQPSK	Middle	1.224
$\pi/4$ DQPSK	High	1.206
8DPSK	Low	1.218
8DPSK	Middle	1.218
8DPSK	High	1.218


Test plots



Date: 23.DEC.2021 09:00:43




Date: 23.DEC.2021 08:59:57




Date: 23.DEC.2021 08:57:26

$\pi/4$ DQPSK Low Channel




Date: 23.DEC.2021 09:01:18

$\pi/4$ DQPSK Middle Channel




Date: 23.DEC.2021 08:59:35

$\pi/4$ DQPSK High Channel




Date: 23.DEC.2021 08:58:01

8DPSK Low Channel




Date: 23.DEC.2021 09:01:42

8DPSK Middle Channel



Date: 23.DEC.2021 08:59:02


8DPSK High Channel



Date: 23.DEC.2021 08:58:27

11. Maximum Peak Output Power

11.1 Block Diagram Of Test Setup



11.2 Limit

FCC Part15 (15.247), Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1)	Peak Output Power	0.125 watt or 21dBm	2400-2483.5	PASS


11.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3MHz. VBW = 3MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.


11.4 Test Result

Temperature :	26°C	Relative Humidity :	54%
Test Voltage :	DC 3.85V	Remark:	N/A


Modulation	Test Channel	Output Power (dBm)	Limit (dBm)
GFSK	Low	-0.44	21
GFSK	Middle	-1.02	21
GFSK	High	-1.44	21
$\pi/4$ DQPSK	Low	-0.49	21
$\pi/4$ DQPSK	Middle	-1.01	21
$\pi/4$ DQPSK	High	-1.46	21
8DPSK	Low	-0.38	21
8DPSK	Middle	-0.94	21
8DPSK	High	-1.33	21




Date: 23.DEC.2021 08:52:07




Date: 23.DEC.2021 08:49:01




Date: 23.DEC.2021 08:55:54




Date: 23.DEC.2021 08:52:31




Date: 23.DEC.2021 08:48:43




Date: 23.DEC.2021 08:55:33



Date: 23.DEC.2021 08:52:52



Date: 23.DEC.2021 08:48:17



Date: 23.DEC.2021 08:53:25

12. Hopping Channel Separation

12.1 Block Diagram Of Test Setup



12.2 Limit


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 0.125W.

12.3 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 30kHz. VBW = 100kHz , Span = 2.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

12.4 Test Result


Modulation	Test Channel	Separation (MHz)	Limit(MHz)	Result
GFSK	Low	1.000	0.580	PASS
GFSK	Middle	1.000	0.596	PASS
GFSK	High	1.000	0.596	PASS
$\pi/4$ DQPSK	Low	1.000	0.816	PASS
$\pi/4$ DQPSK	Middle	1.000	0.816	PASS
$\pi/4$ DQPSK	High	1.000	0.804	PASS
8DPSK	Low	1.000	0.812	PASS
8DPSK	Middle	1.000	0.812	PASS
8DPSK	High	1.000	0.812	PASS



Date: 23.DEC.2021 11:51:18




Date: 23.DEC.2021 11:49:47




Date: 23.DEC.2021 11:52:04

$\pi/4$ DQPSK Low Channel




Date: 23.DEC.2021 11:54:36


$\pi/4$ DQPSK Middle Channel



Date: 23.DEC.2021 11:53:35




Date: 23.DEC.2021 11:52:53




Date: 23.DEC.2021 11:54:36

8DPSK Middle Channel



Date: 23.DEC.2021 11:53:35

8DPSK High Channel



Date: 23.DEC.2021 11:52:53

13. Number Of Hopping Frequency

13.1 Block Diagram Of Test Setup



13.2 Limit


Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

13.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;


13.4 Test Result

Test Plots: 79 Channels in total GFSK




Date: 23.DEC.2021 10:15:28


$\pi/4$ DQPSK



Date: 23.DEC.2021 10:08:01



Date: 23.DEC.2021 10:05:24



14. Dwell Time

14.1 Block Diagram Of Test Setup



14.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

14.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. Centred on a hopping channel;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

14.4 Test Result

DH5 Packet permit maximum 1600 / 79 / 6 hops per second in each channel (5 time slots RX, 1 time slot TX).

DH3 Packet permit maximum 1600 / 79 / 4 hops per second in each channel (3 time slots TX, 1 time slot TX).

DH1 Packet permit maximum 1600 / 79 / 2 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the Dwell Time can be calculated as follows:


DH5: $1600/79/6 \times 0.4 \times 79 \times (\text{MkrDelta})/1000$

DH3: $1600/79/4 \times 0.4 \times 79 \times (\text{MkrDelta})/1000$


DH1: $1600/79/2 \times 0.4 \times 79 \times (\text{MkrDelta})/1000$

Remark: Mkr Delta is once pulse time.


Modulation	Channel Data	Packet	pulse time(ms)	Dwell Time(s)	Limits(s)
GFSK	Middle	DH1	0.372	0.119	0.4
		DH3	1.640	0.262	0.4
		DH5	2.888	0.308	0.4
$\pi/4$ DQPSK	Middle	2DH1	0.376	0.120	0.4
		2DH3	1.640	0.262	0.4
		2DH5	2.888	0.308	0.4
8DPSK	Middle	3DH1	0.380	0.122	0.4
		3DH3	1.640	0.262	0.4
		3DH5	2.888	0.308	0.4




Date: 23.DEC.2021 13:38:07




Date: 23.DEC.2021 13:41:40




Date: 23.DEC.2021 13:42:14




Date: 23.DEC.2021 13:38:52




Date: 23.DEC.2021 13:41:07




Date: 23.DEC.2021 13:42:43



Date: 23.DEC.2021 13:39:45



Date: 23.DEC.2021 13:40:34



Date: 23.DEC.2021 13:43:37


15. Antenna Requirement

15.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.2 Test Result

The EUT antenna is FPC antenna, fulfill the requirement of this section.



16. EUT Photographs

EUT Photo 1



EUT Photo 2





17. EUT Test Setup Photographs

Conducted Measurement Photos



Radiated Measurement Photos





STATEMENT

- 1.The equipment lists are traceable to the national reference standards.
- 2.The test report can not be partially copied unless prior written approval is issued from our lab.
- 3.The test report is invalid without stamp of laboratory.
- 4.The test report is invalid without signature of person(s) testing and authorizing.
- 5.The test process and test result is only related to the Unit Under Test.
- 6.The quality system of our laboratory is in accordance with ISO/IEC17025.
- 7.If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

E-Mail: bctc@bctc-lab.com.cn

***** END *****