




Z (m m) SA R (W/ Kg)	0.00 0.37 35	4.00 0.12 46	6.00 0.06 50	8.00 0.02 38	10.0 0 0.02 36	12.0 0 0.01 72	14.0 0 0.01 82	16.0 0 0.01 82	18.0 0 0.01 99	20.0 0 0.02 14	22.0 0 0.01 85	24.0 0 0.02 22
		0.3° 0.30 0.20 0.20 0.10 0.00 0.00	5-	4 6	8	10 12 Z G	14 16	18 20) 22 2	4 26		





Page 364 of 397

Test Laboratory: AGC Lab Date: Jul. 02, 2022

802.11a -CH116-Mid -Edge2

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: Wi-Fi; Communication System Band: 802.11a; Duty Cycle: 1:1; Conv.F=1.52; Frequency: 5580MHz; Medium parameters used: f = 5600 MHz; $\sigma = 5.23 mho/m$; $\epsilon r = 36.32$; $\rho = 1000 kg/m^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$ C): 21.4, Liquid temperature ($^{\circ}$ C): 21.3

SATIMO Configuration:

• Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

Measurement SW: OpenSAR V4 02 35

Configuration/ 802.11a -CH116-Mid – Edge2 /Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ 802.11a -CH116-Mid – Edge2 /Zoom Scan: Measurement grid: dx=4mm,dy=4mm, dz=2mm

Area Scan	sam_direct_droit2_surf8mm.txt			
ZoomScan	7x7x12 dx=4mm dy=4mm dz=2mm			
Phantom	ELLI			
Device Position	Edge2			
Band	5600MHz			
Channels	Middle			
Signal	Crest factor: 1.0			



Maximum location: X=13.00, Y=61.00


SAR Peak: 0.31 W/kg

SAR 10g (W/Kg)	0.069133
SAR 1g (W/Kg)	0.125072





Z (m m) SA R (W/ Kg)	0.00 0.28 72	0.12 92	6.00 0.07 81	8.00 0.06 02	10.0 0 0.04 99	12.0 0 0.03 29	14.0 0 0.03 82	16.0 0 0.03 58	18.0 0 0.03 68	20.0 0 0.03 39	22.0 0 0.04 71	24.0 0 0.03 88
8		0.29 0.25 0.20 0.15 0.10	5-	4 6	8 1	0 12 Z (m	14 16 m)	18 20	22 2	4 26		





Page 366 of 397

WIFI 5.8GHz MODE

Test Laboratory: AGC Lab Date: Jun. 30, 2022

802.11a-CH157- Mid - Touch-Left

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: Wi-Fi; Communication System Band: 802.11a; Duty Cycle: 1:1; Conv.F=1.42; Frequency: 5785MHz; Medium parameters used: f = 5800 MHz; $\sigma = 5.40 \text{mho/m}$; $\epsilon = 36.35$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$ C): 21.6, Liquid temperature ($^{\circ}$ C): 21.5

SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

· Phantom: SAM twin phantom

• Measurement SW: OpenSAR V4_02_35

Configuration/802.11a-CH157- Mid - Touch-Left /Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/802.11a-CH157- Mid - Touch-Left /Zoom Scan: Measurement grid: dx=4mm,dy=4mm, dz=2mm

Area Scan	dx=8mm dy=8mm, h= 5.00 mm				
ZoomScan	7x7x12 dx=4mm dy=4mm dz=2mm				
Phantom	Left head				
Device Position	Cheek				
Band	5800MHz				
Channels	Middle				
Signal	Crest factor: 1.0				




Maximum location: X=-30.00, Y=25.00 SAR Peak: 0.37 W/kg

SAR 10g (W/Kg)	0.047995				
SAR 1g (W/Kg)	0.123871				





Z (m m) SA R	0.00 0.37 10	4.00 0.11 85	0.02 51	8.00 0.03 13	10.0 0 0.02 16	12.0 0 0.02 14	14.0 0 0.02 16	16.0 0 0.02 16	18.0 0 0.02 16	20.0 0 0.02 17	22.0 0 0.02 16	24.0 0 0.03 09
(W/ Kg)	10	0.5	31	13	10	14	10	10	10	17	10	07
		0.3° 0.2° 0.2° 0.2° 0.2° 0.1° 0.1° 0.0° 0.0° 0.0° 0.0° 0.0° 0.0	5-0-	4 6	8	10 12 Z (14 16	18 20) 22 2	4 26		





Page 368 of 397

Test Laboratory: AGC Lab Date: Jun. 30, 2022

802.11a-CH157- Mid -Edge2

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: Wi-Fi; Communication System Band: 802.11a; Duty Cycle: 1:1; Conv.F=1.42; Frequency: 5785MHz; Medium parameters used: f = 5800 MHz; $\sigma = 5.40 \text{mho/m}$; $\epsilon = 36.35$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature (°C): 21.6, Liquid temperature (°C): 21.5

SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

• Measurement SW: OpenSAR V4_02_35


Configuration/ 802.11a-CH157- Mid – Edge2 /Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ 802.11a-CH157- Mid – Edge2 /Zoom Scan: Measurement grid: dx=4mm,dy=4mm, dz=2mm

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	7x7x12 dx=4mm dy=4mm dz=2mm
Phantom	ELLI
Device Position	Edge2
Band	5800MHz
Channels	Middle
Signal	Crest factor: 1.0




Maximum location: X=8.00, Y=55.00 SAR Peak: 0.26 W/kg

SAR 10g (W/Kg)	0.052913			
SAR 1g (W/Kg)	0.097594			





Z (m m) SA R (W/ Kg)	0.00 0.26 34	0.09 46	6.00 0.05 26	8.00 0.03 74	10.0 0 0.02 82	12.0 0 0.03 01	14.0 0 0.02 82	16.0 0 0.02 68	18.0 0 0.01 88	20.0 0 0.02 01	22.0 0 0.02 45	24.0 0 0.02 48
		0.26 0.20 0.15 0.10 0.05 0.02)-\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	4 6	-8	0 12 Z (m	14 16 nm)	18 20) 22 2	4 26		





Page 370 of 397

Bluetooth Mode

Test Laboratory: AGC Lab Date: Jun. 24, 2022

Bluetooth Mid-Touch-Left (1DH5)

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: BT; Communication System Band: Bluetooth; Duty Cycle: 77%; Conv.F=1.99; Frequency: 2441 MHz; Medium parameters used: f = 2450 MHz; $\sigma = 1.82 \text{mho/m}$; $\epsilon r = 38.56 \rho = 1000 \text{ kg/m}^3$;

Phantom section: Left Section

Ambient temperature ($^{\circ}$ C):20.9, Liquid temperature ($^{\circ}$ C): 20.8

SATIMO Configuration:

• Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

· Phantom: SAM twin phantom

• Measurement SW: OpenSAR V4_02_35


Configuration/ Bluetooth Mid- Touch-Left/Area Scan: Measurement grid: dx=8mm, dy=8mm **Configuration/ Bluetooth Mid- Touch-Left/Zoom Scan:** Measurement grid: dx=5mm,dy=5mm, dz=5mm

Area Scan	dx=8mm dy=8mm, h= 5.00 mm				
ZoomScan	7x7x7,dx=5mm dy=5mm dz=5mm				
Phantom	Left head				
Device Position	Cheek				
Band	Bluetooth				
Channels	Middle				
Signal	Crest factor: 1.299				





Maximum location: X=-22.00, Y=17.00 SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.025367				
SAR 1g (W/Kg)	0.055593				











Page 372 of 397

Test Laboratory: AGC Lab Date: Jun. 24, 2022

Bluetooth Mid-Body-Worn- Back (1DH5)

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: BT; Communication System Band: Bluetooth; Duty Cycle: 77%; Conv.F=1.99;

Frequency: 2441 MHz; Medium parameters used: f = 2450 MHz; $\sigma = 1.82 \text{mho/m}$; $\epsilon r = 38.56$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature (°C):20.9, Liquid temperature (°C): 20.8

SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

• Measurement SW: OpenSAR V4_02_35

Configuration/Bluetooth Mid- Body- Back /Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/Bluetooth Mid- Body- Back /Zoom Scan: Measurement grid: dx=5mm, dy=5mm, dz=5mm;


Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	7x7x7,dx=5mm dy=5mm dz=5mm
Phantom	ELLI
Device Position	Body Back
Band	Bluetooth
Channels	Middle
Signal	Crest factor: 1.299




Maximum location: X=-19.00, Y=63.00


SAR Peak: 0.01 W/kg Kg) 0.00

SAR 10g (W/Kg)	0.003104
SAR 1g (W/Kg)	0.006332











Page 374 of 397

Repeated SAR

Test Laboratory: AGC Lab Date: Jun. 19, 2022

WCDMA Band II Mid-Edge 3(RMC)

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: UMTS; Communication System Band: Band II UTRA/FDD; Duty Cycle:1:1; Conv.F=1.77 Frequency: 1880 MHz; Medium parameters used: f = 1800 MHz; $\sigma = 1.36 \text{ mho/m}$; $\epsilon = 41.34$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$ C): 21.4, Liquid temperature ($^{\circ}$ C): 20.9

SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

• Measurement SW: OpenSAR V4_02_35

Configuration/ WCDMA band II Mid-Edge 3/Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ WCDMA band II Mid-Edge 3/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

Area Scan	dx=8mm dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	ELLI
Device Position	Edge 3
Band	WCDMA band II
Channels	Middle
Signal	CDMA (Crest factor: 1.0)





Maximum location: X=1.00, Y=5.00 SAR Peak: 1.81 W/kg

SAR 10g (W/Kg)	0.595095
SAR 1g (W/Kg)	1.108806











Page 376 of 397

Test Laboratory: AGC Lab Date: Jun. 20, 2022

LTE Band 2 High-Body-Back (1 RB#0)

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: LTE; Communication System Band: LTE Band 2; Duty Cycle:1:1; Conv.F=1.77; Frequency:1900MHz; Medium parameters used: f = 1800 MHz; $\sigma = 1.39$ mho/m; $\epsilon r = 39.96$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$ C): 20.8, Liquid temperature ($^{\circ}$ C): 20.6

SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

• Measurement SW: OpenSAR V4_02_35

Configuration/ LTE Band 2 High-Body-Back/Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ LTE Band 2 High-Body-Back/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5m;


Area Scan	dx=8mm dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	ELLI
Device Position	Body Back
Band	LTE Band 2
Channels	High
Signal	OFDM (Crest factor: 1.0)




Maximum location: X=27.00, Y=-41.00


SAR Peak: 1.56 W/kg

SAR 10g (W/Kg)	0.549419
SAR 1g (W/Kg)	0.992027











Page 378 of 397

Test Laboratory: AGC Lab Date: Jun. 21, 2022

LTE Band 4 High- Edge 3 (1 RB#0)

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: LTE; Communication System Band: LTE Band 4; Duty Cycle:1:1; Conv.F=1.73; Frequency:1745 MHz; Medium parameters used: f = 1800 MHz; $\sigma = 1.33$ mho/m; $\epsilon = 41.34$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$): 20.9, Liquid temperature ($^{\circ}$): 20.5

SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

• Measurement SW: OpenSAR V4_02_35

Configuration/ LTE Band 4 High- Edge 3/Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ LTE Band 4 High- Edge 3/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5m;

Area Scan	dx=8mm dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	ELLI
Device Position	Edge 3
Band	LTE Band 4
Channels	High
Signal	OFDM (Crest factor: 1.0)





Maximum location: X=-2.00, Y=0.00 SAR Peak: 1.33 W/kg

SAR 10g (W/Kg)	0.452496
SAR 1g (W/Kg)	0.825300











Page 380 of 397

Test Laboratory: AGC Lab Date: Jun. 20, 2022

LTE Band 25 Mid-Edge 3 (1 RB#0)

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: LTE; Communication System Band: LTE Band 25; Duty Cycle:1:1; Conv.F=1.77; Frequency:1882.5MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.38 \text{ mho/m}$; $\epsilon r = 40.13$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$ C): 20.8, Liquid temperature ($^{\circ}$ C): 20.6

SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

• Measurement SW: OpenSAR V4_02_35


Configuration/ LTE Band 25 Mid-Edge 3/Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ LTE Band 25 Mid-Edge 3/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5m;

Area Scan	dx=8mm dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	ELLI
Device Position	Edge 3
Band	LTE Band 25
Channels	Middle
Signal	OFDM (Crest factor: 1.0)





Maximum location: X=6.00, Y=-9.00 SAR Peak: 2.07 W/kg

SAR 10g (W/Kg)	0.687498
SAR 1g (W/Kg)	1.279197











Page 382 of 397

Test Laboratory: AGC Lab Date: Jun. 12, 2022

LTE Band 26A Mid-Edge 3 (1 RB#0)

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: LTE; Communication System Band: LTE Band 26A; Duty Cycle:1:1; Conv.F=1.42 Frequency:831.5 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.88$ mho/m; $\epsilon = 41.23$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$): 21.5, Liquid temperature ($^{\circ}$): 21.2

SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

• Measurement SW: OpenSAR V4_02_35

Configuration/ LTE Band 26A Mid-Edge 3/Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ LTE Band 26A Mid-Edge 3/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5m;

Area Scan	dx=8mm dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	ELLI
Device Position	Edge 3
Band	LTE Band 26A
Channels	Middle
Signal	OFDM (Crest factor: 1.0)





Maximum location: X=3.00, Y=6.00 SAR Peak: 1.24 W/kg

SAR 10g (W/Kg)	0.418579
SAR 1g (W/Kg)	0.767748











Page 384 of 397

Test Laboratory: AGC Lab Date: Jun. 23, 2022

LTE Band 40-Lower Side Mid-Body- Back (1 RB#0) DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: LTE; Communication System Band: LTE Band 40-Lower Side; Duty Cycle:61:1.58;

Conv.F=1.98

Frequency: 2310 MHz; Medium parameters used: f = 2300 MHz; $\sigma = 1.66$ mho/m; $\epsilon r = 37.98$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$): 20.8, Liquid temperature ($^{\circ}$): 20.4

SATIMO Configuration:

• Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

Measurement SW: OpenSAR V4_02_35


Configuration/ LTE Band 40-Lower Side - Mid-Body- Back/Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ LTE Band 40-Lower Side - Mid-Body- Back/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

111,	
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm
Phantom	ELLI
Device Position	Body Back
Band	LTE Band 40-Lower Side
Channels	Middle
Signal	Crest factor: 1.58





Maximum location: X=16.00, Y=-48.00 SAR Peak: 1.89 W/kg

SAR 10g (W/Kg)	0.489256
SAR 1g (W/Kg)	1.039695











Page 386 of 397

Test Laboratory: AGC Lab Date: Jun. 21, 2022

LTE Band 66 Mid-Edge 3 (1 RB#0)

DUT: 4G Smart Phone; Type: AGM_H5_PRO

Communication System: LTE; Communication System Band: LTE Band 66; Duty Cycle:1:1; Conv.F=1.73; Frequency:1755 MHz; Medium parameters used: f = 1750 MHz; $\sigma = 1.35$ mho/m; $\epsilon r = 40.86$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$): 20.9, Liquid temperature ($^{\circ}$): 20.5

SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 13, 2022; Serial No.: SN 13/22 EPGO368


• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Phantom: ELLI39 Phantom

• Measurement SW: OpenSAR V4_02_35

Configuration/ LTE Band 66 Mid-Edge 3/Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ LTE Band 66 Mid-Edge 3/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5m;

Area Scan	dx=8mm dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	ELLI
Device Position	Edge 3
Band	LTE Band 66
Channels	Middle
Signal	OFDM (Crest factor: 1.0)





Maximum location: X=2.00, Y=6.00 SAR Peak: 1.24 W/kg

SAR 10g (W/Kg)	0.419347
SAR 1g (W/Kg)	0.767025














APPENDIX C. TEST SETUP PHOTOGRAPHS

LEFT-CHEEK TOUCH



















Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/






Body Back 10mm




Body Front 10mm







Edge 1(Top) Hotspot 10mm



Edge 2(Right) Hotspot 10mm



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





Edge 3(Bottom) Hotspot 10mm




Edge 4(Left) Hotspot 10mm





Page 393 of 397







Page 394 of 397


DEPTH OF THE LIQUID IN THE PHANTOM—ZOOM IN


Note: The position used in the measurement were according to IEEE 1528-2013


















Page 397 of 397

APPENDIX D. CALIBRATION DATA

Refer to Attached files.

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.