

Digital mode CDMA (PCS), Body Worn, With Battery BMS-2V

meas nr:	Phone position	Frequency MHz / channel	Power [dBm]	Whip in (1g)[mW/g]	Whip up (1g)[mW/g]
1,2	Against Flat	1850 / 25	22.5	1.43	1.08
3,4	Against Flat	1880 / 600	22.5	1.09	0.88
5,6	Against Flat	1910 / 1175	22.5	0.74	0.87
FCC ID:GMLNSD-1FW MEASURED: 2000-9- 13 / NMP		FCC limit		1.60[mW/g] (ANSI/IEEE)	1.60[mW/g] (ANSI/IEEE)

Digital mode CDMA (PCS), Body Worn, With Battery BLS-2N

meas nr:	Phone position	Frequency MHz / channel	Power [dBm]	Whip in (1g)[mW/g]	Whip up (1g)[mW/g]
1,2	Against Flat	1850 / 25	22.5	1.45	1.28
3,4	Against Flat	1880 / 600	22.5	1.00	0.87
5,6	Against Flat	1910 / 1175	22.5	0.81	0.92
FCC ID:GMLNSD-1FW MEASURED: 2000-9- 13 / NMP		FCC limit		1.60[mW/g] (ANSI/IEEE)	1.60[mW/g] (ANSI/IEEE)