



FCC RF Test Report

APPLICANT : Espressif Systems (Shanghai) Co.,Ltd.
EQUIPMENT : 2.4GHz Wi-Fi & BT IoT Module
BRAND NAME : ESPRESSIF
MODEL NAME : ESP32-C3-SOLO-1
FCC ID : 2AC7Z-ESPC3SOLO
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Jul. 11, 2022 ~ Aug. 08, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	5
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB Bandwidth Measurement	11
3.2 Output Power Measurement.....	16
3.3 Power Spectral Density Measurement	17
3.4 Conducted Band Edges and Spurious Emission Measurement	26
3.5 Radiated Band Edges and Spurious Emission Measurement	35
3.6 AC Conducted Emission Measurement.....	39
3.7 Antenna Requirements.....	41
4 LIST OF MEASURING EQUIPMENT.....	42
5 UNCERTAINTY OF EVALUATION.....	44
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	
APPENDIX F. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR262714A	Rev. 01	Initial issue of report	Aug. 29, 2022

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.61 dB at 2483.500 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 12.73 dB at 0.176 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-
Remark: Not required means after assessing, test items are not necessary to carry out.					

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Espressif Systems (Shanghai) Co.,Ltd.

Suite 204, Block 2, 690 Bibo Road, Zhang Jiang Hi-Tech Park, Shanghai, China

1.2 Manufacturer

Espressif Systems (Shanghai) Co.,Ltd.

Suite 204, Block 2, 690 Bibo Road, Zhang Jiang Hi-Tech Park, Shanghai, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	2.4GHz Wi-Fi & BT IoT Module
Brand Name	ESPRESSIF
Model Name	ESP32-C3-SOLO-1
FCC ID	2AC7Z-ESPC3SOLO
HW Version	V1.1
SW Version	V1.1.3.0
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	Bluetooth LE 1Mbps : 10.64dBm (0.0116 W) Bluetooth LE 2Mbps : 10.94dBm (0.0124 W)
Antenna Type / Gain	PCB Antenna type with gain 3.26 dBi
Type of Modulation	Bluetooth LE : GFSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH02-KS 03CH06-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	03CH06-KS	AUDIX	E3	6.2009-8-24a1
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz Mode 2: Bluetooth Tx CH19_2440 MHz Mode 3: Bluetooth Tx CH39_2480 MHz
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz Mode 2: Bluetooth Tx CH19_2440 MHz Mode 3: Bluetooth Tx CH39_2480 MHz
AC Conducted Emission	Mode 1: BT Link+ WLAN Link(2.4G)+Adapter

2.3 Connection Diagram of Test System

< AC Conducted Emission >



< Radiated Emission >



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
2.	Notebook	Lenovo	V130-14IKB004	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
3.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
4.	Test Jig	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.4dB.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\
 &= 5.4 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

Bluetooth LE 1Mbps:


6 dB Bandwidth Plot on Channel 00



Date: 14.JUL.2022 01:28:16




6 dB Bandwidth Plot on Channel 19



Date: 14.JUL.2022 01:31:56


6 dB Bandwidth Plot on Channel 39



Date: 14.JUL.2022 01:35:40


Bluetooth LE 2Mbps:

6 dB Bandwidth Plot on Channel 00






6 dB Bandwidth Plot on Channel 19



Date: 14.JUL.2022 01:42:12

6 dB Bandwidth Plot on Channel 39



Date: 14.JUL.2022 01:45:55

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.



3.3.6 Test Result of Power Spectral Density Plots (100kHz)


Bluetooth LE 1Mbps:

PSD 100kHz Plot on Channel 00



Date: 14.JUL.2022 01:28:54


PSD 100kHz Plot on Channel 19



Date: 14.JUL.2022 01:32:34



PSD 100kHz Plot on Channel 39




Date: 14.JUL.2022 01:36:19




Bluetooth LE 2Mbps:

PSD 100kHz Plot on Channel 00



Date: 14.JUL.2022 01:39:45


PSD 100kHz Plot on Channel 19



Date: 14.JUL.2022 01:42:50



PSD 100kHz Plot on Channel 39




Date: 14.JUL.2022 01:46:33



3.3.7 Test Result of Power Spectral Density Plots (3kHz)


Bluetooth LE 1Mbps:

PSD 3kHz Plot on Channel 00



Date: 14.JUL.2022 01:28:35


PSD 3kHz Plot on Channel 19



Date: 14.JUL.2022 01:32:15



PSD 3kHz Plot on Channel 39




Date: 14.JUL.2022 01:36:00




Bluetooth LE 2Mbps:

PSD 3kHz Plot on Channel 00



Date: 14.JUL.2022 01:39:26


PSD 3kHz Plot on Channel 19



Date: 14.JUL.2022 01:42:31



PSD 3kHz Plot on Channel 39



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots


Bluetooth LE 1Mbps:

Low Band Edge Plot on Channel 00



Date: 14.JUL.2022 01:29:13

High Band Edge Plot on Channel 39




Date: 14.JUL.2022 01:36:38




Bluetooth LE 2Mbps:

Low Band Edge Plot on Channel 00



High Band Edge Plot on Channel 39







3.4.6 Test Result of Conducted Spurious Emission Plots

Bluetooth LE 1Mbps:


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19






Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39



Date: 14.JUL.2022 01:36:59

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39




Date: 14.JUL.2022 01:37:19



Bluetooth LE 2Mbps:

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00



Date: 14.JUL.2022 01:40:25

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00



Date: 14.JUL.2022 01:40:45




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19



Date: 14.JUL.2022 01:44:53


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19



Date: 14.JUL.2022 01:45:04




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39



Date: 14.JUL.2022 01:49:21

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39



Date: 14.JUL.2022 01:49:33

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and Appendix D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C and Appendix D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 14, 2021	Jul. 14, 2022	Oct. 13, 2022	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2022	Jul. 14, 2022	Jan. 04, 2023	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2022	Jul. 14, 2022	Jan. 04, 2023	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Oct. 16, 2021	Aug. 08, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz~44G,MAX 30dB	Oct. 16, 2021	Aug. 08, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 23, 2021	Aug. 08, 2022	Oct. 22, 2022	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Dec. 22, 2021	Aug. 08, 2022	Dec. 21, 2022	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 30, 2021	Aug. 08, 2022	Oct. 29, 2022	Radiation (03CH02-KS)
high gain Amplifier	MITEQ	AMF-7D-001 01800-30-10 P	2025788	1Ghz~18Ghz	Jul. 30, 2021	Aug. 08, 2022	Jul. 29, 2023	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2022	Aug. 08, 2022	Jan. 04, 2023	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	413741	9KHz~1GHz	Jan. 05, 2022	Aug. 08, 2022	Jan. 04, 2023	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5GHz	Oct. 16, 2021	Aug. 08, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2022	Aug. 08, 2022	Jan. 04, 2023	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Aug. 08, 2022	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Aug. 08, 2022	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Aug. 08, 2022	NCR	Radiation (03CH02-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 16, 2021	Aug. 08, 2022	Oct. 15, 2022	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz~44GHz	Oct. 26, 2021	Aug. 08, 2022	Oct. 25, 2022	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 30, 2021	Aug. 08, 2022	Oct. 29, 2022	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz~1GHz	May 24, 2022	Aug. 08, 2022	May 23, 2023	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 18, 2022	Aug. 08, 2022	Apr. 17, 2023	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 05, 2022	Aug. 08, 2022	Jan. 04, 2023	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	380827	9KHz ~1GHZ	Jul. 11, 2022	Aug. 08, 2022	Jul. 10, 2023	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2022	Aug. 08, 2022	Jan. 04, 2023	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-001 01800-30-10 P	2082395	1Ghz~18Ghz	Jan. 05, 2022	Aug. 08, 2022	Jan. 05, 2023	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270319	500MHz~26.5GHz	Oct. 14, 2021	Aug. 08, 2022	Oct. 13, 2022	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 08, 2022	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 08, 2022	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 08, 2022	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 24, 2022	Jul. 11, 2022	May 23, 2023	Conduction (CO01-KS)



AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 14, 2021	Jul. 11, 2022	Oct. 13, 2022	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 24, 2022	Jul. 11, 2022	May 23, 2023	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 14, 2021	Jul. 11, 2022	Oct. 13, 2022	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.94dB
---	--------

03CH02:

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.9dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1dB
---	-------

03CH06:

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

----- THE END -----



Appendix A. Conducted Test Results

Bluetooth Low Energy

Test Engineer:	Long Wu	Temperature:	20~26	°C
Test Date:	2022/7/14	Relative Humidity:	40~51	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.01	0.63	0.50	Pass
BLE	1Mbps	1	19	2440	1.02	0.64	0.50	Pass
BLE	1Mbps	1	39	2480	1.02	0.63	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	8.96	30.00	3.26	12.22	36.00	Pass
BLE	1Mbps	1	19	2440	10.64	30.00	3.26	13.90	36.00	Pass
BLE	1Mbps	1	39	2480	10.50	30.00	3.26	13.76	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	0.77	7.81
BLE	1Mbps	1	19	2440	0.77	9.39
BLE	1Mbps	1	39	2480	0.77	8.96

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	8.52	-7.31	3.26	8.00	Pass
BLE	1Mbps	1	19	2440	10.62	-5.19	3.26	8.00	Pass
BLE	1Mbps	1	39	2480	10.07	-5.99	3.26	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Bluetooth Low Energy

Test Engineer:	Long Wu	Temperature:	20~26	°C
Test Date:	2022/7/14	Relative Humidity:	40~51	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.01	1.10	0.50	Pass
BLE	2Mbps	1	19	2440	2.01	1.11	0.50	Pass
BLE	2Mbps	1	39	2480	2.01	1.10	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	9.29	30.00	3.26	12.55	36.00	Pass
BLE	2Mbps	1	19	2440	10.94	30.00	3.26	14.20	36.00	Pass
BLE	2Mbps	1	39	2480	10.35	30.00	3.26	13.61	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	2Mbps	1	0	2402	2.49	8.12
BLE	2Mbps	1	19	2440	2.49	9.60
BLE	2Mbps	1	39	2480	2.49	9.11

TEST RESULTS DATA
Peak Power Density


Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	9.03	-8.50	3.26	8.00	Pass
BLE	2Mbps	1	19	2440	10.58	-6.92	3.26	8.00	Pass
BLE	2Mbps	1	39	2480	10.14	-7.63	3.26	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



Appendix B. AC Conducted Emission Test Results


Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15C LISN-060105-L LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.162	48.67	-16.71	65.38	38.19	0.03	10.45	QP
2	0.162	31.07	-24.31	55.38	20.59	0.03	10.45	Average
3 *	0.176	51.95	-12.73	64.68	41.50	0.03	10.42	QP
4	0.176	35.65	-19.03	54.68	25.20	0.03	10.42	Average
5	0.184	48.63	-15.65	64.28	38.20	0.03	10.40	QP
6	0.184	33.73	-20.55	54.28	23.30	0.03	10.40	Average
7	0.202	46.60	-16.94	63.54	36.20	0.04	10.36	QP
8	0.202	30.70	-22.84	53.54	20.30	0.04	10.36	Average
9	0.497	34.54	-21.51	56.05	24.20	0.10	10.24	QP
10	0.497	25.64	-20.41	46.05	15.30	0.10	10.24	Average
11	18.328	33.69	-26.31	60.00	22.80	0.43	10.46	QP
12	18.328	26.79	-23.21	50.00	15.90	0.43	10.46	Average

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15C LISN-060105-N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1 *	0.151	53.19	-12.77	65.96	42.60	0.11	10.48	QP
2	0.151	37.89	-18.07	55.96	27.30	0.11	10.48	Average
3	0.176	48.72	-15.96	64.68	38.20	0.10	10.42	QP
4	0.176	31.72	-22.96	54.68	21.20	0.10	10.42	Average
5	0.209	41.96	-21.27	63.23	31.50	0.10	10.36	QP
6	0.209	27.06	-26.17	53.23	16.60	0.10	10.36	Average
7	0.264	38.32	-22.97	61.29	27.90	0.10	10.32	QP
8	0.264	28.62	-22.67	51.29	18.20	0.10	10.32	Average
9	2.225	34.27	-21.73	56.00	23.90	0.14	10.23	QP
10	2.225	29.57	-16.43	46.00	19.20	0.14	10.23	Average
11	17.661	36.08	-23.92	60.00	25.20	0.43	10.45	QP
12	17.661	30.48	-19.52	50.00	19.60	0.43	10.45	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

Channel	Power setting
BLE-1Mbps--CH00	11
BLE-1Mbps--CH19	11
BLE-1Mbps--CH39	11
BLE-2Mbps--CH00	11
BLE-2Mbps--CH19	11
BLE-2Mbps--CH39	11



2.4GHz 2400~2483.5MHz

BLE (1M) (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2376.43	54.29	-19.71	74	48.36	32.23	6.58	32.88	117	32	P	H
		2389.3	43.83	-10.17	54	37.8	32.3	6.61	32.88	117	32	A	H
	*	2402	107.88	-	-	101.81	32.3	6.61	32.84	117	32	P	H
	*	2402	105.98	-	-	99.91	32.3	6.61	32.84	117	32	A	H
		2343.41	54.12	-19.88	74	48.41	32.1	6.53	32.92	395	230	P	V
		2389.69	43.58	-10.42	54	37.55	32.3	6.61	32.88	385	230	A	V
	*	2402	104.55	-	-	98.48	32.3	6.61	32.84	395	230	P	V
	*	2402	102.61	-	-	96.54	32.3	6.61	32.84	395	230	A	V
BLE CH 39 2480MHz		2483.68	57.74	-16.26	74	51.22	32.43	6.73	32.64	161	32	P	H
		2483.5	47.75	-6.25	54	41.23	32.43	6.73	32.64	161	32	A	H
	*	2480	107.76	-	-	101.24	32.43	6.73	32.64	161	32	P	H
	*	2480	106.11	-	-	99.59	32.43	6.73	32.64	161	32	A	H
		2484.1	55.14	-18.86	74	48.62	32.43	6.73	32.64	356	341	P	V
		2483.5	45.91	-8.09	54	39.39	32.43	6.73	32.64	356	341	A	V
	*	2480	104.39	-	-	97.87	32.43	6.73	32.64	356	341	P	V
	*	2480	102.72	-	-	96.2	32.43	6.73	32.64	356	341	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (1M) (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4800	41.99	-32.01	74	59.46	34.3	9.45	61.22	300	0	P	H
		4800	41.67	-32.33	74	59.14	34.3	9.45	61.22	100	0	P	V
BLE CH 19 2440MHz		4875	45.98	-28.02	74	63.49	34.14	9.52	61.17	300	0	P	H
		7320	45.02	-28.98	74	58.39	35.7	11.69	60.76	300	0	P	H
		4875	44.54	-29.46	74	62.05	34.14	9.52	61.17	100	0	P	V
		7320	44.95	-29.05	74	58.32	35.7	11.69	60.76	100	0	P	V
BLE CH 39 2480MHz		4965	47.82	-26.18	74	65.21	34.1	9.61	61.1	300	0	P	H
		7440	44.43	-29.57	74	57.94	35.7	11.78	60.99	300	0	P	H
		4965	46.19	-27.81	74	63.58	34.1	9.61	61.1	100	0	P	V
		7440	44.92	-29.08	74	58.43	35.7	11.78	60.99	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE (2M) (Band Edge @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		2344.19	54.87	-19.13	74	49.16	32.1	6.53	32.92	118	31	P	H
		2389.95	44.44	-9.56	54	38.37	32.3	6.61	32.84	118	31	A	H
	*	2402	108.5	-	-	102.43	32.3	6.61	32.84	118	31	P	H
	*	2402	105.49	-	-	99.42	32.3	6.61	32.84	118	31	A	H
		2389.56	54.37	-19.63	74	48.34	32.3	6.61	32.88	386	327	P	V
		2389.95	44.07	-9.93	54	38	32.3	6.61	32.84	386	327	A	V
	*	2402	104.61	-	-	98.54	32.3	6.61	32.84	386	327	P	V
	*	2402	101.78	-	-	95.71	32.3	6.61	32.84	386	327	A	V



BLE CH 39 2480MHz		2483.5	57.1	-16.9	74	50.58	32.43	6.73	32.64	160	31	P	H
		2483.5	48.39	-5.61	54	41.87	32.43	6.73	32.64	160	31	A	H
	*	2480	108.04	-	-	101.52	32.43	6.73	32.64	160	31	P	H
	*	2480	105.13	-	-	98.61	32.43	6.73	32.64	160	31	A	H
		2483.92	55.24	-18.76	74	48.72	32.43	6.73	32.64	357	342	P	V
		2483.56	46.39	-7.61	54	39.87	32.43	6.73	32.64	357	342	A	V
	*	2480	104.26	-	-	97.74	32.43	6.73	32.64	357	342	P	V
	*	2480	101.66	-	-	95.14	32.43	6.73	32.64	357	342	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE (2M) (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		4800	40.84	-33.16	74	58.31	34.3	9.45	61.22	300	0	P	H
		4800	39.9	-34.1	74	57.37	34.3	9.45	61.22	100	0	P	V
BLE CH 19 2440MHz		4875	45.84	-28.16	74	63.35	34.14	9.52	61.17	300	0	P	H
		7320	44.99	-29.01	74	58.36	35.7	11.69	60.76	300	0	P	H
		4875	44.46	-29.54	74	61.97	34.14	9.52	61.17	100	0	P	V
		7320	44.69	-29.31	74	58.06	35.7	11.69	60.76	100	0	P	V
BLE CH 39 2480MHz		4965	47.9	-26.1	74	65.29	34.1	9.61	61.1	300	0	P	H
		7440	44.98	-29.02	74	58.49	35.7	11.78	60.99	300	0	P	H
		4965	45.44	-28.56	74	62.83	34.1	9.61	61.1	100	0	P	V
		7440	45.96	-28.04	74	59.47	35.7	11.78	60.99	100	0	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		30.97	26.43	-13.57	40	33.37	24.7	0.76	32.4	-	-	P	H
		159.98	21.22	-22.28	43.5	35.58	16.2	1.84	32.4	-	-	P	H
		238.55	26.74	-19.26	46	39.97	17.08	2.09	32.4	-	-	P	H
		320.03	26.54	-19.46	46	37.01	19.3	2.63	32.4	-	-	P	H
		481.05	29.14	-16.86	46	34.98	23.42	3.14	32.4	-	-	P	H
		704.15	34.94	-11.06	46	36.97	26.4	3.96	32.39	-	-	P	H
		38.73	23.21	-16.79	40	34.67	20.1	0.84	32.4	-	-	P	V
		46.49	24.95	-15.05	40	40.49	15.9	0.96	32.4	-	-	P	V
		65.89	22.36	-17.64	40	42.02	11.6	1.14	32.4	-	-	P	V
		320.03	26.83	-19.17	46	37.3	19.3	2.63	32.4	-	-	P	V
		438.37	27.56	-18.44	46	34.21	22.64	3.11	32.4	-	-	P	V
		763.32	32.36	-13.64	46	32.36	28.14	4.11	32.25	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.









Appendix D. Radiated Spurious Emission Plots

Note symbol

-L	Low channel location
-R	High channel location





BLE		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																												
ANT		BLE CH39 2480MHZ																																																												
1	Vertical	Fundamental																																																												
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-KS Condition : FCC PART 15C 3m 3117 SN 00218602- VERTICAL Project : RSM 1000 000KHz VSW:3000.000KHz SMT:Auto Bode : (FR)262714 Plane : 2 Full-directivity IMEI : 82 power : 11 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 2484.10</td><td>55.14</td><td>-18.86</td><td>74.00</td><td>48.62</td><td>32.43</td><td>6.73</td><td>32.64</td><td>356</td><td>341 Peak VERTICAL</td></tr></table> <td>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-KS Condition : FCC PART 15C 3m 3117 SN 00218602- VERTICAL Project : RSM 1000 000KHz VSW:3000.000KHz SMT:Auto Bode : (FR)262714 Plane : 2 Full-directivity IMEI : 82 power : 11 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 * 2480.00</td><td>104.39</td><td>30.39</td><td>74.00</td><td>97.87</td><td>32.43</td><td>6.73</td><td>32.64</td><td>356</td><td>341 Peak VERTICAL</td></tr></table> </td>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	cm	deg			1 2484.10	55.14	-18.86	74.00	48.62	32.43	6.73	32.64	356	341 Peak VERTICAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-KS Condition : FCC PART 15C 3m 3117 SN 00218602- VERTICAL Project : RSM 1000 000KHz VSW:3000.000KHz SMT:Auto Bode : (FR)262714 Plane : 2 Full-directivity IMEI : 82 power : 11 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 * 2480.00</td><td>104.39</td><td>30.39</td><td>74.00</td><td>97.87</td><td>32.43</td><td>6.73</td><td>32.64</td><td>356</td><td>341 Peak VERTICAL</td></tr></table>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	cm	deg			1 * 2480.00	104.39	30.39	74.00	97.87	32.43	6.73	32.64	356	341 Peak VERTICAL
	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																				
MHz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	cm	deg																																																							
1 2484.10	55.14	-18.86	74.00	48.62	32.43	6.73	32.64	356	341 Peak VERTICAL																																																					
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																					
MHz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	cm	deg																																																							
1 * 2480.00	104.39	30.39	74.00	97.87	32.43	6.73	32.64	356	341 Peak VERTICAL																																																					
Avg.	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-KS Condition : FCC PART 15C (AVG) 3m 3117 SN 00218602- VERTICAL Project : RSM 1000 000KHz VSW:3.0100KHz SMT:Auto Bode : (FR)262714 Plane : 2 Full-directivity IMEI : 82 power : 11 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 2483.50</td><td>45.91</td><td>-8.09</td><td>54.00</td><td>39.39</td><td>32.43</td><td>6.73</td><td>32.64</td><td>356</td><td>341 Average VERTICAL</td></tr></table> <td>  No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-KS Condition : FCC PART 15C (AVG) 3m 3117 SN 00218602- VERTICAL Project : RSM 1000 000KHz VSW:3.0100KHz SMT:Auto Bode : (FR)262714 Plane : 2 Full-directivity IMEI : 82 power : 11 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 * 2480.00</td><td>102.72</td><td>48.72</td><td>54.00</td><td>96.20</td><td>32.43</td><td>6.73</td><td>32.64</td><td>356</td><td>341 Average VERTICAL</td></tr></table> </td>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	cm	deg			1 2483.50	45.91	-8.09	54.00	39.39	32.43	6.73	32.64	356	341 Average VERTICAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-KS Condition : FCC PART 15C (AVG) 3m 3117 SN 00218602- VERTICAL Project : RSM 1000 000KHz VSW:3.0100KHz SMT:Auto Bode : (FR)262714 Plane : 2 Full-directivity IMEI : 82 power : 11 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 * 2480.00</td><td>102.72</td><td>48.72</td><td>54.00</td><td>96.20</td><td>32.43</td><td>6.73</td><td>32.64</td><td>356</td><td>341 Average VERTICAL</td></tr></table>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	cm	deg			1 * 2480.00	102.72	48.72	54.00	96.20	32.43	6.73	32.64	356	341 Average VERTICAL
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																					
MHz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	cm	deg																																																							
1 2483.50	45.91	-8.09	54.00	39.39	32.43	6.73	32.64	356	341 Average VERTICAL																																																					
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																					
MHz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	dBm/100Hz	cm	deg																																																							
1 * 2480.00	102.72	48.72	54.00	96.20	32.43	6.73	32.64	356	341 Average VERTICAL																																																					



2.4GHz 2400~2483.5MHz





BLE (1M) (Harmonic @ 3m)

BLE		2.4GHz 2400~2483.5MHz Harmonic @ 3m																																																																																								
ANT		BLE CH39 2480MHz																																																																																								
1	Horizontal	Vertical																																																																																								
Peak	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn SPORTON LAB. Data: 9 Level (dBm/100kHz) 117 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2000 4000 6000 8000 10000 12000 14000 16000 18000 Frequency (MHz) FCC PART 15C (dB) FCC PART 15C (AUS) Site : 030906-KS Condition : FCC PART 15C 3m 3117 SN 00318653- HORIZONTAL Project : FR262714 Mode : 2 Plane : 2 Full-directivity : 62 Power : 11 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pow</th><th>T/Pow</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100kHz</th><th>dB</th><th>dBm/100kHz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th></tr><tr><td>1 4965.00</td><td>47.82</td><td>-26.18</td><td>74.00</td><td>65.21</td><td>34.10</td><td>9.61</td><td>61.10</td><td>300</td><td>0 Peak</td><td>HORIZONTAL</td></tr><tr><td>2 7440.00</td><td>44.43</td><td>-29.57</td><td>74.00</td><td>57.94</td><td>35.70</td><td>11.78</td><td>60.99</td><td>300</td><td>0 Peak</td><td>HORIZONTAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pow	T/Pow	Remark	Pol/Phas	MHz	dBm/100kHz	dB	dBm/100kHz	dB	dB	dB	dB	dB	dB	deg	1 4965.00	47.82	-26.18	74.00	65.21	34.10	9.61	61.10	300	0 Peak	HORIZONTAL	2 7440.00	44.43	-29.57	74.00	57.94	35.70	11.78	60.99	300	0 Peak	HORIZONTAL	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn SPORTON LAB. Data: 10 Level (dBm/100kHz) 117 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2000 4000 6000 8000 10000 12000 14000 16000 18000 Frequency (MHz) FCC PART 15C (dB) FCC PART 15C (AUS) Site : 030906-KS Condition : FCC PART 15C 3m 3117 SN 00318653- VERTICAL Project : FR262714 Mode : 2 Plane : 2 Full-directivity : 62 Power : 11 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pow</th><th>T/Pow</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100kHz</th><th>dB</th><th>dBm/100kHz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th></tr><tr><td>1 4965.00</td><td>46.19</td><td>-27.81</td><td>74.00</td><td>63.58</td><td>34.10</td><td>9.61</td><td>61.10</td><td>100</td><td>0 Peak</td><td>VERTICAL</td></tr><tr><td>2 7440.00</td><td>44.92</td><td>-29.08</td><td>74.00</td><td>58.43</td><td>35.70</td><td>11.78</td><td>60.99</td><td>100</td><td>0 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pow	T/Pow	Remark	Pol/Phas	MHz	dBm/100kHz	dB	dBm/100kHz	dB	dB	dB	dB	dB	dB	deg	1 4965.00	46.19	-27.81	74.00	63.58	34.10	9.61	61.10	100	0 Peak	VERTICAL	2 7440.00	44.92	-29.08	74.00	58.43	35.70	11.78	60.99	100	0 Peak	VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pow	T/Pow	Remark	Pol/Phas																																																																															
MHz	dBm/100kHz	dB	dBm/100kHz	dB	dB	dB	dB	dB	dB	deg																																																																																
1 4965.00	47.82	-26.18	74.00	65.21	34.10	9.61	61.10	300	0 Peak	HORIZONTAL																																																																																
2 7440.00	44.43	-29.57	74.00	57.94	35.70	11.78	60.99	300	0 Peak	HORIZONTAL																																																																																
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pow	T/Pow	Remark	Pol/Phas																																																																																
MHz	dBm/100kHz	dB	dBm/100kHz	dB	dB	dB	dB	dB	dB	deg																																																																																
1 4965.00	46.19	-27.81	74.00	63.58	34.10	9.61	61.10	100	0 Peak	VERTICAL																																																																																
2 7440.00	44.92	-29.08	74.00	58.43	35.70	11.78	60.99	100	0 Peak	VERTICAL																																																																																







2.4GHz 2400~2483.5MHz

BLE (2M) (Band Edge @ 3m)

BLE		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																																																																																					
ANT		BLE CH39 2480MHz																																																																																																																																					
1	Horizontal	Fundamental																																																																																																																																					
Peak	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel : +86-512-57900158 fax : +86-512-57900958 http://www.sporton.com.cn Site : 030906-K3 Condition : FCC PART 15C 3m 3117 SN 00218662- HORIZONTAL Project : RSM 1000 000000 YSR 3000 000000 SMT Auto Model : FR262714 Plane : 0 Full-directivity : 0 IMEI : 82 power : 11 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Poss</th><th>T/Poss</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2483.50</td><td>57.10</td><td>-16.90</td><td>74.00</td><td>50.58</td><td>32.43</td><td>6.73</td><td>32.64</td><td>160</td><td>31 Peak</td></tr></tbody></table>  No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel : +86-512-57900158 fax : +86-512-57900958 http://www.sporton.com.cn Site : 030906-K3 Condition : FCC PART 15C 3m 3117 SN 00218662- HORIZONTAL Project : RSM 1000 000000 YSR 3000 000000 SMT Auto Model : FR262714 Plane : 0 Full-directivity : 0 IMEI : 82 power : 11 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Poss</th><th>T/Poss</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>108.04</td><td>34.04</td><td>74.00</td><td>101.52</td><td>32.43</td><td>6.73</td><td>32.64</td><td>160</td><td>31 Peak</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Poss	T/Poss	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	dB	dB	deg		1	2483.50	57.10	-16.90	74.00	50.58	32.43	6.73	32.64	160	31 Peak	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Poss	T/Poss	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	dB	dB	deg		1	2480.00	108.04	34.04	74.00	101.52	32.43	6.73	32.64	160	31 Peak	Avg.	 No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel : +86-512-57900158 fax : +86-512-57900958 http://www.sporton.com.cn Site : 030906-K3 Condition : FCC PART 15C (AVG) 3m 3117 SN 00218662- HORIZONTAL Project : RSM 1000 000000 YSR 3000 000000 SMT Auto Model : FR262714 Plane : 0 Full-directivity : 0 IMEI : 82 power : 11 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Poss</th><th>T/Poss</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2483.50</td><td>48.39</td><td>-5.61</td><td>54.00</td><td>41.87</td><td>32.43</td><td>6.73</td><td>32.64</td><td>160</td><td>31 Average</td></tr></tbody></table>  No. 1098, Pengxi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel : +86-512-57900158 fax : +86-512-57900958 http://www.sporton.com.cn Site : 030906-K3 Condition : FCC PART 15C (AVG) 3m 3117 SN 00218662- HORIZONTAL Project : RSM 1000 000000 YSR 3000 000000 SMT Auto Model : FR262714 Plane : 0 Full-directivity : 0 IMEI : 82 power : 11 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Poss</th><th>T/Poss</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100Hz</th><th>dB</th><th>dBm/100Hz</th><th>dBm/100Hz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>105.13</td><td>51.13</td><td>54.00</td><td>98.61</td><td>32.43</td><td>6.73</td><td>32.64</td><td>160</td><td>31 Average</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Poss	T/Poss	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	dB	dB	deg		1	2483.50	48.39	-5.61	54.00	41.87	32.43	6.73	32.64	160	31 Average	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Poss	T/Poss	Remark	Pol/Phas	MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	dB	dB	deg		1	2480.00	105.13	51.13	54.00	98.61	32.43	6.73	32.64	160	31 Average
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Poss	T/Poss	Remark	Pol/Phas																																																																																																																												
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	dB	dB	deg																																																																																																																														
1	2483.50	57.10	-16.90	74.00	50.58	32.43	6.73	32.64	160	31 Peak																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Poss	T/Poss	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	dB	dB	deg																																																																																																																														
1	2480.00	108.04	34.04	74.00	101.52	32.43	6.73	32.64	160	31 Peak																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Poss	T/Poss	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	dB	dB	deg																																																																																																																														
1	2483.50	48.39	-5.61	54.00	41.87	32.43	6.73	32.64	160	31 Average																																																																																																																													
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Poss	T/Poss	Remark	Pol/Phas																																																																																																																													
MHz	dBm/100Hz	dB	dBm/100Hz	dBm/100Hz	dB	dB	dB	dB	deg																																																																																																																														
1	2480.00	105.13	51.13	54.00	98.61	32.43	6.73	32.64	160	31 Average																																																																																																																													





BLE		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																																																																									
ANT		BLE CH39 2480MHZ																																																																																																																									
1	Vertical	Fundamental																																																																																																																									
Peak	 No. 1098, Pengji North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-K5 Condition : FCC PART 15C 3m 3117 SN 00218602- VERTICAL Project : FR262714 Mode : 6 Plane : 3 Full-directivity : 11 IMEI : 82 power : 11 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>cn</th><th>deg</th></tr></thead><tbody><tr><td>1 2483.92</td><td>55.24</td><td>-18.76</td><td>74.00</td><td>48.72</td><td>32.43</td><td>6.73</td><td>32.64</td><td>357</td><td>342 Peak</td></tr></tbody></table>  No. 1098, Pengji North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-K5 Condition : FCC PART 15C 3m 3117 SN 00218602- VERTICAL Project : FR262714 Mode : 6 Plane : 3 Full-directivity : 11 IMEI : 82 power : 11 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>cn</th><th>deg</th></tr></thead><tbody><tr><td>1 * 2480.00</td><td>104.26</td><td>30.26</td><td>74.00</td><td>97.74</td><td>32.43</td><td>6.73</td><td>32.64</td><td>357</td><td>342 Peak</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	cn	deg	1 2483.92	55.24	-18.76	74.00	48.72	32.43	6.73	32.64	357	342 Peak	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	cn	deg	1 * 2480.00	104.26	30.26	74.00	97.74	32.43	6.73	32.64	357	342 Peak	Avg.	 No. 1098, Pengji North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-K5 Condition : FCC PART 15C (AVG) 3m 3117 SN 00218602- VERTICAL Project : FR262714 Mode : 6 Plane : 3 Full-directivity : 11 IMEI : 82 power : 11 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>cn</th><th>deg</th></tr></thead><tbody><tr><td>1 2483.56</td><td>46.39</td><td>-7.61</td><td>54.00</td><td>39.87</td><td>32.43</td><td>6.73</td><td>32.64</td><td>357</td><td>342 Average</td></tr></tbody></table>  No. 1098, Pengji North Road, Kunshan Economic & Technical Development Zone, Jiangsu China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Site : 030906-K5 Condition : FCC PART 15C (AVG) 3m 3117 SN 00218602- VERTICAL Project : FR262714 Mode : 6 Plane : 3 Full-directivity : 11 IMEI : 82 power : 11 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>dBm/100m</th><th>cn</th><th>deg</th></tr></thead><tbody><tr><td>1 * 2480.00</td><td>101.66</td><td>47.66</td><td>54.00</td><td>95.14</td><td>32.43</td><td>6.73</td><td>32.64</td><td>357</td><td>342 Average</td></tr></tbody></table>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	cn	deg	1 2483.56	46.39	-7.61	54.00	39.87	32.43	6.73	32.64	357	342 Average	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	cn	deg	1 * 2480.00	101.66	47.66	54.00	95.14	32.43	6.73	32.64	357	342 Average
	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																	
MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	cn	deg																																																																																																																		
1 2483.92	55.24	-18.76	74.00	48.72	32.43	6.73	32.64	357	342 Peak																																																																																																																		
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																		
MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	cn	deg																																																																																																																		
1 * 2480.00	104.26	30.26	74.00	97.74	32.43	6.73	32.64	357	342 Peak																																																																																																																		
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																		
MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	cn	deg																																																																																																																		
1 2483.56	46.39	-7.61	54.00	39.87	32.43	6.73	32.64	357	342 Average																																																																																																																		
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																		
MHz	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	dBm/100m	cn	deg																																																																																																																		
1 * 2480.00	101.66	47.66	54.00	95.14	32.43	6.73	32.64	357	342 Average																																																																																																																		



2.4GHz 2400~2483.5MHz

BLE (2M) (Harmonic @ 3m)

BLE		2.4GHz 2400~2483.5MHz Harmonic @ 3m																																																																																												
ANT		BLE CH39 2480MHz																																																																																												
1	Horizontal	Vertical																																																																																												
Peak	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900058 http://www.sporton.com.cn Date: 9  Site : 030906-K3 Condition : FCC PART 15C 3m 3117 SN 00318653- HORIZONTAL Project : FR262714 Mode : 0 Plane : 0 Full-directivity : 0 power : 11 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th></tr><tr><td>1</td><td>49.65</td><td>0.0</td><td>47.90</td><td>-26.10</td><td>74.00</td><td>65.29</td><td>34.10</td><td>9.61</td><td>61.10</td><td>300</td><td>0 Peak</td><td>HORIZONTAL</td></tr><tr><td>2</td><td>74.40</td><td>0.0</td><td>44.99</td><td>-29.02</td><td>74.00</td><td>58.49</td><td>35.70</td><td>11.78</td><td>60.99</td><td>300</td><td>0 Peak</td><td>HORIZONTAL</td></tr></table>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	1	49.65	0.0	47.90	-26.10	74.00	65.29	34.10	9.61	61.10	300	0 Peak	HORIZONTAL	2	74.40	0.0	44.99	-29.02	74.00	58.49	35.70	11.78	60.99	300	0 Peak	HORIZONTAL	 No. 1098, Pengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900058 http://www.sporton.com.cn Date: 9  Site : 030906-K3 Condition : FCC PART 15C 3m 3117 SN 00318653- VERTICAL Project : FR262714 Mode : 0 Plane : 0 Full-directivity : 0 power : 11 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th><th>dBm/100kHz</th></tr><tr><td>1</td><td>49.65</td><td>0.0</td><td>45.44</td><td>-28.56</td><td>74.00</td><td>62.83</td><td>34.10</td><td>9.61</td><td>61.10</td><td>100</td><td>0 Peak</td><td>VERTICAL</td></tr><tr><td>2</td><td>74.40</td><td>0.0</td><td>45.96</td><td>-28.04</td><td>74.00</td><td>59.47</td><td>35.70</td><td>11.78</td><td>60.99</td><td>100</td><td>0 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	1	49.65	0.0	45.44	-28.56	74.00	62.83	34.10	9.61	61.10	100	0 Peak	VERTICAL	2	74.40	0.0	45.96	-28.04	74.00	59.47	35.70	11.78	60.99	100	0 Peak	VERTICAL
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																					
MHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz																																																																																					
1	49.65	0.0	47.90	-26.10	74.00	65.29	34.10	9.61	61.10	300	0 Peak	HORIZONTAL																																																																																		
2	74.40	0.0	44.99	-29.02	74.00	58.49	35.70	11.78	60.99	300	0 Peak	HORIZONTAL																																																																																		
Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																					
MHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz	dBm/100kHz																																																																																					
1	49.65	0.0	45.44	-28.56	74.00	62.83	34.10	9.61	61.10	100	0 Peak	VERTICAL																																																																																		
2	74.40	0.0	45.96	-28.04	74.00	59.47	35.70	11.78	60.99	100	0 Peak	VERTICAL																																																																																		



Emission below 1GHz


2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz																																																																																																																																																													
ANT	BLE LF																																																																																																																																																													
1	Horizontal	Vertical																																																																																																																																																												
QP / Peak	Site : 030602-KS Condition : FCC PART 15C 3m CBL 61110 59913 HORIZONTAL Project : RSW 100.000KHz VSW 300.000KHz SRT Auto Model : FR262714 Plane : 0 Polarization : Full-directivity IME1 : 01 <table><tr><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100kHz</th><th>dB</th><th>dBm/100kHz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th></tr><tr><td>1</td><td>30.97</td><td>26.43</td><td>-13.57</td><td>40.00</td><td>33.37</td><td>24.70</td><td>0.76</td><td>32.40</td><td>--- Peak HORIZONTAL</td></tr><tr><td>2</td><td>159.98</td><td>21.22</td><td>-22.28</td><td>40.00</td><td>35.58</td><td>16.20</td><td>1.84</td><td>32.40</td><td>--- Peak HORIZONTAL</td></tr><tr><td>3</td><td>238.05</td><td>26.74</td><td>-19.26</td><td>40.00</td><td>39.97</td><td>17.08</td><td>2.09</td><td>32.40</td><td>--- Peak HORIZONTAL</td></tr><tr><td>4</td><td>320.03</td><td>26.54</td><td>-19.46</td><td>40.00</td><td>37.01</td><td>16.30</td><td>2.63</td><td>32.40</td><td>--- Peak HORIZONTAL</td></tr><tr><td>5</td><td>481.05</td><td>29.14</td><td>-16.86</td><td>40.00</td><td>34.99</td><td>23.42</td><td>3.14</td><td>32.40</td><td>--- Peak HORIZONTAL</td></tr><tr><td>6</td><td>704.15</td><td>34.14</td><td>-11.86</td><td>40.00</td><td>38.97</td><td>26.40</td><td>3.76</td><td>32.39</td><td>--- Peak HORIZONTAL</td></tr></table>	Line	Level	Factor	Loss	Factor	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100kHz	dB	dBm/100kHz	dB	dB	dB	dB	deg	1	30.97	26.43	-13.57	40.00	33.37	24.70	0.76	32.40	--- Peak HORIZONTAL	2	159.98	21.22	-22.28	40.00	35.58	16.20	1.84	32.40	--- Peak HORIZONTAL	3	238.05	26.74	-19.26	40.00	39.97	17.08	2.09	32.40	--- Peak HORIZONTAL	4	320.03	26.54	-19.46	40.00	37.01	16.30	2.63	32.40	--- Peak HORIZONTAL	5	481.05	29.14	-16.86	40.00	34.99	23.42	3.14	32.40	--- Peak HORIZONTAL	6	704.15	34.14	-11.86	40.00	38.97	26.40	3.76	32.39	--- Peak HORIZONTAL	Site : 030602-KS Condition : FCC PART 15C 3m CBL 61110 59913 VERTICAL Project : RSW 100.000KHz VSW 300.000KHz SRT Auto Model : FR262714 Plane : 0 Polarization : Full-directivity IME1 : 01 <table><tr><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBm/100kHz</th><th>dB</th><th>dBm/100kHz</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th></tr><tr><td>1</td><td>38.73</td><td>23.21</td><td>-16.79</td><td>40.00</td><td>34.67</td><td>25.10</td><td>0.84</td><td>32.40</td><td>--- Peak VERTICAL</td></tr><tr><td>2</td><td>40.49</td><td>24.95</td><td>-15.05</td><td>40.00</td><td>40.49</td><td>15.90</td><td>0.90</td><td>32.40</td><td>--- Peak VERTICAL</td></tr><tr><td>3</td><td>60.89</td><td>22.30</td><td>-17.64</td><td>40.00</td><td>42.02</td><td>11.60</td><td>1.14</td><td>32.40</td><td>--- Peak VERTICAL</td></tr><tr><td>4</td><td>320.03</td><td>26.54</td><td>-19.46</td><td>40.00</td><td>37.01</td><td>16.30</td><td>2.63</td><td>32.40</td><td>--- Peak VERTICAL</td></tr><tr><td>5</td><td>438.37</td><td>27.50</td><td>-18.44</td><td>40.00</td><td>34.31</td><td>22.64</td><td>3.11</td><td>32.40</td><td>--- Peak VERTICAL</td></tr><tr><td>6</td><td>703.32</td><td>32.36</td><td>-12.64</td><td>40.00</td><td>32.36</td><td>28.14</td><td>4.11</td><td>32.25</td><td>--- Peak VERTICAL</td></tr></table>	Line	Level	Factor	Loss	Factor	A/Pos	T/Pos	Remark	Pol/Phase	MHz	dBm/100kHz	dB	dBm/100kHz	dB	dB	dB	dB	deg	1	38.73	23.21	-16.79	40.00	34.67	25.10	0.84	32.40	--- Peak VERTICAL	2	40.49	24.95	-15.05	40.00	40.49	15.90	0.90	32.40	--- Peak VERTICAL	3	60.89	22.30	-17.64	40.00	42.02	11.60	1.14	32.40	--- Peak VERTICAL	4	320.03	26.54	-19.46	40.00	37.01	16.30	2.63	32.40	--- Peak VERTICAL	5	438.37	27.50	-18.44	40.00	34.31	22.64	3.11	32.40	--- Peak VERTICAL	6	703.32	32.36	-12.64	40.00	32.36	28.14	4.11	32.25	--- Peak VERTICAL
	Line	Level	Factor	Loss	Factor	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																																																					
MHz	dBm/100kHz	dB	dBm/100kHz	dB	dB	dB	dB	deg																																																																																																																																																						
1	30.97	26.43	-13.57	40.00	33.37	24.70	0.76	32.40	--- Peak HORIZONTAL																																																																																																																																																					
2	159.98	21.22	-22.28	40.00	35.58	16.20	1.84	32.40	--- Peak HORIZONTAL																																																																																																																																																					
3	238.05	26.74	-19.26	40.00	39.97	17.08	2.09	32.40	--- Peak HORIZONTAL																																																																																																																																																					
4	320.03	26.54	-19.46	40.00	37.01	16.30	2.63	32.40	--- Peak HORIZONTAL																																																																																																																																																					
5	481.05	29.14	-16.86	40.00	34.99	23.42	3.14	32.40	--- Peak HORIZONTAL																																																																																																																																																					
6	704.15	34.14	-11.86	40.00	38.97	26.40	3.76	32.39	--- Peak HORIZONTAL																																																																																																																																																					
Line	Level	Factor	Loss	Factor	A/Pos	T/Pos	Remark	Pol/Phase																																																																																																																																																						
MHz	dBm/100kHz	dB	dBm/100kHz	dB	dB	dB	dB	deg																																																																																																																																																						
1	38.73	23.21	-16.79	40.00	34.67	25.10	0.84	32.40	--- Peak VERTICAL																																																																																																																																																					
2	40.49	24.95	-15.05	40.00	40.49	15.90	0.90	32.40	--- Peak VERTICAL																																																																																																																																																					
3	60.89	22.30	-17.64	40.00	42.02	11.60	1.14	32.40	--- Peak VERTICAL																																																																																																																																																					
4	320.03	26.54	-19.46	40.00	37.01	16.30	2.63	32.40	--- Peak VERTICAL																																																																																																																																																					
5	438.37	27.50	-18.44	40.00	34.31	22.64	3.11	32.40	--- Peak VERTICAL																																																																																																																																																					
6	703.32	32.36	-12.64	40.00	32.36	28.14	4.11	32.25	--- Peak VERTICAL																																																																																																																																																					

Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE 1Mbps	83.81	2.101	0.476	0.51kHz
Bluetooth LE 2Mbps	56.37	1.058	0.945	1kHz

Bluetooth LE 1Mbps



Bluetooth LE 2Mbps

