



SAR MEASUREMENT REPORT

FCC ID: HD5-CT40PL0N

Applicant: Honeywell International Inc.
Honeywell Safety and Productivity Solutions.

Application Type: Certification

Product: Mobile Computer

Model No.: CT40P-L0N

Brand Name: Honeywell

FCC Rule Part(s): FCC 47 CFR Part 2.1093

Test Procedure(s): IEEE 1528:2013; IEEE C95.1- 2005;
KDB 447498 D01v06; KDB 865664 D01v01r04;
KDB 248227 D01v02r02; KDB 648474 D04v01r03

Test Date: July 9 ~ 20, 2020

Reviewed By:

(Jame Yuan)

Approved By:

(Robin Wu)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in IEEE1528, KDB 447498 and KDB 865664. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2006RSU069-U8	Rev. 01	Initial report	07-25-2020	Valid

CONTENTS

Description	Page
1. Introduction.....	6
1.1. Scope	6
1.2. MRT Test Location	6
2. Product Information.....	7
2.1. General Description for EUT	7
2.2. Product Specification Subjective to this Report.....	8
2.3. Description of Available Antennas	9
2.4. Ancillary Equipment.....	9
3. Summary of Test Result.....	10
3.1. Test Standards	10
3.2. Environment Condition	10
3.3. RF Exposure Limits	10
3.4. Test Result Summary	11
4. Specific Absorption Rate (SAR).....	12
4.1. Introduction.....	12
4.2. Definition	12
5. DASY6 Measurement System	13
5.1. Introduction.....	13
5.2. DASY6 Measurement System Diagram	13
5.3. System Components Details.....	14
6. The SAR Measurement Procedure	25
6.1. Measurement Process Diagram.....	25
6.2. Test Position Definition	26
6.3. Test Procedure	29
7. System Verificaiton.....	31
7.1. Tissue Check.....	31
7.2. System Check	34
8. Analysis and Results.....	36
8.1. Antenna Location.....	36
8.2. Conducted Power	37
8.3. SAR Exclusion Analysis.....	43
8.4. Required Configurations of SAR Test	53

8.5.	SAR Test Results	54
8.6.	Estimated SAR Calculation	62
9.	Simultaneous Transmission Analysis.....	63
10.	Test Equipment Used	64
11.	Measurement Uncertainty	65
Annex A - System Check Result		67
Annex B - Test Data Plots		75
Annex C - SAR Test Setup Photos.....		102
Annex D - EUT External Photos		103
Annex E - Equipment Calibration Report		104

General Information

Applicant:	Honeywell International Inc. Honeywell Safety and Productivity Solutions
Applicant Address:	9680 Old Bailes Road, Fort Mill, SC 29707 United States
Manufacturer:	Honeywell International Inc. Honeywell Safety and Productivity Solutions
Manufacturer Address:	9680 Old Bailes Road, Fort Mill, SC 29707 United States
Test Site:	MRT Technology (Suzhou) Co., Ltd
Test Site Address:	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 893164) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-20025, G-20034, C-20020, T-20020) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications, Radio and SAR testing.



1. Introduction

1.1. Scope

Measurement and determination of specific absorption rate (SAR) of radio frequency devices including intentional and/or unintentional radiators is compliance with the technical rules and regulations of the Federal Communications Commission.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The measurement facility compliant with the test site requirements specified in ANSI C63.4-2014.



2. Product Information

2.1. General Description for EUT

Product Name	Mobile Computer
Model No.	CT40P-L0N
Serial No.	1914B4105
Hardware Version	V2.0
Software Version	OS.03.001
EUT Type	Portable Device
Exposure Category	General Population/Uncontrolled Exposure
Qualcomm Chipset	
Wi-Fi Specification	802.11a/b/g/n/ac
Bluetooth Version	v5.0 dual mode
Antenna Delivery	2*TX + 2*RX
Nordic Chipset	
Bluetooth Version	v5.1 single mode, LE only
NXP Chipset	
NFC Working Frequency	13.56MHz

2.2. Product Specification Subjective to this Report

Wi-Fi Specification	
Frequency Range	<u>For 2.4GHz Wi-Fi</u> 802.11b/g/n-HT20: 2412 ~ 2462 MHz 802.11n-HT40: 2422 ~ 2452 MHz <u>For 5GHz Wi-Fi</u> 802.11a/ac-VHT20: 5180~5240 MHz, 5260~5320 MHz, 5500~5720 MHz, 5745~5825 MHz 802.11ac-VHT40: 5190~5230 MHz, 5270~5310 MHz, 5510~5710 MHz, 5755~5795 MHz 802.11ac-VHT80: 5210 MHz, 5290 MHz, 5530 MHz, 5610 MHz, 5775 MHz
Type of Modulation	802.11b: DSSS 802.11a/g/n: OFDM
Data Rate	802.11b: 1/2/5.5/11Mbps 802.11a/g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 300Mbps 802.11ac: up to 866.6Mbps
Bluetooth Specification	
Frequency Range	2400MHz~ 2483.5MHz
Channel Spacing	For Bluetooth: 1MHz For BT-LE: 2MHz
Type of Modulation	1Mbps (GFSK), 2Mbps (Pi/4 DQPSK), 3Mbps (8DPSK)

2.3. Description of Available Antennas

Operating Condition	802.11b/g/n for 2.4GHz Wi-Fi (1Tx, 1Rx) 802.11n for 2.4GHz Wi-Fi (2Tx, 2Rx) 802.11a/ac for 5GHz Wi-Fi (1Tx, 1Rx) 802.11ac for 5GHz Wi-Fi (2Tx, 2Rx) Bluetooth BR/EDR/LE (1Tx, 1Rx)	
Antenna Type	FPC Antenna	
Antenna Gain	Ant 0	2400 ~ 2483.5MHz: 0.60dBi 5150 ~ 5350MHz: 1.30dBi 5470 ~ 5725MHz: 1.30dBi 5725 ~ 5850MHz: 1.80dBi
	Ant 1	2400 ~ 2483.5MHz: 2.20dBi 5150 ~ 5350MHz: 3.35dBi 5470 ~ 5725MHz: 3.35dBi 5725 ~ 5850MHz: 2.48dBi
Simultaneously Transmitting Scenarios	Ant 0 transmit simultaneously with Ant1	

Note: SISO mode only support Ant 0 port.

2.4. Ancillary Equipment

Ancillary Equipment 1	Adapter
Model No.	ADS-12B-06 05010E
Input	100-240V ~ 50/60Hz, 0.3A
Output	5V=2.0A
Ancillary Equipment 2	Battery
Brand Name	Honeywell
Model No.	CT50-BTSC
Capacity	4020mAh/15.5Wh
Rated Voltage	DC 3.85V

3. Summary of Test Result

3.1. Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	IEEE 1528-2013	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
3	IEEE C95.1-2005	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
4	KDB 447498 D01 v06	General RF Exposure Guidance
5	KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	KDB 865664 D02 v01r02	RF Exposure Reporting
7	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitter
8	KDB 648474 D04v01r03	Sar Evaluation Considerations for Wireless Handsets

3.2. Environment Condition

Ambient Temperature	20.5°C~24.0°C
Temperature of Simulant	20.0°C~23.5°C
Relative Humidity	38%RH ~55%RH

3.3. RF Exposure Limits

Human Exposure	Basic restrictions for electric, magnetic and electromagnetic fields. (Unit in mW/g or W/kg)
Spatial Peak SAR ¹ (Head and Body)	1.60
Spatial Average SAR ² (Whole Body)	0.08
Spatial Peak SAR ³ (Arms and Legs)	4.00

Notes:

1. The Spatial Peak value of the SAR averaged over any 1gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over appropriate averaging time.

3.4. Test Result Summary

Worst SAR List

Highest Reported SAR	Ant 0		
	Head 1g SAR (W/kg)	Body-worn 1g SAR (W/kg)	Extremity 10g SAR (W/kg)
DTS Band Wi-Fi	0.63	0.57	0.70
U-NII-2A Band Wi-Fi	0.23	0.59	0.53
U-NII-2C Band Wi-Fi	0.31	0.82	0.51
U-NII-3 Band Wi-Fi	0.42	0.78	0.52
Bluetooth	0.11	0.10	0.06

Highest Simultaneous SAR

Highest Simultaneous SAR	Head 1g SAR (W/kg)	Body 1g SAR (W/kg)	Extremity 10g SAR (W/kg)
Ant 0 + Ant 1	1.37	0.86	0.96

4. Specific Absorption Rate (SAR)

4.1. Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational /controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

4.2. Definition

The SAR in the tissue-equivalent liquid can be determined by the rate of temperature increase or by E-field measurements, according to Formulas (1) or (2):

$$SAR = \frac{\sigma E^2}{\rho} \quad (1)$$

$$SAR = c_h \left. \frac{dT}{dt} \right|_{t=0} \quad (2)$$

where

- SAR is the specific absorption rate in W/kg;
- E is the rms value of the electric field strength in the tissue medium in V/m;
- σ is the electrical conductivity of the tissue medium in S/m;
- ρ is the mass density of the tissue medium in kg/m³;
- c_h is the specific heat capacity of the tissue medium in J/(kg K);

$\left. \frac{dT}{dt} \right|_{t=0}$ is the initial time derivative of temperature in the tissue medium in K/s.


5. DASY6 Measurement System

5.1. Introduction

DASY6 is the latest generation of the Dosimetric Assessment System optimized for specific absorption rate (SAR) measurements, SAR compliance. DASY6 builds on the power of our industry - leading dosimetric and near-field evaluation system, DASY52. Running on a significantly more robust platform and a more powerful measurement server, DASY6 offers much faster scanning with no sacrifice of measurement precision. All hardware and software are fully compatible with DASY52. The new system seamlessly integrates two software solutions, the novel cDASY V6.6 - optimized for SAR compliance testing to significantly reduce SAR assessment costs - and the widely used DASY V5.2 for generalized near-field evaluations with maximized flexibility.

5.2. DASY6 Measurement System Diagram

The DASY6 system in cDASY6/DASY5 V5.2 SAR Configuration is shown below:



The System consist of the following components:

DASY6 Measurement Server, Data Acquisition Electronics (DAE), Probes, Light-Beam Unit, Phantoms, Media, Device Holder for SAM-Twin Phantom, Laptop Extension Kit to Mounting Device, Robot System Platform & Pedestal, Verification of the Parameters with the Dielectric Assessment Kit (DAK), Modulation and Interference Analyzer (MAIA), Omni-Directional Ultra-Wideband Antenna (ANT), cDASY6 software, DASY5 NEO software and SEMCAD data evaluation software.

5.3. System Components Details

DASY6 Platforms MP6E-TX60L

MP6E-TX60L platform is a compact cost-effective platform based on TX60L. It consists of:

- a stable non-metallic platform for the TX60L robot
- a frame for two standard-size phantoms (1.0×0.5 m)
- a frame for one half-size phantom (0.5×0.5 m)

It includes two easily moveable trolleys for the phone and tablet/computer positioner and two platforms for positioning dipoles and other antennas.



Material The beams consist of a composite of wood and epoxy (permittivity of 3.3 and loss tangent of <0.07)

Size The footprint of the platform is 1590 mm $\times$ 1060 mm.

Robots -TX60L

The MRT DASY6 system uses the high-precision industrial robots TX60L from Staubli SA (France). The TX robot family - the successor of the well-known RX robot family - continues to offer the features important for DASY6 applications:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance-free as all gears are direct drive, no belt drives)
- Jerk-free straight movements (brushless synchron motors, no stepper motors)
- Low extremely low frequency (ELF) interference (motor control fields are shielded by the closed metallic construction)

The robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is provided on CDs delivered with the robot. Paper manuals are available directly from Staubli upon request.




DASY6 Measurement Server

The DASY6 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 electronics box, as well as the 16-bit AD converter system for optical detection and digital I/O interface are contained on the DASY6 I/O board, which is directly connected to the PC/104 bus of the CPU board. The measurement server performs all real-time data evaluations of field measurements and surface detection, controls robot movements, and handles safety operations.



Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter, and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



Probes

E-Field Probe(EX3DV4)

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN 62209-1, IEC 62209, etc.) under ISO 17025.

Construction:

Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

Frequency: 4 MHz ~ 10 GHz

Linearity: ± 0.2 dB (30 MHz ~ 10 GHz)

Directivity:

± 0.1 dB in TSL (rotation around probe axis)

± 0.3 dB in TSL (rotation normal to probe axis)

Dynamic Range: 10 μ W/g to 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)

Dimensions:

Overall length: 337 mm (Tip: 20 mm)

Tip diameter: 2.5 mm (Body: 12 mm)

Typical distance from probe tip to dipole centers: 1 mm

Applications:

High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better than 30%.



MSTV1 (Mother Scan Teaching V1) Electronics & TP6V2 (Teaching Probe 6V2) Probe

MSTV1 (Mother Scan Teaching V1) electronics together with the TP6V2 (Teaching Probe 6V2) probe is used for mother scan of DASY6 system. This probe uses a 3D Renishaw LP2 sensor which ensures accurate detection of any shape and a measurement repeatability of 8 μ m.



Light-Beam Unit

The light beam switch allows automatic "tooling" of the probe. During the process, the actual position of the probe tip with respect to the robot arm, as well as the probe length and the horizontal probe offset, are measured. The software then corrects all movements within the measurement jobs, such that the robot coordinates are valid for the probe tip.



The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.

Phantoms

SAM-Twin Phantom

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body-mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

SAM-Twin V5.0 and higher has the same shell geometry and is manufactured from the same material as SAM-Twin V4.0, but with the top structure reinforced.

Material Vinyl ester, fiberglass reinforced (VE-GF)

Liquid Compatibility The phantom shell is compatible with SPEAG tissue simulating liquids (sugar and oil based). Use of other liquids may render the phantom warranty void (see note or consult SPEAG support).

Shell Thickness 2 ± 0.2 mm (6 ± 0.2 mm at ear point)

Dimensions Length: 1000 mm
(incl. Wooden Width: 500 mm
Support) Height: adjustable feet

Filling Volume approx. 25 liters

Support DASY6: standard-size platform slot
DASY52 stand-alone: SPEAG standard phantom table



ELI phantom

The ELI phantom is used for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 and higher has the same shell geometry and is manufactured from the same material as ELI V4.0, but has reinforced top structure. ELI V6.0, released in August 2014, has the same shell geometry as ELI V4.0 but offers increased longterm stability.


Material	Vinyl ester, fiberglass reinforced (VE-GF)
Liquid Compatibility	The phantom shell is compatible with SPEAG tissue simulating liquids (sugar and oil based). Use of other liquids may render the phantom warranty void (see note or consult SPEAG support).
Shell Thickness	2.0 ± 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	approx. 30 liters
Support	DASY6: standard-size platform slot DASY52 stand-alone: SPEAG standard phantom table



SAM Face Down Phantom

The SAM Face Down Phantom V10 allows assessment of the exposure of the face and in particular the eyes for handheld devices operated in front of the face. e.g., video phones, cameras, organizers, etc. It is manufactured from high precision injection molded polypropylene. The Mounting Device for Transmitters including extensions kit can be used to position the device.


Material	Epoxy based
Liquid Compatibility	The phantom shell is compatible with SPEAG tissue simulating liquids (sugar and oil based). Use of other liquids may render the phantom warranty void (see note or consult SPEAG support).
Shell Thickness	2 ± 0.2 mm (6 mm at ear point)
Head Shape	Standard compatible SAM head.



SAM Head Stand Phantom

The SAM Head Stand Phantom V10 allows assessment of the exposure of the top-head or around-the-head wireless accessories, e.g., head-belts, etc. It is manufactured from high precision injection molded polypropylene. The Mounting Device for Transmitters including extensions kit can be used to position the device.

Material	Epoxy based
Liquid Compatibility	The phantom shell is compatible with SPEAG tissue simulating liquids (sugar and oil based). Use of other liquids may render the phantom warranty void (see note or consult SPEAG support).
Shell Thickness	2 ± 0.2 mm (6 mm at ear point)
Head Shape	Standard compatible SAM head.



Wrist Phantom

The Wrist Phantom V10 is shape-compatible with the CTIA approved OTA GFPC-V1 and optimized for SAR evaluation of watches and other wireless hand accessories.

Material	Epoxy based
Liquid Compatibility	The phantom shell is compatible with SPEAG tissue simulating liquids (sugar and oil based). Use of other liquids may render the phantom warranty void (see note or consult SPEAG support).
Shell Thickness	Shell Thickness
Wrist Shape	Design compatible with CTIA forearm.



Device Holder for SAM-Twin Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of $\pm 0.5\text{mm}$ would produce uncertainty in the SAR of $\pm 20\%$. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions at which the devices must be measured are defined by the standards.

MD4HHTV5 - Mounting Device for Hand-Held Transmitters

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).

Material: Polyoxymethylene (POM)



MDA4WTV5 - Mounting Device Adaptor for Ultra Wide Transmitters

An upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.

Material: Polyoxymethylene (POM)



MDA4SPV6 - Mounting Device Adaptor for Smart Phones

The solid low-density MDA4SPV6 adaptor assuring no impact on the DUT radiation performance and is conform with any DUT design and shape.

Material: ROHACELL



MD4LAPV5 - Mounting Device for Laptops and other Body-Worn Transmitters

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device (Body-Worn) enables testing of transmitter devices according to IEC 62209-2 specifications. The device holder can be locked for positioning at a flat phantom section.

Material: Polyoxymethylene (POM), PET-G, Foam



MDA4LAP - Mounting Device Adaptor for Laptops

A simple but effective and easy-to-use extension for the Mounting Device; facilitates testing of larger devices (e.g., laptops, cameras, etc.) according to IEC 62209-2; lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin SAM as well as ELI and other Flat Phantoms.

Material: Polyoxymethylene (POM), PET-G, Foam



Modulation and Interference Analyzer(MAIA)

MAIA is a hardware interface used to evaluate the modulation and audio interference characteristics of RF signals in the frequency range 698 - 6000 MHz. DASY6 evaluates the time-domain and frequency domain properties of the uplink signal transmitted by the DUT during SAR measurement with MAIA. MAIA uses USB powered active electronics to identify the modulation of the DUT. It can be operated over the air interface using the built-in ultra-broadband planar log spiral antenna (698 - 6000 MHz) or in conducted mode using the coaxial SMA 50 Ohm connector (300 - 6000 MHz).



To prevent damage in conducted mode due to high peak power, an external RF attenuator may be mounted. The LED on the MAIA hardware also indicates whether it is connected.

DAK-3.5 (200MHz – 20GHz)

This precision dielectric measurement system is designed to cover the 200MHz – 20GHz frequency range with a single open-ended coaxial dielectric probe. The system uses advanced algorithms and novel hardware to measure the dielectric properties of liquids, solids, and semi-solids over a broad range of parameters. The measurement method is fast and non-destructive to the material under test.



Evaluation of reference liquids over a broad frequency range for specific absorption rate (SAR) measurements, in accordance with IEC 62209, IEEE 1528, and several federal regulations.

Evaluating Software: DAK software version 2.0

MRT simulating liquid

Product	Test Frequency (MHz)	Main Ingredients
HSL450	400 – 500	Water, Sucrose, NaCl
MSL450	400 – 500	Water, Sucrose, NaCl

Speag Broad-Band simulating liquid



Product	Test Frequency (MHz)	Main Ingredients
HBBL600-10000V6	600 – 10000	Water, Oil
MBBL600-6000V6	600 – 6000	Water, Oil

6. The SAR Measurement Procedure

6.1. Measurement Process Diagram

General Procedure

For IEEE1528-2013 Head SAR





For Body SAR


SAR scan procedures described in section 2.7 of KDB 865664 D01 v01r04 should be applied to body SAR test.

6.2. Test Position Definition

■ Head SAR Test Position


Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output [point A in Fixed case and Clamshell case], and the midpoint of the width w_b at the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output [see Fixed case]. The horizontal line is also tangential to the face of the handset at point A. The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset [see Clamshell case], especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets, the vertical centerline passes through point A but not the tip edge of the phone.





Key

- B Direction of B-M line back endpoint
- F Direction of N-F line front endpoint
- N Direction of N-F line neck endpoint
- M Mouth reference point
- LE Left ear reference point (ERP)




Key

- B Line B-M back endpoint
- M Line B-M front endpoint
- N Line N-F neck endpoint
- F Line N-F front endpoint
- RE Right ear reference point (ERP)

Cheek Position

The cheek position has the following characteristics, based on the geometrical lines described above:

- The N-F line (see above) is in the plane defined by the handset vertical centerline and horizontal line
- Handset touches the pinna
- The handset vertical centerline is aligned with the Reference Plane.




Key

- M Mouth reference point
- LE Left ear reference point
- RE Right ear reference point

Tilt Position

The tilt position is established as follows:

- Repeat the steps to place the device in the cheek position.
- While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15° .
- Rotate the handset around the horizontal line by 15° .
- While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point on the handset is in contact with the phantom, e.g., the antenna with the back of the head.



Key

- | | |
|----|---------------------------|
| M | Mouth reference point |
| LE | Left ear reference point |
| RE | Right ear reference point |

■ Body SAR Test Position

For body-worn accessory, hotspot mode and other exposure conditions to human body should be conducted pursuant to the test position requirements of SAR KDBs for certain product.

6.3. Test Procedure

Step 1 Setup a Connection

First, engineer should record the conducted power before the test. Then establish a call in handset at the maximum power level with a base station simulator via air interface, or make the EUT establish transmission by itself in testing band. Place the EUT to certain test position.

Step 2 Power Reference Measurements

To measure the local E-field value at a fixed location which value will be taken as a reference value for calculating a possible power drift.

Step 3 Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01v01r04

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 mm ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 - 3 GHz: ≤ 12 mm	3 - 4 GHz: ≤ 12 mm 4 - 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.		

Step 4 Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB 865664 D01 v01r04

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: Δx _{Zoom} , Δy _{Zoom}			≤ 2 GHz: ≤ 8 mm 2 - 3 GHz: ≤ 5 mm*	3 - 4 GHz: ≤ 5 mm* 4 - 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz _{Zoom} (n)		≤ 5 mm	3 - 4 GHz: ≤ 4 mm 4 - 5 GHz: ≤ 3 mm 5 - 6 GHz: ≤ 2 mm
	graded grid	Δz _{Zoom} (1): between 1 st two points closest to phantom surface	≤ 4 mm	3 - 4 GHz: ≤ 3 mm 4 - 5 GHz: ≤ 2.5 mm 5 - 6 GHz: ≤ 2 mm
		Δz _{Zoom} (n>1): between subsequent points	≤ 1.5·Δz _{Zoom} (n-1) mm	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3-4 GHz: ≥ 28 mm 4-5 GHz: ≥ 25 mm 5-6 GHz: ≥ 22 mm
Note: * When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 5 Power Drift Measurements

Repetition of the E-field measurement at the fixed location mentioned in Step 1 to make sure the two results differ by less than ± 0.2 dB.


Step 6 Test Data



After the test, SAR test data should be exported by SEMCAD.

7. System Verificaiton

7.1. Tissue Check

- Refer to KDB 865664 D01 v01r04, the depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm with $\leq \pm 0.5$ cm variation for SAR measurements ≤ 3 GHz and ≥ 10.0 cm with $\leq \pm 0.5$ cm variation for measurements > 3 GHz.

15cm Depth Head Tissue for ≤ 3 GHz band

10cm Depth Head Tissue for > 3 GHz band

15cm Depth Head Tissue for ≤ 3 GHz band

10cm Depth Head Tissue for > 3 GHz band


■ Dielectric properties of the head tissue-equivalent liquid

Frequency MHz	Relative Permittivity ϵ_r	Conductivity (σ) S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
<i>1 450</i>	<i>40.5</i>	<i>1.20</i>
<i>1 500</i>	<i>40.4</i>	<i>1.23</i>
<i>1 640</i>	<i>40.2</i>	<i>1.31</i>
<i>1 750</i>	<i>40.1</i>	<i>1.37</i>
1 800	40.0	1.40
1 900	40.0	1.40
2 000	40.0	1.40
<i>2 100</i>	<i>39.8</i>	<i>1.49</i>
<i>2 300</i>	<i>39.5</i>	<i>1.67</i>
2 450	39.2	1.80
<i>2 600</i>	<i>39.0</i>	<i>1.96</i>
3 000	38.5	2.40
<i>3 500</i>	<i>37.9</i>	<i>2.91</i>
<i>4 000</i>	<i>37.4</i>	<i>3.43</i>
<i>4 500</i>	<i>36.8</i>	<i>3.94</i>
<i>5 000</i>	<i>36.2</i>	<i>4.45</i>
<i>5 200</i>	<i>36.0</i>	<i>4.66</i>
<i>5 400</i>	<i>35.8</i>	<i>4.86</i>
<i>5 600</i>	<i>35.5</i>	<i>5.07</i>
<i>5 800</i>	<i>35.3</i>	<i>5.27</i>
<i>6 000</i>	<i>35.1</i>	<i>5.48</i>

Note: For convenience, permittivity and conductivity values at those frequencies which are not part of the original data provided by Drossos et al. [33] or the extension to 5800MHz are provided (i.e. the values shown in italics). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6000MHz that were linearly extrapolated from the values at 3000MHz and 5800MHz.

■ Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using DASY6 Dielectric Assessment Kit and keysight PNA-L Network Analyzer N5234B.

Tissue parameter for Head								
Freq. (MHz)	Perm.	Cond.	Target Perm.	Target Cond.	Deviation Perm. %	Deviation Cond. %	Tissue Temperature	Test Date
2450	40.00	1.85	39.20	1.80	2.04	2.78	22.5°C	2020.07.09
5250	35.12	4.55	35.93	4.71	-2.25	-3.40	22.5°C	2020.07.10
5600	34.51	4.94	35.53	5.07	-2.87	-2.56	22.5°C	2020.07.11
5750	34.24	5.11	35.36	5.22	-3.17	-2.11	22.5°C	2020.07.13
2450	40.60	1.83	39.20	1.80	3.57	1.67	22.5°C	2020.07.14
5250	35.90	4.61	35.93	4.71	-0.08	-2.12	22.5°C	2020.07.15
5600	35.27	5.01	35.53	5.07	-0.73	-1.18	22.5°C	2020.07.16
5750	34.98	5.19	35.36	5.22	-1.07	-0.57	22.5°C	2020.07.20


Note: The $\pm 5\%$ deviation of tissue parameter is recommended.

7.2. System Check

■ Purpose

The purpose of the system check is to verify that the system operates within its specifications at the device test frequencies. System check verifies the measurement repeatability of a SAR system before compliance testing and is not a validation of all system specifications. The latter is not required for testing a device but is mandatory before the system is deployed.

■ System Performance Check Setup Diagram



■ System Check Procedure

The system check procedure is a complete 1g and 10g peak spatial-average SAR measurement using a source having a previously determined system check target value. The measured 1g and 10g SAR are normalized to the target input power of the specific source and compared to their respective target values. A description of the different measurement tasks to be performed is given below, together with the information that can be deduced from their results:

- The Power Reference Measurement and Power Drift Measurement are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the amplifier output power. If it is too high (above ± 0.1 dB), the system check should be repeated; some amplifiers have very high drift during warm-up. A stable amplifier gives drift results in the DASY6 system below ± 0.02 dB.

- b. The second step is optional. For probes with integrated optical surface detection sensor this step must be conducted, otherwise the step can be skipped. The Surface Check tests the optical surface detection system of the DASY6 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1 mm). In that case it is better to abort the system check and stir the liquid.
- c. The Area Scan measures the SAR above the dipole on a plane parallel to the surface. It is used to locate the approximate location of the peak SAR. The proposed scan uses large grid spacing for faster measurement; due to the symmetric field, the peak detection is reliable. If a finer graphic is desired, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result.
- d. The Zoom Scan measures the field in a volume around the peak SAR value assessed in the previous Area Scan.

If the system check gives reasonable results, the SAR peak, 1 g and 10 g spatial average SAR values normalized to 1 W dipole input power give reference data for comparisons. The next sections analyze the expected uncertainties of these values, as well as additional checks for further information or troubleshooting.

■ Result of System Performance Check


System check for Head								
Freq. (MHz)	1g SAR (W/kg)	10g SAR (W/kg)	Target 1g SAR (W/kg)	Target 10g SAR (W/kg)	Deviation 1g SAR (%)	Deviation 10g SAR (%)	Tissue Temp.	Test Date
2450	54.00	24.84	52.10	24.40	3.65	1.80	22.5°C	2020.07.09
5250	78.40	22.30	81.70	23.30	-4.04	-4.29	22.5°C	2020.07.10
5600	80.70	22.60	85.40	24.30	-5.50	-7.00	22.5°C	2020.07.11
5750	74.80	21.10	79.10	22.50	-5.44	-6.22	22.5°C	2020.07.13
2450	52.80	24.56	52.10	24.40	1.34	0.66	22.5°C	2020.07.14
5250	81.90	23.50	81.70	23.30	0.24	0.86	22.5°C	2020.07.15
5600	84.90	24.10	85.40	24.30	-0.59	-0.82	22.5°C	2020.07.16
5750	79.10	22.40	79.10	22.50	0.00	-0.44	22.5°C	2020.07.20

Note:

1. The $\pm 10\%$ deviation of system check result is required.
2. System check value listed above has been harmonized to 1W.

8. Analysis and Results

8.1. Antenna Location



Note: The overall diagonal dimension of EUT is 175mm.

Antenna Distance to Surfaces/Edges (mm)						
Antenna configuration	Front-side	Back-side	Left-side	Right-side	Top-side	Bottom-side
Ant 0	6	9	4	72	72	69
Ant 1	7	7	64	4	4	136

8.2. Conducted Power

■ DTS Band Wi-Fi - SISO Mode

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
b	1	2412	17.77	19.0	N/A	N/A	98.78
	6	2437	17.73	19.0	N/A	N/A	
	11	2462	17.89	19.0	N/A	N/A	
g	1	2412	14.72	16.0	N/A	N/A	95.06
	6	2437	14.67	16.0	N/A	N/A	
	11	2462	14.87	16.0	N/A	N/A	
n (HT20)	1	2412	14.92	16.0	15.62	16.0	95.19
	6	2437	17.22	19.0	15.53	16.0	
	11	2462	16.78	18.0	15.42	16.0	
n (HT40)	3	2422	15.02	16.0	13.43	14.0	91.46
	6	2437	16.61	18.0	15.26	16.0	
	9	2452	13.97	15.0	14.30	15.0	

Note: Ant 1 SISO mode is only used to evaluated simultaneous transmission.

■ DTS Band Wi-Fi - MIMO Mode

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
802.11n (HT20)	1	2412	13.71	15.0	14.83	15.0	95.19
	6	2437	13.76	15.0	14.67	15.0	
	11	2462	13.83	15.0	14.64	15.0	
802.11n (HT40)	3	2422	12.04	14.0	12.46	14.0	91.46
	6	2437	13.87	15.0	14.81	15.0	
	9	2452	13.16	15.0	13.57	15.0	

■ U-NII-1 Band Wi-Fi - SISO

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
a	36	5180	15.28	16.0	N/A	N/A	94.81
	44	5220	15.27	16.0	N/A	N/A	
	48	5240	15.25	16.0	N/A	N/A	
ac (VHT20)	36	5180	15.21	16.0	12.66	14.0	94.47
	44	5220	15.19	16.0	12.47	14.0	
	48	5240	15.25	16.0	13.48	14.0	
ac (VHT40)	38	5190	13.34	14.0	10.53	11.0	90.24
	46	5230	13.31	14.0	10.25	11.0	
ac (VHT80)	42	5210	9.52	11.0	8.18	9.0	84.75

Note: Ant 1 SISO mode is only used to evaluated simultaneous transmission.

■ U-NII-1 Band Wi-Fi - MIMO

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
ac (VHT20)	36	5180	11.30	13.0	11.98	13.0	95.45
	44	5220	11.39	13.0	11.87	13.0	
	48	5240	12.04	13.0	12.65	13.0	
ac (VHT40)	38	5190	9.45	11.0	10.26	11.0	91.63
	46	5230	9.52	11.0	9.83	11.0	
ac (VHT80)	42	5210	6.54	8.0	7.56	8.0	84.36

■ U-NII-2A Band Wi-Fi - SISO

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
a	52	5260	15.24	16.0	N/A	N/A	94.81
	60	5300	15.13	16.0	N/A	N/A	
	64	5320	15.31	16.0	N/A	N/A	
ac (VHT20)	52	5260	15.22	16.0	13.49	14.0	94.47
	60	5300	15.14	16.0	13.52	14.0	
	64	5320	15.25	16.0	13.41	14.0	
ac (VHT40)	54	5270	13.25	14.0	10.33	12.0	90.24
	62	5310	13.13	14.0	11.24	12.0	
ac (VHT80)	58	5290	9.54	11.0	7.84	8.0	84.75

Note: Ant 1 SISO mode is only used to evaluated simultaneous transmission.

■ U-NII-2A Band Wi-Fi - MIMO

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
ac (VHT20)	52	5260	11.94	13.0	12.58	13.0	95.45
	60	5300	11.98	13.0	12.45	13.0	
	64	5320	12.15	13.0	12.46	13.0	
ac (VHT40)	54	5270	9.21	11.0	9.78	11.0	91.63
	62	5310	10.11	11.0	10.52	11.0	
ac (VHT80)	58	5290	6.56	8.0	7.49	8.0	84.36

■ U-NII-2C Band Wi-Fi - SISO

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
a	100	5500	15.38	16.0	N/A	N/A	94.81
	116	5580	15.16	16.0	N/A	N/A	
	140	5700	15.13	16.0	N/A	N/A	
	144	5720	15.16	16.0	N/A	N/A	
ac (VHT20)	100	5500	15.27	16.0	13.12	14.0	94.47
	116	5580	15.17	16.0	13.11	14.0	
	140	5700	15.24	16.0	13.08	14.0	
	144	5720	15.18	16.0	12.96	14.0	
ac (VHT40)	102	5510	13.26	14.0	10.88	12.0	90.24
	110	5550	13.18	14.0	10.74	12.0	
	134	5670	13.37	14.0	10.79	12.0	
	142	5710	13.30	14.0	10.69	12.0	
ac (VHT80)	106	5530	9.74	11.0	7.52	8.0	84.75
	112	5610	9.68	11.0	7.36	8.0	
	138	5690	9.54	11.0	7.41	8.0	

Note: Ant 1 SISO mode is only used to evaluated simultaneous transmission.

■ U-NII-2C Band Wi-Fi - MIMO

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
ac (VHT20)	100	5500	12.29	13.0	12.35	13.0	95.45
	116	5580	12.03	13.0	12.23	13.0	
	140	5700	12.35	13.0	12.37	13.0	
	144	5720	12.27	13.0	12.23	13.0	
ac (VHT40)	102	5510	10.42	11.0	10.45	11.0	91.63
	110	5550	10.39	11.0	10.51	11.0	
	134	5670	10.42	11.0	10.46	11.0	
	142	5710	10.37	11.0	10.42	11.0	
ac (VHT80)	106	5530	6.61	8.0	7.21	8.0	84.36
	112	5610	6.79	8.0	6.95	8.0	
	138	5690	6.84	8.0	6.93	8.0	

■ U-NII-3 Band Wi-Fi - SISO

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
a	149	5745	15.24	16.0	N/A	N/A	94.81
	157	5785	15.03	16.0	N/A	N/A	
	165	5825	14.81	16.0	N/A	N/A	
ac (VHT20)	149	5745	15.16	16.0	13.16	14.0	94.47
	157	5785	14.95	16.0	13.27	14.0	
	165	5825	14.78	16.0	13.35	14.0	
ac (VHT40)	151	5755	13.10	14.0	10.64	11.0	90.24
	159	5795	12.84	14.0	10.76	11.0	
ac (VHT80)	155	5775	9.51	11.0	7.57	8.0	84.75

Note: Ant 1 SISO mode is only used to evaluated simultaneous transmission.

■ U-NII-3 Band Wi-Fi - MIMO

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Ant 1 Average Power (dBm)	Ant 1 Tune-up Limit Power (dBm)	Duty Cycle %
ac (VHT20)	149	5745	12.22	13.0	12.52	13.0	95.45
	157	5785	11.99	13.0	12.55	13.0	
	165	5825	11.73	13.0	12.68	13.0	
ac (VHT40)	151	5755	10.24	11.0	10.39	11.0	91.63
	159	5795	9.98	11.0	10.36	11.0	
ac (VHT80)	155	5775	6.82	8.0	6.96	8.0	84.36

Bluetooth - 1#

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)	Duty Cycle %
DH5	0	2402	5.21	6.0	76.66
	39	2441	4.29	6.0	
	78	2480	6.45	7.0	
2DH5	0	2402	8.73	9.0	76.87
	39	2441	7.55	9.0	
	78	2480	8.93	9.5	
3DH5	0	2402	9.07	10.0	76.71
	39	2441	7.55	9.0	
	78	2480	8.65	9.0	
BLE 1Mbps	0	2402	1.36	2.0	62.26
	19	2440	0.31	2.0	
	39	2480	0.56	2.0	
BLE 2Mbps	0	2402	1.34	2.0	32.43
	19	2440	0.26	2.0	
	39	2480	0.52	2.0	

Bluetooth - 2#

Mode	CH.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 0 Tune-up Limit Power (dBm)
BLE 1Mbps	0	2402	0.48	2.0
	19	2440	0.81	2.0
	39	2480	1.17	2.0
BLE 2Mbps	0	2402	0.52	2.0
	19	2440	0.84	2.0
	39	2480	1.18	2.0

8.3. SAR Exclusion Analysis

Per FCC KDB 447498 D01v06, the SAR exclusion threshold for distances < 50 mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Distance (mm)}} \times \sqrt{\text{Frequency (GHz)}} \leq 3.0, \text{ for head and body SAR;}$$

For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

- 1) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance – 50 mm) * (f(MHz)/150)]} mW, for 100 MHz to 1500 MHz
- 2) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance – 50 mm)*10]} mW, for > 1500 MHz and ≤ 6 GHz

Antenna Distance to User (mm)						
Antenna configuration	Front-side	Back-side	Left-side	Right-side	Top-side	Bottom-side
Ant 0	6	9	4	72	72	69
Ant 1	7	7	64	4	4	136

Note:

1. Antenna to User distance = Antenna to out-surface of EUT distance + Out-surface of EUT to User distance.
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

6mm Ant 0 Distance to Front Side

Band	Mode	Channel	Frequency (MHz)	Ant-to-user distance (mm)	Thresholds (mW)	Tune-up Power		SAR Test (Y/N)
						dBm	mW	
DTS	b	1	2412	6	11.59	19.0	79.43	Y
		6	2437	6	11.53	19.0	79.43	Y
		11	2462	6	11.47	19.0	79.43	Y
U-NII-1	a	36	5180	6	7.91	16.0	39.81	Y
		44	5220	6	7.88	16.0	39.81	Y
		48	5240	6	7.86	16.0	39.81	Y
U-NII-2A	a	52	5260	6	7.85	16.0	39.81	Y
		60	5300	6	7.82	16.0	39.81	Y
		64	5320	6	7.80	16.0	39.81	Y
U-NII-2C	a	100	5500	6	7.68	16.0	39.81	Y
		116	5580	6	7.62	16.0	39.81	Y
		140	5700	6	7.54	16.0	39.81	Y
		144	5720	6	7.53	16.0	39.81	Y
U-NII-3	a	149	5745	6	7.51	16.0	39.81	Y
		157	5785	6	7.48	16.0	39.81	Y
		165	5825	6	7.46	16.0	39.81	Y
DSS	3DH5	0	2402	6	11.61	10.0	10.00	N
		39	2441	6	11.52	9.0	7.94	N
		78	2480	6	11.43	9.0	7.94	N

9mm Ant 0 Distance to Back Side

Band	Mode	Channel	Frequency (MHz)	Ant-to-user distance (mm)	Thresholds (mW)	Tune-up Power		SAR Test (Y/N)
						dBm	mW	
DTS	b	1	2412	9	17.39	19.0	79.43	Y
		6	2437	9	17.30	19.0	79.43	Y
		11	2462	9	17.21	19.0	79.43	Y
U-NII-1	a	36	5180	9	11.86	16.0	39.81	Y
		44	5220	9	11.82	16.0	39.81	Y
		48	5240	9	11.80	16.0	39.81	Y
U-NII-2A	a	52	5260	9	11.77	16.0	39.81	Y
		60	5300	9	11.73	16.0	39.81	Y
		64	5320	9	11.71	16.0	39.81	Y
U-NII-2C	a	100	5500	9	11.51	16.0	39.81	Y
		116	5580	9	11.43	16.0	39.81	Y
		140	5700	9	11.31	16.0	39.81	Y
		144	5720	9	11.29	16.0	39.81	Y
U-NII-3	a	149	5745	9	11.26	16.0	39.81	Y
		157	5785	9	11.23	16.0	39.81	Y
		165	5825	9	11.19	16.0	39.81	Y
DSS	3DH5	0	2402	9	17.42	10.0	10.00	N
		39	2441	9	17.28	9.0	7.94	N
		78	2480	9	17.15	9.0	7.94	N

4mm Ant 0 Distance to Left Side

Band	Mode	Channel	Frequency (MHz)	Ant-to-user distance (mm)	Thresholds (mW)	Tune-up Power		SAR Test (Y/N)
						dBm	mW	
DTS	b	1	2412	5	9.66	19.0	79.43	Y
		6	2437	5	9.61	19.0	79.43	Y
		11	2462	5	9.56	19.0	79.43	Y
U-NII-1	a	36	5180	5	6.59	16.0	39.81	Y
		44	5220	5	6.57	16.0	39.81	Y
		48	5240	5	6.55	16.0	39.81	Y
U-NII-2A	a	52	5260	5	6.54	16.0	39.81	Y
		60	5300	5	6.52	16.0	39.81	Y
		64	5320	5	6.50	16.0	39.81	Y
U-NII-2C	a	100	5500	5	6.40	16.0	39.81	Y
		116	5580	5	6.35	16.0	39.81	Y
		140	5700	5	6.28	16.0	39.81	Y
		144	5720	5	6.27	16.0	39.81	Y
U-NII-3	a	149	5745	5	6.26	16.0	39.81	Y
		157	5785	5	6.24	16.0	39.81	Y
		165	5825	5	6.22	16.0	39.81	Y
DSS	3DH5	0	2402	5	9.68	10.0	10.00	Y
		39	2441	5	9.60	9.0	7.94	N
		78	2480	5	9.53	9.0	7.94	N

72mm Ant 0 Distance to Right/Top Side

Band	Mode	Channel	Frequency (MHz)	Ant-to-user distance (mm)	Thresholds (mW)	Tune-up Power		SAR Test (Y/N)
						dBm	mW	
DTS	b	1	2412	72	316.58	19.0	79.43	N
		6	2437	72	316.09	19.0	79.43	N
		11	2462	72	315.60	19.0	79.43	N
U-NII-1	a	36	5180	72	285.91	16.0	39.81	N
		44	5220	72	285.65	16.0	39.81	N
		48	5240	72	285.53	16.0	39.81	N
U-NII-2A	a	52	5260	72	285.40	16.0	39.81	N
		60	5300	72	285.16	16.0	39.81	N
		64	5320	72	285.03	16.0	39.81	N
U-NII-2C	a	100	5500	72	283.96	16.0	39.81	N
		116	5580	72	283.50	16.0	39.81	N
		140	5700	72	282.83	16.0	39.81	N
		144	5720	72	282.72	16.0	39.81	N
U-NII-3	a	149	5745	72	282.58	16.0	39.81	N
		157	5785	72	282.36	16.0	39.81	N
		165	5825	72	282.15	16.0	39.81	N
DSS	3DH5	0	2402	72	316.78	10.0	10.00	N
		39	2441	72	316.01	9.0	7.94	N
		78	2480	72	315.25	9.0	7.94	N

69mm Ant 0 Distance to Bottom Side

Band	Mode	Channel	Frequency (MHz)	Ant-to-user distance (mm)	Thresholds (mW)	Tune-up Power		SAR Test (Y/N)
						dBm	mW	
DTS	b	1	2412	69	286.58	19.0	79.43	N
		6	2437	69	286.09	19.0	79.43	N
		11	2462	69	285.60	19.0	79.43	N
U-NII-1	a	36	5180	69	255.91	16.0	39.81	N
		44	5220	69	255.65	16.0	39.81	N
		48	5240	69	255.53	16.0	39.81	N
U-NII-2A	a	52	5260	69	255.40	16.0	39.81	N
		60	5300	69	255.16	16.0	39.81	N
		64	5320	69	255.03	16.0	39.81	N
U-NII-2C	a	100	5500	69	253.96	16.0	39.81	N
		116	5580	69	253.50	16.0	39.81	N
		140	5700	69	252.83	16.0	39.81	N
		144	5720	69	252.72	16.0	39.81	N
U-NII-3	a	149	5745	69	252.58	16.0	39.81	N
		157	5785	69	252.36	16.0	39.81	N
		165	5825	69	252.15	16.0	39.81	N
DSS	3DH5	0	2402	69	286.78	10.0	10.00	N
		39	2441	69	286.01	9.0	7.94	N
		78	2480	69	285.25	9.0	7.94	N

7mm Ant 1 Distance to Front/Back Side

Band	Mode	Channel	Frequency (MHz)	Ant-to-user distance (mm)	Thresholds (mW)	Tune-up Power		SAR Test (Y/N)
						dBm	mW	
DTS	n (HT20)	1	2412	7	13.52	16.0	39.81	Y
		6	2437	7	13.45	16.0	39.81	Y
		11	2462	7	13.38	16.0	39.81	Y
U-NII-1	ac (VHT20)	36	5180	7	9.23	14.0	25.12	Y
		44	5220	7	9.19	14.0	25.12	Y
		48	5240	7	9.17	14.0	25.12	Y
U-NII-2A	ac (VHT20)	52	5260	7	9.16	14.0	25.12	Y
		60	5300	7	9.12	14.0	25.12	Y
		64	5320	7	9.10	14.0	25.12	Y
U-NII-2C	ac (VHT20)	100	5500	7	8.95	14.0	25.12	Y
		116	5580	7	8.89	14.0	25.12	Y
		140	5700	7	8.80	14.0	25.12	Y
		144	5720	7	8.78	14.0	25.12	Y
U-NII-3	ac (VHT20)	149	5745	7	8.76	14.0	25.12	Y
		157	5785	7	8.73	14.0	25.12	Y
		165	5825	7	8.70	14.0	25.12	Y

64mm Ant 1 Distance to Left Side

Band	Mode	Channel	Frequency (MHz)	Ant-to-user distance (mm)	Thresholds (mW)	Tune-up Power		SAR Test (Y/N)
						dBm	mW	
DTS	n (HT20)	1	2412	64	236.58	16.0	39.81	N
		6	2437	64	236.09	16.0	39.81	N
		11	2462	64	235.60	16.0	39.81	N
U-NII-1	ac (VHT20)	36	5180	64	205.91	14.0	25.12	N
		44	5220	64	205.65	14.0	25.12	N
		48	5240	64	205.53	14.0	25.12	N
U-NII-2A	ac (VHT20)	52	5260	64	205.40	14.0	25.12	N
		60	5300	64	205.16	14.0	25.12	N
		64	5320	64	205.03	14.0	25.12	N
U-NII-2C	ac (VHT20)	100	5500	64	203.96	14.0	25.12	N
		116	5580	64	203.50	14.0	25.12	N
		140	5700	64	202.83	14.0	25.12	N
		144	5720	64	202.72	14.0	25.12	N
U-NII-3	ac (VHT20)	149	5745	64	202.58	14.0	25.12	N
		157	5785	64	202.36	14.0	25.12	N
		165	5825	64	202.15	14.0	25.12	N

4mm Ant 1 Distance to Right/Top Side

Band	Mode	Channel	Frequency (MHz)	Ant-to-user distance (mm)	Thresholds (mW)	Tune-up Power		SAR Test (Y/N)
						dBm	mW	
DTS	n (HT20)	1	2412	5	9.66	16.0	39.81	Y
		6	2437	5	9.61	16.0	39.81	Y
		11	2462	5	9.56	16.0	39.81	Y
U-NII-1	ac (VHT20)	36	5180	5	6.59	14.0	25.12	Y
		44	5220	5	6.57	14.0	25.12	Y
		48	5240	5	6.55	14.0	25.12	Y
U-NII-2A	ac (VHT20)	52	5260	5	6.54	14.0	25.12	Y
		60	5300	5	6.52	14.0	25.12	Y
		64	5320	5	6.50	14.0	25.12	Y
U-NII-2C	ac (VHT20)	100	5500	5	6.40	14.0	25.12	Y
		116	5580	5	6.35	14.0	25.12	Y
		140	5700	5	6.28	14.0	25.12	Y
		144	5720	5	6.27	14.0	25.12	Y
U-NII-3	ac (VHT20)	149	5745	5	6.26	14.0	25.12	Y
		157	5785	5	6.24	14.0	25.12	Y
		165	5825	5	6.22	14.0	25.12	Y

136mm Ant 1 Distance to Bottom Side

Band	Mode	Channel	Frequency (MHz)	Ant-to-user distance (mm)	Thresholds (mW)	Tune-up Power		SAR Test (Y/N)
						dBm	mW	
DTS	n (HT20)	1	2412	136	956.58	16.0	39.81	N
		6	2437	136	956.09	16.0	39.81	N
		11	2462	136	955.60	16.0	39.81	N
U-NII-1	ac (VHT20)	36	5180	136	925.91	14.0	25.12	N
		44	5220	136	925.65	14.0	25.12	N
		48	5240	136	925.53	14.0	25.12	N
U-NII-2A	ac (VHT20)	52	5260	136	925.40	14.0	25.12	N
		60	5300	136	925.16	14.0	25.12	N
		64	5320	136	925.03	14.0	25.12	N
U-NII-2C	ac (VHT20)	100	5500	136	923.96	14.0	25.12	N
		116	5580	136	923.50	14.0	25.12	N
		140	5700	136	922.83	14.0	25.12	N
		144	5720	136	922.72	14.0	25.12	N
U-NII-3	ac (VHT20)	149	5745	136	922.58	14.0	25.12	N
		157	5785	136	922.36	14.0	25.12	N
		165	5825	136	922.15	14.0	25.12	N

8.4. Required Configurations of SAR Test

■ Head & Body Exposure Conditions

Mobile Computer							
Antenna Configuration	Test Band	Front-side	Back-side	Left-side	Right-side	Top-side	Bottom-side
Ant 0	DTS	Yes	Yes	Yes	Yes *	Yes *	Yes *
	U-NII-1	Yes	Yes	Yes	Yes *	Yes *	Yes *
	U-NII-2A	Yes	Yes	Yes	Yes *	Yes *	Yes *
	U-NII-2C	Yes	Yes	Yes	Yes *	Yes *	Yes *
	U-NII-3	Yes	Yes	Yes	Yes *	Yes *	Yes *
	DSS	Yes *	Yes *	Yes	Yes *	Yes *	Yes *
Ant 1	DTS	Yes	Yes	Yes *	Yes	Yes	Yes *
	U-NII-1	Yes	Yes	Yes *	Yes	Yes	Yes *
	U-NII-2A	Yes	Yes	Yes *	Yes	Yes	Yes *
	U-NII-2C	Yes	Yes	Yes *	Yes	Yes	Yes *
	U-NII-3	Yes	Yes	Yes *	Yes	Yes	Yes *

Note: “ * ”, marked configuration SAR test is required, which is to get more conservative SAR values.

■ Extremity Exposure Conditions

Mobile Computer							
Antenna Configuration	Test Band	Front-side	Back-side	Left-side	Right-side	Top-side	Bottom-side
Ant 0	DTS	Yes	Yes	Yes	No	No	No
	U-NII-1	Yes	Yes	Yes	No	No	No
	U-NII-2A	Yes	Yes	Yes	No	No	No
	U-NII-2C	Yes	Yes	Yes	No	No	No
	U-NII-3	Yes	Yes	Yes	No	No	No
	DSS	Yes	Yes	Yes	No	No	No
Ant 1	DTS	Yes	Yes	No	Yes	Yes	No
	U-NII-1	Yes	Yes	No	Yes	Yes	No
	U-NII-2A	Yes	Yes	No	Yes	Yes	No
	U-NII-2C	Yes	Yes	No	Yes	Yes	No
	U-NII-3	Yes	Yes	No	Yes	Yes	No

Note: SAR evaluation is required for all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB Publication 865664 D01 to address interactive hand use exposure conditions, per KDB648474 D04 v01r03 section 2.5 b).

8.5. SAR Test Results

■ Head

Ant 0													
Test Band	Test Mode	CH.	Freq. (MHz)	Head Position	Dist. (mm)	Cond. Power (dBm)	Max. Tune-up Power (dBm)	Scaling Factor	Duty Cycle (%)	Duty Cycle Factor	Meas. SAR-1g (W/kg)	Reported SAR-1g (W/kg)	SAR Plot #
DTS	b	1	2412	Left Cheek	0	17.77	19.0	1.33	98.78	1.01	0.43	0.58	
		6	2437	Left Cheek	0	17.73	19.0	1.34	98.78	1.01	0.45	0.61	
		11	2462	Left Cheek	0	17.89	19.0	1.29	98.78	1.01	0.48	0.63	1
				Left tilt	0	17.89	19.0	1.29	98.78	1.01	0.07	0.09	
				Right Cheek	0	17.89	19.0	1.29	98.78	1.01	0.23	0.30	
				Right tilt	0	17.89	19.0	1.29	98.78	1.01	0.12	0.16	
U-NII-2A	a	52	5260	Left Cheek	0	15.24	16.0	1.19	94.81	1.05	0.18	0.23	
		60	5300	Left Cheek	0	15.13	16.0	1.22	94.81	1.05	0.18	0.23	
		64	5320	Left Cheek	0	15.31	16.0	1.17	94.81	1.05	0.19	0.23	2
				Left tilt	0	15.31	16.0	1.17	94.81	1.05	0.04	0.05	
				Right Cheek	0	15.31	16.0	1.17	94.81	1.05	0.08	0.08	
				Right tilt	0	15.31	16.0	1.17	94.81	1.05	0.03	0.04	
U-NII-2C	a	100	5500	Left Cheek	0	15.38	16.0	1.15	94.81	1.05	0.14	0.17	
				Left tilt	0	15.38	16.0	1.15	94.81	1.05	0.04	0.05	
				Right Cheek	0	15.38	16.0	1.15	94.81	1.05	0.05	0.06	
				Right tilt	0	15.38	16.0	1.15	94.81	1.05	0.03	0.04	
		116	5580	Left Cheek	0	15.16	16.0	1.21	94.81	1.05	0.23	0.29	
		144	5720	Left Cheek	0	15.16	16.0	1.21	94.81	1.05	0.24	0.31	3
U-NII-3	a	149	5745	Left Cheek	0	15.24	16.0	1.19	94.81	1.05	0.28	0.35	
				Left tilt	0	15.24	16.0	1.19	94.81	1.05	0.05	0.06	
				Right cheek	0	15.24	16.0	1.19	94.81	1.05	0.09	0.11	
				Right tilt	0	15.24	16.0	1.19	94.81	1.05	0.01	0.01	
		157	5785	Left cheek	0	15.03	16.0	1.25	94.81	1.05	0.32	0.42	4
		165	5825	Left cheek	0	14.81	16.0	1.32	94.81	1.05	0.26	0.36	
DSS	3DH5	0	2402	Left Cheek	0	9.07	10.0	1.24	76.71	1.30	0.07	0.11	5
				Left tilt	0	9.07	10.0	1.24	76.71	1.30	0.01	0.02	
				Right cheek	0	9.07	10.0	1.24	76.71	1.30	0.02	0.03	
				Right tilt	0	9.07	10.0	1.24	76.71	1.30	0.01	0.02	
		39	2441	Left cheek	0	7.55	9.0	1.40	76.71	1.30	0.06	0.11	
		78	2480	Left cheek	0	8.65	9.0	1.08	76.71	1.30	0.07	0.10	

Ant 1													
Test Band	Test Mode	CH.	Freq. (MHz)	Head Position	Dist. (mm)	Cond. Power (dBm)	Max. Tune-up Power (dBm)	Scaling Factor	Duty Cycle (%)	Duty Cycle Factor	Meas. SAR-1g (W/kg)	Reported SAR-1g (W/kg)	SAR Plot #
DTS	n (HT20)	1	2412	Left cheek	0	15.62	16.0	1.09	95.19	1.05	0.61	0.70	
				Left tilt	0	15.62	16.0	1.09	95.19	1.05	0.33	0.38	
				Right cheek	0	15.62	16.0	1.09	95.19	1.05	0.21	0.24	
				Right tilt	0	15.62	16.0	1.09	95.19	1.05	0.12	0.14	
		6	2437	Left cheek	0	15.53	16.0	1.11	95.19	1.05	0.63	0.74	6
		11	2462	Left cheek	0	15.42	16.0	1.14	95.19	1.05	0.56	0.67	
U-NII-2A	ac (VHT20)	52	5260	Left cheek	5	13.49	14.0	1.12	94.47	1.06	0.12	0.14	
		60	5300	Left cheek	5	13.52	14.0	1.12	94.47	1.06	0.14	0.17	7
				Left tilt	5	13.52	14.0	1.12	94.47	1.06	0.14	0.17	
				Right cheek	5	13.52	14.0	1.12	94.47	1.06	0.14	0.17	
				Right tilt	5	13.52	14.0	1.12	94.47	1.06	0.12	0.14	
		64	5320	Left cheek	5	13.41	14.0	1.15	94.47	1.06	0.12	0.15	
U-NII-2C	ac (VHT20)	100	5500	Left cheek	5	13.12	14.0	1.22	94.47	1.06	0.14	0.18	
				Left tilt	5	13.12	14.0	1.22	94.47	1.06	0.15	0.19	
				Right cheek	5	13.12	14.0	1.22	94.47	1.06	0.15	0.19	
				Right tilt	5	13.12	14.0	1.22	94.47	1.06	0.19	0.25	8
		116	5580	Right tilt	5	13.11	14.0	1.23	94.47	1.06	0.13	0.17	
		144	5720	Right tilt	5	12.96	14.0	1.27	94.47	1.06	0.14	0.19	
U-NII-3	ac (VHT20)	149	5745	Left cheek	5	13.16	14.0	1.21	94.47	1.06	0.13	0.17	
		157	5785	Left cheek	5	13.27	14.0	1.18	94.47	1.06	0.14	0.18	9
		165	5825	Left cheek	5	13.35	14.0	1.16	94.47	1.06	0.14	0.17	
				Left tilt	5	13.35	14.0	1.16	94.47	1.06	0.13	0.16	
				Right cheek	5	13.35	14.0	1.16	94.47	1.06	0.09	0.11	
				Right tilt	5	13.35	14.0	1.16	94.47	1.06	0.09	0.11	

■ Body

Ant 0													
Test Band	Test Mode	CH.	Freq. (MHz)	Body Position	Dist. (mm)	Cond. Power (dBm)	Max. Tune-up Power (dBm)	Scaling Factor	Duty Cycle (%)	Duty Cycle Factor	Meas. SAR-1g (W/kg)	Reported SAR-1g (W/kg)	SAR Plot #
DTS	b	1	2412	Left	5	17.77	19.0	1.33	98.78	1.01	0.42	0.56	
		6	2437	Left	5	17.73	19.0	1.34	98.78	1.01	0.42	0.57	10
		11	2462	Front	5	17.89	19.0	1.29	98.78	1.01	0.28	0.37	
				Back	5	17.89	19.0	1.29	98.78	1.01	0.22	0.29	
				Left	5	17.89	19.0	1.29	98.78	1.01	0.38	0.50	
				Right	5	17.89	19.0	1.29	98.78	1.01	0.09	0.12	
				Top	5	17.89	19.0	1.29	98.78	1.01	0.04	0.05	
				Bottom	5	17.89	19.0	1.29	98.78	1.01	0.05	0.07	
U-NII-2A	a	52	5260	Left	5	15.24	16.0	1.19	94.81	1.05	0.46	0.58	
		60	5300	Left	5	15.13	16.0	1.22	94.81	1.05	0.46	0.59	11
		64	5320	Front	5	15.31	16.0	1.17	94.81	1.05	0.10	0.12	
				Back	5	15.31	16.0	1.17	94.81	1.05	0.08	0.10	
				Left	5	15.31	16.0	1.17	94.81	1.05	0.46	0.57	
				Right	5	15.31	16.0	1.17	94.81	1.05	0.01	0.01	
				Top	5	15.31	16.0	1.17	94.81	1.05	0.01	0.01	
				Bottom	5	15.31	16.0	1.17	94.81	1.05	0.01	0.01	
U-NII-2C	a	100	5500	Front	5	15.38	16.0	1.15	94.81	1.05	0.12	0.15	
				Back	5	15.38	16.0	1.15	94.81	1.05	0.14	0.17	
				Left	5	15.38	16.0	1.15	94.81	1.05	0.43	0.52	
				Right	5	15.38	16.0	1.15	94.81	1.05	0.01	0.01	
				Top	5	15.38	16.0	1.15	94.81	1.05	0.03	0.04	
				Bottom	5	15.38	16.0	1.15	94.81	1.05	0.01	0.01	
		116	5580	Left	5	15.16	16.0	1.21	94.81	1.05	0.52	0.67	
		144	5720	Left	5	15.16	16.0	1.21	94.81	1.05	0.64	0.82	12
U-NII-3	a	149	5745	Front	5	15.24	16.0	1.19	94.81	1.05	0.19	0.24	
				Back	5	15.24	16.0	1.19	94.81	1.05	0.21	0.26	
				Left	5	15.24	16.0	1.19	94.81	1.05	0.62	0.78	13
				Right	5	15.24	16.0	1.19	94.81	1.05	0.03	0.04	
				Top	5	15.24	16.0	1.19	94.81	1.05	0.05	0.06	
				Bottom	5	15.24	16.0	1.19	94.81	1.05	0.01	0.01	
		157	5785	Left	5	15.03	16.0	1.25	94.81	1.05	0.54	0.71	
		165	5825	Left	5	14.81	16.0	1.32	94.81	1.05	0.48	0.67	

<Continue>

DSS	3DH5	0	2402	Front	5	9.07	10.0	1.24	76.71	1.30	0.01	0.02	
				Back	5	9.07	10.0	1.24	76.71	1.30	0.04	0.06	
				Left	5	9.07	10.0	1.24	76.71	1.30	0.06	0.10	14
				Right	5	9.07	10.0	1.24	76.71	1.30	0.01	0.02	
				Top	5	9.07	10.0	1.24	76.71	1.30	0.01	0.02	
				Bottom	5	9.07	10.0	1.24	76.71	1.30	0.01	0.02	
		39	2441	Left	5	7.55	9.0	1.40	76.71	1.30	0.05	0.09	
		78	2480	Left	5	8.65	9.0	1.08	76.71	1.30	0.04	0.06	

Ant 1													
Test Band	Test Mode	CH.	Freq. (MHz)	Body Position	Dist. (mm)	Cond. Power (dBm)	Max. Tune-up Power (dBm)	Scaling Factor	Duty Cycle (%)	Duty Cycle Factor	Meas. SAR-1g (W/kg)	Reported SAR-1g (W/kg)	SAR Plot #
DTS	n (HT20)	1	2412	Front	5	15.62	16.0	1.09	95.19	1.05	0.32	0.37	15
				Back	5	15.62	16.0	1.09	95.19	1.05	0.28	0.32	
				Left	5	15.62	16.0	1.09	95.19	1.05	0.01	0.01	
				Right	5	15.62	16.0	1.09	95.19	1.05	0.21	0.24	
				Top	5	15.62	16.0	1.09	95.19	1.05	0.08	0.09	
				Bottom	5	15.62	16.0	1.09	95.19	1.05	0.01	0.01	
		6	2437	Front	5	15.53	16.0	1.11	95.19	1.05	0.31	0.36	
		11	2462	Front	5	15.42	16.0	1.14	95.19	1.05	0.27	0.32	
U-NII-2A	ac (VHT20)	52	5260	Back	5	13.49	14.0	1.12	94.47	1.06	0.48	0.57	16
		60	5300	Front	5	13.52	14.0	1.12	94.47	1.06	0.10	0.12	
				Back	5	13.52	14.0	1.12	94.47	1.06	0.47	0.56	
				Left	5	13.52	14.0	1.12	94.47	1.06	0.02	0.02	
				Right	5	13.52	14.0	1.12	94.47	1.06	0.41	0.48	
				Top	5	13.52	14.0	1.12	94.47	1.06	0.12	0.14	
				Bottom	5	13.52	14.0	1.12	94.47	1.06	0.01	0.01	
		64	5320	Back	5	13.41	14.0	1.15	94.47	1.06	0.47	0.57	
U-NII-2C	ac (VHT20)	100	5500	Front	5	13.12	14.0	1.22	94.47	1.06	0.13	0.17	
				Back	5	13.12	14.0	1.22	94.47	1.06	0.42	0.54	
				Left	5	13.12	14.0	1.22	94.47	1.06	0.01	0.01	
				Right	5	13.12	14.0	1.22	94.47	1.06	0.43	0.56	17
				Top	5	13.12	14.0	1.22	94.47	1.06	0.17	0.22	
				Bottom	5	13.12	14.0	1.22	94.47	1.06	0.01	0.01	
		116	5580	Right	5	13.11	14.0	1.23	94.47	1.06	0.36	0.47	
		144	5720	Right	5	12.96	14.0	1.27	94.47	1.06	0.21	0.28	
U-NII-3	ac (VHT20)	149	5745	Right	5	13.16	14.0	1.21	94.47	1.06	0.20	0.26	
		157	5785	Right	5	13.27	14.0	1.18	94.47	1.06	0.20	0.25	
		165	5825	Front	5	13.35	14.0	1.16	94.47	1.06	0.08	0.10	
				Back	5	13.35	14.0	1.16	94.47	1.06	0.19	0.23	
				Left	5	13.35	14.0	1.16	94.47	1.06	0.01	0.01	
				Right	5	13.35	14.0	1.16	94.47	1.06	0.22	0.27	18
				Top	5	13.35	14.0	1.16	94.47	1.06	0.10	0.12	
				Bottom	5	13.35	14.0	1.16	94.47	1.06	0.01	0.01	

■ Extremity

Ant 0													
Test Band	Test Mode	CH.	Freq. (MHz)	Body Position	Dist. (mm)	Cond. Power (dBm)	Max. Tune-up Power (dBm)	Scaling Factor	Duty Cycle (%)	Duty Cycle Factor	Meas. SAR-10g (W/kg)	Reported SAR-10g (W/kg)	SAR Plot #
DTS	b	1	2412	Left	0	17.77	19.0	1.33	98.78	1.01	0.52	0.70	19
		6	2437	Left	0	17.73	19.0	1.34	98.78	1.01	0.49	0.66	
		11	2462	Front	0	17.89	19.0	1.29	98.78	1.01	0.36	0.47	
				Back	0	17.89	19.0	1.29	98.78	1.01	0.14	0.18	
				Left	0	17.89	19.0	1.29	98.78	1.01	0.49	0.64	
U-NII-2A	a	52	5260	Left	0	15.24	16.0	1.19	94.81	1.05	0.42	0.53	20
		60	5300	Left	0	15.13	16.0	1.22	94.81	1.05	0.40	0.52	
		64	5320	Front	0	15.31	16.0	1.17	94.81	1.05	0.17	0.21	
				Back	0	15.31	16.0	1.17	94.81	1.05	0.05	0.06	
				Left	0	15.31	16.0	1.17	94.81	1.05	0.40	0.49	
U-NII-2C	a	100	5500	Front	0	15.38	16.0	1.15	94.81	1.05	0.15	0.18	
				Back	0	15.38	16.0	1.15	94.81	1.05	0.06	0.07	
				Left	0	15.38	16.0	1.15	94.81	1.05	0.36	0.44	
		116	5580	Left	0	15.16	16.0	1.21	94.81	1.05	0.35	0.45	
		144	5720	Left	0	15.16	16.0	1.21	94.81	1.05	0.40	0.51	21
U-NII-3	a	149	5745	Front	0	15.24	16.0	1.19	94.81	1.05	0.18	0.23	
				Back	0	15.24	16.0	1.19	94.81	1.05	0.09	0.11	
				Left	0	15.24	16.0	1.19	94.81	1.05	0.41	0.52	22
		157	5785	Left	0	15.03	16.0	1.25	94.81	1.05	0.39	0.51	
		165	5825	Left	0	14.81	16.0	1.32	94.81	1.05	0.35	0.49	
DSS	3DH5	0	2402	Front	0	9.07	10.0	1.24	76.71	1.30	0.03	0.05	
				Back	0	9.07	10.0	1.24	76.71	1.30	0.01	0.02	
				Left	0	9.07	10.0	1.24	76.71	1.30	0.04	0.06	23
		39	2441	Left	0	7.55	9.0	1.40	76.71	1.30	0.03	0.05	
		78	2480	Left	0	8.65	9.0	1.08	76.71	1.30	0.04	0.057	

Ant 1													
Test Band	Test Mode	CH.	Freq. (MHz)	Body Position	Dist. (mm)	Cond. Power (dBm)	Max. Tune-up Power (dBm)	Scaling Factor	Duty Cycle (%)	Duty Cycle Factor	Meas. SAR-10g (W/kg)	Reported SAR-10g (W/kg)	SAR Plot #
DTS	n (HT20)	1	2412	Front	0	15.62	16.0	1.09	95.19	1.05	0.43	0.49	24
				Back	0	15.62	16.0	1.09	95.19	1.05	0.25	0.29	
				Right	0	15.62	16.0	1.09	95.19	1.05	0.27	0.31	
				Top	0	15.62	16.0	1.09	95.19	1.05	0.08	0.09	
		6	2437	Front	0	15.53	16.0	1.11	95.19	1.05	0.41	0.48	
		11	2462	Front	0	15.42	16.0	1.14	95.19	1.05	0.37	0.44	
U-NII-2A	ac (VHT20)	52	5260	Back	5	13.49	14.0	1.12	94.47	1.06	0.33	0.39	
		60	5300	Front	5	13.52	14.0	1.12	94.47	1.06	0.06	0.07	
				Back	5	13.52	14.0	1.12	94.47	1.06	0.35	0.41	
				Right	5	13.52	14.0	1.12	94.47	1.06	0.18	0.21	
				Top	5	13.52	14.0	1.12	94.47	1.06	0.13	0.15	
		64	5320	Back	5	13.41	14.0	1.15	94.47	1.06	0.36	0.44	25
U-NII-2C	ac (VHT20)	100	5500	Front	5	13.12	14.0	1.22	94.47	1.06	0.09	0.12	
				Back	5	13.12	14.0	1.22	94.47	1.06	0.34	0.44	26
				Right	5	13.12	14.0	1.22	94.47	1.06	0.22	0.29	
				Top	5	13.12	14.0	1.22	94.47	1.06	0.13	0.17	
		116	5580	Back	5	13.11	14.0	1.23	94.47	1.06	0.27	0.35	
		144	5720	Back	5	12.96	14.0	1.27	94.47	1.06	0.17	0.23	
U-NII-3	ac (VHT20)	149	5745	Back	5	13.16	14.0	1.21	94.47	1.06	0.17	0.22	
		157	5785	Back	5	13.27	14.0	1.18	94.47	1.06	0.17	0.21	
		165	5825	Front	5	13.35	14.0	1.16	94.47	1.06	0.08	0.10	
				Back	5	13.35	14.0	1.16	94.47	1.06	0.18	0.22	27
				Right	5	13.35	14.0	1.16	94.47	1.06	0.17	0.21	
				Top	5	13.35	14.0	1.16	94.47	1.06	0.11	0.14	

Note:

- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, 802.11g/n OFDM SAR is not required, per KDB248227 D01 v02r02 section 5.2.2 2).
- For devices that operate in both U-NII-1 and U-NII-2A bands and same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR. When different maximum output power is specified for the bands,

begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR, per KDB248227 D01 v02r02 section 5.3.1).

3. When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n, per KDB248227 D01 v02r02 section 5.3.2 4).
4. When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration, per KDB248227 D01 v02r02 section 5.3.4 b).

8.6. Estimated SAR Calculation

Per FCC KDB 447498 D01v06 section 4.3.2 b) 1), when an antenna qualifies for the standalone SAR test exclusion of 4.3.1 and also transmits simultaneously with other antennas, the standalone SAR value was estimated according to the following formula to result in substantially conservative SAR values of $\leq 0.4\text{W/kg}$ for test separation distance $\leq 50\text{mm}$ to determine the simultaneous transmission SAR test exclusion criteria:

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation, mm}}, \text{ for 1-g SAR}$$

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{18.75} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation, mm}}, \text{ for 10-g SAR}$$

When the test separation distance is $> 50\text{ mm}$, estimated 1g-SAR 0.4W/kg /10g-SAR 1.0W/kg is used for simultaneous evaluation.

N/A

9. Simultaneous Transmission Analysis

■ Head Exposure Conditions

Transmit Configuration	Test Position	Maximum SAR(1g) (W/kg)		Summed SAR(1g) (W/kg)
		Ant 0	Ant 1	
Ant 0 + Ant 1	Left Cheek	0.63	0.74	1.37
	Left tilt	0.09	0.38	0.47
	Right Cheek	0.30	0.24	0.54
	Right tilt	0.16	0.25	0.41

Note: SISO antenna SAR value is used to evaluate simultaneous transmission to get more conservative SAR values.

■ Body Exposure Conditions

Transmit Configuration	Test Position	Maximum SAR(1g) (W/kg)		Summed SAR(1g) (W/kg)
		Ant 0	Ant 1	
Ant 0 + Ant 1	Front	0.37	0.37	0.74
	Back	0.29	0.57	0.86
	Left	0.78	0.02	0.80
	Right	0.12	0.56	0.68
	Top	0.06	0.22	0.28
	Bottom	0.07	0.01	0.08

Note: SISO antenna SAR value is used to evaluate simultaneous transmission to get more conservative SAR values.

■ Extremity Exposure Conditions

Transmit Configuration	Test Position	Maximum SAR(1g) (W/kg)		Summed SAR(1g) (W/kg)
		Ant 0	Ant 1	
Ant 0 + Ant 1	Front	0.47	0.49	0.96
	Back	0.18	0.44	0.62
	Left	0.70	N/A	0.70
	Right	N/A	0.31	0.31
	Top	N/A	0.17	0.17

Note: SISO antenna SAR value is used to evaluate simultaneous transmission to get more conservative SAR values.

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06.

10. Test Equipment Used

SR3 - SAR					
Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Stäubli Robot TX60L	Stäubli	TX60L	MRTSUE06412	only once	only once
Robot Controller	Stäubli	CS8C	MRTSUE06412	only once	only once
SAM Twin Phantom	Speag	QD 000 P41 AA	MRTSUE06419	N/A	N/A
ELI Phantom Shell	Speag	V8	MRTSUE06420	N/A	N/A
DAK	Speag	DAK-3.5	MRTSUE06435	N/A	N/A
Dipole Validation Kits	Speag	D2450V2	MRTSUE06430	3 year	2021/05/08
Dipole Validation Kits	Speag	D5GHzV2	MRTSUE06434	3 year	2022/04/15
DAE4	Speag	SD 000 D04 BN	MRTSUE06414	1 year	2021/05/05
E-Field Probe	Speag	EX3DV4	MRTSUE06438	1 year	2021/05/19
Network Analyzer	Keysight	N5234B	MRTSUE06454	1 year	2021/07/02
Directional Coupler	Agilent	778D	MRTSUE06083	1 year	2021/03/25
Directional Coupler	Agilent	87301D OPT 292	MRTSUE06082	1 year	2021/03/25
Signal Generator	Keysight	N5183B	MRTSUE06197	1 year	2021/04/14
Power Sensor	Keysight	U2021XA	MRTSUE06447	1 year	2021/06/11
Thermohygrometer	Testo	622	MRTSUE06361	1 year	2021/05/12

Software	Version	Function
DASY NEO	52.10.2.1495	SAR Test Software

11. Measurement Uncertainty

DASY5 Uncertainty Budget, according to IEEE 1528 (0.3 - 3 GHz range)								
Error Description	Uncert. value	Prob. Dist.	Div.	(ci) 1g	(ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(vi) v _{eff}
Measurement System								
Probe Calibration	±6.0 %	N	1	1	1	±6.0 %	±6.0 %	∞
Axial Isotropy	±4.7 %	R	$\sqrt{3}$	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	$\sqrt{3}$	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Linearity	±4.7 %	R	$\sqrt{3}$	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Modulation Response	±2.4 %	R	$\sqrt{3}$	1	1	±1.4 %	±1.4 %	∞
Readout Electronics	±0.3 %	N	1	1	1	±0.3 %	±0.3 %	∞
Response Time	±0.8 %	R	$\sqrt{3}$	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	$\sqrt{3}$	1	1	±1.5 %	±1.5 %	∞
RF Ambient Noise	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
RF Ambient Reflections	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.02 %	R	$\sqrt{3}$	1	1	±0.0 %	±0.0 %	∞
Probe Positioning	±0.4 %	R	$\sqrt{3}$	1	1	±0.2 %	±0.2 %	∞
Max. SAR Eval.	±2.0 %	R	$\sqrt{3}$	1	1	±1.2 %	±1.2 %	∞
Test Sample Related								
Device Positioning	±2.9%	N	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6%	N	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9 %	±2.9 %	∞
Power Scaling	±0%	R	$\sqrt{3}$	1	1	±0.0 %	±0.0 %	∞
Phantom and Setup								
Phantom Uncertainty	±6.1%	R	$\sqrt{3}$	1	1	±3.5 %	±3.5 %	∞
SAR correction	±1.9%	N	1	1	0.84	±1.9 %	±1.6 %	∞
Liquid Cond. (mea.) ^{DAK}	±2.5%	N	1	0.78	0.71	±2.0 %	±1.8 %	∞
Liquid Perm. (mea.) ^{DAK}	±2.5%	N	1	0.23	0.26	±0.6 %	±0.7 %	∞
Temp. unc. – Conductivity	±3.4%	R	$\sqrt{3}$	0.78	0.71	±1.5 %	±1.4 %	∞
Temp. unc. – Permittivity	±0.4%	R	$\sqrt{3}$	0.23	0.26	±0.1 %	±0.1 %	∞
Combined Std. Uncertainty						±11.3%	±11.2%	459
Expanded STD Uncertainty						±22.6%	±22.4%	

DASY5 Uncertainty Budget, according to IEEE 1528 (3 - 6 GHz range)								
Error Description	Uncert. value	Prob. Dist.	Div.	(ci) 1g	(ci) 10g	Std. Unc. (10g)	Std. Unc. (10g)	(vi) v _{eff}
Measurement System								
Probe Calibration	±6.55 %	N	1	1	1	±6.55 %	±6.55 %	∞
Axial Isotropy	±4.7 %	R	$\sqrt{3}$	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	$\sqrt{3}$	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±2.0 %	R	$\sqrt{3}$	1	1	±1.2 %	±1.2 %	∞
Linearity	±4.7 %	R	$\sqrt{3}$	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Modulation Response	±2.4 %	R	$\sqrt{3}$	1	1	±1.4 %	±1.4 %	∞
Readout Electronics	±0.3 %	N	1	1	1	±0.3 %	±0.3 %	∞
Response Time	±0.8 %	R	$\sqrt{3}$	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	$\sqrt{3}$	1	1	±1.5 %	±1.5 %	∞
RF Ambient Noise	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
RF Ambient Reflections	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.04 %	R	$\sqrt{3}$	1	1	±0.0 %	±0.0 %	∞
Probe Positioning	±0.8 %	R	$\sqrt{3}$	1	1	±0.5 %	±0.5 %	∞
Max. SAR Eval.	±4.0 %	R	$\sqrt{3}$	1	1	±2.3 %	±2.3 %	∞
Test Sample Related								
Device Positioning	±2.9%	N	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6%	N	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9 %	±2.9 %	∞
Power Scaling	±0%	R	$\sqrt{3}$	1	1	±0.0 %	±0.0 %	∞
Phantom and Setup								
Phantom Uncertainty	±6.6%	R	$\sqrt{3}$	1	1	±3.8 %	±3.8 %	∞
SAR correction	±1.9%	N	1	1	0.84	±1.9 %	±1.6 %	∞
Liquid Cond. (mea.) ^{DAK}	±2.5%	N	1	0.78	0.71	±2.0 %	±1.8 %	∞
Liquid Perm. (mea.) ^{DAK}	±2.5%	N	1	0.23	0.26	±0.6 %	±0.7 %	∞
Temp. unc. – Conductivity	±3.4%	R	$\sqrt{3}$	0.78	0.71	±1.5 %	±1.4 %	∞
Temp. unc. – Permittivity	±0.4%	R	$\sqrt{3}$	0.23	0.26	±0.1 %	±0.1 %	∞
Combined Std. Uncertainty						±11.9%	±11.8%	569
Expanded STD Uncertainty						±23.8%	±23.6%	

Annex A - System Check Result

Test Date: 07/09/2020

SystemPerformanceCheck-SAM1-D2450HSL

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.85$ S/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2450 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


configuration/d=10mm, Pin=250mW, dist=4mm (EX-Probe)/Area Scan (7x9x1): Measurement grid:

dx=12mm, dy=12mm; Maximum value of SAR (measured) = 15.2 W/kg

configuration/d=10mm, Pin=250mW, dist=4mm (EX-Probe)/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm; Reference Value = 108.8 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 28.2 W/kg

SAR(1 g) = 13.5 W/kg; SAR(10 g) = 6.21 W/kg Maximum value of SAR (measured) = 15.2 W/kg


0 dB = 15.2 W/kg = 11.82 dBW/kg

Test Date: 07/10/2020

SystemPerformanceCheck-SAM1-D5250HSL

DUT: Dipole D5GHzV2; Type: D5GHzV2

Communication System: CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5250 \text{ MHz}$; $\sigma = 4.55 \text{ S/m}$; $\epsilon_r = 35.12$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(5.15, 5.15, 5.15) @ 5250 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/d=10mm, Pin=100 mW, dist=2.0mm (EX-Probe)/Area Scan (7x9x1): Measurement grid:


dx=10mm, dy=10mm; Maximum value of SAR (measured) = 16.2 W/kg

Configuration/d=10mm, Pin=100 mW, dist=2.0mm (EX-Probe)/Zoom Scan (8x8x8) (8x8x6)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 64.01 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 31.4 W/kg

SAR(1 g) = 7.84 W/kg; SAR(10 g) = 2.23 W/kg Maximum value of SAR (measured) = 15.2 W/kg



0 dB = 15.2 W/kg = 11.82 dBW/kg

Test Date: 07/11/2020

SystemPerformanceCheck-SAM1-D5600HSL

DUT: Dipole D5GHzV2; Type: D5GHzV2

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 4.94$ S/m; $\epsilon_r = 34.51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.77, 4.77, 4.77) @ 5600 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/d=10mm, Pin=100mW, dist=2mm (EX-Probe)/Area Scan (7x9x1): Measurement grid:


dx=10mm, dy=10mm; Maximum value of SAR (measured) = 16.8 W/kg

Configuration/d=10mm, Pin=100mW, dist=2mm (EX-Probe)/Zoom Scan (8x8x8) (8x8x6)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 63.02 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 35.2 W/kg

SAR(1 g) = 8.07 W/kg; SAR(10 g) = 2.26 W/kg Maximum value of SAR (measured) = 16.0 W/kg



0 dB = 16.0 W/kg = 12.04 dBW/kg

Test Date: 07/13/2020

SystemPerformanceCheck-SAM1-D5750HSL

DUT: Dipole D5GHzV2; Type: D5GHzV2

Communication System: CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5750 \text{ MHz}$; $\sigma = 5.11 \text{ S/m}$; $\epsilon_r = 34.24$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5750 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/d=10mm, Pin=100 mW, dist=2mm (EX-Probe)/Area Scan (7x9x1): Measurement grid:


$dx=10\text{mm}$, $dy=10\text{mm}$; Maximum value of SAR (measured) = 15.7 W/kg

Configuration/d=10mm, Pin=100 mW, dist=2mm (EX-Probe)/Zoom Scan (8x8x8) (8x8x6)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$; Reference Value = 59.77 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 33.3 W/kg

SAR(1 g) = 7.48 W/kg; SAR(10 g) = 2.11 W/kg Maximum value of SAR (measured) = 14.9 W/kg



0 dB = 14.9 W/kg = 11.73 dBW/kg

Test Date: 07/14/2020

SystemPerformanceCheck-SAM2-D2450HSL

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450 \text{ MHz}$; $\sigma = 1.83 \text{ S/m}$; $\epsilon_r = 40.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2450 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

configuration/d=10mm, Pin=250mW, dist=4mm (EX-Probe)/Area Scan (7x9x1): Measurement grid:


$dx=12\text{mm}$, $dy=12\text{mm}$; Maximum value of SAR (measured) = 14.0 W/kg

configuration/d=10mm, Pin=250mW, dist=4mm (EX-Probe)/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$; Reference Value = 102.3 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 27.3 W/kg

SAR(1 g) = 13.2 W/kg; SAR(10 g) = 6.14 W/kg Maximum value of SAR (measured) = 15.0 W/kg



0 dB = 15.0 W/kg = 11.76 dBW/kg

Test Date: 07/15/2020

SystemPerformanceCheck-SAM2-D5250HSL

DUT: Dipole D5GHzV2; Type: D5GHzV2

Communication System: CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5250 \text{ MHz}$; $\sigma = 4.61 \text{ S/m}$; $\epsilon_r = 35.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(5.15, 5.15, 5.15) @ 5250 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/d=10mm, Pin=100 mW, dist=2.0mm (EX-Probe)/Area Scan (7x9x1): Measurement grid:


$dx=10\text{mm}$, $dy=10\text{mm}$; Maximum value of SAR (measured) = 15.2 W/kg

Configuration/d=10mm, Pin=100 mW, dist=2.0mm (EX-Probe)/Zoom Scan (8x8x8) (8x8x6)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$; Reference Value = 61.46 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 32.3 W/kg

SAR(1 g) = 8.19 W/kg; SAR(10 g) = 2.35 W/kg Maximum value of SAR (measured) = 16.0 W/kg



0 dB = 16.0 W/kg = 12.04 dBW/kg

Test Date: 07/16/2020

SystemPerformanceCheck-SAM2-D5600HSL

DUT: Dipole D5GHzV2; Type: D5GHzV2

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.01$ S/m; $\epsilon_r = 35.27$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.77, 4.77, 4.77) @ 5600 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/d=10mm, Pin=100mW, dist=2mm (EX-Probe)/Area Scan (7x9x1): Measurement grid:


dx=10mm, dy=10mm; Maximum value of SAR (measured) = 13.8 W/kg

Configuration/d=10mm, Pin=100mW, dist=2mm (EX-Probe)/Zoom Scan (8x8x8) (8x8x6)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 53.92 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 36.4 W/kg

SAR(1 g) = 8.49 W/kg; SAR(10 g) = 2.41 W/kg Maximum value of SAR (measured) = 16.9 W/kg



0 dB = 16.9 W/kg = 12.28 dBW/kg

Test Date: 07/20/2020

SystemPerformanceCheck-SAM2-D5750HSL

DUT: Dipole D5GHzV2; Type: D5GHzV2

Communication System: CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5750 \text{ MHz}$; $\sigma = 5.19 \text{ S/m}$; $\epsilon_r = 34.98$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5750 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/d=10mm, Pin=100 mW, dist=2mm (EX-Probe)/Area Scan (7x9x1): Measurement grid:


$dx=10\text{mm}$, $dy=10\text{mm}$; Maximum value of SAR (measured) = 12.9 W/kg

Configuration/d=10mm, Pin=100 mW, dist=2mm (EX-Probe)/Zoom Scan (8x8x8) (8x8x6)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$; Reference Value = 51.71 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 35.1 W/kg

SAR(1 g) = 7.91 W/kg; SAR(10 g) = 2.24 W/kg Maximum value of SAR (measured) = 15.8 W/kg



0 dB = 15.8 W/kg = 11.99 dBW/kg

Annex B - Test Data Plots

Plot 1#

Test Date: 07/09/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11b 2462MHz Left cheek

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 1.86 \text{ S/m}$; $\epsilon_r = 39.99$; $\rho = 1000 \text{ kg/m}^3$; Tissue Temp (celsius)-22.5°C; Phantom section: Left Section


DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2462 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11b 2462MHz Left cheek/Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$; Maximum value of SAR (measured) = 0.514 W/kg

Configuration/802.11b 2462MHz Left cheek/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$; Reference Value = 2.495 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 1.10 W/kg

SAR(1 g) = 0.475 W/kg; SAR(10 g) = 0.195 W/kg Maximum value of SAR (measured) = 0.563 W/kg


0 dB = 0.563 W/kg = -2.49 dBW/kg

Plot 2#

Test Date: 07/10/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11a 5320MHz Left cheek

Communication System: 802.11a; Frequency: 5320 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5320$ MHz; $\sigma = 4.63$ S/m; $\epsilon_r = 35$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Left Section


DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(5.15, 5.15, 5.15) @ 5320 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11a 5320MHz Left cheek/Area Scan (13x21x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.315 W/kg

Configuration/802.11a 5320MHz Left cheek/Zoom Scan (8x8x6)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 0.752 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.695 W/kg

SAR(1 g) = 0.187 W/kg; SAR(10 g) = 0.066 W/kg Maximum value of SAR (measured) = 0.369 W/kg


0 dB = 0.369 W/kg = -4.33 dBW/kg

Plot 3#

Test Date: 07/13/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11a 5720MHz Left cheek

Communication System: 802.11a; Frequency: 5720 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5720$ MHz; $\sigma = 5.07$ S/m; $\epsilon_r = 34.3$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Left Section


DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5720 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11a 5720MHz Left cheek/Area Scan (13x21x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.408 W/kg

Configuration/802.11a 5720MHz Left cheek/Zoom Scan (9x9x6)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 1.444 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 1.10 W/kg

SAR(1 g) = 0.242 W/kg; SAR(10 g) = 0.072 W/kg Maximum value of SAR (measured) = 0.556 W/kg


0 dB = 0.556 W/kg = -2.55 dBW/kg

Plot 4#

Test Date: 07/13/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11a 5785MHz Left cheek

Communication System: 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5785$ MHz; $\sigma = 5.15$ S/m; $\epsilon_r = 34.19$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Left Section


DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5785 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11a 5785MHz Left cheek/Area Scan (13x21x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.466 W/kg

Configuration/802.11a 5785MHz Left cheek/Zoom Scan (8x9x6)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 0.630 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.319 W/kg; SAR(10 g) = 0.087 W/kg Maximum value of SAR (measured) = 0.777 W/kg


0 dB = 0.777 W/kg = -1.10 dBW/kg

Plot 5#

Test Date: 07/09/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: Bluetooth 3DH5 2402MHz Left Cheek

Communication System: Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2402$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 40.08$; $\rho = 1000$ kg/m³; Tissue

Temp (celsius)-22.5°C; Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2402 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/Bluetooth 3DH5 2402MHz Left Cheek/Area Scan (11x17x1): Measurement grid:

dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.0796 W/kg

Configuration/Bluetooth 3DH5 2402MHz Left Cheek/Zoom Scan (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm; Reference Value = 0.319 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.155 W/kg

SAR(1 g) = 0.071 W/kg; SAR(10 g) = 0.027 W/kg Maximum value of SAR (measured) = 0.0878 W/kg


0 dB = 0.0878 W/kg = -10.57 dBW/kg

Plot 6#

Test Date: 07/09/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11n-HT20 2437MHz Left cheek

Communication System: 802.11n; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.84$ S/m; $\epsilon_r = 40.02$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Left Section

DASY5 Configuration:


- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2437 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11n-HT20 2437MHz Left cheek/Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.644 W/kg

Configuration/802.11n-HT20 2437MHz Left cheek/Zoom Scan (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm; Reference Value = 7.456 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.54 W/kg

SAR(1 g) = 0.630 W/kg; SAR(10 g) = 0.258 W/kg Maximum value of SAR (measured) = 0.732 W/kg


0 dB = 0.732 W/kg = -1.35 dBW/kg

Plot 7#

Test Date: 07/10/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11ac-VHT20 5300MHz Left cheek

Communication System: 802.11ac; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5300$ MHz; $\sigma = 4.61$ S/m; $\epsilon_r = 35.04$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(5.15, 5.15, 5.15) @ 5300 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11ac-VHT20 5300MHz Left cheek/Area Scan (13x21x1): Measurement grid:

dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.272 W/kg

Configuration/802.11ac-VHT20 5300MHz Left cheek/Zoom Scan (8x8x6)/Cube 0: Measurement grid:

dx=4mm, dy=4mm, dz=2mm; Reference Value = 1.889 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.605 W/kg

SAR(1 g) = 0.142 W/kg; SAR(10 g) = 0.045 W/kg Maximum value of SAR (measured) = 0.310 W/kg


0 dB = 0.310 W/kg = -5.09 dBW/kg

Plot 8#

Test Date: 07/11/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11ac-VHT20 5500MHz Right Tilt

Communication System: 802.11ac; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5500$ MHz; $\sigma = 4.82$ S/m; $\epsilon_r = 34.69$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.77, 4.77, 4.77) @ 5500 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11ac-VHT20 5500MHz Right Tilt/Area Scan (13x21x1): Measurement grid:

dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.328 W/kg

Configuration/802.11ac-VHT20 5500MHz Right Tilt/Zoom Scan (9x9x6)/Cube 0: Measurement grid:

dx=4mm, dy=4mm, dz=2mm; Reference Value = 3.069 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 2.05 W/kg

SAR(1 g) = 0.191 W/kg; SAR(10 g) = 0.062 W/kg Maximum value of SAR (measured) = 0.332 W/kg


0 dB = 0.332 W/kg = -4.79 dBW/kg

Plot 9#

Test Date: 07/13/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11ac-VHT20 5785MHz Left Cheek

Communication System: 802.11ac; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5785$ MHz; $\sigma = 5.15$ S/m; $\epsilon_r = 34.19$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5785 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1954
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11ac-VHT20 5785MHz Left Cheek/Area Scan (13x21x1): Measurement grid:

dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.302 W/kg

Configuration/802.11ac-VHT20 5785MHz Left Cheek/Zoom Scan (8x8x6)/Cube 0: Measurement grid:

dx=4mm, dy=4mm, dz=2mm; Reference Value = 2.225 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.754 W/kg

SAR(1 g) = 0.135 W/kg; SAR(10 g) = 0.044 W/kg Maximum value of SAR (measured) = 0.326 W/kg


0 dB = 0.326 W/kg = -4.87 dBW/kg

Plot 10#

Test Date: 07/14/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11b 2437MHz Body Left

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.83$ S/m; $\epsilon_r = 40.62$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section


DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2437 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11b 2437MHz Body Left/Area Scan (6x17x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.361 W/kg

Configuration/802.11b 2437MHz Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm; Reference Value = 10.58 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.854 W/kg

SAR(1 g) = 0.415 W/kg; SAR(10 g) = 0.201 W/kg Maximum value of SAR (measured) = 0.466 W/kg


0 dB = 0.466 W/kg = -3.32 dBW/kg

Plot 11#

Test Date: 07/15/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11a 5300MHz Body Left

Communication System: 802.11a; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5300$ MHz; $\sigma = 4.67$ S/m; $\epsilon_r = 35.8$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section


DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(5.15, 5.15, 5.15) @ 5300 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11a 5300MHz Body Left/Area Scan (7x21x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.695 W/kg

Configuration/802.11a 5300MHz Body Left/Zoom Scan (8x8x6)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 13.04 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 0.463 W/kg; SAR(10 g) = 0.126 W/kg Maximum value of SAR (measured) = 0.987 W/kg


0 dB = 0.987 W/kg = -0.06 dBW/kg

Plot 12#

Test Date: 07/20/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11a 5720MHz Body Left

Communication System: 802.11a; Frequency: 5720 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5720$ MHz; $\sigma = 5.15$ S/m; $\epsilon_r = 35.05$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section


DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5720 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11a 5720MHz Body Left/Area Scan (7x21x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.10 W/kg

Configuration/802.11a 5720MHz Body Left/Zoom Scan (8x8x6)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 12.89 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.60 W/kg

SAR(1 g) = 0.636 W/kg; SAR(10 g) = 0.174 W/kg Maximum value of SAR (measured) = 1.36 W/kg


0 dB = 1.36 W/kg = 1.34 dBW/kg

Plot 13#

Test Date: 07/20/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11a 5745MHz Body Left

Communication System: 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5745$ MHz; $\sigma = 5.19$ S/m; $\epsilon_r = 35$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section


DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5745 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11a 5745MHz Body Left/Area Scan (7x21x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.09 W/kg

Configuration/802.11a 5745MHz Body Left/Zoom Scan (8x8x6)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 12.26 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 2.58 W/kg

SAR(1 g) = 0.621 W/kg; SAR(10 g) = 0.170 W/kg; Maximum value of SAR (measured) = 1.36 W/kg


0 dB = 1.36 W/kg = 1.34 dBW/kg

Plot 14#

Test Date: 07/14/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: Bluetooth 3DH5 2402MHz Body Left

Communication System: Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2402$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 40.68$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:


- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2402 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/Bluetooth 3DH5 2402MHz Body Left/Area Scan (6x17x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.0605 W/kg

Configuration/Bluetooth 3DH5 2402MHz Body Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm; Reference Value = 3.910 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.120 W/kg

SAR(1 g) = 0.060 W/kg; SAR(10 g) = 0.026 W/kg Maximum value of SAR (measured) = 0.0688 W/kg


0 dB = 0.0688 W/kg = -11.62 dBW/kg

Plot 15#

Test Date: 07/14/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11n-HT20 2412MHz Body Front

Communication System: 802.11n; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 40.66$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2412 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11n-HT20 2412MHz Body Front/Area Scan (11x17x1): Measurement grid:

dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.310 W/kg

Configuration/802.11n-HT20 2412MHz Body Front/Zoom Scan (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm; Reference Value = 3.195 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.731 W/kg

SAR(1 g) = 0.322 W/kg; SAR(10 g) = 0.139 W/kg Maximum value of SAR (measured) = 0.365 W/kg


0 dB = 0.365 W/kg = -4.38 dBW/kg

Plot 16#

Test Date: 07/15/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11ac-VHT20 5260MHz Body Back

Communication System: 802.11ac; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5300$ MHz; $\sigma = 4.67$ S/m; $\epsilon_r = 35.8$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(5.15, 5.15, 5.15) @ 5300 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11ac-VHT20 5260MHz Body Back/Area Scan (13x21x1): Measurement grid:

dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.913 W/kg

Configuration/802.11ac-VHT20 5260MHz Body Back/Zoom Scan (8x8x6)/Cube 0: Measurement grid:

dx=4mm, dy=4mm, dz=2mm; Reference Value = 0.911 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 0.482 W/kg; SAR(10 g) = 0.152 W/kg Maximum value of SAR (measured) = 0.964 W/kg


0 dB = 0.964 W/kg = -0.16 dBW/kg

Plot 17#

Test Date: 07/16/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11ac-VHT20 5500MHz Body Right

Communication System: 802.11ac; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5500$ MHz; $\sigma = 4.89$ S/m; $\epsilon_r = 35.44$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.77, 4.77, 4.77) @ 5500 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11ac-VHT20 5500MHz Body Right/Area Scan (7x21x1): Measurement grid:

dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.718 W/kg

Configuration/802.11ac-VHT20 5500MHz Body Right/Zoom Scan (8x8x6)/Cube 0: Measurement grid:

dx=4mm, dy=4mm, dz=2mm; Reference Value = 1.083 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 1.54 W/kg

SAR(1 g) = 0.431 W/kg; SAR(10 g) = 0.148 W/kg; Maximum value of SAR (measured) = 0.861 W/kg


0 dB = 0.861 W/kg = -0.65 dBW/kg

Plot 18#

Test Date: 07/20/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11ac-VHT20 5825MHz Body Right

Communication System: 802.11ac; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5825$ MHz; $\sigma = 5.29$ S/m; $\epsilon_r = 34.86$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5825 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11ac-VHT20 5825MHz Body Right/Area Scan (7x21x1): Measurement grid:

dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.381 W/kg

Configuration/802.11ac-VHT20 5825MHz Body Right/Zoom Scan (8x8x6)/Cube 0: Measurement grid:

dx=4mm, dy=4mm, dz=2mm; Reference Value = 0.807 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.923 W/kg

SAR(1 g) = 0.223 W/kg; SAR(10 g) = 0.074 W/kg Maximum value of SAR (measured) = 0.477 W/kg


0 dB = 0.477 W/kg = -3.21 dBW/kg

Plot 19#

Test Date: 07/14/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11b 2412MHz Extremity Left

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 40.66$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:


- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2412 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11b 2412MHz Extremity Left/Area Scan (6x17x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.14 W/kg

Configuration/802.11b 2412MHz Extremity Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm; Reference Value = 23.64 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 2.93 W/kg

SAR(1 g) = 1.23 W/kg; SAR(10 g) = 0.517 W/kg Maximum value of SAR (measured) = 1.43 W/kg


0 dB = 1.43 W/kg = 1.55 dBW/kg

Plot 20#

Test Date: 07/15/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11a 5260MHz Extremity Left

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5260$ MHz; $\sigma = 4.62$ S/m; $\epsilon_r = 35.87$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:


- Probe: EX3DV4 - SN7524; ConvF(5.15, 5.15, 5.15) @ 5260 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11a 5260MHz Extremity Left/Area Scan (7x21x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.73 W/kg

Configuration/802.11a 5260MHz Extremity Left/Zoom Scan (9x9x6)/Cube 0: Measurement grid:

dx=4mm, dy=4mm, dz=2mm; Reference Value = 25.99 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 8.76 W/kg

SAR(1 g) = 1.78 W/kg; SAR(10 g) = 0.415 W/kg Maximum value of SAR (measured) = 3.88 W/kg


0 dB = 3.88 W/kg = 5.89 dBW/kg

Plot 21#

Test Date: 07/20/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11a 5720MHz Extremity Left

Communication System: 802.11a; Frequency: 5720 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5720$ MHz; $\sigma = 5.15$ S/m; $\epsilon_r = 35.05$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:


- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5720 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11a 5720MHz Extremity Left/Area Scan (7x21x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.88 W/kg

Configuration/802.11a 5720MHz Extremity Left/Zoom Scan (9x9x6)/Cube 0: Measurement grid:

dx=4mm, dy=4mm, dz=2mm; Reference Value = 25.26 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 9.24 W/kg

SAR(1 g) = 1.75 W/kg; SAR(10 g) = 0.403 W/kg Maximum value of SAR (measured) = 3.89 W/kg


0 dB = 3.89 W/kg = 5.90 dBW/kg

Plot 22#

Test Date: 07/20/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11a 5745MHz Extremity Left

Communication System: 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1


Medium parameters used: $f = 5745 \text{ MHz}$; $\sigma = 5.19 \text{ S/m}$; $\epsilon_r = 35$; $\rho = 1000 \text{ kg/m}^3$; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5745 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Configuration/802.11a 5745MHz Extremity Left/Area Scan (7x21x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$; Maximum value of SAR (measured) = 3.27 W/kg

Configuration/802.11a 5745MHz Extremity Left/Zoom Scan (9x9x6)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$; Reference Value = 26.70 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 9.41 W/kg

SAR(1 g) = 1.77 W/kg; SAR(10 g) = 0.411 W/kg Maximum value of SAR (measured) = 4.04 W/kg


0 dB = 4.04 W/kg = 6.06 dBW/kg

Plot 23#

Test Date: 07/14/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: Bluetooth 3DH5 2402MHz Extremity Left

Communication System: Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2402$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 40.68$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2402 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/Bluetooth 3DH5 2402MHz Extremity Left/Area Scan (6x17x1): Measurement grid:

dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.0858 W/kg

Configuration/Bluetooth 3DH5 2402MHz Extremity Left/Zoom Scan (7x7x7)/Cube 0: Measurement

grid: dx=5mm, dy=5mm, dz=5mm; Reference Value = 6.148 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.231 W/kg

SAR(1 g) = 0.095 W/kg; SAR(10 g) = 0.037 W/kg Maximum value of SAR (measured) = 0.113 W/kg


0 dB = 0.113 W/kg = -9.47 dBW/kg

Plot 24#

Test Date: 07/14/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11n-HT20 2412MHz Extremity Front

Communication System: 802.11n; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 40.66$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(7.6, 7.6, 7.6) @ 2412 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11n-HT20 2412MHz Extremity Front/Area Scan (11x17x1): Measurement grid:

dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.07 W/kg

Configuration/802.11n-HT20 2412MHz Extremity Front/Zoom Scan (7x7x7)/Cube 0: Measurement

grid: dx=5mm, dy=5mm, dz=5mm; Reference Value = 2.212 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 2.81 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.430 W/kg Maximum value of SAR (measured) = 1.27 W/kg


0 dB = 1.27 W/kg = 1.04 dBW/kg

Plot 25#

Test Date: 07/15/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11ac-VHT20 5320MHz Extremity Back

Communication System: 802.11ac; Frequency: 5320 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5320$ MHz; $\sigma = 4.7$ S/m; $\epsilon_r = 35.77$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(5.15, 5.15, 5.15) @ 5320 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11ac-VHT20 5320MHz Extremity Back/Area Scan (13x21x1): Measurement grid:

dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.57 W/kg

Configuration/802.11ac-VHT20 5320MHz Extremity Back/Zoom Scan (8x8x6)/Cube 0: Measurement

grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 0.846 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 5.29 W/kg

SAR(1 g) = 1.36 W/kg; SAR(10 g) = 0.363 W/kg Maximum value of SAR (measured) = 2.79 W/kg


0 dB = 2.79 W/kg = 4.46 dBW/kg

Plot 26#

Test Date: 07/16/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11ac-VHT20 5500MHz Extremity Back

Communication System: 802.11ac; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5500$ MHz; $\sigma = 4.89$ S/m; $\epsilon_r = 35.44$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.77, 4.77, 4.77) @ 5500 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11ac-VHT20 5500MHz Extremity Back/Area Scan (13x21x1): Measurement grid:

dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.22 W/kg

Configuration/802.11ac-VHT20 5500MHz Extremity Back/Zoom Scan (8x8x6)/Cube 0: Measurement

grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 1.212 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 4.60 W/kg

SAR(1 g) = 1.22 W/kg; SAR(10 g) = 0.341 W/kg Maximum value of SAR (measured) = 2.39 W/kg


0 dB = 2.39 W/kg = 3.78 dBW/kg

Plot 27#

Test Date: 07/20/2020

DUT: Mobile Computer; Type: CT40P-L0N
Procedure Name: 802.11ac-VHT20 5825MHz Extremity Back

Communication System: 802.11ac; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5825$ MHz; $\sigma = 5.29$ S/m; $\epsilon_r = 34.86$; $\rho = 1000$ kg/m³; Tissue Temp (celsius)-22.5°C; Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7524; ConvF(4.84, 4.84, 4.84) @ 5825 MHz; Calibrated: 5/20/2020
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1552; Calibrated: 5/6/2020
- Phantom: SAM2; Type: QD OVA 004 AA; Serial: 2089
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Configuration/802.11ac-VHT20 5825MHz Extremity Back/Area Scan (13x21x1): Measurement grid:

dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.31 W/kg

Configuration/802.11ac-VHT20 5825MHz Extremity Back/Zoom Scan (8x8x6)/Cube 0: Measurement

grid: dx=4mm, dy=4mm, dz=2mm; Reference Value = 0.961 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 3.39 W/kg

SAR(1 g) = 0.690 W/kg; SAR(10 g) = 0.182 W/kg Maximum value of SAR (measured) = 1.44 W/kg


0 dB = 1.44 W/kg = 1.58 dBW/kg

Annex C - SAR Test Setup Photos

Refer to "2006RSU069-UT" file.

Annex D - EUT External Photos

Refer to "2006RSU069-UE" file.

Annex E - Equipment Calibration Report

Please refer to document "Annex E - Equipment Calibration Report.pdf".