



RF EXPOSURE REPORT

Applicant	YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
Address	309, 3rd Floor, No.16, Yun Ding North Road, Huli District, Xiamen City, Fujian, P.R. China

Manufacturer or Supplier	YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
Address	309, 3rd Floor, No.16, Yun Ding North Road, Huli District, Xiamen City, Fujian, P.R. China
Product	Video Conferencing Endpoint
Brand Name	YEALINK
Model	MeetingEye 600
Additional Model & Model Difference	PVT960, difference the model number only.
Date of tests	Jun. 24, 2020 ~ Jul. 25, 2020

- ☒ FCC Part 2 (Section 2.1091)
☒ KDB 447498 D01
☒ IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Andy Zhu Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date: Jul. 31, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FM200624N080

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM200624N080	Original release	Jul. 31, 2020



Test Report No.: FM200624N080

1. CERTIFICATION

PRODUCT: Video Conferencing Endpoint

BRAND NAME: YEALINK

MODEL NO.: MeetingEye 600

ADDITIONAL MODEL: PVT960

FCC ID: T2C-ME600

TEST SAMPLE: ENGINEERING SAMPLE

APPLICANT: YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.

TESTED DATES: Jun. 24, 2020 ~ Jul. 25, 2020

STANDARDS: FCC Part 2 (Section 2.1091)
KDB 447498 D01
IEEE C95.1

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Frequency Band	Antenna Gain (dBi)	Antenna Type
BT 2.4GHz	3	PCB Antenna
Wi-Fi 2.4GHz	3	PCB Antenna
Wi-Fi 5GHz (5150-5250MHz)	3	PCB Antenna
Wi-Fi 5GHz (5250-5350MHz)	3	PCB Antenna
Wi-Fi 5GHz (5500-5725MHz)	3	PCB Antenna
Wi-Fi 5GHz (5725-5850MHz)	3	PCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT (GFSK)	2402-2480MHz	4	+2	2	6
BT (8DPSK)	2402-2480MHz	4	+2	2	6
BT-LE (GFSK)	2402-2480MHz	-1	+2	-3	1
802.11b	2412-2462MHz	13	+2	11	15
802.11g	2412-2462MHz	13	+2	11	15
802.11n HT20	2412-2462MHz	12	+2	10	14
802.11n HT40	2422-2452MHz	12	+2	10	14
Wi-Fi 5GHz(Band1)	5150-5250MHz	12	+3	9	15
Wi-Fi 5GHz(Band2)	5250-5350MHz	13	+2	11	15
Wi-Fi 5GHz(Band3)	5500-5725MHz	12	+4	8	16
Wi-Fi 5GHz(Band4)	5725-5850MHz	13	+2	11	15

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
BT (GFSK)	2441	4.14
BT (8DPSK)	2402	4.75
BT-LE (GFSK)	2440	-0.94
802.11b	2462	13.75
802.11g	2462	13.26
802.11n HT20	2437	13.05
802.11n HT40	2452	12.94
Wi-Fi 5GHz(Band1)	5200	13.63
Wi-Fi 5GHz(Band2)	5260	13.57
Wi-Fi 5GHz(Band3)	5610	14.31
Wi-Fi 5GHz(Band4)	5775	13.78

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
BT	6	3	20	0.0015803	1.0
Wi-Fi 2.4GHz	15	3	20	0.0125525	1.0
Wi-Fi 5GHz	16	3	20	0.0158026	1.0

CONCLUSION:

The BT and Wi-Fi can transmit simultaneously, but Wi-Fi 2.4G and Wi-Fi 5G can not transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$(0.0015803 / 1) + (0.0158026 / 1) = 0.017383 < 1, \text{ which is less than the "1" limit.}$$

--- END ---