Antenna Specification


| No. | Contents | Number of Page | Page |
|------|-----------------------|----------------|--------------|
| INO. | Contents | Number of Page | Page Code |
| 1 | Antenna describe | 2 | 2 |
| 2 | External view drawing | 2 | 2 |
| 3 | Antenna Pattern | 3 | 4 |

1. Antenna describe.

| Frequency range | 2400 MHz-2500 MHz |
|--------------------|-------------------|
| Antenna type | PCB Antenna |
| Antenna plate | Monoploe |
| Antenna gain(Peak) | -0.58 dBi |
| Antenna impedance | 50Ω |
| V.S.W.R | <= 2.0 Max |

2. External view drawing.

Company: mm




3. Antenna Pattern.

2D Pattern

Horizontal: 2400 MHz 2450 MHz 2500 MHz

Power (dBm)

Max: 0 Min: -40 Scale: 5/div




| Frequency | | Gain(dB) | Avg |
|-----------|-----------|----------|----------|
| (MHz) | Max | Min | |
| 2400 | -1.26174 | -30.0801 | -7.18716 |
| 2450 | -0.765802 | -36.5604 | -7.48023 |
| 2500 | -0.585582 | -22.0315 | -6.59127 |

Vertical: 2400 MHz 2450 MHz 2500 MHz

Power (dBm)

Max: 0 Min: -30 Scale: 5/div

SHENZHEN PENGLIN ELECTRONIC CO., LTD



| Frequency | | Gain(dB) | Avg |
|-----------|----------|----------|----------|
| (MHz) | Max | Min | |
| 2400 | -5.2537 | -22.1424 | -12.4294 |
| 2450 | -2.4652 | -24.5837 | -10.4702 |
| 2500 | -1.86120 | -29.5214 | -9.20432 |