

Appendix A: Effective (Isotropic) Radiated Power Output Data

Test Result

Band	Channel	PCL	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GSM850	128	5	33.59	25.10	38.45	PASS
GSM850	190	5	33.89	25.40	38.45	PASS
GSM850	251	5	33.57	25.08	38.45	PASS
GSM1900	512	0	31.13	28.01	33.00	PASS
GSM1900	661	0	31.33	28.21	33.00	PASS
GSM1900	810	0	31.22	28.10	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GPRS850	128	5	1	33.56	25.07	38.45	PASS
GPRS850	128	5	2	32.37	23.88	38.45	PASS
GPRS850	128	5	3	30.02	21.53	38.45	PASS
GPRS850	128	5	4	28.62	20.13	38.45	PASS
GPRS850	190	5	1	33.83	25.34	38.45	PASS
GPRS850	190	5	2	32.71	24.22	38.45	PASS
GPRS850	190	5	3	30.36	21.87	38.45	PASS
GPRS850	190	5	4	28.98	20.49	38.45	PASS
GPRS850	251	5	1	33.48	24.99	38.45	PASS
GPRS850	251	5	2	32.26	23.77	38.45	PASS
GPRS850	251	5	3	29.93	21.44	38.45	PASS
GPRS850	251	5	4	28.53	20.04	38.45	PASS
GPRS1900	512	0	1	31.16	28.04	33.00	PASS
GPRS1900	512	0	2	30.36	27.24	33.00	PASS
GPRS1900	512	0	3	28.03	24.91	33.00	PASS
GPRS1900	512	0	4	26.18	23.06	33.00	PASS
GPRS1900	661	0	1	31.35	28.23	33.00	PASS
GPRS1900	661	0	2	30.59	27.47	33.00	PASS
GPRS1900	661	0	3	28.24	25.12	33.00	PASS
GPRS1900	661	0	4	26.47	23.35	33.00	PASS
GPRS1900	810	0	1	31.23	28.11	33.00	PASS
GPRS1900	810	0	2	30.44	27.32	33.00	PASS
GPRS1900	810	0	3	28.15	25.03	33.00	PASS
GPRS1900	810	0	4	26.44	23.32	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
EGPRS850	128	8	1	28.47	19.98	38.45	PASS
EGPRS850	128	8	2	27.22	18.73	38.45	PASS
EGPRS850	128	8	3	25.20	16.71	38.45	PASS
EGPRS850	128	8	4	23.98	15.49	38.45	PASS
EGPRS850	190	8	1	28.56	20.07	38.45	PASS
EGPRS850	190	8	2	27.39	18.9	38.45	PASS
EGPRS850	190	8	3	25.25	16.76	38.45	PASS
EGPRS850	190	8	4	24.11	15.62	38.45	PASS
EGPRS850	251	8	1	28.47	19.98	38.45	PASS
EGPRS850	251	8	2	27.28	18.79	38.45	PASS
EGPRS850	251	8	3	25.21	16.72	38.45	PASS
EGPRS850	251	8	4	23.99	15.5	38.45	PASS
EGPRS1900	512	2	1	27.51	24.39	33.00	PASS
EGPRS1900	512	2	2	26.35	23.23	33.00	PASS
EGPRS1900	512	2	3	24.18	21.06	33.00	PASS
EGPRS1900	512	2	4	22.96	19.84	33.00	PASS
EGPRS1900	661	2	1	27.97	24.85	33.00	PASS
EGPRS1900	661	2	2	26.84	23.72	33.00	PASS
EGPRS1900	661	2	3	24.74	21.62	33.00	PASS
EGPRS1900	661	2	4	23.49	20.37	33.00	PASS
EGPRS1900	810	2	1	28.03	24.91	33.00	PASS
EGPRS1900	810	2	2	26.92	23.8	33.00	PASS
EGPRS1900	810	2	3	24.79	21.67	33.00	PASS
EGPRS1900	810	2	4	23.58	20.46	33.00	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For GSM1900)

ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For GSM850)


Appendix B: Peak-to-Average Ratio(CCDF)

Test Result

Band	Channel	PCL	Result(dB)	Limit(dB)	Verdict
GSM850	190	5	2.73	13	PASS
EGPRS850	190	8	5.66	13	PASS
GSM1900	661	0	2.71	13	PASS
EGPRS1900	661	2	5.65	13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test Result

Band	Channel	PCL	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM850	128	5	0.24690	0.3155	---	PASS
GSM850	190	5	0.24414	0.3095	---	PASS
GSM850	251	5	0.24723	0.3168	---	PASS
EGPRS850	128	8	0.24819	0.3188	---	PASS
EGPRS850	190	8	0.24644	0.3157	---	PASS
EGPRS850	251	8	0.24782	0.3187	---	PASS
GSM1900	512	0	0.24670	0.3159	---	PASS
GSM1900	661	0	0.24655	0.3128	---	PASS
GSM1900	810	0	0.24572	0.3116	---	PASS
EGPRS1900	512	2	0.25063	0.3166	---	PASS
EGPRS1900	661	2	0.24713	0.3015	---	PASS
EGPRS1900	810	2	0.24758	0.3135	---	PASS

Test Graphs







Appendix D: Band Edge

Test Result

Band	Channel	PCL	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM850	128	5	824.00	-23.45	-13	PASS
GSM850	251	5	849.02	-23.94	-13	PASS
EGPRS850	128	8	823.98	-32.32	-13	PASS
EGPRS850	251	8	849.02	-34.01	-13	PASS
GSM1900	512	0	1849.99	-26.01	-13	PASS
GSM1900	810	0	1910.03	-26.81	-13	PASS
EGPRS1900	512	2	1849.99	-17.36	-13	PASS
EGPRS1900	810	2	1910.01	-16.90	-13	PASS

Test Graphs






Appendix E: Conducted Spurious Emission

Test Result

Band	Channel	PCL	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM850	128	5	0.009~0.15MHz	0.01	-56.21	-33	PASS
GSM850	128	5	0.15~30MHz	0.15	-41.35	-13	PASS
GSM850	128	5	30~1000MHz	488.45	-45.23	-13	PASS
GSM850	128	5	1000~10000MHz	1648.6	-28.76	-13	PASS
GSM850	190	5	0.009~0.15MHz	0.01	-54.14	-33	PASS
GSM850	190	5	0.15~30MHz	0.15	-41.57	-13	PASS
GSM850	190	5	30~1000MHz	956.41	-44.82	-13	PASS
GSM850	190	5	1000~10000MHz	1673.2	-28.61	-13	PASS
GSM850	251	5	0.009~0.15MHz	0.01	-56.16	-33	PASS
GSM850	251	5	0.15~30MHz	0.15	-44.58	-13	PASS
GSM850	251	5	30~1000MHz	517.49	-44.81	-13	PASS
GSM850	251	5	1000~10000MHz	1697.5	-29.81	-13	PASS
GSM1900	512	0	0.009~0.15MHz	0.01	-55.95	-43	PASS
GSM1900	512	0	0.15~30MHz	0.15	-44.12	-23	PASS
GSM1900	512	0	30~1000MHz	495.5	-45.47	-13	PASS
GSM1900	512	0	1000~18000MHz	16225.77	-22.27	-13	PASS
GSM1900	661	0	0.009~0.15MHz	0.01	-54.95	-43	PASS
GSM1900	661	0	0.15~30MHz	0.15	-44.11	-23	PASS
GSM1900	661	0	30~1000MHz	713.43	-45.53	-13	PASS
GSM1900	661	0	1000~18000MHz	16169.1	-21.98	-13	PASS
GSM1900	810	0	0.009~0.15MHz	0.01	-56.84	-43	PASS
GSM1900	810	0	0.15~30MHz	0.15	-42.39	-23	PASS
GSM1900	810	0	30~1000MHz	888.61	-45.36	-13	PASS
GSM1900	810	0	1000~18000MHz	16730.1	-22.27	-13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





JianYan Testing Group Shenzhen Co., Ltd.


No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Project No.: JYTSZR2406066







Appendix F: Frequency Stability

Test Result

Reference Frequency: GSM850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	-8.27	-0.009885	±2.5	Pass
	-20	-5.29	-0.006323		
	-10	-3.84	-0.004590		
	0	-8.01	-0.009574		
	10	-3.68	-0.004399		
	20	-3.97	-0.004745		
	30	-5.46	-0.006526		
	40	-5.81	-0.006945		
	50	0.81	0.000968		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-9.30	-0.011116	±2.5	Pass
	3.87	-6.49	-0.007758		
	4.45	-7.30	-0.008726		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	-6.65	-0.007949	±2.5	Pass
	-20	-4.29	-0.005128		
	-10	-8.62	-0.010304		
	0	-8.07	-0.009646		
	10	-2.49	-0.002976		
	20	-3.58	-0.004279		
	30	-4.07	-0.004865		
	40	-3.68	-0.004399		
	50	-0.13	-0.000155		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-4.16	-0.004973	±2.5	Pass
	3.87	-11.04	-0.013196		
	4.45	-7.23	-0.008642		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: PCS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	-21.08	-0.011213	Within authorized band for PCS 1900	Pass
	-20	-26.57	-0.014133		
	-10	-17.66	-0.009394		
	0	-23.02	-0.012245		
	10	-19.86	-0.010564		
	20	-14.88	-0.007915		
	30	-17.27	-0.009186		
	40	-14.50	-0.007713		
	50	-15.17	-0.008069		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-29.09	-0.015473	Within authorized band for PCS 1900	Pass
	3.87	-31.90	-0.016968		
	4.45	-24.86	-0.013223		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	1.74	0.000926	Within authorized band for PCS 1900	Pass
	-20	-2.03	-0.001080		
	-10	-4.29	-0.002282		
	0	-0.39	-0.000207		
	10	-4.88	-0.002596		
	20	1.90	0.001011		
	30	5.84	0.003106		
	40	5.94	0.003160		
	50	5.49	0.002920		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-6.78	-0.003606	Within authorized band for PCS 1900	Pass
	3.87	-9.43	-0.005016		
	4.45	-3.71	-0.001973		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Appendix G: Modulation Characteristics

Test Result

Band	Channel	Result	Verdict
GSM850	190	PASS	PASS
EGPRS850	190	PASS	PASS
GSM1900	661	PASS	PASS
EGPRS1900	661	PASS	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs

