RF EXPOSURE EVALUATION

MPE-Based Exemption

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Report No.: 2401Z45477E-RF-00D

According to KDB 447498 D04 Interim General RF Exposure Guidance V01

MPE-Based Exemption:

following equation:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation					
RF Source frequency (MHz)	Threshold ERP (watts)				
0.3-1.34	1,920 R ² .				
1.34-30	3,450 R ² /f ² .				
30-300	3.83 R ² .				
300-1,500	0.0128 R ² f.				
1,500-100,000	19.2R ² .				

R is the minimum separation distance in meters f = f frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the

$$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$

TR-EM-RF015 Page 96 of 99 Version 4.0

Result

Mode	Frequency (MHz)	Tune up conducted power [#] (dBm)	Antenna Gain [#]		ERP		Evaluation Distance	ERP Limit
			(dBi)	(dBd)	(dBm)	(mW)	(m)	(mW)
Bluetooth	2402-2480	15.5	1.2	-0.95	14.55	28.51	0.2	768
BLE	2402-2480	14.0	1.2	-0.95	13.05	20.18	0.2	768
2.4G Wi-Fi	2412-2462	23.0	2.1	-0.05	22.95	197.24	0.2	768
5.2G Wi-Fi	5180-5240	15.5	2.3	0.15	15.65	36.73	0.2	768
5.8G Wi-Fi	5745-5825	14.5	3.8	1.65	16.15	41.21	0.2	768

Report No.: 2401Z45477E-RF-00D

Note: 1. The tune up conducted power[#] and antenna gain[#] was declared by the applicant.
2. The BT and Wi-Fi can transmit at same time, the 2.4G and 5G Wi-Fi cannot transmit at same time.

Simultaneous transmitting consideration (worst case):

The ratio= $ERP_{BT}/limit + ERP_{2.4G~Wi-Fi}/limit = 28.51/768 + 197.24/768 = 0.294 < 1.0$

So simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant