

RADIO TEST REPORT

Report No: 1707217W03

Issued for

General Procurement,INC.

800 E Dyer Road Santa Ana,Ca 92705 Santa Ana California
United States

Product Name:	5inch 3G Smartphone
Brand Name:	VULCAN , HYUNDAI
Model Name:	VS5016
Series Model:	G25028K, T26
FCC ID:	S94VS5016
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from BZT, All Test Data Presented in this report is only applicable to presented Test sample.

BZT Testing Technology Co., Ltd

Add. : Buliding 17, Xinghua Road Xingwei industrial Park Fuyong,
Baoan District, Shenzhen, Guangdong, China

TEL: +86-755 3307 1680 FAX: +86-755 27341758 E-mail:bruce@bzt.Cn

TEST RESULT CERTIFICATION

Applicant's name : General Procurement,INC.
Address : 800 E Dyer Road Santa Ana, Ca 92705 Santa Ana California United States
Manufacture's Name : Sintave
Address : 6th F, 3rd building, Sangtai Technology Park, Xili Nanshan Shenzhen, China

Product description

Product name : 5inch 3G Smartphone
Model and/or type reference : VS5016
Series Model : G25028K, T26

Standards : FCC Part15.247

Test procedure ANSI C63.10-2013

This device described above has been tested by BZT, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BZT, this document may be altered or revised by BZT, personal only, and shall be noted in the revision of the document

Date of Test :

Date (s) of performance of tests : 26 June. 2017~30 June. 2017

Date of Issue : 01 July. 2017

Test Result : **Pass**

Testing Engineer :



(Sean she)

Technical Manager :



(Hakim.hou)

Authorized Signatory :



(Vita Li)

Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 TEST PROCEDURE	15
3.3 TEST SETUP	15
3.4 EUT OPERATING CONDITIONS	15
3.5 TEST RESULTS	16
4. RADIATED EMISSION MEASUREMENT	18
4.1 RADIATED EMISSION LIMITS	18
4.2 TEST PROCEDURE	19
4.3 TEST SETUP	20
4.4 EUT OPERATING CONDITIONS	20
4.5 TEST RESULTS	21
5. CONDUCTED SPURIOUS & BAND EDGE EMISSION	28
5.1 REQUIREMENT	28
5.2 TEST PROCEDURE	28
5.3 TEST SETUP	28
5.4 EUT OPERATION CONDITIONS	28
5.5 TEST RESULTS	29
6. POWER SPECTRAL DENSITY TEST	32
6.1 APPLIED PROCEDURES / LIMIT	32
6.2 TEST PROCEDURE	32
6.3 TEST SETUP	32
6.4 EUT OPERATION CONDITIONS	32
6.5 TEST RESULTS	33

Table of Contents	Page
7. BANDWIDTH TEST	35
7.1 APPLIED PROCEDURES / LIMIT	35
7.2 TEST PROCEDURE	35
7.3 TEST SETUP	35
7.4 EUT OPERATION CONDITIONS	35
7.5 TEST RESULTS	36
8. PEAK OUTPUT POWER TEST	38
8.1 APPLIED PROCEDURES / LIMIT	38
8.2 TEST PROCEDURE	38
8.3 TEST SETUP	38
8.4 EUT OPERATION CONDITIONS	38
8.5 TEST RESULTS	39
9. ANTENNA REQUIREMENT	40
9.1 STANDARD REQUIREMENT	40
9.2 EUT ANTENNA	40
10. EUT TEST PHOTO	41

Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	01 July. 2017	1707217W03	ALL	Initial Issue

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 DTS Meas Guidance v04

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.247 (c)	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
Part 15.247(d)/part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report
- (2) All tests are according to ANSI C63.10-2013

1.1 TEST FACTORY

BZT Testing Technology Co., Ltd.

Add. : Buliding 17, Xinghua Road Xingwei industrial Park Fuyong,
Baoan District, Shenzhen, Guangdong, China

FCC Registration No.: 701733

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %** .

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.88\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.67\text{dB}$
3	RF power,conducted	$\pm 0.70\text{dB}$
4	Spurious emissions,conducted	$\pm 1.19\text{dB}$
5	All emissions,radiated(<30M) (9KHz-30MHz)	$\pm 2.45\text{dB}$
6	All emissions,radiated(<1G) 30MHz-200MHz	$\pm 2.83\text{dB}$
7	All emissions,radiated(<1G) 200MHz-1000MHz	$\pm 2.94\text{dB}$
8	All emissions,radiated(>1G)	$\pm 3.03\text{dB}$
9	Temperature	$\pm 0.5^{\circ}\text{C}$
10	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	5inch 3G Smartphone	
Trade Name	VULCAN, HYUNDAI	
Model Name	VS5016	
Series Model	G25028K, T26	
Model Difference	Only different in model name and brand name	
Product Description	The EUT is a 5inch 3G Smartphone	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK
	Radio Technology	BLE
	Number Of Channel	40
	Antenna Designation:	Please see Note 3.
	Antenna Gain (dBi)	1.52 dBi
Channel List	Please refer to the Note 2.	
Adapter	Input: AC 100-240V, 0.4A, 50/60 Hz Output: DC 5V, 1A	
Battery	Rated Voltage: 3.8V Charge Limit: 4.2V Capacity: 1700mAh	
Hardware version number	T960W-v1.2	
Software version number	VULCAN_VS5016_ V03	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402	11	2422	21	2442	31	2462
02	2404	12	2424	22	2444	32	2464
03	2406	13	2426	23	2446	33	2466
04	2408	14	2428	24	2448	34	2468
05	2410	15	2430	25	2450	35	2470
06	2412	16	2432	26	2452	36	2472
07	2414	17	2434	27	2454	37	2474
08	2416	18	2436	28	2456	38	2476
09	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	VULCAN , HYUNDAI	VS5016	PIFA Antenna	N/A	1.52	BT 4.0 ANT

2.2 DESCRIPTION OF TEST MODES

For conducted test items and radiated spurious emissions

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively..

Worst Mode	Description	Data/Modulation
Mode 1	TX CH1(2402MHz)	1 MHz/GFSK
Mode 2	TX CH20(2440MHz)	1 MHz/GFSK
Mode 3	TX CH40(2480MHz)	1 MHz/GFSK

Note:


- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- (2) We have be tested for all avaiable U.S. voltage and frequencies (For 120V,50/60Hz and 240V,50/60Hz) for which the device is capable of operation.
- (3) The EUT was programmed to be in continuously transmitting with a modulated carrier at maximum power on bottom/middle/top channels as required using the supported data rates/modulation types and the transmit duty cycle is not less than 98%.
- (4) Controlled using a bespoke application on the laptop PC supplied by the customer. The application was used to enable a continuous transmission mode and to select the test channels, data rates and modulation schemes as required.

For AC Conducted Emission


Test Case	
AC Conducted Emission	Mode 4 : Keeping BT TX

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	5inch 3G Smartphone	VULCAN, HYUNDAI	VS5016	N/A	EUT
E-2	Adapter	VULCAN	RWX-AA05100U	N/A	EUT
E-3	Earphone	N/A	N/A	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable shielded line (Charging)	NO	100cm	N/A
C-2	Earphone Line	NO	110cm	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2017.3.11	2018.3.10
Test Receiver	R&S	ESCI	101427	2016.10.23	2017.10.22
Bilog Antenna	TESEQ	CBL6111D	34678	2017.03.24	2018.03.23
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2017.03.06	2018.03.05
Horn Antenna	Schwarzbeck	BBHA 9170	9170-0741	2017.05.02	2018.05.01
PreAmplifier	Agilent	8449B	60538	2016.10.23	2017.10.22
Loop Antenna	EMCO	6502	9003-2485	N/A	N/A
Low frequency cable	EM	R01	N/A	2017.03.12	2018.03.11
Low frequency cable	EM	R06	N/A	2017.03.12	2018.03.11
High frequency cable	SCHWARZBECK	AK9515H	SN-96286/96287	2017.03.12	2018.03.11
Semi-anechoic chamber	Changling	966	N/A	2016.10.23	2017.10.22

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESCI	101427	2016.10.23	2017.10.22
LISN	R&S	ENV216	101242	2016.10.26	2017.10.25
LISN	EMCO	3810/2NM	000-23625	2016.10.26	2017.10.25
Conduction Cable	EM	C01	N/A	2017.03.12	2018.03.11
Shielding Room	Changling	854	N/A	2016.10.23	2017.10.22

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2016.10.23	2017.10.22
Spectrum Analyzer	Agilent	E4407B	MY50140340	2017.03.11	2018.03.10
Signal Analyzer	Agilent	N9020A	MY49100060	2016.10.23	2017.10.22

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.5 TEST RESULTS

Temperature:	25.4 °C	Relative Humidity:	61%
Pressure:	1010hPa	Phase:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1780	41.32	9.78	51.10	64.58	-13.48	QP
0.1780	27.04	9.78	36.82	54.58	-17.76	AVG
0.5100	37.98	10.02	48.00	56.00	-8.00	QP
0.5100	21.39	10.02	31.41	46.00	-14.59	AVG
1.0660	40.15	9.80	49.95	56.00	-6.05	QP
1.0660	28.43	9.80	38.23	46.00	-7.77	AVG
2.2660	36.61	9.80	46.41	56.00	-9.59	QP
2.2660	17.03	9.80	26.83	46.00	-19.17	AVG
3.7500	36.35	9.83	46.18	56.00	-9.82	QP
3.7500	16.06	9.83	25.89	46.00	-20.11	AVG
10.9900	29.63	10.22	39.85	60.00	-20.15	QP
10.9900	8.92	10.22	19.14	50.00	-30.86	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor)–Limit




Temperature:	25.4°C	Relative Humidity:	61%
Pressure:	1010hPa	Phase:	N
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1500	46.47	9.75	56.22	66.00	-9.78	QP
0.1500	21.83	9.75	31.58	56.00	-24.42	AVG
0.5020	41.26	9.98	51.24	56.00	-4.76	QP
0.5020	29.08	9.98	39.06	46.00	-6.94	AVG
1.1580	43.02	9.81	52.83	56.00	-3.17	QP
1.1580	29.73	9.81	39.54	46.00	-6.46	AVG
2.2820	39.75	9.89	49.64	56.00	-6.36	QP
2.2820	23.90	9.89	33.79	46.00	-12.21	AVG
5.0180	35.36	9.92	45.28	60.00	-14.72	QP
5.0180	18.58	9.92	28.50	50.00	-21.50	AVG
10.0060	31.80	9.93	41.73	60.00	-18.27	QP
10.0060	15.94	9.93	25.87	50.00	-24.13	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (Frequency Range 9kHz-1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2403 MHz Upper Band Edge: 2479 to 2500 MHz
RB / VB (emission in restricted band)	1 MHz / 3 MHz

Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.5 TEST RESULTS

(Between 9KHz – 30 MHz)

Temperature:	26°C	Relative Humidity:	60%
Pressure:	1010 hPa	Test Voltage:	3.8V from Battery
Test Mode:	TX Mode	Polarization:	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the Permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.


(30MHz -1000MHz)

Temperature:	26 °C	Relative Humidity:	60%
Pressure:	1010hPa	Phase:	Horizontal
Test Voltage:	3.8V from Battery	Test Mode:	Mode1/2/3 (Mode 1- worst mode)

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
48.8430	41.49	-20.89	20.60	40.00	-19.40	QP
144.8418	47.08	-17.74	29.34	43.50	-14.16	QP
181.9202	60.01	-19.60	40.41	43.50	-3.09	QP
364.2595	47.53	-13.03	34.50	46.00	-11.50	QP
545.1826	40.83	-6.89	33.94	46.00	-12.06	QP
729.3583	40.90	-4.11	36.79	46.00	-9.21	QP

Remark:

1. Margin = Result (Result =Reading + Factor)–Limit




Temperature:	26 °C	Relative Humidity:	60%
Pressure:	1010hPa	Phase:	Vertical
Test Voltage:	3.8V from Battery	Test Mode:	Mode1/2/3 (Mode 1- worst mode)

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
35.2512	50.81	-13.88	36.93	40.00	-3.07	QP
146.3735	45.27	-17.80	27.47	43.50	-16.03	QP
181.6434	59.68	-19.58	40.10	43.50	-3.40	QP
364.2595	48.16	-13.03	35.13	46.00	-10.87	QP
545.1826	42.69	-6.89	35.80	46.00	-10.20	QP
726.8052	42.73	-4.26	38.47	46.00	-7.53	QP

Remark:

1. Margin = Result (Result =Reading + Factor)–Limit



(1GHz-25GHz)Restricted band and Spurious emission Requirements

GFSK Low Channel

			Antenna		Corrected	Emission				
Frequency	Reading	Amplifier	Loss	Factor	Factor	Level	Limits	Margin	Detector	
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	Comment
Low Channel (2402 MHz)										
48.50	44.70	6.70	28.20	-9.80	38.70	74.00	-35.30	48.50	PK	Vertical
38.66	44.70	6.70	28.20	-9.80	28.86	54.00	-25.14	38.66	AV	Vertical
47.89	44.70	6.70	28.20	-9.80	38.09	74.00	-35.91	47.89	PK	Horizontal
38.61	44.70	6.70	28.20	-9.80	28.81	54.00	-25.19	38.61	AV	Horizontal
59.46	44.20	9.04	31.60	-3.56	55.90	74.00	-18.10	59.46	PK	Vertical
38.45	44.20	9.04	31.60	-3.56	34.89	54.00	-19.11	38.45	AV	Vertical
59.19	44.20	9.04	31.60	-3.56	55.63	74.00	-18.37	59.19	PK	Horizontal
39.03	44.20	9.04	31.60	-3.56	35.47	54.00	-18.53	39.03	AV	Horizontal
45.44	44.20	9.86	32.00	-2.34	43.10	74.00	-30.90	45.44	PK	Vertical
37.62	44.20	9.86	32.00	-2.34	35.28	54.00	-18.72	37.62	AV	Vertical
45.85	44.20	9.86	32.00	-2.34	43.51	74.00	-30.49	45.85	PK	Horizontal
37.82	44.20	9.86	32.00	-2.34	35.48	54.00	-18.52	37.82	AV	Horizontal
51.13	43.50	11.40	35.50	3.40	54.53	74.00	-19.47	51.13	PK	Vertical
32.80	43.50	11.40	35.50	3.40	36.20	54.00	-17.80	32.80	AV	Vertical
51.19	43.50	11.40	35.50	3.40	54.59	74.00	-19.41	51.19	PK	Horizontal
32.95	43.50	11.40	35.50	3.40	36.35	54.00	-17.65	32.95	AV	Horizontal
40.83	43.60	14.30	39.50	10.20	51.03	74.00	-22.97	40.83	PK	Vertical
30.68	43.60	14.30	39.50	10.20	40.88	54.00	-13.12	30.68	AV	Vertical
41.11	43.60	14.30	39.50	10.20	51.31	74.00	-22.69	41.11	PK	Horizontal
30.07	43.60	14.30	39.50	10.20	40.27	54.00	-13.73	30.07	AV	Horizontal
39.66	42.60	15.90	38.90	12.20	51.86	74.00	-22.14	39.66	PK	Vertical
28.54	42.60	15.90	38.90	12.20	40.74	54.00	-13.26	28.54	AV	Vertical
40.76	42.60	15.90	38.90	12.20	52.96	74.00	-21.04	40.76	PK	Horizontal
29.48	42.60	15.90	38.90	12.20	41.68	54.00	-12.32	29.48	AV	Horizontal
40.30	42.70	18.00	37.10	12.40	52.70	74.00	-21.30	40.30	PK	Vertical
28.64	42.70	18.00	37.10	12.40	41.04	54.00	-12.96	28.64	AV	Vertical
40.83	42.70	18.00	37.10	12.40	53.23	74.00	-20.77	40.83	PK	Horizontal
29.42	42.70	18.00	37.10	12.40	41.82	54.00	-12.18	29.42	AV	Horizontal
30.89	42.70	19.40	46.50	23.20	54.09	74.00	-19.91	30.89	PK	Vertical
18.94	42.70	19.40	46.50	23.20	42.14	54.00	-11.86	18.94	AV	Vertical
30.65	42.70	19.40	46.50	23.20	53.85	74.00	-20.15	30.65	PK	Horizontal
18.38	42.70	19.40	46.50	23.20	41.58	54.00	-12.42	18.38	AV	Horizontal

GFSK Mid Channel

Antenna										
Corrected										
Emission										
Frequency	Reading	Amplifier	Loss	Factor	Factor	Level	Limits	Margin	Detector	
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	Comment
Mid Channel (2440 MHz)										
48.40	44.70	6.70	28.20	-9.80	38.60	74.00	-35.40	48.40	PK	Vertical
39.20	44.70	6.70	28.20	-9.80	29.40	54.00	-24.60	39.20	AV	Vertical
48.72	44.70	6.70	28.20	-9.80	38.92	74.00	-35.08	48.72	PK	Horizontal
38.26	44.70	6.70	28.20	-9.80	28.46	54.00	-25.54	38.26	AV	Horizontal
58.95	44.20	9.04	31.60	-3.56	55.39	74.00	-18.61	58.95	PK	Vertical
38.85	44.20	9.04	31.60	-3.56	35.29	54.00	-18.71	38.85	AV	Vertical
58.80	44.20	9.04	31.60	-3.56	55.24	74.00	-18.76	58.80	PK	Horizontal
38.59	44.20	9.04	31.60	-3.56	35.03	54.00	-18.97	38.59	AV	Horizontal
45.71	44.20	9.86	32.00	-2.34	43.37	74.00	-30.63	45.71	PK	Vertical
37.23	44.20	9.86	32.00	-2.34	34.89	54.00	-19.11	37.23	AV	Vertical
45.32	44.20	9.86	32.00	-2.34	42.98	74.00	-31.02	45.32	PK	Horizontal
37.66	44.20	9.86	32.00	-2.34	35.32	54.00	-18.68	37.66	AV	Horizontal
51.54	43.50	11.40	35.50	3.40	54.94	74.00	-19.06	51.54	PK	Vertical
32.95	43.50	11.40	35.50	3.40	36.35	54.00	-17.65	32.95	AV	Vertical
51.77	43.50	11.40	35.50	3.40	55.17	74.00	-18.83	51.77	PK	Horizontal
32.84	43.50	11.40	35.50	3.40	36.24	54.00	-17.76	32.84	AV	Horizontal
40.49	43.60	14.30	39.50	10.20	50.69	74.00	-23.31	40.49	PK	Vertical
30.68	43.60	14.30	39.50	10.20	40.88	54.00	-13.12	30.68	AV	Vertical
40.84	43.60	14.30	39.50	10.20	51.04	74.00	-22.96	40.84	PK	Horizontal
30.44	43.60	14.30	39.50	10.20	40.64	54.00	-13.36	30.44	AV	Horizontal
39.66	42.60	15.90	38.90	12.20	51.86	74.00	-22.14	39.66	PK	Vertical
28.54	42.60	15.90	38.90	12.20	40.74	54.00	-13.26	28.54	AV	Vertical
40.31	42.60	15.90	38.90	12.20	52.51	74.00	-21.49	40.31	PK	Horizontal
29.42	42.60	15.90	38.90	12.20	41.62	54.00	-12.38	29.42	AV	Horizontal
40.20	42.70	18.00	37.10	12.40	52.60	74.00	-21.40	40.20	PK	Vertical
28.64	42.70	18.00	37.10	12.40	41.04	54.00	-12.96	28.64	AV	Vertical
40.27	42.70	18.00	37.10	12.40	52.67	74.00	-21.33	40.27	PK	Horizontal
30.33	42.70	18.00	37.10	12.40	42.73	54.00	-11.27	30.33	AV	Horizontal
30.86	42.70	19.40	46.50	23.20	54.06	74.00	-19.94	30.86	PK	Vertical
20.06	42.70	19.40	46.50	23.20	43.26	54.00	-10.74	20.06	AV	Vertical
30.13	42.70	19.40	46.50	23.20	53.33	74.00	-20.67	30.13	PK	Horizontal
18.48	42.70	19.40	46.50	23.20	41.68	54.00	-12.32	18.48	AV	Horizontal

GFSK High Channel

Antenna										
Frequency	Reading	Amplifier	Loss	Factor	Corrected	Emission				
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	Comment
High Channel (2480 MHz)										
47.99	44.70	6.70	28.20	-9.80	38.19	74.00	-35.81	47.99	PK	Vertical
39.58	44.70	6.70	28.20	-9.80	29.78	54.00	-24.22	39.58	AV	Vertical
48.23	44.70	6.70	28.20	-9.80	38.43	74.00	-35.57	48.23	PK	Horizontal
38.31	44.70	6.70	28.20	-9.80	28.51	54.00	-25.49	38.31	AV	Horizontal
58.79	44.20	9.04	31.60	-3.56	55.23	74.00	-18.77	58.79	PK	Vertical
38.48	44.20	9.04	31.60	-3.56	34.92	54.00	-19.08	38.48	AV	Vertical
58.64	44.20	9.04	31.60	-3.56	55.08	74.00	-18.92	58.64	PK	Horizontal
39.13	44.20	9.04	31.60	-3.56	35.57	54.00	-18.43	39.13	AV	Horizontal
46.34	44.20	9.86	32.00	-2.34	44.00	74.00	-30.00	46.34	PK	Vertical
37.21	44.20	9.86	32.00	-2.34	34.87	54.00	-19.13	37.21	AV	Vertical
45.37	44.20	9.86	32.00	-2.34	43.03	74.00	-30.97	45.37	PK	Horizontal
38.08	44.20	9.86	32.00	-2.34	35.74	54.00	-18.26	38.08	AV	Horizontal
51.34	43.50	11.40	35.50	3.40	54.74	74.00	-19.26	51.34	PK	Vertical
33.34	43.50	11.40	35.50	3.40	36.74	54.00	-17.26	33.34	AV	Vertical
51.33	43.50	11.40	35.50	3.40	54.73	74.00	-19.27	51.33	PK	Horizontal
33.78	43.50	11.40	35.50	3.40	37.18	54.00	-16.82	33.78	AV	Horizontal
39.99	43.60	14.30	39.50	10.20	50.19	74.00	-23.81	39.99	PK	Vertical
30.43	43.60	14.30	39.50	10.20	40.63	54.00	-13.37	30.43	AV	Vertical
40.88	43.60	14.30	39.50	10.20	51.08	74.00	-22.92	40.88	PK	Horizontal
30.16	43.60	14.30	39.50	10.20	40.36	54.00	-13.64	30.16	AV	Horizontal
39.69	42.70	18.00	37.10	12.40	52.09	74.00	-21.91	39.69	PK	Vertical
28.54	42.70	18.00	37.10	12.40	40.94	54.00	-13.06	28.54	AV	Vertical
40.12	42.70	18.00	37.10	12.40	52.52	74.00	-21.48	40.12	PK	Horizontal
28.72	42.70	18.00	37.10	12.40	41.12	54.00	-12.88	28.72	AV	Horizontal
31.27	42.70	19.40	46.50	23.20	54.47	74.00	-19.53	31.27	PK	Vertical
19.39	42.70	19.40	46.50	23.20	42.59	54.00	-11.41	19.39	AV	Vertical
30.55	42.70	19.40	46.50	23.20	53.75	74.00	-20.25	30.55	PK	Horizontal
18.69	42.70	19.40	46.50	23.20	41.89	54.00	-12.11	18.69	AV	Horizontal

Note:

- Corrected Factor = Amplifier- Antenna Factor- Cable Loss.
Emission Level = Reading + Corrected Factor

4.6 TEST RESULTS (Restricted Bands Requirements)

Frequency	Reading	Amplifier	Loss	Antenna Factor	Corrected Factor	Emission Level	Limits	Margin	Detector	
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	Comment
GFSK										
2390.00	68.61	43.80	4.91	25.90	-12.99	55.62	74.00	-18.38	PK	Vertical
2390.00	53.76	43.80	4.91	25.90	-12.99	40.77	54.00	-13.23	AV	Vertical
2390.00	69.56	43.80	4.91	25.90	-12.99	56.57	74.00	-17.43	PK	Horizontal
2390.00	52.89	43.80	4.91	25.90	-12.99	39.90	54.00	-14.10	AV	Horizontal
2483.50	69.25	43.80	5.12	25.90	-12.78	56.47	74.00	-17.53	PK	Vertical
2483.50	52.49	43.80	5.12	25.90	-12.78	39.71	54.00	-14.29	AV	Vertical
2483.50	69.40	43.80	5.12	25.90	-12.78	56.62	74.00	-17.38	PK	Horizontal
2483.50	52.06	43.80	5.12	25.90	-12.78	39.28	54.00	-14.72	AV	Horizontal
Low measurement frequencies is range from 2300 to 2403 MHz, high measurement frequencies is range from 2479 to 2500 MHz. Only show the worst point data of the emissions in the frequency 2300-2403 MHz and 2479-2500 MHz.										

Note:

- Corrected Factor = Amplifier- Antenna Factor- Cable Loss.
Emission Level = Reading + Corrected Factor

5. CONDUCTED SPURIOUS & BAND EDGE EMISSION

5.1 REQUIREMENT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 – 2403 MHz Upper Band Edge: 2479 – 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

5.3 TEST SETUP




The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.


5.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

20 CH




40 CH




For Band edge

01 CH



40 CH



6. POWER SPECTRAL DENSITY TEST


6.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤ 8 dBm (RBW ≥ 3 KHz)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

6.5 TEST RESULTS


Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1015 hPa	Test Voltage:	DC 3.8V
Test Mode:	TX Mode /CH01, CH20, CH40		

Frequency	Power Density (dBm/3kHz)	Limit (dBm/3KHz)	Result
2402 MHz	-18.634	≤8	PASS
2440 MHz	-19.813	≤8	PASS
2480 MHz	-20.476	≤8	PASS


TX CH01



TX CH20



TX CH40



7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

7.5 TEST RESULTS


Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage:	DC 3.8V
Test Mode:	TX Mode /CH01, CH20, CH40		

Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2402 MHz	0.715	>=500KHz	PASS
2440 MHz	0.715	>=500KHz	PASS
2480 MHz	0.711	>=500KHz	PASS


TX CH 01



TX CH 20



TX CH 40



8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power Sensor&PC

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

8.5 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage:	DC 3.8V
Test Mode:	TX Mode /CH01, CH20, CH40		

TX Mode				
Test Channel	Frequency	Conducted Output Power		LIMIT
	(MHz)	Peak (dBm)	AVG (dBm)	dBm
CH01	2402	-3.62	-5.63	30
CH20	2440	-3.84	-5.86	30
CH40	2480	-4.12	-6.13	30

9. ANTENNA REQUIREMENT


9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


9.2 EUT ANTENNA

The EUT antenna is Internal PIFA Antenna. It comply with the standard requirement.

10. EUT TEST PHOTO

Radiated Measurement Photos

Conducted Measurement Photos



*****END OF THE REPORT*****